

```

1  #include <stdio.h>
2  int main()
3  {
4      int A[100][4];
5      int i, j, n, total = 0, index, temp;
6      float avg_wt, avg_tat;
7      printf("Enter number of process: ");
8      scanf("%d", &n);
9      printf("Enter Burst Time:\n");
10     for(i = 0; i < n; i++)
11     {
12         printf("P%d: ", i + 1);
13         scanf("%d", &A[i][1]);
14         A[i][0] = i + 1;
15     }
16     for(i = 0; i < n; i++)
17     {
18         index = i;
19         for(j = i + 1; j < n; j++)
20         {
21             if(A[j][1] < A[index][1])
22                 index = j;
23         }
24         temp = A[i][1];
25         A[i][1] = A[index][1];
26         A[index][1] = temp;
27         temp = A[i][0];
28         A[i][0] = A[index][0];
29         A[index][0] = temp;
30     }
31     A[0][2] = 0;
32     for(i = 1; i < n; i++)
33     {
34         A[i][2] = 0;
35         for(j = 0; j < i; j++)
36         {
37             A[i][2] += A[j][1];
38         }
39         total += A[i][2];
40     }
41     avg_wt = (float)total / n;
42     total = 0;
43     printf("\nP\tBT\tWT\tTAT\n");
44     for(i = 0; i < n; i++)
45     {
46         A[i][3] = A[i][1] + A[i][2];
47         total += A[i][3];
48         printf("P%d\t%d\t%d\t%d\n",
49             A[i][0],
50             A[i][1],
51             A[i][2],
52             A[i][3]);
53     }
54     avg_tat = (float)total / n;
55     printf("\nAverage Waiting Time = %.6f", avg_wt);
56     printf("\nAverage Turnaround Time = %.6f\n", avg_tat);
57     return 0;
58 }

```

```

Enter number of process: 4
Enter Burst Time:
P1: 12
P2: 14
P3: 15
P4: 16

```

P	BT	WT	TAT
P1	12	0	12
P2	14	12	26
P3	15	26	41
P4	16	41	57

```

Average Waiting Time = 19.750000
Average Turnaround Time = 34.000000

```

```

-----
Process exited after 11.16 seconds with return value 0
Press any key to continue . . .

```