ETSI TS 132 654 V5.2.0 (2003-09)

Technical Specification

Digital cellular telecommunications system (Phase 2+);

Telecommunication management;

Configuration Management (CM);

GERAN network resources Integration Reference Point (IRP):

Common Management Information Protocol (CMIP)

solution set

(3GPP TS 32.654 version 5.2.0 Release 5)



Reference
RTS/TSGS-0532654v520

Keywords
GSM

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, send your comment to: editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2003.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**TM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**TM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Contents

Intelle	ectual Property Rights	2
Forew	ord	2
Forew	vord	5
Introd	uction	5
1	Scope	<i>6</i>
2	References	6
3	Definitions, symbols and abbreviations	7
3.1	Definitions	
3.2	Abbreviations	
4	Basic aspects	
4 4.1	Architectural Aspects	
4.1	•	
4.2.1	Mapping	
4.2.1	Mapping of Information Object Class Attributes.	
4.2.2 4.2.2.1		
4.2.2.1		
4.2.2.3	11 0	
4.2.2.3	11 0	
4.2.2.5	11 6	
4.2.2.6		
4.2.2.0	11 6	
5	GDMO Definitions	10
5.1	Managed Object Classes	10
5.1.1	bssFunction	10
5.1.2	btsSiteMgr	10
5.1.3	gsmCell	10
5.1.4	externalGsmCell	10
5.1.5	gsmRelation	
5.1.6	externalBssFunction	11
5.2	Packages	11
5.2.1	bssFunctionBasicPackage	11
5.2.2	btsSiteMgrBasicPackage	
5.2.3	btsSiteMgrGeoPositionPackage	11
5.2.4	gsmCellBasicPackage	
5.2.5	gsmCellMandatoryPackage	
5.2.6	gsmCellOptionalPackage	
5.2.7	externalGsmCellBasicPackage	
5.2.8	externalGsmCellMandatoryPackage	
5.2.9	gsmRelationBasicPackage	
5.2.10	gsmRelationOptionalPackage	
5.2.11	ExternalBssFunctionBasicPackage	
5.3	Attributes	
5.3.1	bssFunctionId	
5.3.2	btsSiteMgrId	
5.3.3	longitude	
5.3.4	latitude	
5.3.5	gsmCellId	
5.3.6	racc	
5.3.7	gsmRelationId	
5.3.8	externalGsmCellId	
5.3.9	externalBssFunctionId	
5.4	Name Binding	
5.4.1	bssFunction - managedElement	15

5.4.2	btsSiteMgr - bssFunction	15
5.4.3	gsmCell - btsSiteMgr	
5.4.4	gsmRelation - gsmCell	
5.4.5	externalGsmCell - subNetwork	16
5.4.6	externalBssFunction - subNetwork	17
6	ASN.1 Definitions	18
Anne	ex A (informative): Change history	19
	•	
Histo	ory	20

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The interface Itf-N, defined in 3GPP TS 32.102 [2], is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2].

1 Scope

The present document specifies the Common Management Information Protocol (CMIP) Solution Set (SS) for the GERAN Network Resource Integration Reference Point (IRP): Network Resource Model defined in 3GPP TS 32.652 [4]. In detail:

- Clause 4 contains an introduction to some concepts that are the base for some specific aspects of the CMIP interfaces.
- Clause 5 contains the GDMO definitions for the Alarm Management over the CMIP interfaces
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

This Solution Set specification is related to 3GPP TS 32.652 V5.1.x.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

Release as th	ne present document.
[1]	3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
[2]	3GPP TS 32.102: "Telecommunication management; Architecture".
[3]	3GPP TS 32.304: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".
[4]	3GPP TS 32.652: "Telecommunication management; Configuration Management (CM); GERAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
[5]	ITU-T Recommendation X.710 (1991): "Common Management Information Service Definition for CCITT Applications".
[6]	ITU-T Recommendation X.721 (02/92): "Information Technology - Open Systems Interconnection – Structure of Management Information: Definition of Management Information".
(7)	TITLE D

- [7] ITU-T Recommendation X.730 (01/92): "Information Technology Open Systems Interconnection Systems Management: Object Management Function".
- [8] ITU-T Recommendation X.733 (02/92): "Information Technology Open Systems Interconnection Alarm Reporting Function".
- [9] ITU-T Recommendation M.3100 (07/95): "Maintenance Telecommunications Management Network Generic Network Information Model".
- [10] GSM 12.20 (06/1996): "Digital cellular communication system (Phase 2); Base Station System (BSS) Management Information".
- [11] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".

Definitions, symbols and abbreviations 3

3.1 **Definitions**

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.600 [11] and 3GPP TS 32.652 [4] apply.

3.2 **Abbreviations**

For the purposes of the present document, the following abbreviations apply:

CMIP Common Management Information Protocol DN Distinguished Name **GDMO** Guidelines for the Definition of Managed Objects GSM-EDGE Radio Access Network **GERAN** IDL Interface Definition Language **IEC** International Electro-technical Commission ISO **International Standards Organization MIB** Management Information Base MIM Management Information Model MIT Management Information Tree (or Naming Tree) Managed Object Class MOC Managed Object Instance MOI NE Network Element NR Network Resource

Network Resource Model **TMN** Telecommunications Management Network **UTRAN** Universal Terrestrial Radio Access Network

4 Basic aspects

Architectural Aspects 4.1

A technology independent GERAN network resource model is defined in 3GPP TS 32.652 [4] for 3G networks. This document provides an implementation of this GERAN network resource model by using CMIP technology.

4.2 Mapping

NRM

The semantic of the GERAN Network Resource Model is defined in 3GPP TS 32.652 [4]. The specification of the information object classes defined there is independent of any implementation technology and protocol. This subclause maps these technology and protocol independent definitions onto the equivalencies of the CMIP Solution Set of the GERAN Network Resource IRP.

4.2.1 Mapping of Information Object Classes

The following table maps the information object classes defined in the GERAN Network Resource Model onto the equivalent MOCs of the CMIP Solution Set.

Table 4.1: Mapping of MOCs

IS IOC	CMIP SS MOC
BssFunction	bssFunction
BtsSiteMgr	btsSiteMgr
GsmCell	gsmCell
GsmRelation	gsmRelation
ExternalGsmCell	externalGsmCell
ExternalBssFunction	externalBssFunction

4.2.2 Mapping of Information Object Class Attributes

This subclause depicts the mapping of the attributes defined in 3GPP TS 32.652 [4] on the corresponding attributes of the CMIP Solution Set.

4.2.2.1 Attribute Mapping of the IOC BssFunction

Table 4.2: Attribute mapping of the IOC BssFunction

IS Attribute	CMIP SS Attribute	Qualifier
bssFunctionId	bssFunctionId	M
userLabel	userLabel (ITU-T M.3100 [9])	M

4.2.2.2 Attribute Mapping of the IOC *BtsSiteMgr*

Table 4.3: Attribute mapping of the IOC BtsSiteMgr

IS Attribute	CMIP SS Attribute	Qualifier
btsSiteMgrId	btsSiteMgrId	M
userLabel	userLabel (ITU-T M.3100 [9])	M
latitude	latitude	0
longitude	longitude	0

4.2.2.3 Attribute Mapping of the IOC *GsmCell*

Table 4.4: Attribute mapping of the IOC GsmCell

IS Attribute	CMIP SS Attribute	Qualifier
gsmCellId	gsmCellId	М
userLabel	userLabel (ITU-T M.3100 [9])	M
cellIdentity		
lac	cellGlobalIdentity (GSM 12.20 [10])	М
mcc		IVI
mnc		
cellAllocation	cellAllocation (GSM 12.20 [10])	М
ncc	bsIdentityCode.ncc (GSM 12.20 [10])	М
bcc	bsIdentityCode.bcc (GSM 12.20 [10])	М
rac	rac (3GPP TS32.644 V5.0.x)	0
racc	racc	0
tsc	tsc (GSM 12.20 [10])	М
rxLevAccessMin	rxLevAccessMin (GSM 12.20 [10])	M
msTxPwrMaxCCH	msTxPwrMaxCCH (GSM 12.20 [10])	M
hoppingSequenceNumber	hoppingSequenceNumber (GSM 12.20 [10])	M
plmnPermitted	plmnPermitted (GSM 12.20 [10])	M

4.2.2.4 Attribute Mapping of the IOC GsmRelation

Table 4.5: Attribute mapping of the IOC GsmRelation

IS Attribute	CMIP SS Attribute	Qualifier
gsmRelationId	gsmRelationId	М
adjacentCell	adjacentCell (3GPP TS32.644 V5.0.x)	M
bcchFrequency	bcchFrequency (GSM 12.20 [10])	0
ncc	bsIdentityCode.ncc (GSM 12.20 [10])	0
bcc	bsIdentityCode.bcc (GSM 12.20 [10])	0
lac	lac (3GPP TS32.644 V.5.0.x)	0

4.2.2.5 Attribute Mapping of the IOC ExternalGsmCell

Table 4.6: Attribute mapping of the IOC ExternalGsmCell

IS Attribute CMIP SS Attribute			
externalGsmCellId	externalGsmCellId	М	
userLabel	userLabel (ITU-T M.3100 [9])	М	
cellIdentity			
lac	cellGlobalIdentity (GSM 12.20 [10])	М	
mcc	celiolobalideritity (Gow 12.20 [10])		
mnc			
bcchFrequency	bcchFrequency (GSM 12.20 [10])		
ncc	bsIdentityCode.ncc (GSM 12.20 [10])		
bcc	bsIdentityCode.bcc (GSM 12.20 [10])		
rac	rac (3GPP TS32.644 V5.0.x)		
acc racc			

4.2.2.6 Attribute Mapping of the IOC *ExternalBssFunction*

Table 4.7: Attribute mapping of the IOC ExternalBssFunction

IS Attribute	CMIP SS Attribute	Qualifier
externalBssFunctionId	externalBssFunctionId	M
userLabel	userLabel (ITU-T M.3100 [9])	M

5 GDMO Definitions

5.1 Managed Object Classes

5.1.1 bssFunction

```
bssFunction MANAGED OBJECT CLASS
   DERIVED FROM
     "3GPP TS 32.624 Release 5": managedFunction;
   CHARACTERIZED BY
     bssFunctionBasicPackage;
REGISTERED AS {ts32-6540bjectClass 1};
```

5.1.2 btsSiteMgr

```
btsSiteMgr MANAGED OBJECT CLASS

DERIVED FROM

"3GPP TS 32.624 Release 5": managedFunction;

CHARACTERIZED BY

btsSiteMgrBasicPackage;

CONDITIONAL PACKAGES

"3GPP TS 32.674 Release 5": operationalStateAttributePackage

PRESENT IF

"Instances of this MOC support operationalState attribute.",

btsSiteMgrGeoPositionPackage

PRESENT IF

"the attributes defined in this package are supported by an instance of this class.";

REGISTERED AS {ts32-6540bjectClass 2};
```

5.1.3 gsmCell

```
gsmCell MANAGED OBJECT CLASS
   DERIVED FROM
    "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
    gsmCellBasicPackage,
    gsmCellMandatoryPackage;
CONDITIONAL PACKAGES
    gsmCellOptionalPackage PRESENT IF
    "the attributes defined in this package are supported by an instance of this class.";
REGISTERED AS {ts32-6540bjectClass 3};
```

5.1.4 externalGsmCell

5.1.5 gsmRelation

```
gsmRelation MANAGED OBJECT CLASS

DERIVED FROM

"Recommendation X.721: 1992":top;
CHARACTERIZED BY
gsmRelationBasicPackage;
CONDITIONAL PACKAGES
gsmRelationOptionalPackage
PRESENT IF
```

```
"the attributes defined in this package are supported by an instance of this class.",

"Recommendation M.3100: 1995":createDeleteNotificationsPackage

PRESENT IF

"the objectCreation and the objectDeletion defined in Recommendation X.721

are supported by an instance of this class.",

"Recommendation M.3100: 1995":attributeValueChangeNotificationPackage

PRESENT IF

"the attributeValueChange notifications defined in Recommendation X.721

are supported by an instance of this class.";

REGISTERED AS {ts32-6540bjectClass 5};
```

5.1.6 externalBssFunction

```
externalBssFunction MANAGED OBJECT CLASS
   DERIVED FROM
    "3GPP TS 32.624 Release 5": managedFunction;
   CHARACTERIZED BY
    externalBssFunctionBasicPackage;
REGISTERED AS {ts32-6540bjectClass 6};
```

5.2 Packages

5.2.1 bssFunctionBasicPackage

```
bssFunctionBasicPackage PACKAGE

BEHAVIOUR

bssFunctionBasicPackageBehaviour;

ATTRIBUTES

bssFunctionId GET;

REGISTERED AS {ts32-654Package 1};

bssFunctionBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"The Managed Object Class bssFunction represents BSS functionality.";
```

5.2.2 btsSiteMgrBasicPackage

```
btsSiteMgrBasicPackage PACKAGE

BEHAVIOUR

btsSiteMgrBasicPackageBehaviour;

ATTRIBUTES

btsSiteMgrId GET;

REGISTERED AS {ts32-654Package 2};

btsSiteMgrBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"The 'BtsSiteMgr' managed object contains site specific information for a BTS site.";
```

5.2.3 btsSiteMgrGeoPositionPackage

```
btsSiteMgrGeoPositionPackage PACKAGE

BEHAVIOUR

btsSiteMgrGeoPositionPackageBehaviour;

ATTRIBUTES

longitude GET-REPLACE,
latitude GET-REPLACE;

REGISTERED AS {ts32-654Package 3};

btsSiteMgrGeoPositionPackageBehaviour BEHAVIOUR

DEFINED AS

"This package contains the attributes describing the geographic position of a BTS site.";
```

5.2.4 gsmCellBasicPackage

```
gsmCellBasicPackage PACKAGE
BEHAVIOUR
gsmCellBasicPackageBehaviour;
ATTRIBUTES
GsmCellId GET;
```

```
REGISTERED AS {ts32-654Package 4};
gsmCellBasicPackageBehaviour BEHAVIOUR
DEFINED AS
    "The managed object class gsmCell represents the GSM radio cell.";
```

5.2.5 gsmCellMandatoryPackage

```
gsmCellMandatoryPackage PACKAGE
   BEHAVIOUR
      gsmCellMandatoryPackageBehaviour;
   ATTRIBUTES
      "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": cellAllocation
                                                                                   GET-REPLACE,
      "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bsIdentityCode
                                                                                   GET-REPLACE.
      "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": cellGlobalIdentity
                                                                                   GET-REPLACE,
      "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": tsc
                                                                                   GET-REPLACE,
      "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": rxLevAccessMin
                                                                                   GET-REPLACE,
      "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": msTxPwrMaxCCH
                                                                                   GET-REPLACE.
      "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": hoppingSequenceNumber
                                                                                  GET-REPLACE,
      "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": plmnPermitted
                                                                                   GET-REPLACE;
REGISTERED AS {ts32-654Package 5};
{\tt gsmCellMandatoryPackageBehaviour} \ \ {\tt BEHAVIOUR}
DEFINED AS
   "This package contains the elementary mandatory attributes of a gsmCell.";
```

5.2.6 gsmCellOptionalPackage

5.2.7 externalGsmCellBasicPackage

```
externalGsmCellBasicPackage PACKAGE

BEHAVIOUR
    externalGsmCellBasicPackageBehaviour;

ATTRIBUTES
    externalGsmCellId GET;

REGISTERED AS {ts32-654Package 7};

externalGsmCellBasicPackageBehaviour BEHAVIOUR

DEFINED AS
    "This Managed Object Class represents a radio cell controlled by another IRPAgent. It is a necessary attribute for inter-system handover. This MOC is a subreplication of a MOC in another NEM.";
```

5.2.8 externalGsmCellMandatoryPackage

```
externalGsmCellMandatoryPackage PACKAGE

BEHAVIOUR
    externalGsmCellMandatoryPackageBehaviour;

ATTRIBUTES
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bsIdentityCode GET-REPLACE,
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": cellGlobalIdentity GET-REPLACE,
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bcchFrequency GET-REPLACE;

REGISTERED AS {ts32-654Package 8};

externalGsmCellMandatoryPackageBehaviour BEHAVIOUR

DEFINED AS

"This package contains the elementary mandatory attributes of a externalGsmCell.";
```

5.2.9 gsmRelationBasicPackage

```
gsmRelationBasicPackage PACKAGE
   BEHAVIOUR
      gsmRelationBasicPackageBehaviour;
   ATTRIBUTES
      gsmRelationId
                                                GET,
     "3GPP TS 32.644 Release 5": adjacentCell
                                                GET-REPLACE;
REGISTERED AS {ts32-654Package 9};
gsmRelationBasicPackageBehaviour BEHAVIOUR
DEFINED AS
   "The 'GsmRelation' managed object contains radio network related parameters for the relation
    to the 'GsmCell' or 'ExternalGsmCell' managed object. Note: In handover relation terms, the
    cell containing the GSM Relation object is the source cell for the handover. The cell referred
    to in the GSM relation object is the target cell for the handover. This defines a one-way
   handover relation where the direction is from source cell to target cell.";
```

5.2.10 gsmRelationOptionalPackage

```
gsmRelationOptionalPackage PACKAGE

BEHAVIOUR
gsmRelationOptionalPackageBehaviour;

ATTRIBUTES
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bsIdentityCode GET-REPLACE,
"3GPP TS 32.644 Release 5": lac GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bcchFrequency GET-REPLACE;
REGISTERED AS {ts32-654Package 10};

gsmRelationOptionalPackageBehaviour BEHAVIOUR
DEFINED AS
"This package contains the optional attributes of a gsmRelation.";
```

5.2.11 ExternalBssFunctionBasicPackage

```
externalBssFunctionBasicPackage PACKAGE

BEHAVIOUR
    externalBssFunctionBasicPackageBehaviour;

ATTRIBUTES
    externalBssFunctionId GET;

REGISTERED AS {ts32-654Package 11};

externalBssFunctionBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"The Managed Object Class externalBssFunction represents external BSS functionality.";
```

5.3 Attributes

5.3.1 bssFunctionId

```
bssFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-654TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
bssFunctionIdBehaviour;
REGISTERED AS {ts32-654Attribute 1};
bssFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a bssFunction object.";
```

5.3.2 btsSiteMgrld

```
btsSiteMgrId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
    TS32-654TypeModule.GeneralObjectId;
MATCHES FOR
    EQUALITY;
```

```
BEHAVIOUR
     btsSiteMgrIdBehaviour;
REGISTERED AS {ts32-654Attribute 2};
btsSiteMgrIdBehaviour BEHAVIOUR
DEFINED AS
   "This attribute identifies a btsSiteMgr object.";
5.3.3
           longitude
longitude ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
      TS32-654TypeModule.Longitude;
  MATCHES FOR
     EQUALITY;
   BEHAVIOUR
     longitudeBehaviour;
REGISTERED AS {ts32-654Attribute 3};
longitudeBehaviour BEHAVIOUR
   "Used for geographical positioning of the sitemanager.";
5.3.4
           latitude
latitude ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
     TS32-654TypeModule.Latitude;
  MATCHES FOR
     EQUALITY;
   BEHAVIOUR
     latitudeBehaviour;
REGISTERED AS {ts32-654Attribute 4};
latitudeBehaviour BEHAVIOUR
   "Used for geographical positioning of the sitemanager.";
5.3.5
           gsmCellId
gsmCellId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
     TS32-654TypeModule.GeneralObjectId;
  MATCHES FOR
      EQUALITY;
   BEHAVIOUR
     gsmCellIdBehaviour;
REGISTERED AS {ts32-654Attribute 5};
gsmCellIdBehaviour BEHAVIOUR
DEFINED AS
   "Cell Identity (Ref GSM 03.03).";
5.3.6
           racc
racc ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
     TS32-654TypeModule.Racc;
  MATCHES FOR
     EQUALITY;
   BEHAVIOUR
     raccBehaviour;
REGISTERED AS {ts32-654Attribute 7};
raccBehaviour BEHAVIOUR
DEFINED AS
   "Routing Area Colour Code, RACC.";
```

5.3.7 gsmRelationId

gsmRelationId ATTRIBUTE
WITH ATTRIBUTE SYNTAX

5.3.8 externalGsmCellId

```
externalGsmCellId ATTRIBUTE

WITH ATTRIBUTE SYNTAX

TS32-654TypeModule.GeneralObjectId;

MATCHES FOR
EQUALITY;
BEHAVIOUR
externalGsmCellIdBehaviour;

REGISTERED AS {ts32-654Attribute 9};

externalGsmCellIdBehaviour BEHAVIOUR

DEFINED AS
"This attribute identifies a externalGsmCell object.";
```

5.3.9 externalBssFunctionId

```
externalBssFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-654TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
externalBssFunctionIdBehaviour;
REGISTERED AS {ts32-654Attribute 10};
externalBssFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies an externalBssFunction object.";
```

5.4 Name Binding

5.4.1 bssFunction - managedElement

```
bssFunction-managedElement NAME BINDING
   SUBORDINATE OBJECT CLASS
      bssFunction;
   NAMED BY SUPERIOR OBJECT CLASS
      "3GPP TS 32.624 Release 5": managedElement;
   WITH ATTRIBUTE
     bssFunctionId;
   BEHAVIOUR
      bssFunction-managedElementBehaviour;
   CREATE
      WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
     ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 1};
bssFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
   "The name binding represents a relationship in which a managedElement contains
    and controls a bssFunction. When automatic instance naming is used, the choice
    of name bindings is left as a local matter.";
```

5.4.2 btsSiteMgr - bssFunction

```
btsSiteMgr-bssFunction NAME BINDING
SUBORDINATE OBJECT CLASS
btsSiteMgr;
```

```
NAMED BY SUPERIOR OBJECT CLASS
      bssFunction;
   WITH ATTRIBUTE
     btsSiteMgrId;
   BEHAVIOUR
     btsSiteMgr-bssFunctionBehaviour;
   CREATE
     WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
   DELETE
      ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 2};
btsSiteMgr-bssFunctionBehaviour BEHAVIOUR
DEFINED AS
   "The name binding represents a relationship in which a bssFunction contains
    and controls a btsSiteMgr. When automatic instance naming is used, the choice
    of name bindings is left as a local matter.";
```

5.4.3 gsmCell - btsSiteMgr

```
gsmCell-btsSiteMgr NAME BINDING
   SUBORDINATE OBJECT CLASS
      qsmCell;
  NAMED BY SUPERIOR OBJECT CLASS
     btsSiteMgr;
   WITH ATTRIBUTE
     qsmCellId;
   BEHAVIOUR
      gsmCell-btsSiteMgrBehaviour;
     WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
   DELETE
      ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 3};
gsmCell-btsSiteMgrBehaviour BEHAVIOUR
DEFINED AS
   "The name binding represents a relationship in which a btsSiteMgr contains
    and controls a gsmCell. When automatic instance naming is used, the choice
    of name bindings is left as a local matter.";
```

5.4.4 gsmRelation - gsmCell

```
gsmRelation-gsmCell NAME BINDING
   SUBORDINATE OBJECT CLASS
      qsmRelation;
  NAMED BY SUPERIOR OBJECT CLASS
     gsmCell;
   WITH ATTRIBUTE
     gsmRelationId;
   BEHAVIOUR
     gsmRelation-gsmCellBehaviour;
   CREATE
     WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
   DELETE
      ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 4};
gsmRelation-gsmCellBehaviour BEHAVIOUR
DEFINED AS
   "The name binding represents a relationship in which a gsmCell contains
    and controls a gsmRelation. When automatic instance naming is used, the choice
    of name bindings is left as a local matter.";
```

5.4.5 externalGsmCell - subNetwork

```
externalGsmCell-subNetwork NAME BINDING
SUBORDINATE OBJECT CLASS
externalGsmCell;
NAMED BY SUPERIOR OBJECT CLASS
"3GPP TS 32.624 Release 5": subNetwork;
WITH ATTRIBUTE
externalGsmCellId;
BEHAVIOUR
```

```
externalGsmCell-subNetworkBehaviour;

CREATE

WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE

ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-654NameBinding 5};

externalGsmCell-subNetworkBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a subNetwork contains and controls an externalGsmCell. When automatic instance naming is used, the choice of name bindings is left as a local matter.";
```

5.4.6 externalBssFunction - subNetwork

```
externalBssFunction-subNetwork NAME BINDING
  SUBORDINATE OBJECT CLASS
      externalBssFunction;
  NAMED BY SUPERIOR OBJECT CLASS
      "3GPP TS 32.624 Release 5": subNetwork;
   WITH ATTRIBUTE
     externalBssFunctiond;
   BEHAVIOUR
      externalBssFunction-subNetworkBehaviour;
   CREATE
     WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
   DELETE
      ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 6};
externalBssFunction-subNetworkBehaviour BEHAVIOUR
DEFINED AS
   "The name binding represents a relationship in which a subNetwork contains
   and controls an externalBssFunction. When automatic instance naming is used, the choice
   of name bindings is left as a local matter.";
```

TS32-654TypeModule {ccitt (0) identified-organization (4) etsi (0) mobileDomain (0)

6 ASN.1 Definitions

```
umts-Operation-Maintenance (3) ts-32-654 (654) informationModel (0) asnlModule (2) version1 (1)}
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
--EXPORTS everything
TMPORTS
GeneralObjectId
    FROM TS32-624TypeModule {ccitt (0) identified-organization (4) etsi (0) mobileDomain (0)
    umts-Operation-Maintenance (3) ts32-624 (624) informationModel (0) asn1Module (2) version1 (1)}
    FROM TS32-644TypeModule {ccitt (0) identified-organization (4) etsi (0) mobileDomain (0)
    umts-Operation-Maintenance (3) ts-32-644 (644) informationModel (0) asnlModule (2)
    version1 (1)};
-- 3GPP TS 32.654 related Object Identifiers
baseNodeUMTS
                                 OBJECT IDENTIFIER ::= {itu-t(0) identified-organization(4) etsi(0)
                                                                  mobileDomain(0) umts-Operation-Maintenance(3)}
                                OBJECT IDENTIFIER ::= {baseNodeUMTS ts32-654 OBJECT IDENTIFIER ::= {ts32-654 informationModel
ts32-654
                                                                                                                         (654)}
ts32-654InfoModel
ts32-6540bjectClass OBJECT IDENTIFIER ::= \{ts32-654InfoModel managedObjectClass (3)\} ts32-654Package OBJECT IDENTIFIER ::= \{ts32-654InfoModel package (4)\} ts32-654Parameter OBJECT IDENTIFIER ::= \{ts32-654InfoModel parameter (5)\} ts32-654NameBinding OBJECT IDENTIFIER ::= \{ts32-654InfoModel nameBinding (6)\} ts32-654Attribute OBJECT IDENTIFIER ::= \{ts32-654InfoModel attribute (7)\} ts32-654Action OBJECT IDENTIFIER ::= \{ts32-654InfoModel action (9)\}
ts32-654Action OBJECT IDENTIFIER ::= {ts32-654InfoModel action ts32-654Notification OBJECT IDENTIFIER ::= {ts32-654InfoModel notification
                                                                                                                        ( 10)}
-- Start of 3GPP SA5 own definitions
Longitude ::= INTEGER
Latitude ::= INTEGER
Racc ::= INTEGER
          -- of TS32-654TypeModule
```

Annex A (informative): Change history

	Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New	
Jun 2001	S_12	SP-010283			Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0	
Sep 2001	S_13	SP-010478	001		Correction due to TS renumbering	4.0.0	4.1.0	
Sep 2001	S_13	SP-010477	002		Addition of mcc and mnc in the object model of GERAN	4.0.0	4.1.0	
Dec 2002	S_18	SP-020749	003		Alignment of the CMIP SS with the Rel-5 version of the IS in 32.652	4.1.0	5.0.0	
Jun 2003	S_20	SP-030283	005		Removal of relationType	5.0.0	5.1.0	
Jun 2003	S_20	SP-030286	006		Alignment of object class names to externalGsmCell - Alignment with 32.624	5.0.0	5.1.0	
Sep 2003	S_21	SP-030418	007		Inclusion of ExternalBssFunction - Alignment with 32.652	5.1.0	5.2.0	

History

	Document history					
V5.0.0 December 2002 Publication						
V5.1.0	June 2003	Publication				
V5.2.0	September 2003	Publication				