ETSI TS 132 766 V11.3.0 (2013-02)



Universal Mobile Telecommunications System (UMTS); LTE;

Telecommunication management;
Evolved Universal Terrestrial Radio
Access Network (E-UTRAN) Network Resource Model (NRM)
Integration Reference Point (IRP);
Solution Set (SS) definitions
(3GPP TS 32.766 version 11.3.0 Release 11)



Reference
RTS/TSGS-0532766vb30

Keywords
LTE,UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013. All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Contents

Intelle	ectual Property Rights	2
Forev	word	2
Forev	word	5
Introd	duction	5
	Scope	
1	•	
2	References	6
3	Definitions and abbreviations	
3.1	Definitions	
3.2	Abbreviations	
4	Solution Set Definitions	8
Anne	ex A (normative): CORBA Solution Set	9
A.1	Architectural features	
A.1.1	- J	
A.1.2		
A.1.2.		
A.1.2.	.2 Extensions not allowed	
A.2	Mapping	10
A.2.1	** *	
A.2.2		
A.2.2.	.1 IOC ENBFunction	10
A.2.2.		
A.2.2.	- -	
A.2.2.		
A.2.2. A.2.2.		
A.2.2.	1 7	
A.2.2.		
A.2.2.		
A.2.2.	1 11 6	
A.2.2.		
A.2.2.		
A.3	Solution Set definitions	22
A.3.1		
A.3.2		
Anne	ex B (normative): XML Definitions	31
B.1	Architectural features	31
B.1.1	Syntax for Distinguished Names	
D.Z	Mapping	

B.2.1	General mapping	31
B.2.2		31
B.3	Solution Set definitions	32
B.3.1	XML definition structure	
B.3.2	Graphical Representation	
B.3.3		33
Anne	x C (informative): Change history	48
	•	
Histor	ry	49

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

TS 32.766	Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions
TS 32.762	Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP): Information Service (IS)
TS 32.761	Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP): Requirements

1 Scope

The present document is part of an Integration Reference Point (IRP) named E-UTRAN Network Resource Model (NRM) IRP, through which an IRPAgent can communicate configuration management information to one or several IRPManagers concerning E-UTRAN resources. The E-UTRAN NRM IRP comprises a set of specifications defining Requirements, a protocol neutral Information Service and one or more Solution Set(s).

The present document specifies the Solution Sets for the E-UTRAN NRM IRP.

This Solution Set specification is related to 3GPP TS 32.762 V11.4.X [4].

2 References

[10]

[11]

[12]

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

ine same Kei	euse us ine present document.
[1]	3GPP TS 21.905: "Vocabulary for 3GPP Specifications".
[2]	3GPP TS 32.153: "Telecommunication management; Integration Reference Point (IRP) technology specific templates, rules and guidelines".
[3]	3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
[4]	3GPP TS 32.762: "Telecommunications management; Evolved Universal Terrestrial Radio Access Network (E-UTRAN) Network Resource Model (NRM) Integration Reference Point (IRP): Information Service (IS)".
[5]	3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
[6]	3GPP TS 32.606: "Telecommunication management; Configuration Management (CM); Basic CM Integration Reference Point (IRP); Solution Set (SS) definitions".
[7]	3GPP TS 32.616: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Solution Set (SS) definitions".
[8]	W3C REC-xml-20001006: "Extensible Markup Language (XML) 1.0 (Second Edition)".
[9]	W3C REC-xmlschema-0-20010502: "XML Schema Part 0: Primer".

W3C REC-xmlschema-1-20010502: "XML Schema Part 1: Structures".

W3C REC-xmlschema-2-20010502: "XML Schema Part 2: Datatypes".

W3C REC-xml-names-19990114: "Namespaces in XML".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1], TS 32.600 [3] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

XML file: file containing an XML document

XML document: composed of the succession of an optional XML declaration followed by a root XML element

NOTE: See [8]; in the scope of the present document.

XML declaration: it specifies the version of XML being used

NOTE: See [8].

XML element: has a type, is identified by a name, may have a set of XML attribute specifications and is either composed of the succession of an XML start-tag followed by the XML content of the XML element followed by an XML end-tag, or composed simply of an XML empty-element tag; each XML element may contain other XML elements

NOTE: See [8].

empty XML element: having an empty XML content; an empty XML element still possibly has a set of XML attribute specifications; an empty XML element is either composed of the succession of an XML start-tag directly followed by an XML end-tag, or composed simply of an XML empty-element tag

NOTE: See [8].

XML content (of an XML element): empty if the XML element is simply composed of an XML empty-element tag; otherwise the part, possibly empty, of the XML element between its XML start-tag and its XML end-tag

XML start-tag: the beginning of a non-empty XML element is marked by an XML start-tag containing the name and the set of XML attribute specifications of the XML element

NOTE: See [8].

XML end-tag: the end of a non-empty XML element is marked by an XML end-tag containing the name of the XML element

NOTE: See [8].

XML empty-element tag: composed simply of an empty-element tag containing the name and the set of XML attribute specifications of the XML element.

NOTE: See [8].

XML attribute specification: has a name and a value

NOTE: See [8].

DTD: defines structure and content constraints to be respected by an XML document to be valid with regard to this DTD

NOTE: See [8].

XML schema: more powerful than a DTD, an XML schema defines structure and content constraints to be respected by an XML document to conform with this XML schema; through the use of XML namespaces several XML schemas can be used together by a single XML document; an XML schema is itself also an XML document that shall conform with the XML schema for XML schemas

NOTE: See [9], [10] and [11].

XML namespace: enables qualifying element and attribute names used in XML documents by associating them with namespaces identified by different XML schemas

NOTE: See [12], in the scope of the present document.

XML complex type: defined in an XML schema; cannot be directly used in an XML document; can be the concrete type or the derivation base type for an XML element type or for another XML complex type; ultimately defines constraints for an XML element on its XML attribute specifications and/or its XML content

NOTE: See [9], [10] and [11].

XML element type: declared by an XML schema; can be directly used in an XML document; as the concrete type of an XML element, directly or indirectly defines constraints on its XML attribute specifications and/or its XML content; can also be the concrete type or the derivation base type for another XML element type

NOTE: See [9], [10] and [11].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1], TS 32.600 [3], and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

CM Configuration Management

CORBA Common Object Request Broker Architecture

DN Distinguished Name
DTD Document Type Definition
EDGE Enhanced Data for GSM Evolution
GERAN GSM/EDGE Radio Access Network
GSM Global System for Mobile communication

IS Information Service

IDL Interface Definition Language (OMG)

IOCInformation Object ClassIRPIntegration Reference PointISInformation Service

MO Managed Object
MOC Managed Object Class
NRM Network Resource Model
OMG Object Management Group

SS Solution Set

UMTS Universal Mobile Telecommunications System UTRAN Universal Terrestrial Radio Access Network

XML eXtensible Markup Language XSD XML Schema Definition

4 Solution Set Definitions

This specification defines the following 3GPP E-UTRAN NRM IRP Solution Set Definitions:

- 3GPP E-UTRAN NRM IRP CORBA SS (Annex A)
- 3GPP E-UTRAN NRM IRP XML Definitions (Annex B)

Annex A (normative): CORBA Solution Set

This annex contains the CORBA Solution Set for the IRP whose semantics is specified in E-UTRAN NRM IRP: Information Service (TS 32.762 [4]).

A.1 Architectural features

The overall architectural feature of E-UTRAN Network Resources IRP is specified in 3GPP TS 32.762 [4]. This clause specifies features that are specific to the CORBA SS.

A.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

A.1.2 Rules for NRM extensions

This clause discusses how the models and IDL definitions provided in the present document can be extended for a particular implementation and still remain compliant with 3GPP SA5's specifications (see also Annex B of TS 32.153 [2].).

A.1.2.1 Allowed extensions

Vendor-specific MOCs may be supported. The vendor-specific MOCs may support new types of attributes. The 3GPP SA5-specified notifications may be issued referring to the vendor-specific MOCs and vendor-specific attributes. New MOCs shall be distinguishable from 3GPP SA5 MOCs by name. 3GPP SA5-specified and vendor-specific attributes may be used in vendor-specific MOCs. Vendor-specific attribute names shall be distinguishable from existing attribute names.

NRM MOCs may be subclassed. Subclassed MOCs shall maintain the specified behaviour of the 3GPP SA5's superior classes. They may add vendor-specific behaviour with vendor-specific attributes. When subclassing, naming attributes cannot be changed. The subclassed MOC shall support all attributes of its superior class. Vendor-specific attributes cannot be added to 3GPP SA5 NRM MOCs without subclassing.

When subclassing, the 3GPP SA5-specified containment rules and their specified cardinality shall still be followed. As an example, ManagementNode (or its subclasses) shall be contained under SubNetwork (or its subclasses).

Managed Object Instances may be instantiated as CORBA objects. This requires that the MOCs be represented in IDL. 3GPP SA5's NRM MOCs are not currently specified in IDL, but may be specified in IDL for instantiation or subclassing purposes. However, management information models should not require that IRPManagers access the instantiated managed objects other than through supported methods in the present document.

Extension rules related to notifications (Notification categories, Event Types, Extended Event Types etc.) are for further study.

A.1.2.2 Extensions not allowed

The IDL specifications in the present document cannot be edited or altered. Any additional IDL specifications shall be specified in separate IDL files.

IDL interfaces (note: not MOCs) specified in the present document may not be subclassed or extended. New interfaces may be defined with vendor-specific methods.

A.2 Mapping

A.2.1 General mapping

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MOReference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MOReferenceSet, which contains a sequence of MO references.

A.2.2 Information Object Class (IOC) mapping

This Solution Set supports reference attributes for relations other than containment relations between objects. Reference attributes are therefore introduced in each MOC where needed.

A.2.2.1 IOC ENBFunction

Mapping from NRM IOC ENBFunction attributes and associations to SS equivalent MOC ENBFunction attributes

Attribute of IOC ENBFunction	SS Attribute	SS Type	Support	Re
in 3GPP TS 32.762 [4]			Qualifier	Qua
id	id	string	M	N
eNBId	eNBId	unsignedLong	M	1
intraANRSwitch	intraANRSwitch	boolean	CM	N
iRATANRSwitch	iRATANRSwitch	boolean	CM	N
x2BlackList	x2BlackList	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet	СМ	N
x2WhiteList	x2WhiteList	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet	CM	N
x2HOBlackList	x2HOBlackList	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet	CM	N
x2IpAddressList	x2IpAddressList	genericEUTRANNRMAttributeTypes:: ipAddressListType	0	N
tcelDMappingInfoList	tceIDMappingInfoList	genericEUTRANNRMAttributeTypes:: TceIDMappingInfoListType	СМ	М
sharNetTceMappingInfoList	sharNetTceMappingInfoList	genericEUTRANNRMAttributeTypes:: SharNetTceMappingInfo	CM	М
Note: For all conditional qualifiers,	see attribute constraints in 32.762	[4]	•	

A.2.2.2 IOC EUtranGenericCell

Mapping from NRM IOC EUtranGenericCell attributes and associations to SS equivalent MOC EUtranGenericCell attributes

Attribute of IOC EUtranGenericCell in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	М	М	-
cellLocalId	cellLocalId	unsignedShort	М	М	М
cellSize	cellSize	genericEUTRANNRMAttributeTypes:: cellSizeEnumType	M	M	M
plmnIdList	plmnIdList Note: the first plmnId in the SS attribute plmnIdList is the primary PLMN id	genericEUTRANNRMAttributeTypes:: plmnldListType	М	M	М
tac	tac	long	М	M	М
pci	pci	short	М	М	CM
pciList	pciList	genericEUTRANNRMAttributeTypes:: pciListType	СМ	М	M
maximumTransmissionPower	maximumTransmissionPower	short	М	M	CM
referenceSignalPower	referenceSignalPower	short	М	M	М
pb	pb	short	М	М	М
partOfSectorPower	partOfSectorPower	short	CM	М	М
relatedTmaList	relatedTmaList	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet	CO	M	-
relatedAntennaList	relatedAntennaList	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet	СО	M	-
relatedSector	relatedSector	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReference	CM	M	-
operationalState	operationalState	StateManagementIRPOptConstDefs:: OperationalStateTypeOpt	0	M	_
administrativeState	administrativeState	StateManagementIRPOptConstDefs:: AdministrativeStateTypeOpt	0	M	M
availabilityStatus	availabilityStatus	StateManagementIRPOptConstDefs:: AvailabilityStatusTypeOpt	0	M	-
cellResvInfo	cellResvInfo	genericEUTRANNRMAttributeTypes:: cellResvInfoType	CM	М	М
allowedAccessClasses	allowedAccessClasses	genericEUTRANNRMAttributeTypes:: allowedAccessEnumClassesType	M	М	M
isChangeForEnergySavingAllowed	isChangeForEnergySavingAllowed	GenericNetworkResourcesIRPSystem:: AttributeTypes::yesNoType	CM	M	M
Note: For all conditional qualifiers, see att	ribute constraints in 32.762 [4]				

A.2.2.3 IOC ExternalEUtranGenericCell

Mapping from NRM IOC ExternalEUtranGenericCell attributes and associations to SS equivalent MOC ExternalEUtranGenericCell attributes

Attribute of IOC ExternalEUtranGenericCell in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	M	M	-
pci	pci	short	M	M	M
plmnIdList	plmnIdList Note: the first plmnId in the SS attribute plmnIdList is the primary PLMN id	genericEUTRANNRMAttributeTypes:: plmnldListType	М	М	M
cellLocalId	cellLocalId	unsignedShort	M	M	M
eNBId	eNBId	unsignedLong	CM	M	М

A.2.2.4 IOC EUtranCellFDD

Mapping from NRM IOC EUtranCellFDD attributes and associations to SS equivalent MOC EUtranCellFDD attributes

Attribute of IOC EUtranCellFDD in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
earfcnDl	earfcnDl	short	M	М	M
earfcnUl	earfcnUl	short	M	М	М

A.2.2.5 IOC ExternalEUtranCellFDD

Mapping from NRM IOC ExternalEUtranCellFDD attributes and associations to SS equivalent MOC ExternalEUtranCellFDD attributes

Attribute of IOC ExternalEUtranCellFDD in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
earfcnDl	earfcnDl	short	M	M	M
earfcnUl	earfcnUl	short	M	M	М

A.2.2.6 IOC EUtranRelation

Mapping from NRM IOC EUtranRelation attributes and associations to SS equivalent MOC EUtranRelation attributes

Attribute of IOC EUtranRelation in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Qu Qu
id	id	string	М	М	
tCI	tCI	long	0	М	
isRemoveAllowed	isRemoveAllowed	boolean	CM	М	
isHOAllowed	isHOAllowed	boolean	CM	М	
adjacentCell	adjacentCell	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReference	М	M	
isICICInformationSendAllowed	isICICInformationSendAllowed	boolean	CM	M	
isLBAllowed	isLBAllowed	boolean	CM	M	
isESCoveredBy	isESCoveredBy	genericEUTRANNRMAttributeTypes::IsEsCoveredByEnumType	CM	M	
cellIndividualOffset	cellIndividualOffset	genericEUTRANNRMAttributeTypes::qOffsetEnumType	CM	M	
qOffset	qOffset	genericEUTRANNRMAttributeTypes::gOffsetEnumType	CM	M	

A.2.2.7 IOC Link_ENB_ENB

Mapping from NRM IOC Link_ENB_ENB attributes and associations to SS equivalent MOC Link_ENB_ENB attributes

Attribute of IOC Link_ENB_ENB in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier

A.2.2.8 IOC Cdma2000Relation

Mapping from NRM IOC Cdma2000Relation attributes and associations to SS equivalent MOC Cdma2000Relation attributes

Attribute of IOC Cdma2000Relation in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	M	M	-
adjacentSector	adjacentSector	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReference	M	M	-

A.2.2.9 Void

A.2.2.10 IOC ExternalENBFunction

Mapping from NRM IOC ExternalENBFunction attributes and associations to SS equivalent MOC ExternalENBFunction attributes

Attribute of IOC ExternalENBFunction in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	M	M	-
eNBId	eNBId	unsignedLong	М	М	-

A.2.2.11 IOC EUtranCellTDD

Mapping from NRM IOC EUtranCellTDD attributes and associations to SS equivalent MOC EUtranCellTDD attributes

Attribute of IOC EUtranCellTDD in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
earfcn	earfcn	short	М	М	M
sfAssignment	sfAssignment	short	М	М	М
specialSfPatterns	specialSfPatterns	short	M	М	М

A.2.2.12 IOC ExternalEUtranCellTDD

Mapping from NRM IOC ExternalEUtranCellTDD attributes and associations to SS equivalent MOC ExternalEUtranCellTDD attributes

Attribute of IOC ExternalEUtranCelITDD in 3GPP TS 32.762 [4]	SS	SS	Support	Read	Write
	Attribute	Type	Qualifier	Qualifier	Qualifier
earfcn	earfcn	short	M	M	М

A.2.2.13 IOC MCEFunction

Attribute of IOC MCEFunction in	SS	SS	Support	Read	Write
3GPP TS 32.762 [2]	Attribute	Type	Qualifier	Qualifier	Qualifier
id	id	string	M	M	-

A.2.2.14 IOC MBSFNArea

Attribute of IOC MBSFNArea in 3GPP TS 32.762 [2]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	М	М	-
mbsfnAreaId	mbsfnAreaId	short	М	М	M
cellIdList	cellIdList	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet	M	M	M

A.2.2.15 IOC RNFunction

Mapping from NRM IOC RNFunction attributes and associations to SS equivalent MOC RNFunction attributes

Attribute of IOC RNFunction in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	М	M	-
servingCell	servingCell	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReference	M	M	М
candidateDeNBCells	candidateDeNBCells	genericEUTRANNRMAttributeTypes:: EcgiListType	M	M	М

Editor's note: the need of attribute candidate ${\tt DeNBCells}$ is for ${\tt FFS}$.

A.2.2.16 IOC DeNBCapability

Mapping from NRM IOC DeNBCapabilityattributes and associations to SS equivalent MOC DeNBCapabilityattributes

Attribute of IOC DeNBCapabilityin 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	М	М	-
servedRN	servedRN	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet	M	M	М
maxNbrRNAllowed	maxNbrRNAllowed	unsignedShort	М	М	M

A.2.2.17 IOC ExternalRNFunction

Mapping from NRM IOC ExternalRNFunction attributes and associations to SS equivalent MOC ExternalRNFunction attributes

Attribute of IOC RNFunction in	SS	SS	Support	Read	Write
3GPP TS 32.762 [4]	Attribute	Type	Qualifier	Qualifier	Qualifier
id	id	string	М	М	

A.2.2.18 Void

A.2.2.19 IOC QciDscpMapping

Mapping from NRM IOC QciDscpMapping attributes and associations to SS equivalent MOC QciDscpMapping attributes

Attribute of IOC RNFunction in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
id	id	string	М	М	-
qciDscpMappingList	qciDscpMappingList	genericEUTRANNRMAttributeTypes:: qciDscpMappingListType	M	M	M

A.2.2.20 Void

A.2.2.21 IOC CellOutageCompensationInformation

Attribute of IOC SONTargets in 3GPP TS 32.522 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
cocstatus	cellOutageCompens ationStatus	GenericSONPolicyNR MAttributeTypes:: cellOutageCompensati onStatus	М	М	-
isCOCAllowed	isCOCAllowed	Boolean	М	M	M

A.2.2.22 IOC EUtranCellNMCentralizedSON

Mapping from NRM IOC EUtranCellNMCentralizedSON attributes and associations to SS equivalent MOC EUtranCellNMCentralizedSON attributes

Attribute of IOC ENBFunction in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
a1ThresholdRsrp	alThresholdRsrp	unsignedShort	CM	M	M
a1ThresholdRsrq	alThresholdRsrq	unsignedShort	CM	M	M
a2ThresholdRsrp	a2ThresholdRsrp	unsignedShort	CM	M	M
a2ThresholdRsrq	a2ThresholdRsrq	unsignedShort	CM	M	M
a3Offset	a30ffset	short	CM	M	M
a4ThresholdRsrp	a4ThresholdRsrp	unsignedShort	CM	M	M
a4ThresholdRsrq	a4ThresholdRsrq	unsignedShort	CM	M	M
a5Threshold1Rsrp	a5Threshold1Rsrp	unsignedShort	CM	M	M
a5Threshold1Rsrq	a5Threshold1Rsrq	unsignedShort	CM	M	М
b1ThresholdUtraR scp	blThresholdUtraRscp	short	СМ	М	М
blThresholdUtraE cN0	b1ThresholdUtraEcN0	unsignedShort	СМ	М	М
b1ThresholdGeran	b1ThresholdGeran	unsignedShort	CM	M	М
b1ThresholdCdma2 000	b1ThresholdCdma2000	unsignedShort	СМ	М	М
b2Threshold1Rsrp	b2Threshold1Rsrp	unsignedShort	CM	M	М
b2Threshold1Rsrq	b2Threshold1Rsrq	unsignedShort	CM	M	М
b2Threshold2Utra Rscp	b2Threshold2UtraRscp	short	СМ	М	М
b2Threshold2Utra EcN0	b2Threshold2UtraEcN0	unsignedShort	СМ	М	М
b2Threshold2Gera n	b2Threshold2Geran	unsignedShort	СМ	М	М
b2Threshold2Cdma	b2Threshold2Cdma2000	unsignedShort	СМ	М	М
commonChannelPow erOffset	commonChannelPowerOff set	short	СМ	М	М
configurationInd ex	configurationIndex	unsignedShort	СМ	М	М
contentionResolu tionTimer	contentionResolutionT imer	genericEUTRANNRM AttributeTypes:: contentionResolutionTi merEnumType	СМ	М	M
hysteresisEutraA 1	hysteresisEutraA1	unsignedShort	СМ	М	М
hysteresisEutraA 2	hysteresisEutraA2	unsignedShort	СМ	М	М
hysteresisEutraA	hysteresisEutraA3	unsignedShort	CM	М	M

19

Attribute of IOC ENBFunction in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
3					
hysteresisEutraA 4	hysteresisEutraA4	unsignedShort	CM	М	M
hysteresisEutraA 5	hysteresisEutraA5	unsignedShort	СМ	М	M
hysteresisIratB1	hysteresisIratB1	unsignedShort	CM	М	М
hysteresisIratB2	hysteresisIratB2	unsignedShort	CM	М	М
numberOfRaPreamb les	numberOfRaPreambles	genericEUTRANNRM AttributeTypes:: numberOfRaPreamble sEnumType	СМ	М	M
preambleInitialR eceivedTargetPow er	preambleInitialReceiv edTargetPower	genericEUTRANNRM AttributeTypes:: preambleInitialReceive dTargetPowerEnumTy pe	СМ	М	M
preambleTransMax	preambleTransMax	genericEUTRANNRM AttributeTypes:: preambleTransMaxEn umType	СМ	М	M
pMax	pMax	short	CM	M	M
powerRampingStep	powerRampingStep	genericEUTRANNRM AttributeTypes:: powerRampingStepEn umType	СМ	М	M
qHyst	qHyst	genericEUTRANNRM AttributeTypes:: qHystEnumType	СМ	М	M
qOffsetUtra	qOffsetUtra	unsignedShort	CM	М	М
qOffsetGeran	qOffsetGeran	unsignedShort	CM	М	M
qOffsetCdma2000	qOffsetCdma2000	unsignedShort	CM	М	M
qQualMinUtra	qQualMinUtra	unsignedShort	CM	М	M
qRxLevMinEUtraSi b1	qRxLevMinEUtraSib1	short	СМ	М	M
qRxLevMinEUtraSi b3	qRxLevMinEUtraSib3	short	СМ	М	M
qRxLevMinGeran	qRxLevMinGeran	unsignedShort	CM	М	М
qRxLevMinUtra	qRxLevMinUtra	short	CM	М	М
responseWindowSi ze	responseWindowSize	genericEUTRANNRM AttributeTypes:: responseWindowSizeE numType	СМ	М	M
rootSequenceInde	rootSequenceIndex	unsignedShort	CM	М	M

Attribute of IOC ENBFunction in 3GPP TS 32.762 [4]	SS Attribute	SS Type	Support Qualifier	Read Qualifier	Write Qualifier
X					
sIntraSearch	sIntraSearch	unsignedShort	CM	M	M
sizeOfRAPreamble sGroupA	sizeOfRAPreamblesGrou pA	genericEUTRANNRM AttributeTypes:: sizeOfRAPreambleGro upAEnumType	СМ	М	M
timeToTriggerEut raA1	timeToTriggerEutraA1	genericEUTRANNRM AttributeTypes:: timeToTriggerEUtraEn umType	СМ	M	М
timeToTriggerEut raA2	timeToTriggerEutraA2	genericEUTRANNRM AttributeTypes:: timeToTriggerEUtraEn umType	СМ	М	М
timeToTriggerEut raA3	timeToTriggerEutraA3	genericEUTRANNRM AttributeTypes:: timeToTriggerEUtraEn umType	СМ	М	М
timeToTriggerEut raA4	timeToTriggerEutraA4	genericEUTRANNRM AttributeTypes:: timeToTriggerEUtraEn umType	СМ	M	М
timeToTriggerEut raA5	timeToTriggerEutraA5	genericEUTRANNRM AttributeTypes:: timeToTriggerEUtraEn umType	СМ	М	М
timeToTriggerIra tB1	timeToTriggerIratB1	genericEUTRANNRM AttributeTypes:: timeToTriggerEUtraEn umType	СМ	М	М
timeToTriggerIra tB2	timeToTriggerIratB2	genericEUTRANNRM AttributeTypes:: timeToTriggerEUtraEn umType	СМ	М	М
tReselectionCdma 2000	tReselectionCdma2000	unsignedShort	СМ	М	М
tReselectionEUtr a	tReselectionEUtra	unsignedShort	СМ	М	М
tReselectionGera n	tReselectionGeran	unsignedShort	СМ	М	М
tReselectionUtra	tReselectionUtra	unsignedShort	CM	M	M
tStoreUeContext	tStoreUeContext	unsignedShort	CM	M	М

20

A.3 Solution Set definitions

A.3.1 IDL definition structure

Clause A.3.2 defines the MO classes for the E-UTRAN NRM IRP.

A.3.2 IDL specification "EUtranNetworkResourcesNRMDefs.idl"

```
//File:EUtranNetworkResourcesNRMDefs.idl
#ifndef _EUTRANNETWORKRESOURCESNRMDEFS_IDL_
#define _EUTRANNETWORKRESOURCESNRMDEFS_IDL
#include "GenericNetworkResourcesNRMDefs.idl"
#include "EPCResourcesNRMDefs.idl"
#pragma prefix "3gppsa5.org"
* This module defines constants for each MO class name and
\boldsymbol{\star} the attribute names for each defined MO class.
module EUtranNetworkResourcesNRMDefs
    * Definitions for MO class ENBFunction
    * /
    interface ENBFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
        const string CLASS = "ENBFunction";
        // Attribute Names
        const string id= "id";
        const string intraANRSwitch= "intraANRSwitch";
const string iRATANRSwitch= "iRATANRSwitch";
        const string eNBId = "eNBId";
        const string x2BlackList= "x2BlackList";
        const string x2WhiteList= "x2WhiteList";
        const string x2HOBlackList= "x2HOBlackList";
        const string x2IpAddressList= "x2IpAddressList";
        const string tceIDMappingInfoList= "tceIDMappingInfoList";
         const string sharNetTceMappingInfoList= "sharNetTceMappingInfoList";
     * Definitions for MO class RNFunction
    * /
    interface RNFunction: ENBFunction
        const string CLASS = "RNFunction";
        // Attribute Names
        const string servingCell = "servingCell";
        const string candidateDeNBCells = "candidateDeNBCells";
    };
    * Definitions for MO class DeNBCapability
    \verb|interface DeNBCapability: GenericNetworkResourcesNRMDefs:: \\ \verb|ManagedFunction|| \\
        const string CLASS = "DeNBCapability";
        // Attribute Names
        const string id= "id";
        const string servedRN= "servedRN";
        const string maxNbrRNAllowed= "maxNbrRNAllowed";
     * Definitions for MO class ExternalRNFunction
    interface ExternalRNFunction: ExternalENBFunction
        const string CLASS = "ExternalRNFunction";
```

/*

```
// Attribute Names
    //
};
/*
* Definitions for MO class EUtranGenericCell
interface EUtranGenericCell: GenericNetworkResourcesNRMDefs::ManagedFunction
    const string CLASS = "EUtranGenericCell";
    // Attribute Names
    //
    const string id = "id";
    const string cellLocalId = "cellLocalId";
    const string cellSize = "cellSize";
    const string plmnIdList = "plmnIdList";
    const string tac = "tac";
    const string pci = "pci";
    const string pciList = "pciList";
    const string operationalState = "operationalState";
    const string administrativeState = "administrativeState";
const string availabilityStatus = "availabilityStatus";
    const string maximumTransmissionPower = "maximumTransmissionPower";
    const string referenceSignalPower = "referenceSignalPower";
    const string pb = "pb";
    const string partOfSectorPower = "partOfSectorPower";
    const string relatedTmaList = "relatedTmaList";
    const string relatedAntennaList = "relatedAntennaList";
    const string relatedSectorEquipment = "relatedSectorEquipment";
    const string allowedAccessClasses = "allowedAccessClasses";
    const string isChangeForEnergySavingAllowed = "isChangeForEnergySavingAllowed";
};
 * Definitions for MO class ExternalEUtranGenericCell
interface ExternalEUtranGenericCell: GenericNetworkResourcesNRMDefs::ManagedFunction
    const string CLASS = "ExternalEUtranGenericCell";
    // Attribute Names
//
    const string id= "id";
    const string pci= "pci";
    const string plmnIdList = "plmnIdList";
const string cellLocalId = "cellLocalId";
    const string eNBId = "eNBId";
};
 * Definitions for MO class EUtranCellFDD
interface EUtranCellFDD: EUtranGenericCell
    const string CLASS = "EUtranCellFDD";
    // Attribute Names
    const string earfcnDl = "earfcnDl";
    const string earfcnUl = "earfcnUl";
};
* Definitions for MO class ExternalEUtranCellFDD
interface ExternalEUtranCellFDD: ExternalEUtranGenericCell
    const string CLASS = "ExternalEUtranCellFDD";
    // Attribute Names
    //
    const string earfcnDl = "earfcnDl";
    const string earfcnUl = "earfcnUl";
};
```

```
* Definitions for MO class EUtranCellTDD
interface EUtranCellTDD: EUtranGenericCell
    const string CLASS = "EUtranCellTDD";
    // Attribute Names
    const string earfcn = "earfcn";
    const string sfAssignment = "sfAssignment";
    const string specialSfPatterns = "specialSfPatterns";
};
* Definitions for MO class ExternalEUtranCellTDD
interface ExternalEUtranCellTDD: ExternalEUtranGenericCell
    const string CLASS = "ExternalEUtranCellTDD";
    // Attribute Names
    const string earfcn = "earfcn";
};
* Definitions for MO class EUtranRelation
interface EUtranRelation: GenericNetworkResourcesNRMDefs::Top
    const string CLASS = "EUtranRelation";
    // Attribute Names
    //
    const string id= "id";
    const string tCI = "tCI";
    const string isRemoveAllowed = "isRemoveAllowed";
   const string isHOAllowed = "isHOAllowed";
const string adjacentCell = "adjacentCell";
    const string isICICInformationSendAllowed = "isICICInformationSendAllowed";
    const string isLBAllowed = "isLBAllowed";
    const string cellIndividualOffset = "cellIndividualOffset";
   const string qOffset = "qOffset";
};
 * Definitions for MO class Link_ENB_ENB
interface Link ENB ENB: GenericNetworkResourcesNRMDefs::Link
    const string CLASS = "Link ENB ENB";
    // Attribute Names
};
 * Definitions for MO class Cdma2000Relation
* /
interface Cdma2000Relation:GenericNetworkResourcesNRMDefs::Top
    const string CLASS = "Cdma2000Relation";
    // Attribute Names
    //
    const string id= "id";
    const string adjacentSector = "adjacentSector";
};
 * Definitions for MO class ExternalENBFunction
interface ExternalENBFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
    const string CLASS = "ExternalENBFunction";
    // Attribute Names
```

```
const string id = "id";
                const string eNBId = "eNBId";
  };
     * Definitions for MO class MCEFunction
  interface MCEFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
                const string CLASS = "MCEFunction";
                // Attribute Names
               const string id= "id";
  };
      * Definitions for MO class Link_MCE_ENB
  interface Link_MCE_ENB: GenericNetworkResourcesNRMDefs::Link
                const string CLASS = "Link_MCE ENB";
                // Attribute Names
  };
      * Definitions for MO class Link_MCE_MME
  interface Link_MCE_MME: GenericNetworkResourcesNRMDefs::Link
                const string CLASS = "Link_MCE_MME";
                // Attribute Names
  };
      * Definitions for MO class MBSFNArea
  interface MBSFNArea: GenericNetworkResourcesNRMDefs::Top
                const string CLASS = "MBSFNArea";
                // Attribute Names
               const string id= "id";
               const string mbsfnAreaId= "mbsfnAreaId";
const string cellIdList= "cellIdList";
  };
     * Definitions for MO class EnergySavingProperties
  interface EnergySavingProperties: GenericNetworkResourcesNRMDefs::Top
                const string CLASS = "EnergySavingProperties";
                // Attribute Names
                const string energySavingState= "energySavingState";
                const string energySavingControl= "energySavingControl";
  };
  * Definitions for MO class CellOutageCompensationInformation
interface \ \texttt{CellOutageCompensationInformation:} \ \texttt{GenericNetworkResourcesNRMDefs::} \\ \texttt{Top} \ \texttt
            const string CLASS = "CellOutageCompensationInformation";
           // Attribute Names
```

};

{

```
const string cellOutageCompensationStatus = "cellOutageCompensationStatus";
      const string isCOCAllowed =
            "isCOCAllowed":
    * Definitions for MO class EUtranCellNMCentralizedSON
   interface EUtranCellNMCentralizedSON: GenericNetworkResourcesNRMDefs::Top
       const string CLASS = "EUtranCellNMCentralizedSON";
      // Attribute Names
      //
      const string alThresholdRsrp = "alThresholdRsrp";
      const string alThresholdRsrg = "alThresholdRsrg";
      const string a2ThresholdRsrp = "a2ThresholdRsrp";
      const string a2ThresholdRsrq = "a2ThresholdRsrq";
      const string a3Offset = "a3Offset";
      const string a4ThresholdRsrp = "a4ThresholdRsrp";
      const string a4ThresholdRsrq = "a4ThresholdRsrq";
      const string a5Threshold1Rsrp = "a5Threshold1Rsrp";
       const string a5Threshold1Rsrq = "a5Threshold1Rsrq";
      const string b1ThresholdUtraRscp = "b1ThresholdUtraRscp";
      const string b1ThresholdUtraEcN0 = "b1ThresholdUtraEcN0";
      const string b1ThresholdGeran = "b1ThresholdGeran";
      const string b1ThresholdCdma2000 = "b1ThresholdCdma2000";
      const string b2Threshold1Rsrp = "b2Threshold1Rsrp";
      const string b2Threshold1Rsrg = "b2Threshold1Rsrg";
      const string b2Threshold2UtraRscp = "b2Threshold2UtraRscp";
const string b2Threshold2UtraEcN0 = "b2Threshold2UtraEcN0";
      const string b2Threshold2Geran = "b2Threshold2Geran";
      const string b2Threshold2Cdma2000 = "b2Threshold2Cdma2000";
      const string commonChannelPowerOffset = "commonChannelPowerOffset";
      const string configurationIndex = "configurationIndex";
      const string contentionResolutionTimer = "contentionResolutionTimer";
      const string hysteresisEutraA1 = "hysteresisEutraA1";
      const string hysteresisEutraA2 = "hysteresisEutraA2";
      const string hysteresisEutraA3 = "hysteresisEutraA3";
      const string hysteresisEutraA4 = "hysteresisEutraA4";
      const string hysteresisEutraA5 = "hysteresisEutraA5";
      const string hysteresisIratB1 = "hysteresisIratB1";
      const string hysteresisIratB2 = "hysteresisIratB2";
      const string numberOfRaPreambles = "numberOfRaPreambles";
      const string preambleInitialReceivedTargetPower = "preambleInitialReceivedTargetPower";
      const string preambleTransMax = "preambleTransMax";
      const string pMax = "pMax";
      const string powerRampingStep = "powerRampingStep";
       const string qHyst = "qHyst";
      const string qOffsetUtra = "qOffsetUtra";
      const string qoffsetGeran = " qoffsetGeran";
const string qoffsetCdma2000 = "qoffsetCdma2000";
      const string qQualMinUtra = "qQualMinUtra";
      const string qRxLevMinEUtraSib1 = "qRxLevMinEUtraSib1";
      const string qRxLevMinEUtraSib3 = "qRxLevMinEUtraSib3";
      const string qRxLevMinGeran = "qRxLevMinGeran";
const string qRxLevMinUtra = "qRxLevMinUtra";
      const string responseWindowSize = "responseWindowSize";
      const string rootSequenceIndex = "rootSequenceIndex";
      const string sIntraSearch = "sIntraSearch";
      const string sizeOfRAPreamblesGroupA = "sizeOfRAPreamblesGroupA";
       const string timeToTriggerEutraA1 = "timeToTriggerEutraA1";
      const string timeToTriggerEutraA2 = "timeToTriggerEutraA2";
      const string timeToTriggerEutraA3 = "timeToTriggerEutraA3";
      const string timeToTriggerEutraA4 = "timeToTriggerEutraA4";
       const string timeToTriggerEutraA5 = "timeToTriggerEutraA5";
      const string timeToTriggerIratB1 = "timeToTriggerIratB1";
      const string timeToTriggerIratB2 = "timeToTriggerIratB2";
      const string tReselectionCdma2000 = "tReselectionCdma2000";
      const string tReselectionEUtra = "tReselectionEUtra";
      const string tReselectionGeran = "tReselectionGeran";
      const string tReselectionUtra = "tReselectionUtra";
      const string tStoreUeContext = "tStoreUeContext";
module genericEUTRANNRMAttributeTypes
```

```
enum CellSizeEnumType
      verysmall,
      small,
      medium,
      large
  enum AllowedAccessClassesValues
  EmergencyCall,
  ForPLMNUse,
  SecurityServices,
  PublicUtilities,
  EmergencyServices,
  PLMNStaff
 typedef sequence < AllowedAccessClassesValues,6> AllowedAccessClasses
  struct PlmnIdType
      short mcc;
      short mnc;
  const short PLMNID LIST LENGTH = 6;
  typedef sequence<PlmnIdType > plmnIdListType;
  const short NO OF PCIS = 504;
  typedef sequence<short,NO_OF_PCIS> pciListType;
  typedef sequence<string> ipAddressListType;
  enum CellResvInfoType
      reservedCell,
      nonReservedCell
  };
  struct QciDscpMappingType
      short qci;
      short dscp;
  typedef sequence<QciDscpMappingType> QciDscpMappingListType;
  struct EcgiType
      short mcc;
      short mnc:
      unsignedlong eci
  typedef sequence <EcgiType> EcgiListType;
enum isEsCoveredByEnumType
  no,
  partial,
  yes
};
enum yesNoType
yes
};
  no,
  struct TceIDMappingInfo
      short tceID;
      string tceIPAddr;
  typedef sequence<TceIDMappingInfo> TceIDMappingInfoListType;
  struct SharNetTceMappingInfo
    long PLMNId
```

n60,

```
short tceID;
     string tceIPAddr;
    };
    typedef sequence<SharNetTceMappingInfo> SharNetTceMappingInfoListType;
enum CellOutageCompensationState
   cOCActivating,
   cOCActive,
   cOCDeactivating,
   cOCDeactive
};
enum qOffsetEnumType
   dB-24,
   dB-22,
   dB-20,
   dB-18,
   dB-16,
   dB-14,
   dB-12,
   dB-10,
   dB-8,
   dB-6,
   dB-5,
   dB-4,
   dB-3,
   dB-2,
   dB-1,
   dB0,
   dB1,
   dB2,
   dB3,
   dB4,
   dB5,
   dB6,
   dB8,
   dB10,
   dB12,
   dB14,
   dB16,
   dB18,
   dB20,
   dB22,
   dB24
};
enum contentionResolutionTimerEnumType
{
   sf8,
  sf16,
  sf24,
  sf32,
  sf40,
   sf48,
   sf56,
   sf64
};
enum numberOfRaPreamblesEnumType
   n4,
   n8,
   n12,
   n16,
   n20,
   n24,
   n28,
   n32,
   n36,
   n40,
   n44,
   n48,
   n52,
   n56,
```

```
n64
};
\verb"enum preambleInitialReceivedTargetPowerEnumType"
   dBm-120,
   dBm-118,
   dBm-116,
   dBm-114,
   dBm-112,
   dBm-110,
   dBm-108,
   dBm-106,
   dBm-104,
   dBm-102,
   dBm-100,
   dBm-98,
   dBm-96,
   dBm-94,
   dBm-92,
   dBm-90
};
enum preambleTransMaxEnumType
   n3,
   n4,
   n5,
   n6,
   n7,
   n8,
   n10,
   n20,
   n50,
   n100,
   n200
};
enum powerRampingStepEnumType
{
   dB0,
   dB2,
   dB4,
   dB6
};
enum qHystEnumType
   dB0,
   dB1,
   dB2,
   dB3,
   dB4,
   dB5,
   dB6,
   dB8,
   dB10,
   dB12,
   dB14,
   dB16,
   dB18,
   dB20,
   dB22,
   dB24
};
enum responseWindowSizeEnumType
   sf2,
   sf3,
   sf4,
   sf5,
   sf6,
   sf7,
   sf8,
   sf10
};
```

```
enum sizeOfRAPreambleGroupAEnumType
{
  n4,
   n8,
   n12,
   n16,
   n20,
   n24,
   n28,
   n32,
   n36,
   n40,
   n44,
   n48,
   n52,
  n56,
  n60,
};
enum timeToTriggerEUtraEnumType
   ms0,
   ms40,
   ms64,
   ms80,
   ms100,
   ms128,
   ms160,
   ms256,
   ms320,
   ms480,
   ms512,
   ms640,
  ms1024,
   ms1280,
   ms2560,
   ms5120
};
   typedef sequence<string> DnList;
struct CellOutageCompensationStatus
   CellOutageCompensationState cellOutageCompensationState;
   DnList errorList;
   };
};
```

#endif // _EUTRANNETWORKRESOURCESNRMDEFS_IDL_

Annex B (normative): XML Definitions

This annex contains the XML Definitions for the E-UTRAN NRM IRP as it applies to Itf-N, in accordance with UTRAN NRM IRP IS definitions [4].

B.1 Architectural features

The overall architectural feature of E-UTRAN Network Resources IRP is specified in 3GPP TS 32.762 [4]. This clause specifies features that are specific to the Schema definitions.

The XML definitions of this document specify the schema for a configuration content.

When using the XML definitions for a configuration file transfer with the Bulk CM IRP, using either CORBA Solution Set of 3GPP TS 32.616 [7] or SOAP Solution Set of 3GPP TS 32.616 [7], the basic part of the XML file format definition is provided by 3GPP TS 32.616 [7]. The XML definitions of this document provide the schema for the configuration content to be included in such a configuration file.

When using the XML definitions with a SOAP Solution Set of any Interface IRP that perform operations on managed objects, for example the Basic CM IRP SOAP SS of 3GPP TS 32.606 [6], the XML definitions of this document provides the schema for the configuration content operated on by the interface IRP. Such configuration content can be name of managed object and, if applicable, IOC attributes.

B.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

B.2 Mapping

B.2.1 General mapping

An IOC maps to an XML element of the same name as the IOC's name in the IS. An IOC attribute maps to a subelement of the corresponding IOC's XML element, and the name of this sub-element is the same as the attribute's name in the IS.

B.2.2 Information Object Class (IOC) mapping

Not present in the current version of this specification.

B.3 Solution Set definitions

B.3.1 XML definition structure

The overall description of the file format of configuration data XML files is provided by 3GPP TS 32.616 [7].

Annex B.3.3 of the present document defines the NRM-specific XML schema eutranNrm.xsd for the E-UTRAN Network Resources IRP NRM defined in 3GPP TS 32.762 [4].

XML schema eutranNrm.xsd explicitly declares NRM-specific XML element types for the related NRM.

The definition of those NRM-specific XML element types complies with the generic mapping rules defined in 3GPP TS 32.616 [7].

B.3.2 Graphical Representation

Not present in the current version of this specification.

B.3.3 XML schema "eutranNrm.xsd"

```
<?xml version="1.0" encoding="UTF-8"?>
<!--
 3GPP TS 32.766 E-UTRAN Network Resource Model IRP
 XML schema definition
 eutranNrm.xsd
<schema xmlns="http://www.w3.org/2001/XMLSchema"</pre>
xmlns:xn="http://www.3gpp.org/ftp/specs/archive/32_series/32.626#genericNrm"
xmlns:en="http://www.3gpp.org/ftp/specs/archive/32_series/32.766#eutranNrm"
xmlns:epc="http://www.3gpp.org/ftp/specs/archive/32_series/32.756#epcNrm"
xmlns:un="http://www.3gpp.org/ftp/specs/archive/32_series/32.646#utranNrm"
xmlns:gn="http://www.3gpp.org/ftp/specs/archive/32_series/32.656#geranNrm"
xmlns:sm="http://www.3gpp.org/ftp/specs/archive/32 series/32.676#stateManagementIRP"
xmlns:sp="http://www.3gpp.org/ftp/specs/archive/32 series/32.526#sonPolicyNrm"
targetNamespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.766#eutranNrm"
elementFormDefault="qualified">
 <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.626#genericNrm"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.756#epcNrm"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.646#utranNrm"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.656#geranNrm"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32 series/32.676#stateManagementIRP"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/32 series/32.526#sonPolicyNrm"/>
  <complexType name="IpAddressList">
   <sequence>
     <element name="ipAddress" type="string" minOccurs="0" maxOccurs="unbounded"/>
   </sequence>
  </complexType>
  <simpleType name="EnbId">
   <restriction base="unsignedLong">
     <maxInclusive value="268435455"/>
   </restriction>
  </simpleType>
  <simpleType name="Eci">
    <restriction base="unsignedLong">
      <maxInclusive value="268435455"/>
    </restriction>
  </simpleType>
<simpleType name="CellLocalId">
   <restriction base="unsignedShort">
     <maxInclusive value="255"/>
   </restriction>
  </simpleType>
  <simpleType name="cellSize">
   <restriction base="string">
     <enumeration value="verysmall"/>
     <enumeration value="small"/>
     <enumeration value="medium"/>
     <enumeration value="large"/>
   </restriction>
  </simpleType>
  <simpleType name="allowedAccessClassesElementType">
    <restriction base="string">
      <enumeration value="EmergencyCall"/>
      <enumeration value="ForPLMNUse"/>
      <enumeration value="SecurityServices"/>
      <enumeration value="PublicUtilities"/>
      <enumeration value="EmergencyServices"/>
      <enumeration value="PLMNStaff"/>
    </restriction>
</simpleType>
  <complexType name="allowedAccessClassesType">
    <sequence minOccurs="0" maxOccurs="6">
      <element name="allowedAccessClassesElement" type="en:allowedAccessClassesElementType"/>
    </sequence>
  </complexType>
  <complexType name="PLMNId">
   <sequence>
     <element name="mcc" type="short"/>
     <element name="mnc" type="short"/>
   </sequence>
  </complexType>
  <complexType name="PLMNIdList">
     <element name="pLMNId" type="en:PLMNId" maxOccurs="6"/>
```

```
<!-- The first pLMNId of the pLMNIdList is primary PLMN id -->
 </sequence>
</complexType>
<complexType name="EcgiList">
 <sequence>
   <element name="plmnId" type="en:PLMNId" minOccurs="0"/>
   <element name="eci" type="en:Eci" minOccurs="0"/>
 </sequence>
</complexType>
<simpleType name="Pci">
 <restriction base="unsignedShort">
   <maxInclusive value="503"/>
   <!-- Minimum value is 0, maximum value is 3x167+2=503 -->
 </restriction>
</simpleType>
<complexType name="PciList">
 <sequence>
   <element name="pci" type="en:Pci" maxOccurs="504"/>
 </sequence>
</complexType>
<simpleType name="cellResvInfoTyoe">
 <restriction base="string">
   <enumeration value="reservedCell"/>
   <enumeration value="nonReservedCell"/>
 </restriction>
</simpleType>
<simpleType name="mbsfnAreaIdType">
  <restriction base="unsignedLong">
 <maxInclusive value="255"/>
  </restriction>
 </simpleType>
<complexType name="QciDscpMappingType">
 <sequence>
   <element name="qci" type="short"/>
   <element name="dscp" type="short"/>
 </sequence>
</complexType>
<complexType name="QciDscpMappingListType">
 <sequence>
   <element name="QciDscpMappingPair" type="en:QciDscpMappingType"/>
 </sequence>
</complexType>
<simpleType name="isEsCoveredByEnumType">
 <restriction base="string">
   <enumeration value="no"/>
   <enumeration value="partial"/>
   <enumeration value="yes"/>
 </restriction>
</simpleType>
<simpleType name="yesNoType">
 <restriction base="string">
   <enumeration value="yes"/>
   <enumeration value="no"/>
 </restriction>
</simpleType>
<simpleType name="QOffsetEnumType">
 <restriction base="string">
   <enumeration value="dB-24"/>
   <enumeration value="dB-22"/>
   <enumeration value="dB-20"/>
   <enumeration value="dB-18"/>
   <enumeration value="dB-16"/>
   <enumeration value="dB-14"/>
   <enumeration value="dB-12"/>
   <enumeration value="dB-10"/>
   <enumeration value="dB-8"/>
   <enumeration value="dB-6"/>
   <enumeration value="dB-5"/>
   <enumeration value="dB-4"/>
   <enumeration value="dB-3"/>
   <enumeration value="dB-2"/>
   <enumeration value="dB-1"/>
   <enumeration value="dB0"/>
   <enumeration value="dB1"/>
   <enumeration value="dB2"/>
   <enumeration value="dB3"/>
   <enumeration value="dB4"/>
   <enumeration value="dB5"/>
```

```
<enumeration value="dB6"/>
   <enumeration value="dB8"/>
   <enumeration value="dB10"/>
   <enumeration value="dB12"/>
   <enumeration value="dB14"/>
   <enumeration value="dB16"/>
   <enumeration value="dB18"/>
   <enumeration value="dB20"/>
   <enumeration value="dB22"/>
   <enumeration value="dB24"/>
 </restriction>
</simpleType>
<simpleType name="ContentionResolutionTimerEnumType">
 <restriction base="string">
   <enumeration value="sf8"/>
   <enumeration value="sf16"/>
   <enumeration value="sf24"/>
   <enumeration value="sf32"/>
   <enumeration value="sf40"/>
   <enumeration value="sf48"/>
   <enumeration value="sf56"/>
   <enumeration value="sf64"/>
 </restriction>
</simpleType>
<simpleType name="NumberOfRaPreamblesEnumType">
 <restriction base="string">
   <enumeration value="n4"/>
   <enumeration value="n8"/>
   <enumeration value="n12"/>
   <enumeration value="n16"/>
   <enumeration value="n20"/>
   <enumeration value="n24"/>
   <enumeration value="n28"/>
   <enumeration value="n32"/>
   <enumeration value="n36"/>
   <enumeration value="n40"/>
   <enumeration value="n44"/>
   <enumeration value="n48"/>
   <enumeration value="n52"/>
   <enumeration value="n56"/>
   <enumeration value="n60"/>
   <enumeration value="n64"/>
 </restriction>
</simpleType>
<simpleType name="PreambleInitialReceivedTargetPowerEnumType">
 <restriction base="string">
   <enumeration value="dBm-120"/>
   <enumeration value="dBm-118"/>
   <enumeration value="dBm-116"/>
   <enumeration value="dBm-114"/>
   <enumeration value="dBm-112"/>
   <enumeration value="dBm-110"/>
   <enumeration value="dBm-108"/>
   <enumeration value="dBm-106"/>
   <enumeration value="dBm-104"/>
   <enumeration value="dBm-102"/>
   <enumeration value="dBm-100"/>
   <enumeration value="dBm-98"/>
   <enumeration value="dBm-96"/>
   <enumeration value="dBm-94"/>
   <enumeration value="dBm-92"/>
   <enumeration value="dBm-90"/>
 </restriction>
</simpleType>
<simpleType name="PreambleTransMaxEnumType">
 <restriction base="string">
   <enumeration value="n3"/>
   <enumeration value="n4"/>
   <enumeration value="n5"/>
   <enumeration value="n6"/>
   <enumeration value="n7"/>
   <enumeration value="n8"/>
   <enumeration value="n10"/>
   <enumeration value="n20"/>
   <enumeration value="n50"/>
   <enumeration value="n100"/>
   <enumeration value="n200"/>
 </restriction>
```

```
</simpleType>
<simpleType name="PowerRampingStepEnumType">
 <restriction base="string">
   <enumeration value="dB0"/>
   <enumeration value="dB2"/>
   <enumeration value="dB4"/>
   <enumeration value="dB6"/>
 </restriction>
</simpleType>
<simpleType name="QHystEnumType">
 <restriction base="string">
   <enumeration value="dB0"/>
   <enumeration value="dB1"/>
   <enumeration value="dB2"/>
   <enumeration value="dB3"/>
   <enumeration value="dB4"/>
   <enumeration value="dB5"/>
   <enumeration value="dB6"/>
   <enumeration value="dB8"/>
   <enumeration value="dB10"/>
   <enumeration value="dB12"/>
   <enumeration value="dB14"/>
   <enumeration value="dB16"/>
   <enumeration value="dB18"/>
   <enumeration value="dB20"/>
   <enumeration value="dB22"/>
   <enumeration value="dB24"/>
  </restriction>
</simpleType>
<simpleType name="ResponseWindowSizeEnumType">
 <restriction base="string">
   <enumeration value="sf2"/>
   <enumeration value="sf3"/>
   <enumeration value="sf4"/>
   <enumeration value="sf5"/>
   <enumeration value="sf6"/>
   <enumeration value="sf7"/>
   <enumeration value="sf8"/>
   <enumeration value="sf10"/>
 </restriction>
</simpleType>
<simpleType name="SizeOfRAPreambleGroupAEnumType">
 <restriction base="string">
   <enumeration value="n4"/>
   <enumeration value="n8"/>
   <enumeration value="n12"/>
   <enumeration value="n16"/>
   <enumeration value="n20"/>
   <enumeration value="n24"/>
   <enumeration value="n28"/>
   <enumeration value="n32"/>
   <enumeration value="n36"/>
   <enumeration value="n40"/>
   <enumeration value="n44"/>
   <enumeration value="n48"/>
   <enumeration value="n52"/>
   <enumeration value="n56"/>
   <enumeration value="n60"/>
 </restriction>
</simpleType>
<simpleType name="TimeToTriggerEUtraEnumType">
 <restriction base="string">
   <enumeration value="ms0"/>
   <enumeration value="ms40"/>
   <enumeration value="ms64"/>
   <enumeration value="ms80"/>
   <enumeration value="ms100"/>
   <enumeration value="ms128"/>
   <enumeration value="ms160"/>
   <enumeration value="ms256"/>
   <enumeration value="ms320"/>
   <enumeration value="ms480"/>
   <enumeration value="ms512"/>
   <enumeration value="ms640"/>
   <enumeration value="ms1024"/>
   <enumeration value="ms1280"/>
   <enumeration value="ms2560"/>
   <enumeration value="ms5120"/>
```

```
</restriction>
</simpleType>
<simpleType name="ThresholdRsrpRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="97"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdRsrqRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="34"/>
  </restriction>
</simpleType>
<simpleType name="OffsetRangeType">
  <restriction base="short">
    <minInclusive value="-30"/>
    <maxInclusive value="30"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdUtraRscpRangeType">
  <restriction base="short">
    <minInclusive value="-5"/>
    <maxInclusive value="91"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdUtraEcN0RangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="49"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdGeranRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="63"/>
  </restriction>
</simpleType>
<simpleType name="ThresholdCDMA2000RangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="63"/>
  </restriction>
</simpleType>
<simpleType name="CommonChannelPowerOffsetRangeType">
  <restriction base="short">
    <minInclusive value="-350"/>
    <maxInclusive value="150"/>
  </restriction>
</simpleType>
<simpleType name="ConfigurationIndexRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="63"/>
  </restriction>
</simpleType>
<simpleType name="HysteresisRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="30"/>
  </restriction>
</simpleType>
<simpleType name="PMaxRangeType">
  <restriction base="short">
    <minInclusive value="-30"/>
    <maxInclusive value="33"/>
  </restriction>
</simpleType>
<simpleType name="QOffsetRangeType">
  <restriction base="short">
    <minInclusive value="-15"/>
    <maxInclusive value="15"/>
  </restriction>
</simpleType>
<simpleType name="QQualMinUtraRangeType">
  <restriction base="short">
    <minInclusive value="-24"/>
    <maxInclusive value="0"/>
```

```
</restriction>
</simpleType>
<simpleType name="QRxLevMinEUtraRangeType">
  <restriction base="short">
    <minInclusive value="-77"/>
    <maxInclusive value="-22"/>
  </restriction>
</simpleType>
<simpleType name="QRxLevMinGeranRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="63"/>
  </restriction>
</simpleType>
<simpleType name="QRxLevMinUtraRangeType">
  <restriction base="short">
    <minInclusive value="-60"/>
    <maxInclusive value="-13"/>
  </restriction>
</simpleType>
<simpleType name="RootSequenceIndexRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="837"/>
  </restriction>
</simpleType>
<simpleType name="SIntraSearchRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="31"/>
  </restriction>
</simpleType>
<simpleType name="TReselectionRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="7"/>
  </restriction>
</simpleType>
<simpleType name="TStoreUeContextRangeType">
  <restriction base="unsignedShort">
    <minInclusive value="0"/>
    <maxInclusive value="1023"/>
  </restriction>
</simpleType>
<complexType name="TceIDMappingInfo">
 <sequence>
   <element name="tceID" type="short"/>
   <element name="tceIPAddr" type="string"/>
 </sequence>
</complexType>
<complexType name="TceIDMappingInfoList">
   <element name="tceIDMappingInfo" type="en:TceIDMappingInfo" minOccurs="0"/>
 </sequence>
</complexType>
<complexType name="SharNetTceMappingInfo">
    <element name="pLMNId"type="long"/>
    <element name="tceID" type="short"/>
    <element name="tceIPAddr" type="string"/>
  </sequence>
</complexType>
<complexType name="SharNetTceMappingInfo">
  <sequence>
    <element name="sharNetTceMappingInfo" type="en:SharNetTceMappingInfo" minOccurs="0"/>
  </sequence>
</complexType>
<simpleType name="cellOutageCompensationState">
 <restriction base="string">
   <enumeration value="cOCActivating"/>
   <enumeration value="cOCActive"/>
   <enumeration value="cOCDeactivating"/>
   <enumeration value="cOCDeactive"/>
 </restriction>
</simpleType>
<complexType name="cellOutageCompensationStatus">
```

```
<sequence>
      <element name="cellOutageCompensationState" type="en:cellOutageCompensationState"/>
      <element name="errorList" type="xn:dnList"/>
    </sequence>
  </complexType>
  <element name="CellOutageCompensationInformation">
    <complexType>
      <complexContent>
        <extension base="xn:NrmClass">
          <sequence>
             <element name="attributes">
               <complexType>
                 <a11>
                   <element name="cellOutageCompensationStatus"</pre>
                             type="en:cellOutageCompensationStatus"/>
                   <element name="isCOCAllowed" type="boolean"/>
                 </all>
               </complexType>
             </element>
           </sequence>
        </extension>
      </complexContent>
    </complexType>
  </element>
  <element name="EUtranCellNMCentralizedSON">
    <complexType>
      <complexContent>
        <extension base="xn:NrmClass">
           <sequence>
             <element name="attributes">
               <complexType>
                 <all>
                   <element name="alThresholdRsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
                   <element name="alThresholdRsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>
                   <element name="a2ThresholdRsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
<element name="a2ThresholdRsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>
                   <element name="a3Offset" type="en:OffsetRangeType" minOccurs="0"/>
                   <element name="a4ThresholdRsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
                   <element name="a4ThresholdRsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>
                   <element name="a5Threshold1Rsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
                   <element name="a5Threshold1Rsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>
                   <element name="b1ThresholdUtraRscp" type="en:ThresholdUtraRscpRangeType"</pre>
minOccurs="0"/>
                   <element name="b1ThresholdUtraEcN0" type="en:ThresholdUtraEcN0RangeType"</pre>
minOccurs="0"/>
                   <element name="b1ThresholdGeran" type="en:ThresholdGeranRangeType" minOccurs="0"/>
                   <element name="b1ThresholdCdma2000" type="en:ThresholdCDMA2000RangeType"</pre>
minOccurs="0"/>
                   <element name="b2Threshold1Rsrp" type="en:ThresholdRsrpRangeType" minOccurs="0"/>
                   <element name="b2Threshold1Rsrq" type="en:ThresholdRsrqRangeType" minOccurs="0"/>
                   <element name="b2Threshold2UtraRscp" type="en:ThresholdUtraRscpRangeType"</pre>
minOccurs="0"/>
                   <element name="b2Threshold2UtraEcN0" type="en:ThresholdUtraEcN0RangeType"</pre>
minOccurs="0"/>
                   <element name="b2Threshold2Geran" type="en:ThresholdGeranRangeType"</pre>
minOccurs="0"/>
                   <element name="b2Threshold2Cdma2000" type="en:ThresholdCDMA2000RangeType"</pre>
minOccurs="0"/>
                   <element name="commonChannelPowerOffset"</pre>
type="en:CommonChannelPowerOffsetRangeType" minOccurs="0"/>
                   <element name="configurationIndex" type="en:ConfigurationIndexRangeType"</pre>
minOccurs="0"/>
                   <element name="contentionResolutionTimer"</pre>
type="en:ContentionResolutionTimerEnumType" minOccurs="0"/>
                   <element name="hysteresisEutraA1" type="en:HysteresisRangeType" minOccurs="0"/>
                   <element name="hysteresisEutraA2" type="en:HysteresisRangeType" minOccurs="0"/>
<element name="hysteresisEutraA3" type="en:HysteresisRangeType" minOccurs="0"/>

                   <element name="hysteresisEutraA4" type="en:HysteresisRangeType" minOccurs="0"/>
                   <element name="hysteresisEutraA5" type="en:HysteresisRangeType" minOccurs="0"/>
                   <element name="hysteresisIratB1" type="en:HysteresisRangeType" minOccurs="0"/>
                   <element name="hysteresisIratB2" type="en:HysteresisRangeType" minOccurs="0"/>
                   <element name="numberOfRaPreambles" type="en:NumberOfRaPreamblesEnumType"</pre>
minOccurs="0"/>
                   <element name="preambleInitialReceivedTargetPower"</pre>
type="en:PreambleInitialReceivedTargetPowerEnumType" minOccurs="0"/>
```

```
<element name="preambleTransMax" type="en:PreambleTransMaxEnumType"</pre>
minOccurs="0"/>
                  <element name="pMax" type="en:PMaxRangeType" minOccurs="0"/>
                  <element name="powerRampingStep" type="en:PowerRampingStepEnumType"</pre>
minOccurs="0"/>
                   <element name="qHyst" type="en:PreambleInitialReceivedTargetPowerEnumType"</pre>
minOccurs="0"/>
                  <element name="qOffsetUtra" type="en:QOffsetRangeType" minOccurs="0"/>
                  <element name="qOffsetGeran" type="en:QOffsetRangeType" minOccurs="0"/>
                  <element name="qOffsetCdma2000" type="en:QOffsetRangeType" minOccurs="0"/>
                  <element name="qQualMinUtra" type="en:QQualMinUtraRangeType" minOccurs="0"/>
                  <element name="qRxLevMinEUtraSib1" type="en:QRxLevMinEUtraRangeType"</pre>
minOccurs="0"/>
                  <element name="qRxLevMinEUtraSib3" type="en:QRxLevMinEUtraRangeType"</pre>
minOccurs="0"/>
                  <element name="qRxLevMinGeran" type="en:QRxLevMinGeranRangeType" minOccurs="0"/>
                  <element name="qRxLevMinUtra" type="en:QRxLevMinUtraRangeType" minOccurs="0"/>
                  <element name="responseWindowSize" type="en:ResponseWindowSizeEnumType"</pre>
minOccurs="0"/>
                  <element name="rootSequenceIndex" type="en:RootSequenceIndexRangeType"</pre>
minOccurs="0"/>
                  <element name="sIntraSearch" type="en:SIntraSearchRangeType" minOccurs="0"/>
                  <element name="sizeOfRAPreamblesGroupA" type="en:SizeOfRAPreambleGroupAEnumType"</pre>
minOccurs="0"/>
                  <element name="timeToTriggerEutraA1" type="en:TimeToTriggerEUtraEnumType"</pre>
minOccurs="0"/>
                  <element name="timeToTriggerEutraA2" type="en:TimeToTriggerEUtraEnumType"</pre>
minOccurs="0"/>
                  <element name="timeToTriggerEutraA3" type="en:TimeToTriggerEUtraEnumType"</pre>
minOccurs="0"/>
                  <element name="timeToTriggerEutraA4" type="en:TimeToTriggerEUtraEnumType"</pre>
minOccurs="0"/>
                  <element name="timeToTriggerEutraA5" type="en:TimeToTriggerEUtraEnumType"</pre>
minOccurs="0"/>
                  <element name="timeToTriggerIratB1" type="en:TimeToTriggerEUtraEnumType"</pre>
minOccurs="0"/>
                  <element name="timeToTriqqerIratB2" type="en:TimeToTriqqerEUtraEnumType"</pre>
minOccurs="0"/>
                  <element name="tReselectionCdma2000" type="en:TReselectionRangeType"</pre>
minOccurs="0"/>
                  <element name="tReselectionEUtra" type="en:TReselectionRangeType" minOccurs="0"/>
                  <element name="tReselectionGeran" type="en:TReselectionRangeType" minOccurs="0"/>
                  <element name="tReselectionUtra" type="en:TReselectionRangeType" minOccurs="0"/>
                  <element name="tStoreUeContext" type="en:TStoreUeContextRangeType" minOccurs="0"/>
                </all>
              </complexType>
            </element>
          </sequence>
        </extension>
      </complexContent>
    </complexType>
  </element>
 <element name="ENBFunction" substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
               <element name="userLabel" type="string"/>
               <element name="intraANRSwitch" type="boolean" minOccurs="0"/>
               <element name="iRATANRSwitch" type="boolean" minOccurs="0"/>
               <element name="enbId" type="en:EnbId" minOccurs="0"/>
               <element name="x2BlackList" type="xn:dnList" minOccurs="0"/>
               <element name="x2WhiteList" type="xn:dnList" minOccurs="0"/>
               <element name="x2HOBlackList" type="xn:dnList" minOccurs="0"/>
               <element name="x2IpAddressList" type="string" minOccurs="0"/>
                  <element name="tceIDMappingInfoList" type="en:TceIDMappingInfoList"</pre>
minOccurs="0"/>
                <element name="sharNetTceMappingInfoList" type="en:SharNetTceMappingInfoList"</pre>
minOccurs="0"/>
               <!-- linkList attribute is to be added when defined in the IS -->
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
```

```
<element ref="en:EUtranCellFDD"/>
           <element ref="en:EUtranCellTDD"/>
           <element ref="epc:EP RP EPS"/>
           <element ref="en:ENBFunctionOptionallyContainedNrmClass"/>
           <element ref="en:DeNBCapability"/>
           <element ref="xn:VsDataContainer"/>
          </choice>
          <choice minOccurs="0" maxOccurs="1">
           <element ref="sp:ESPolicies"/>
          </choice>
        </sequence>
      </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="RNFunction" substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
   <complexType>
     <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
           <complexType>
             <all>
               <element name="userLabel" type="string"/>
               <element name="servingCell" type="xn:dn"/>
             </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
           <element ref="epc:EP_RP_EPS"/>
           <element ref="en:RNFunctionOptionallyContainedNrmClass"/>
           <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="DeNBCapability">
   <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
           <complexType>
             <all>
               <element name="userLabel" type="string"/>
               <element name="servedRN" type="xn:dnList" minOccurs="0"/>
               <element name="maxNbrRNAllowed" type="unsignedShort"/>
             </all>
           </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
   </complexType>
   </element>
 <element name="ExternalRNFunction"</pre>
substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
   <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
           <complexType>
             <all>
               <element name="userLabel" type="string"/>
               <element name="candidateDeNBCells" type="en:EcgiList" minOccurs="0"/>
             </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
           <element ref="epc:EP_RP_EPS"/>
           <element ref="en:ExternalRNFunctionOptionallyContainedNrmClass"/>
           <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
       </extension>
```

```
</complexContent>
 </complexType>
</element>
<element name="ExternalENBFunction" substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
 <complexType>
   <complexContent>
     <extension base="xn:NrmClass">
      <sequence>
        <element name="attributes" minOccurs="0">
          <complexType>
           <all>
             <element name="userLabel" type="string"/>
             <element name="enbId" type="en:EnbId" minOccurs="0"/>
             <!-- Attributes are to be added when defined in the IS -->
            </all>
          </complexType>
        </element>
        <choice minOccurs="0" maxOccurs="unbounded">
          <element ref="en:ExternalEUtranCellFDD"/>
          <element ref="en:ExternalEUtranCellTDD"/>
          <element ref="en:ExternalENBFunctionOptionallyContainedNrmClass"/>
          <element ref="xn:VsDataContainer"/>
        </choice>
        <choice minOccurs="0" maxOccurs="1">
          <element ref="sp:InterRatEsPolicies"/>
        </chaice>
       </sequence>
     </extension>
   </complexContent>
 </complexType>
</element>
<element name="EUtranCellFDD">
 <complexType>
   <complexContent>
     <extension base="xn:NrmClass">
      <sequence>
        <element name="attributes" minOccurs="0">
          <complexType>
            <a11>
             <!-- Inherited attributes from EUtranGenericCell-->
             <element name="userLabel" type="string"/>
             <element name="cellLocalId" type="en:CellLocalId"/>
             <element name="cellSize" type="en:cellSize"/>
             <element name="pLMNIdList" type="en:PLMNIdList"/>
             <element name="tac" type="long"/>
             <element name="pci" type="en:Pci"/>
             <element name="pciList" type="en:PciList" minOccurs="0"/>
             <element name="maximumTransmissionPower" type="short"/>
             <element name="partOfSectorPower" type="short" minOccurs="0"/>
             <element name="referenceSignalPower" type="short"/>
             <element name="pb" type="short"/>
             <element name="relatedTmaList" type="xn:dnList" minOccurs="0"/>
             <element name="relatedAntennaList" type="xn:dnList" minOccurs="0"/>
             <element name="relatedSectorEquipment" type="xn:dn" minOccurs="0"/>
<element name="operationalState" type="sm:operationalStateType" minOccurs="0"/>
             <element name="administrativeState" type="sm:administrativeStateType"</pre>
                         minOccurs="0"/>
             <element name="availabilityStatus" type="sm:availabilityStatusType"</pre>
                         minOccurs="0"/>
             <element name="allowedAccessClasses" type="en:allowedAccessClassesType"/>
                 <element name="cellResvInfo" type="en:cellResvInfoType" minOccurs="0"/>
                 <element name="isChangeForEnergySavingAllowed"</pre>
                          type="en:yesNoType" minOccurs="0"/>
             <!-- End of inherited attributes from EUtranGenericCell -->
             <element name="earfcnDl" type="short"/>
             <element name="earfcnUl" type="short"/>
            </all>
          </complexType>
        </element>
        <choice minOccurs="0" maxOccurs="unbounded">
          <element ref="en:EUtranRelation"/>
          <element ref="en:Cdma2000Relation"/>
          <element ref="gn:GsmRelation"/>
          <element ref="un:UtranRelation"/>
          <element ref="en:EUtranCellFDDOptionallyContainedNrmClass"/>
          <element ref="xn:VsDataContainer"/>
        </choice>
        <choice minOccurs="0" maxOccurs="1">
```

```
<element ref="sp:EnergySavingProperties"/>
            <element ref="sp:ESPolicies"/>
          </choice>
        </sequence>
       </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="ExternalEUtranCellFDD"</pre>
substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexTvpe>
              <a11>
               <!-- Inherited attributes from ExternalEUtranGenericCell-->
               <element name="userLabel" type="string"/>
               <element name="pci" type="en:Pci"/>
               <element name="pLMNIdList" type="en:PLMNIdList"/>
               <element name="cellLocalId" type="en:CellLocalId"/>
               <element name="enbId" type="en:EnbId" minOccurs="0"/>
               <!-- End of inherited attributes from ExternalEUtranGenericCell -->
               <element name="earfcnDl" type="short"/>
<element name="earfcnUl" type="short"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:ExternalEUtranCellFDDOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
          <choice minOccurs="0">
            <element ref="en:CellOutageCompensationInformation"/>
          <choice minOccurs="0" maxOccurs="1">
            <element ref="sp:InterRatEsPolicies"/>
          </choice>
        </sequence>
       </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="EUtranCellTDD">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <a11>
               <!-- Inherited attributes from EUtranGenericCell-->
               <element name="userLabel" type="string"/>
               <element name="cellLocalId" type="en:CellLocalId"/>
               <element name="cellSize" type="en:cellSize"/>
               <element name="pLMNIdList" type="en:PLMNIdList"/>
               <element name="tac" type="long"/>
               <element name="pci" type="en:Pci" />
               <element name="pciList" type="en:PciList" minOccurs="0"/>
               <element name="maximumTransmissionPower" type="short"/>
               <element name="partOfSectorPower" type="short" minOccurs="0"/>
               <element name="referenceSignalPower" type="short"/>
               <element name="pb" type="short"/>
               <element name="relatedTmaList" type="xn:dnList" minOccurs="0"/>
               <element name="relatedAntennaList" type="xn:dnList" minOccurs="0"/>
               <element name="relatedSectorEquipment" type="xn:dn" minOccurs="0"/>
<element name="operationalState" type="sm:operationalStateType" minOccurs="0"/>
               <element name="administrativeState" type="sm:administrativeStateType"</pre>
                           minOccurs="0"/>
               <element name="availabilityStatus" type="sm:availabilityStatusType"</pre>
                           minOccurs="0"/>
               <element name="allowedAccessClasses" type="en:allowedAccessClassesType"/>
               <element name="cellResvInfo" type="en:cellResvInfoType" minOccurs="0"/>
                   <element name="isChangeForEnergySavingAllowed"</pre>
                             type="en:yesNoType" minOccurs="0"/>
               <!-- End of inherited attributes from EUtranGenericCell -->
                  <element name="earfcn" type="short"/>
```

```
<element name="sfAssignment" type="short"/>
               <element name="specialSfPatterns" type="short"/>
             </all>
           </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
           <element ref="en:EUtranRelation"/>
           <element ref="en:Cdma2000Relation"/>
           <element ref="gn:GsmRelation"/>
           <element ref="un:UtranRelation"/>
           <element ref="en:EUtranCellTDDOptionallyContainedNrmClass"/>
           <element ref="xn:VsDataContainer"/>
          </chaice>
          <choice minOccurs="0" maxOccurs="1">
           <element ref="sp:EnergySavingProperties"/>
           <element ref="sp:ESPolicies"/>
          </choice>
          <choice minOccurs="0">
           <element ref="en:CellOutageCompensationInformation"/>
          </choice>
        </sequence>
      </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="ExternalEUtranCellTDD"</pre>
substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
   <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
           <complexType>
             <all>
               <!-- Inherited attributes from ExternalEUtranGenericCell-->
               <element name="userLabel" type="string"/>
               <element name="pci" type="en:Pci"/>
               <element name="pLMNIdList" type="en:PLMNIdList"/>
               <element name="cellLocalId" type="en:CellLocalId"/>
               <element name="enbId" type="en:EnbId" minOccurs="0"/>
               <!-- End of inherited attributes from ExternalEUtranGenericCell -->
                <element name="earfcn" type="short"/>
             </all>
           </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
           <element ref="en:ExternalEUtranCellTDDOptionallyContainedNrmClass"/>
           <element ref="xn:VsDataContainer"/>
          </choice>
          <choice minOccurs="0" maxOccurs="1">
           <element ref="sp:InterRatEsPolicies"/>
          </choice>
        </sequence>
      </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="EUtranRelation">
   <complexType>
     <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
           <complexTvpe>
             <all>
               <element name="tCI" type="long" minOccurs="0"/>
               <element name="isRemoveAllowed" type="boolean" minOccurs="0"/>
               <element name="isHOAllowed" type="boolean" minOccurs="0"/>
               <element name="isICICInformationSendAllowed" type="boolean" minOccurs="0"/>
               <element name="isLBAllowed" type="boolean" minOccurs="0"/>
               <element name="adjacentCell" type="xn:dn"/>
               <element name="isEsCoveredBy" type="en:isEsCoveredByEnumType" minOccurs="0"/>
               <element name="cellIndividualOffset" type="en:QOffsetEnumType" minOccurs="0"/>
                  <element name="qOffset" type="en:QOffsetEnumType" minOccurs="0"/>
             </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
```

```
<element ref="en:EUtranRelationOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
            <element ref="en:EUtranRelationSon"/>
          </choice>
        </sequence>
      </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="Cdma2000Relation">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
             <all>
               <element name="adjacentSector" type="xn:dn"/>
             </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:Cdma2000RelationOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
       </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="Link ENB ENB" substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
             <all>
               <!-- Inherited attributes from Link -->
               <element name="aEnd" type="xn:dn"/>
               <element name="linkType" type="xn:linkType" minOccurs="0"/>
               <element name="protocolName" type="string" minOccurs="0"/>
               <element name="protocolVersion" type="string" minOccurs="0"/>
<element name="userLabel" type="string"/>
               <element name="zEnd" type="xn:dn"/>
               <!-- End of inherited attributes from Link -->
             </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:Link ENB ENBOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
       </extension>
     </complexContent>
   </complexType>
 </element>
<element name="MCEFunction" substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
             <all>
               <element name="userLabel" type="string" minOccurs="0"/>
                  <!-- Attributes are to be added when defined in the IS -->
             </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:MCEFunctionOptionallyContainedNrmClass"/>
                 <element ref="en:MBSFNArea"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
       </extension>
```

```
</complexContent>
   </complexType>
 </element>
 <element name="MBSFNArea" >
   <complexType>
     <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
             <all>
                <element name="mbsfnAreaId" type="en:mbsfnAreaIdType" minOccurs="0"/>
                <element name="cellIdList" type="xn:dnList" minOccurs="0"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:MBSFNAreaOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
       </extension>
     </complexContent>
   </complexType>
 </element>
<element name="Link MCE ENB" substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
             <all>
               <!-- Inherited attributes from Link -->
               <element name="aEnd" type="xn:dn" minOccurs="0"/>
               <element name="linkType" type="xn:linkType" minOccurs="0"/>
               <element name="protocolName" type="string" minOccurs="0"/>
               <element name="protocolVersion" type="string" minOccurs="0"/>
<element name="userLabel" type="string" minOccurs="0"/>
               <element name="zEnd" type="xn:dn" minOccurs="0"/>
               <!-- End of inherited attributes from Link -->
             </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:Link_MCE_ENBOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
       </extension>
     </complexContent>
   </complexType>
 </element>
<element name="Link MCE MME" substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexTvpe>
             <all>
               <!-- Inherited attributes from Link -->
               <element name="aEnd" type="xn:dn" minOccurs="0"/>
               <element name="linkType" type="xn:linkType" minOccurs="0"/>
               <element name="protocolName" type="string" minOccurs="0"/>
               <element name="protocolVersion" type="string" minOccurs="0"/>
               <element name="userLabel" type="string" minOccurs="0"/>
               <element name="zEnd" type="xn:dn" minOccurs="0"/>
               <!-- End of inherited attributes from Link -->
             </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="en:Link_MCE_MMEOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
       </extension>
```

```
</complexContent>
   </complexType>
 </element>
 <element name="QciDscpMapping"</pre>
  substitutionGroup="en:RNFunctionOptionallyContainedNrmClass"
   <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
           <complexType>
               <element name="userLabel" type="string"/>
               <element name="QciDscpMappingList" type="en:QciDscpMappingListType"/>
             </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
           <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
     </complexContent>
   </complexType>
 </element>
 <!-- The element definition for {\tt EP\_RP\_EPS} is available through
      the epcNrm.xsd (3GPP TS 32.756), by using epc:EP_RP_EPS -->
 <element name="ENBFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="ExternalENBFunctionOptionallyContainedNrmClass" type="xn:NrmClass"</pre>
abstract="true"/>
 <element name="EUtranCellFDDOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="ExternalEUtranCellFDDOptionallyContainedNrmClass" type="xn:NrmClass"</pre>
abstract="true"/>
 <element name="EUtranCellTDDOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="ExternalEUtranCellTDDOptionallyContainedNrmClass" type="xn:NrmClass"</pre>
abstract="true"/>
 <element name="EUtranRelationOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="Cdma2000RelationOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="Link_ENB_ENBOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="MCEFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="Link_MCE_ENBOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="Link_MCE_MMEOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="MBSFNAreaOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="RNFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
 <element name="ExternalRNFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
```

Annex C (informative): Change history

Change history							
Date	TSG#	TSG Doc.	CR	Rev	Subject/Comment	Old	New
05-200	SA-48	SP-100281			Presentation to SA for information and approval		1.0.0
06-2010	SA-48				Publication	1.0.0	10.0.0
09-2010	SA-49	SP-100489	001		Addition of eNBId and adjustment of cellIdentity	10.0.0	10.1.0
09-2010	SA-49	SP-100489	002		Add IOC MCEFunction and MBSFNArea	10.0.0	10.1.0
09-2010	SA-49	SP-100487	003		Align with IS - Remove cellType	10.0.0	10.1.0
09-2010	SA-49	SP-100488	004		Align with IS - Add attributes for association roles for Radio Equipment view	10.0.0	10.1.0
09-2010	SA-49	SP-100489	005		Correction of EUTRAN NRM IRP XML Definitions	10.0.0	10.1.0
12-2010	SA-50	SP-100833	006	1	Correcting the PLMNID definition of XML schema - Align with 23.003 and 32.762 IS	10.1.0	10.2.0
12-2010	SA-50	SP-100833	007	1	Adding Relay and Donor eNodeB NRM SS - Align with RAN2 TS 36.300	10.1.0	10.2.0
12-2010	SA-50	SP-100833	800	1	Add an attribute to SS EUtranGenericCell to set allowed access class per cell	10.1.0	10.2.0
03-2011	SA-51				Add candidateDeNBCells attribute to RNFunction in E-UTRAN Network	10.2.0	10.3.0
		SP-110095	009	2	Resource Model IRP Solution Set definitions		
03-2011	SA-51	SP-110095	010	3	Add QciDscpMapping IOC		10.3.0
03-2011	SA-51	SP-110100	013	3	Add Energy Saving Management (ESM) items for Itf-N - Align with 32.762 E-UTRAN NRM IRP IS and 32.551 ESM Concepts and requirements		10.3.0
03-2011	SA-51	SP-110100	013	4	Add Energy Saving Management (ESM) items for Itf-N - Align with 32.762, 32.551 NOTE: MCC modification of "toBeNotEnergySaving" instead of "NotToBeEnergySaving" to align with 32.762	10.2.0	10.3.0
03-2011	SA-51	SP-110096	016	1	Removing SectorEquipmentFunction - Align with EUTRAN NRM IS	10.2.0	10.3.0
03-2011	SA-51	SP-110095	018	1	Align with 32.762 - Correct Relay and Donor eNodeB model in E-UTRAN Network Resource Model IRP	10.2.0	10.3.0
03-2011	SA-51	SP-110102	020	1	Adding TCE address and TCE ID mapping information to ENBFunction	10.2.0	10.3.0
03-2011	SA-51	SP-110097	021	1	Add a new object class to hold information about Cell Outage Compensation (COC) and report COC activities - Align with 32.762	10.2.0	10.3.0
06-2011	SA-52	SP-110285	023	-	Fix syntax faults in eUTRAN NRM IRP	10.3.0	10.4.0
06-2011	SA-52	SP-110284	025	-	Introduction of cellIndividualOffset in EUtranRelation	10.3.0	10.4.0
06-2011	SA-52	SP-110365	026	_	Add stage 3 for new IOC EUtranCellNMCentralizedSON named by EUtranGenericCell and add attributes to EUtranRelation IOC	10.3.0	10.4.0
09-2011	SA-53	SP-110526	027	1	Corrections on some data type definitions	10.4.0	10.5.0
09-2011	SA-53	SP-110537	029	1	Adding TCE address and TCE ID mapping information to ENBFunction	10.4.0	10.5.0
03-2012	SA-55	SP-120057	034	1	Add ANR switch management solution – Align with 32.762	10.5.0	11.0.0
06-2012	SA-56	SP-120357	037		Add the missing attribute b2Threshold2UtraEcN0 in IDL specification – Align with 32.762	11.0.0	11.1.0
09-2012	SA-57	SP-120573	039		Add support for Inter-RAT Energy Saving Management	11.1.0	11.2.0
12-2012	SA-58	SP-120800	042	1	Add containment for interRatEsPolicies	11.2.0	11.3.0
12-2012	SA-58	SP-120796	049	-	Addition of Network Sharing for MDT	11.2.0	11.3.0

History

Document history							
V11.2.0	October 2012	Publication					
V11.3.0	February 2013	Publication					