ETSI TS 132 624 V4.2.0 (2001-12)

Technical Specification

Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
Telecommunication Management;
Configuration Management;
Generic network resources: IRP CMIP solution set
(3GPP TS 32.624 version 4.2.0 Release 4)



Reference RTS/TSGS-0532624Uv4R2

Keywords GSM, UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, send your comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001. All rights reserved.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under www.etsi.org/key.

Contents

Intelle	ectual Property Rights	2
Forew	vord	2
Forew	vord	5
Introd	luction	5
1	Scope	7
2	References	7
3	Definitions, symbols and abbreviations	7
3.1	Definitions	
3.1	Abbreviations	
3.2		
4	Basic aspects	8
4.1	Explanation	
4.2	Allowed Alarms of MOCs	8
4.3	Mapping	
4.3.1	Mapping of MOCs	
4.3.2	Mapping of Attributes	9
5	GDMO Definitions	10
5.1	Managed Object Classes	
5.1.1	subNetwork	
5.1.2	managedElement	
5.1.2	managementNode	
5.1.4	vsDataContainer	
5.1.5	bulkCmControl	
5.1.5	irpAgent	
5.1.0	managedFunction	
5.1.7	meContext	
5.1.6	bcmControl	
5.1.9	Packages	
5.2.1	subNetworkBasicPackage	
5.2.1	managedElementBasicPackage	
5.2.2	managedElementAssociationPackage	
5.2.4	vsDataContainerBasicPackage	
5.2.5	bulkCmControlBasicPackage	
5.2.6	bulkCmControlActionPackage	
5.2.7	bulkCmControlNotificationPackage bulkCmControlNotificationPackage	
5.2.7	managementNodeBasicPackage	
5.2.9	managementNodeAssociationPackage managementNodeAssociationPackage	
5.2.10		
5.2.10		
5.2.11		
5.2.12		
5.2.13	· · · · · · · · · · · · · · · · · · ·	
5.2.14		
5.2.15		
5.2.10		
5.2.18		
5.3	Attributes	
5.3.1	managedElementType	
5.3.2	subNetworkId	
5.3.3	vsDataContainerId	
5.3.4	vsDataType	
5.3.5	vsData	
5.3.6	vsDataFormatVersion	21

5.3.7	bulkCmControlId						
5.3.8	irpVersion						
5.3.9	userDefinedNetworkType						
5.3.10	swVersion						
5.3.11	managedElementId						
5.3.12	userDefinedState	23					
5.3.13	meManagedBy						
5.3.14	managementNodeId						
5.3.15	mnManagesList						
5.3.16	irpAgentId	24					
5.3.17	supportedIRPs						
5.3.18	meContextId						
5.3.19	bcmControlId						
5.3.20	supportedBcmIRPVersions	25					
5.4	Actions						
5.4.1	getBcmIRPVersion						
5.5	Name Binding	26					
5.5.1							
5.5.2	managedElement - subNetwork						
5.5.3	meContext - subNetwork						
5.5.4	bulkCmControl - irpAgent	27					
5.5.5	irpAgent - subNetwork						
5.5.6	irpAgent - suonetwork irpAgent - managementNode						
5.5.7	managementNode - subNetwork						
5.5.8	irpAgent - managedElement						
5.5.9	bcmControl - irpAgent						
5.5.10	i v						
6 A	ASN.1 Definitions	31					
Annex	A (informative): Change history	34					
THSTOLY	ý	ວຽ					

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

Due to the growing number of specifications to model new services and Resource Models for Configuration Management (CM), as well as the expected growth in size of each of them from 3GPP Release 4 onwards, a new structure of the specifications is already needed in Release 4. This structure is needed for several reasons, but mainly to enable more independent development and release for each part, as well as a simpler document identification and version handling. Another benefit would be that it becomes easier for bodies outside 3GPP, such as the ITU-T, to refer to telecom management specifications from 3GPP. The new structure of the specifications does not lose any information or functionality supported by the Release 1999. The restructuring also includes defining new IRPs for the Network Resource Model (NRM) parts of R99 Basic CM IRP (Generic, Core Network and UTRAN NRM). These IRPs are named "Network Resources IRP".

Further, the Notification IRP (in Release 1999: 32.106-1 to -4) and the Name convention for Managed Objects (in Release 1999: 32.106-8) have been moved to a separate number series used for specifications common between several management areas (e.g. CM, FM, PM).

Finally, in addition to the restructuring mentioned above, the need to define some new functionality and IRPs for CM compared to Release 1999, has also been identified. Firstly, a new Bulk CM IRP, and secondly an a GERAN Network Resources IRP, have been created. Thirdly, the Generic, UTRAN and GERAN Network Resources IRPs have been extended with support for GSM-UMTS Inter-system handover (ISH), and the 32.600 (Concept and High-level Requirements) has been modified to cover the high-level Bulk CM and ISH requirements.

Table: Mapping between Release '99 and the new specification numbering scheme

R99 Old no.	Old (R99) specification title	Rel-4 New no.	New (Rel-4) specification title
32.106-1	3G Configuration Management: Concept and Requirements	32.600	3G Configuration Management: Concept and
			High-level Requirements
32.106-1	<notification 32.106-1="" 32.106-2="" and="" from="" irp="" requirements=""></notification>	32.301	Notification IRP: Requirements
32.106-2	Notification IRP: IS	32.302	Notification IRP: Information Service
32.106-3	Notification IRP: CORBA SS	32.303	Notification IRP: CORBA SS
32.106-4	Notification IRP: CMIP SS	32.304	Notification IRP: CMIP SS
32.106-8	Name convention for Managed Objects	32.300	Name Convention for Managed Objects
32.106-1	<basic 32.106-1="" 32.106-5="" and="" cm="" from="" irp="" is="" requirements=""></basic>	32.601	Basic CM IRP: Requirements
32.106-5	Basic CM IRP IM (Intro & IS part)	32.602	Basic CM IRP: Information Service
32.106-6	Basic CM IRP CORBA SS (IS related part)	32.603	Basic CM IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (IS related part)	32.604	Basic CM IRP: CMIP SS
32.106-8	Name convention for Managed Objects	32.300	Name Convention for Managed Objects
-	-	32.611	Bulk CM IRP: Requirements
-	-	32.612	Bulk CM IRP: Information Service
-	-	32.613	Bulk CM IRP: CORBA SS
-	-	32.614	Bulk CM IRP: CMIP SS
		32.615	Bulk CM IRP: XML file format definition
32.106-1	<basic 32.106-1="" 32.106-5="" and="" cm="" from="" generic="" irp="" nrm="" requirements=""></basic>	32.621	Generic Network Resources IRP: Requirements
32.106-5	Basic CM IRP IM (Generic NRM part)	32.622	Generic Network Resources IRP: NRM
32.106-6	Basic CM IRP CORBA SS (Generic NRM related part)	32.623	Generic Network Resources IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (Generic NRM related part)	32.624	Generic Network Resources IRP: CMIP SS
32.106-1	<basic 32.106-1="" 32.106-5="" and="" cm="" cn="" from="" irp="" nrm="" requirements=""></basic>	32.631	Core Network Resources IRP: Requirements
32.106-5	Basic CM IRP IM (CN NRM part)	32.632	Core Network Resources IRP: NRM
32.106-6	Basic CM IRP CORBA SS (CN NRM related part)	32.633	Core Network Resources IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (CN NRM related part)	32.634	Core Network Resources IRP: CMIP SS
32.106-1	<basic 32.106-1="" and<br="" cm="" from="" irp="" nrm="" requirements="" utran="">32.106-5></basic>	32.641	UTRAN Network Resources IRP: Requirements
32.106-5	Basic CM IRP IM (UTRAN NRM part)	32.642	UTRAN Network Resources IRP: NRM
32.106-6	Basic CM IRP CORBA SS (UTRAN NRM related part)	32.643	UTRAN Network Resources IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (UTRAN NRM related part)	32.644	UTRAN Network Resources IRP: CMIP SS
	,	32.651	GERAN Network Resources IRP: Requirements
		32.652	GERAN Network Resources IRP: NRM
		32.653	GERAN Network Resources IRP: CORBA SS
		32.654	GERAN Network Resources IRP: CMIP SS

1 Scope

The present document specifies the Common Management Information Protocol (CMIP) Solution Set (SS) for the Generic Network Resource Integration Reference Point (IRP): Network Resource Model defined in 3GPP TS 32.622. In detail:

- Clause 4 contains an introduction to some concepts that are the base for some specific aspects of the CMIP interfaces.
- Clause 5 contains the GDMO definitions for the Alarm Management over the CMIP interfaces
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TS 32.101: "3G Telecom Management principles and high level requirements".
- [2] 3GPP TS 32.102: "3G Telecom Management architecture".
- [3] 3GPP TS 32.304: "Telecommunication Management; Notification Management; Part 4: Notification Integration Reference Point; CMIP Solution Set".
- [4] 3GPP TS 32.622: "Telecommunication Management; Configuration Management: Generic Network Resource Integration Reference Point: Network Resource Model".
- [5] ITU-T Recommendation X.710 (1991): "Common Management Information Service Definition for CCITT Applications".
- [6] ITU-T Recommendation X.721 (02/92): "Information Technology Open Systems Interconnection Structure of Management Information: Definition of Management Information".
- [7] ITU-T Recommendation X.730 (01/92): "Information Technology Open Systems Interconnection Systems Management: Object Management Function".
- [8] ITU-T Recommendation X.733 (02/92): "Information Technology Open Systems Interconnection Alarm Reporting Function".
- [9] ITU-T Recommendation M.3100 (07/95): "Maintenance Telecommunications Management Network Generic Network Information Model".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.600 and 3GPP TS 32.622 apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CMIP Common Management Information Protocol

DN Distinguished Name

GDMO Guidelines for the Definition of Managed Objects

IDL Interface Definition Language

IEC International Electro-technical Commission
ISO International Standards Organization

ITU-T International Telecommunication Union, Telecommunication Sector

MIB Management Information Base
MIM Management Information Model

MIT Management Information Tree (or Naming Tree)

MOC Managed Object Class
MOI Managed Object Instance
NE Network Element
NR Network Resource
NRM Network Resource Model

TMN Telecommunications Management Network

4 Basic aspects

4.1 Explanation

A technology independent generic network resource model is defined in 3GPP TS 32.622 for 3G networks. This document provides an implementation of this generic network resource model by using CMIP technology.

4.2 Allowed Alarms of MOCs

Table 1 defines the allowed alarms of each MOCs for this CMIP Solution Set. The MOCs, which do not appear in table 1, may not issue any alarm except the alarms that are defined as allowed for its super-class MOC(s) in the inheritance tree.

Table 1: Allowed alarms of MOCs

MOCs	Legal Alarms
subNetwork	EnvironmentalAlarm
managedElement	environmentalAlarm
	equipmentAlarm
	communicationsAlarm
	processingErrorAlarm
managementNode	environmentalAlarm
	equipmentAlarm
	communicationsAlarm
	processingErrorAlarm
managedFunction	communicationsAlarm
	processingErrorAlarm
	QualityofServiceAlarm
irpAgent	communicationsAlarm
	processingErrorAlarm
alarmControl (TS 32.111-4)	alarmListRebuiltAlarm

4.3 Mapping

The semantic of the Generic Network Resource Model is defined in 3GPP TS 32.622. The specification of the information object classes defined there is independent of any implementation technology and protocol. This subclause maps these technology and protocol independent definitions onto the equivalencies of the CMIP Solution Set of the Generic Network Resource IRP.

4.3.1 Mapping of MOCs

Table 2 maps the managed object classes defined in the Generic Network Resource Model onto the equivalent MOCs of the CMIP Solution Set.

Table 2: Mapping of MOCs

Managed Objects of the Generic NR IRP NRM	MOCs of this CMIP SS
ManagedElement	managedElement
SubNetwork	subNetwork
IRPAgent	irpAgent
ManagedFunction	managedFunction
ManagementNode	managementNode
MeContext	meContext
BasicCmIRP	bcmControl
VsDataContainer	vsDataContainer
BulkCmIRP	bulkCmControl

4.3.2 Mapping of Attributes

Table 3: Mapping of Attributes

Attribute defined in 3GPP TS 32.622	Attribute defined in this CMIP SS
dnPrefix	systemTitle (ITU-T Recommendation X.721: 1992)
managedElementId	managedElementId
subNetworkId	subNetworkId
irpAgentId	irpAgentId
IocationName	locationName (ITU-T Recommendation M.3100: 1995)
managedBy	meManagedBy
managedElementType	managedElementType
managementNodeId	managementNodeId
manages	mnManagesList
meContextId	meContextId
systemDN	not needed
userDefinedState	userDefinedState
userLabel	userLabel (ITU-T Recommendation M.3100: 1995)
vendorName	vendorName (ITU-T Recommendation M.3100: 1995)
vsDataContainerId	vsDataContainerId
vsDataType	vsDataType
vsData	vsData
vsDataFormatVersion	vsDataFormatVersion
bulkCmlrpId	bulkCmControlld
irpVersion	irpVersion
userDefinedNetworkType	userDefinedNetworkType
swVersion	swVersion

5 GDMO Definitions

5.1 Managed Object Classes

5.1.1 subNetwork

subNetwork MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;

CHARACTERIZED BY

subNetworkBasicPackage;

CONDITIONAL PACKAGES

 $"Recommendation\ M.3100:\ 1995": attribute Value Change Notification Package\ \ PRESENT\ IF$

"the attributeValueChange notifications defined in Recommendation X.721 are supported by an instance of this class.",

"Recommendation M.3100: 1995":environmentalAlarmPackage PRESENT IF

"the environmental Alarm notifications defined in Recommendation X.721 are supported by an instance of this class.";

REGISTERED AS {ts32-624ObjectClass 1};

5.1.2 managedElement

managedElement MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;

CHARACTERIZED BY

managedElementBasicPackage,

managedElementAssociationPackage;

CONDITIONAL PACKAGES

rootOptionalPackage PRESENT IF

"An instance of managedElement is the accessing root of a MIB.",

"Recommendation M.3100: 1995":createDeleteNotificationsPackage PRESENT IF

"the objectCreation and the objectDeletion defined in Recommendation

X.721 are supported by an instance of this class.",

"Recommendation M.3100: 1995":attributeValueChangeNotificationPackage PRESENT IF

"the attributeValueChange notifications defined in Recommendation X.721

are supported by an instance of this class.",

"Recommendation M.3100: 1995":processingErrorAlarmPackage PRESENT IF

"the processingErrorAlarm notifications defined in Recommendation X.721 are supported by an instance of this class.",

"Recommendation M.3100: 1995":environmentalAlarmPackage PRESENT IF

"the environmental Alarm notifications defined in Recommendation X.721 are supported by an instance of this class.",

communications Alarm Package PRESENT IF

"the communications Alarm notifications defined in Recommendation X.721 are supported by an instance of this class.",

equipmentAlarmPackage PRESENT IF

"the equipmentAlarm notifications defined in Recommendation X.721

are supported by an instance of this class."; REGISTERED AS {ts32-624ObjectClass 2};

5.1.3 managementNode

managementNode MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;

CHARACTERIZED BY

managementNodeBasicPackage,

managementNodeAssociationPackage;

CONDITIONAL PACKAGES

"Recommendation M.3100: 1995":createDeleteNotificationsPackage PRESENT IF

"the objectCreation and the objectDeletion defined in Recommendation

X.721 are supported by an instance of this class.",

"Recommendation M.3100: 1995":attributeValueChangeNotificationPackage PRESENT IF

"the attributeValueChange notifications defined in Recommendation X.721 are supported by an instance of this class.",

"Recommendation M.3100: 1995":processingErrorAlarmPackage PRESENT IF

"the processingErrorAlarm notifications defined in Recommendation X.721 are supported by an instance of this class.",

"Recommendation M.3100: 1995":environmentalAlarmPackage PRESENT IF

"the environmental Alarm notifications defined in Recommendation X.721 are supported by an instance of this class.",

communications Alarm Package PRESENT IF

"the communications Alarm notifications defined in Recommendation X.721 are supported by an instance of this class.",

equipmentAlarmPackage PRESENT IF

"the equipmentAlarm notifications defined in Recommendation X.721 are supported by an instance of this class.";

REGISTERED AS {ts32-624ObjectClass 3};

5.1.4 vsDataContainer

vsDataContainer MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;

CHARACTERIZED BY

vsDataContainerBasicPackage;

REGISTERED AS {ts32-624ObjectClass 4};

5.1.5 bulkCmControl

bulkCmControl MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;

CHARACTERIZED BY

bulkCmControlBasicPackage,

bulkCmControlActionPackage,

bulkCmControlNotificationPackage;

REGISTERED AS {ts32-624ObjectClass 5};

5.1.6 irpAgent

irpAgent MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;

CHARACTERIZED BY

irpAgentBasicPackage;

CONDITIONAL PACKAGES

"Recommendation M.3100: 1995":processingErrorAlarmPackage PRESENT IF

"the processingErrorAlarm notifications defined in Recommendation X.721

are supported by an instance of this class.",

communicationsAlarmPackage PRESENT IF

"the communications Alarm notifications defined in Recommendation X.721 are supported by an instance of this class.";

REGISTERED AS {ts32-624ObjectClass 6};

5.1.7 managedFunction

managedFunction MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;

CHARACTERIZED BY

managedFunctionBasicPackage;

CONDITIONAL PACKAGES

"Recommendation M.3100: 1995":createDeleteNotificationsPackage PRESENT IF

"the objectCreation and the objectDeletion defined in Recommendation

X.721 are supported by an instance of this class.",

"Recommendation M.3100: 1995":attributeValueChangeNotificationPackage PRESENT IF

"the attributeValueChange notifications defined in Recommendation X.721 are supported by an instance of this class.",

"Recommendation M.3100: 1995":processingErrorAlarmPackage PRESENT IF

"the processing Error Alarm notifications defined in Recommendation X.721 are supported by an instance of this class.",

communicationsAlarmPackage PRESENT IF

"the communicationsAlarm notifications defined in Recommendation X.721 are supported by an instance of this class.",

qualityOfServiceAlarmPackage PRESENT IF

"the qualityOfServiceAlarm notifications defined in Recommendation X.721 are supported by an instance of this class.";

REGISTERED AS {ts32-624ObjectClass 7};

5.1.8 meContext

meContext MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;

CHARACTERIZED BY

meContextBasicPackage;

CONDITIONAL PACKAGES

rootOptionalPackage PRESENT IF

"An instance of meContext is the accessing root of a MIB.",

"Recommendation M.3100: 1995":createDeleteNotificationsPackage PRESENT IF

"the objectCreation and the objectDeletion defined in Recommendation

X.721 are supported by an instance of this class.";

REGISTERED AS {ts32-624ObjectClass 8};

5.1.9 bcmControl

bcmControl MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;

CHARACTERIZED BY

bcmControlBasicPackage,

bcmIRPVersionPackage;

REGISTERED AS {ts32-624ObjectClass 9};

5.2 Packages

5.2.1 subNetworkBasicPackage

subNetworkBasicPackage PACKAGE

BEHAVIOUR

subNetworkBasicPackageBehaviour;

ATTRIBUTES

subNetworkId GET,

"Recommendation X.721: 1992": systemTitle GET,

"Recommendation M.3100: 1995": userLabel GET-REPLACE,

userDefinedNetworkType GET;

REGISTERED AS {ts32-624Package 1};

subNetworkBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"This managed object class represents collections of interconnected telecommunications and management objects (logical or physical) capable of exchanging information. A network may be nested within another (larger) network, thereby forming a containment relationship.";

5.2.2 managedElementBasicPackage

managedElementBasicPackage PACKAGE

BEHAVIOUR

managedElementBasicPackageBehaviour;

ATTRIBUTES

```
managedElementId GET,
managedElementType GET,
userDefinedState GET-REPLACE,
"Recommendation M.3100: 1995" : userLabel GET-REPLACE,
"Recommendation M.3100: 1995" : vendorName GET,
"Recommendation M.3100: 1995" : locationName GET,
swVersion GET;
REGISTERED AS {ts32-624Package 2};
```

managedElementBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"This managed object class represents telecommunications equipment within the telecommunications network that performs managed element functions, i.e. provides support and/or service to the subscriber. A managed element communicates with a manager (directly or indirectly) over one or more standard interfaces for the purpose of being monitored and/or controlled. A managed element contains equipment that may or may not be geographically distributed. A Managed Element is often referred to as a 'node' or a 'network element'.";

5.2.3 managedElementAssociationPackage

managedElementAssociationPackage PACKAGE

```
BEHAVIOUR
managedElementAssociationPackageBehaviour;
ATTRIBUTES
meManagedBy GET;
```

REGISTERED AS {ts32-624Package 3};

managedElementAssociationPackageBehaviour BEHAVIOUR

DEFINED AS

"The attribute 'meManagedBy' points to the managmentNode instance which manages this managedElement instance. It implements the attribute *managedBy* of MOC ManagedElement defined in TS32.622.";

5.2.4 vsDataContainerBasicPackage

vsDataContainerBasicPackage PACKAGE

```
BEHAVIOUR
vsDataContainerBasicPackageBehaviour;
ATTRIBUTES
vsDataContainerId GET,
vsDataType GET,
vsData GET-REPLACE,
vsDataFormatVersion GET;
REGISTERED AS {ts32-624Package 4};
```

vsDataContainerBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"The 'VsDataContainer' managed object is a container for vendor specific data. The number of instances of the 'VsDataContainer' can differ from vendor to vendor. This MOC shall only be used by the Bulk CM IRP for the UTRAN and GERAN object models.";

5.2.5 bulkCmControlBasicPackage

bulkCmControlBasicPackage PACKAGE

BEHAVIOUR

bulkCmControlBasicPackageBehaviour;

ATTRIBUTES

bulkCmControlId GET,

irpVersion GET;

REGISTERED AS {ts32-624Package 5};

bulkCmControlBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"This Managed Object Class represents the Bulk CM IRP capability associated with each IRPAgent. Restriction in Rel-4: Number of instances = 0..1.";

5.2.6 bulkCmControlActionPackage

bulkCmControlActionPackage PACKAGE

BEHAVIOUR

bulkCmControlActionPackageBehaviour;

ACTIONS

"3GPP TS 32.614 Release 4": startSession,

"3GPP TS 32.614 Release 4": endSession,

"3GPP TS 32.614 Release 4": upload,

"3GPP TS 32.614 Release 4": download,

"3GPP TS 32.614 Release 4": activate,

"3GPP TS 32.614 Release 4": fallback,

"3GPP TS 32.614 Release 4": abortSessionOperation,

"3GPP TS 32.614 Release 4": getSessionIds,

"3GPP TS 32.614 Release 4": getSessionStatus,

"3GPP TS 32.614 Release 4": getSessionLog,

"3GPP TS 32.614 Release 4": getBulkCmIrpVersion;

REGISTERED AS {ts32-624Package 6};

bulkCmControlActionPackageBehaviour BEHAVIOUR

DEFINED AS

"This package specifies all actions a bulkCmControl shall provide.";

5.2.7 bulkCmControlNotificationPackage

bulkCmControlNotificationPackage PACKAGE

```
BEHAVIOUR
```

bulkCmControlNotificationPackageBehaviour;

NOTIFICATIONS

"3GPP TS 32.614 Release 4": sessionStateChanged,

"3GPP TS 32.614 Release 4": getSessionLogEnded;

REGISTERED AS {ts32-624Package 7};

bulkCmControlNotificationPackageBehaviour BEHAVIOUR

DEFINED AS

"This package specifies all notifications a bulkCmControl shall provide.";

5.2.8 managementNodeBasicPackage

managementNodeBasicPackage PACKAGE

ATTRIBUTES

managementNodeId GET,

userDefinedState GET.

"Recommendation M.3100: 1995": userLabel GET-REPLACE,

"Recommendation M.3100: 1995": vendorName GET,

"Recommendation M.3100: 1995": locationName GET;

swVersion: GET;

REGISTERED AS {ts32-624Package 8};

managementNodeBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"This managed object class represents a telecommunications management system (EM or NM) within the TMN, that manages a number of Managed Elements. The management system communicates with the MEs directly or indirectly over one or more standard interfaces for the purpose of monitoring and/or controlling these MEs.";

5.2.9 managementNodeAssociationPackage

managementNodeAssociationPackage PACKAGE

BEHAVIOUR

management Node Association Package Behaviour;

ATTRIBUTES

mnManagesList GET;

REGISTERED AS {ts32-624Package 9};

managementNodeAssociationPackageBehaviour BEHAVIOUR

DEFINED AS

"The attribute 'mnManagesList' points to all managedElement instances which this managementNode instance manages. It implements the attribute *manages* of

MOC ManagementNode defined in TS32.622.";

5.2.10 irpAgentBasicPackage

irpAgentBasicPackage PACKAGE

BEHAVIOUR

irpAgentBasicPackageBehaviour;

ATTRIBUTES

irpAgentId GET,

"Recommendation M.3100: 1995": userLabel GET,

supportedIRPs GET;

REGISTERED AS {ts32-624Package 10};

irpAgentBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"irpAgent may have only one instance in R99 and R4. The instance of this MOC represents the behavior of an IRP Agent which implements one or more IRPs";

5.2.11 managedFunctionBasicPackage

managedFunctionBasicPackage PACKAGE

BEHAVIOUR

managementFunctionBasicPackageBehaviour;

ATTRIBUTES

"Recommendation M.3100: 1995": userLabel GET;

REGISTERED AS {ts32-624Package 11};

managedFunctionBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"This Managed Object class corresponds to the class gsmManagedFunction defined in GSM 12.20 0 and is provided for sub-classing only. It provides the attributes that are common to functional MO classes. Note that a managed element may contain several managed functions. The ManagedFunction may be extended in the future if more common characteristics to functional objects are identified.";

5.2.12 meContextBasicPackage

meContextBasicPackage PACKAGE

BEHAVIOUR

meContextBasicPackageBehaviour;

ATTRIBUTES

meContextId GET;

REGISTERED AS {ts32-624Package 12};

meContextBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"This managed object class represents the Managed Element from the network perspective. It can be used to hold surveillance status information, and also planning status information for the case when the managed element is part of a planned configuration in a management system, before it has been taken into service. It can also support unambiguous naming in all cases, also for scenarios when the Managed Elements have been pre-configured where some of them may have equal names (to avoid necessary administration to make all of them globally unique at creation/installation time). Thus, by means of globally unique names for the MEContext instances, and by using these in the DN, the DNs for all MEs (and MOIs contained in them) can be assured to be globally unique, even in such a scenario as described above.";

5.2.13 bcmControlBasicPackage

bcmControlBasicPackage PACKAGE

BEHAVIOUR

bcmControlBasicPackageBehaviour;

ATTRIBUTES

bcmControlId GET;

REGISTERED AS {ts32-624Package 13};

bcmControlBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"The object class bcmControl offers the functions defined in the CM IRP IS enabling to control the behaviour and to retrieve the management information related a Basic CM IRP agent.

An instance of the 'BCmControl' MOC is identified by the value of the attribute 'bcmControlId'.":

5.2.14 bcmIRPVersionPackage

bcmIRPVersionPackage PACKAGE

BEHAVIOUR

bcmIRPVersionPackageBehaviour;

ATTRIBUTES

supportedBcmIRPVersions GET;

ACTIONS

getBcmIRPVersion;

REGISTERED AS {ts32-624Package 14};

bcmIRPVersionPackageBehaviour BEHAVIOUR

DEFINED AS

"This package has been defined to allow the Manager to get information about the Basic CM IRP versions supported by the Agent.

The attribute 'supportedBCmIRPVersions' indicates all versions of the Basic IRP currently supported by the Agent. .

With the action 'getBasicCmIRPVersion' a manager can find out the versions of the Basic CM IRP CMIP solution sets the Agent supports.";

5.2.15 communicationsAlarmPackage

communicationsAlarmPackage PACKAGE

NOTIFICATIONS

"Recommendation X.721:1992": communicationsAlarm;

REGISTERED AS {ts32-624Package 15};

5.2.16 equipmentAlarmPackage

equipmentAlarmPackage PACKAGE

NOTIFICATIONS

"Recommendation X.721:1992": equipmentAlarm;

REGISTERED AS {ts32-624Package 16};

5.2.17 qualityOfServiceAlarmPackage

qualityOfServiceAlarmPackage PACKAGE

NOTIFICATIONS

"Recommendation X.721:1992": qualityofServiceAlarm;

REGISTERED AS {ts32-624Package 17};

5.2.18 rootOptionalPackage

rootOptionalPackage PACKAGE

BEHAVIOUR

rootOptionalPackageBehaviour;

ATTRIBUTES

"Recommendation X.721: 1992": systemTitle GET;

REGISTERED AS {ts32-624Package 18};

rootOptionalPackageBehaviour BEHAVIOUR

DEFINED AS

"This package shall be present in an instance of meContext or managedElement when it is the accessing point (root) of a MIB.";

5.3 Attributes

5.3.1 managedElementType

managedElementType ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule .ManagedElementType;

MATCHES FOR EQUALITY;

BEHAVIOUR

managedElementTypeBehaviour;

REGISTERED AS {ts32-624Attribute 1};

managedElementTypeBehaviour BEHAVIOUR

DEFINED AS

"This attribute specifies which managed functions a managed element contains.";

5.3.2 subNetworkId

subNetworkId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

subNetworkIdBehaviour;

REGISTERED AS {ts32-624Attribute 2};

subNetworkIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute identifies a subNetwork instance.";

5.3.3 vsDataContainerId

vsDataContainerId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

vsDataContainerIdBehaviour;

REGISTERED AS {ts32-624Attribute 2};

vsDataContainerIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute identifies a vsDataContainer instance.";

5.3.4 vsDataType

vsDataType ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.VsDataType;

MATCHES FOR EQUALITY;

BEHAVIOUR

vsDataTypeBehaviour;

REGISTERED AS {ts32-624Attribute 3};

vsDataTypeBehaviour BEHAVIOUR

DEFINED AS

"Type of vendor specific data contained by this instance, e.g. relation specific algorithem parameters, cell specific parameters for pewer control or re-selection or a timer. The type itself is also vendor specific.";

5.3.5 vsData

vsData ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.VsData;

MATCHES FOR EQUALITY;

BEHAVIOUR

vsDataBehaviour;

REGISTERED AS {ts32-624Attribute 4};

vsDataBehaviour BEHAVIOUR

DEFINED AS

"Vendor specific attributes of the type vsDataType. The attribute definitions including constraints (value ranges, data types, etc.) are specified in a vendor specific data format file.";

5.3.6 vsDataFormatVersion

vsDataFormatVersion ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.VsDataFormatVersion;

MATCHES FOR EQUALITY;

BEHAVIOUR

vsDataFormatVersionBehaviour;

REGISTERED AS {ts32-624Attribute 5};

vsDataFormatVersionBehaviour BEHAVIOUR

DEFINED AS

"Name of the data format file, including version.";

5.3.7 bulkCmControlld

bulkCmControlId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

bulkCmControlIdBehaviour;

REGISTERED AS {ts32-624Attribute 6};

bulkCmControlIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute identifies a bulkCmControl instance.";

5.3.8 irpVersion

irpVersion ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.IrpVersion;

MATCHES FOR EQUALITY;

BEHAVIOUR

irpVersionBehaviour;

REGISTERED AS {ts32-624Attribute 7};

irpVersionBehaviour BEHAVIOUR

DEFINED AS

"One or more Bulk CM IRP version entries.";

5.3.9 userDefinedNetworkType

userDefinedNetworkType ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.UserDefinedNetworkType;

MATCHES FOR EQUALITY;

BEHAVIOUR

userDefinedNetworkTypeBehaviour;

REGISTERED AS {ts32-624Attribute 8};

userDefinedNetworkTypeBehaviour BEHAVIOUR

DEFINED AS

"Textual information regarding the type of network, e.g. UTRAN.";

5.3.10 swVersion

swVersion ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.SwVersion;

MATCHES FOR EQUALITY;

BEHAVIOUR

swVersionBehaviour;

REGISTERED AS {ts32-624Attribute 9};

swVersionBehaviour BEHAVIOUR

DEFINED AS

"The software version of the managed element (this is used for determin which version of the vendor specific information that is valid for the managed element).";

5.3.11 managedElementId

managedElementId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule .GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

managedElementIdBehaviour;

REGISTERED AS {ts32-624Attribute 10};

managedElementIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute names an instance of the '3gManagedElement' object class.";

5.3.12 userDefinedState

userDefinedState ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.UserDefinedState;

MATCHES FOR EQUALITY;

BEHAVIOUR

userDefinedStateBehaviour;

REGISTERED AS {ts32-624Attribute 11};

userDefinedStateBehaviour BEHAVIOUR

DEFINED AS

"This attribute specifies an operator defined state for operator specific usage.";

5.3.13 meManagedBy

meManagedBy ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.GeneralObjectPointer;

MATCHES FOR EQUALITY;

BEHAVIOUR

meManagedByBehaviour;

REGISTERED AS {ts32-624Attribute 12};

meManagedByBehaviour BEHAVIOUR

DEFINED AS

"This attribute points to the managementNode instance which manages the related 3gManagedElement instance.";

5.3.14 managementNodeld

managementNodeId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

managmentNodeIdBehaviour;

REGISTERED AS {ts32-624Attribute 13};

managmentNodeIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute names an instance of the 'managmentNode' object class.";

5.3.15 mnManagesList

mnManagesList ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.GeneralObjectPointerList;

MATCHES FOR EQUALITY;

BEHAVIOUR

mnManagesListBehaviour;

REGISTERED AS {ts32-624Attribute 14};

mnManagesListBehaviour BEHAVIOUR

DEFINED AS

"This attribute points to all 3gManagedElement instances which this

3gManagmentNode instance manages.";

5.3.16 irpAgentId

irpAgentId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

irpAgentIdBehaviour;

REGISTERED AS {ts32-624 Attribute 15};

irpAgentIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute identifies an irpAgent instance.";

5.3.17 supportedIRPs

supportedIRPs ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.SupportedIRPs;

MATCHES FOR EQUALITY;

BEHAVIOUR

supportedIRPsBehaviour;

REGISTERED AS {ts32-624Attribute 16};

supportedIRPsBehaviour BEHAVIOUR

DEFINED AS

"This attribute provides the information about IRPs an IRPAgent supports.";

5.3.18 meContextId

meContextId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

meContextIdBehaviour;

REGISTERED AS {ts32-624Attribute 17};

meContextIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute names an instance of the 'MEContext' object class.";

5.3.19 bcmControlld

bcmControlId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

bcmControlIdBehaviour;

REGISTERED AS {ts32-624Attribute 18};

bcmControlIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute names an instance of the 'bcmControl' object class.";

5.3.20 supportedBcmIRPVersions

supportedBcmIRPVersions ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-624TypeModule.SupportedBCmIRPVersions;

MATCHES FOR EQUALITY;

BEHAVIOUR

supportedBCmIRPVersionsBehaviour;

REGISTERED AS {ts32-624Attribute 19};

supportedBCmIRPVersionsBehaviour BEHAVIOUR

DEFINED AS

"This attribute provides the information concerning the Basic CM IRP versions currently supported by the Agent.";

5.4 Actions

5.4.1 getBcmIRPVersion

getBcmIRPVersion ACTION

BEHAVIOUR

getBcmIRPVersionBehaviour;

MODE CONFIRMED:

WITH REPLY SYNTAX TS32-624TypeModule.GetBCmIRPVersionReply;

REGISTERED AS {ts32-624Action 1};

getBcmIRPVersionBehaviour BEHAVIOUR

DEFINED AS

"A Manager invokes this action to enquiry about the versions of the Basic CM IRP CMIP solution set which the concerned Agent supports.

The 'Action information' field contains no data:

The 'Action response' is composed of the following data:

* versionNumbersList It contains a list of versions supported by the concerned agent which are backwards compatible. A list containing no element, i.e. a NULL list means that the concerned agent doesn't support any version of the Notification IRP.

* status It contains the results of this action. Possible values: noError (0), error (the value indicates the reason of the error).";

5.5 Name Binding

5.5.1 managedElement - meContext

managedElement-meContext NAME BINDING

SUBORDINATE OBJECT CLASS managedElement;

NAMED BY SUPERIOR OBJECT CLASS meContext;

WITH ATTRIBUTE managedElementId;

BEHAVIOUR

managedElement-meContextBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-624NameBinding 1};

managedElement-meContextBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a meContext contains and controls a managedElement. When automatic instance naming is used, the choice of name bindings left as a local matter.";

5.5.2 managedElement - subNetwork

managedElement-subNetwork NAME BINDING

SUBORDINATE OBJECT CLASS managedElement;

NAMED BY SUPERIOR OBJECT CLASS subNetwork;

WITH ATTRIBUTE managedElementId;

BEHAVIOUR

managedElement-subNetworkBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-624NameBinding 2};

managedElement-subNetworkBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a subNetwork contains and controls a managedElement. When automatic instance naming is used, the choice of name bindings left as a local matter.";

5.5.3 meContext - subNetwork

meContext-subNetwork NAME BINDING

SUBORDINATE OBJECT CLASS meContext;

NAMED BY SUPERIOR OBJECT CLASS subNetwork;

WITH ATTRIBUTE meContextId;

BEHAVIOUR

meContext-subNetworkBehaviour:

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-624NameBinding 3};

meContext-subNetworkBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a subNetwork contains and controls a meContext. When automatic instance naming is used, the choice of name bindings left as a local matter.";

5.5.4 bulkCmControl - irpAgent

bulkCmControl-irpAgent NAME BINDING

SUBORDINATE OBJECT CLASS bulkCmControl;

NAMED BY SUPERIOR OBJECT CLASS irpAgent;

WITH ATTRIBUTE bulkCmControlId;

BEHAVIOUR

bulkCmControl-irpAgentBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-624NameBinding 4};

bulkCmControl-irpAgentBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a irpAgent contains and controls a bulkCmControl. When automatic instance naming is used, the choice of name bindings left as a local matter.";

5.5.5 irpAgent - subNetwork

irpAgent-subNetwork NAME BINDING

SUBORDINATE OBJECT CLASS irpAgent;

NAMED BY SUPERIOR OBJECT CLASS subNetwork;

WITH ATTRIBUTE irpAgentId;

BEHAVIOUR

irpAgent-subNetworkBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-624NameBinding 5};

irpAgent-subNetworkBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a subNetwork contains and controls a irpAgent. When automatic instance naming is used, the choice of name bindings left as a local matter.";

5.5.6 irpAgent - managementNode

irpAgent - managementNode NAME BINDING

SUBORDINATE OBJECT CLASS irpAgent;

NAMED BY SUPERIOR OBJECT CLASS managementNode;

WITH ATTRIBUTE "3GPP TS 32.624: 6.2001": irpAgentId;

BEHAVIOUR

irpAgent-managementNodeBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-624NameBinding 6};

irpAgent-managementNodeBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a managedNode contains and controls a irpAgent. When automatic instance naming is used, the choice of name bindings left as a local matter.";

5.5.7 managementNode - subNetwork

managementNode-subNetwork NAME BINDING

SUBORDINATE OBJECT CLASS managementNode;

NAMED BY SUPERIOR OBJECT CLASS subNetwork;

WITH ATTRIBUTE managementNodeId;

BEHAVIOUR

managementNode-subNetworkBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS:

REGISTERED AS {ts32-624NameBinding 7};

managementNode-subNetworkBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a subNetwork contains and controls a managementNode. When automatic instance naming is used, the choice of name bindings left as a local matter.";

5.5.8 irpAgent - managedElement

irpAgent-managedElement NAME BINDING

SUBORDINATE OBJECT CLASS irpAgent;

NAMED BY SUPERIOR OBJECT CLASS managedElement;

WITH ATTRIBUTE irpAgentId;

BEHAVIOUR

irpAgent-managedElementBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-624NameBinding 8};

irpAgent-managedElementBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls an irpAgent. When automatic instance naming is used, the choice of name bindings left as a local matter.";

5.5.9 bcmControl - irpAgent

bcmControl-irpAgent NAME BINDING

SUBORDINATE OBJECT CLASS bcmControl;

NAMED BY SUPERIOR OBJECT CLASS irpAgent;

WITH ATTRIBUTE bcmControlId;

BEHAVIOUR

bcmControl-irpAgentBehavior;

CREATE WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-624NameBinding 9};

bcmControl-irpAgentBehavior BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a irpAgent contains and controls an bcmControl. When automatic instance naming is used, the choice of name bindings left as a local matter.";

5.5.10 vsDataContainer - vsDataContainer

vsDataContainer-vsDataContainer NAME BINDING

SUBORDINATE OBJECT CLASS vsDataContainer;

NAMED BY SUPERIOR OBJECT CLASS vsDataContainer;

WITH ATTRIBUTE vsDataContainerId;

BEHAVIOUR

vsDataContainer-vsDataContainerBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-624NameBinding 10};

vsDataContainer-vsDataContainerBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a vsDataContainer contains and controls another vsDataContainer. When automatic instance naming is used, the choice

of name bindings is left as a local matter. This containment relation shall be used only with Bulk CM IRP CMIP SS defined in 3GPP TS 32.614.";

nodeB

(2),

6 ASN.1 Definitions

TS32-624TypeModule {ccitt (0) identified-organization (4) etsi (0)

```
mobileDomain (0) umts-Operation-Maintenance (3) ts32-624 (624)
      informationModel (0) asn1Module (2) version1 (1)}
DEFINITIONS IMPLICIT TAGS ::=
BEGIN
-- EXPORTS everything
IMPORTS
ObjectInstance FROM CMIP-1 {joint-iso-ccitt ms(9) cmip(1) modules(0) protocol(3)}
-- 3GPP TS 32.624 related Object Identifiers
baseNodeUMTS OBJECT IDENTIFIER ::= {itu-t(0) identified-organization(4) etsi(0) mobileDomain(0)
                         umts-Operation-Maintenance(3)}
ts32-624
           OBJECT IDENTIFIER ::= { baseNodeUMTS ts32-624(624)}
ts32-624InfoModel
                    OBJECT IDENTIFIER ::= { ts32-624 informationModel(0)}
ts32-624ObjectClass OBJECT IDENTIFIER ::= { ts32-624InfoModel managedObjectClass(3)}
ts32-624Package
                    OBJECT IDENTIFIER ::= { ts32-624InfoModel package(4)}
ts32-624Parameter
                    OBJECT IDENTIFIER ::= { ts32-624InfoModel parameter(5)}
ts32-624NameBinding
                      OBJECT IDENTIFIER ::= { ts32-624InfoModel nameBinding(6)}
ts32-624Attribute
                    OBJECT IDENTIFIER ::= { ts32-624InfoModel attribute(7)}
ts32-624Action
                 OBJECT IDENTIFIER ::= { ts32-624InfoModel action(9)}
ts32-624Notification OBJECT IDENTIFIER ::= { ts32-624InfoModel notification(10)}
-- Start of 3GPP SA5 own definitions
ErrorCauses ::= ENUMERATED
{
noError (0),
wrongInput (1),
unspecifiedErrorReason (255)
ManagedElementType::= SET OF ENUMERATED
{
     (1),
rnc
```

```
(3),
msc
hLR
        (4),
vLR
        (5),
aUC
        (6),
eIR
        (7),
sms-IWMSC
              (8),
sms-GMSC (9),
sGSN
        (10),
gGSN
        (11),
bG (12),
gmsc
        (13),
smlc (14),
gmlc (15),
scf(16),
srf (17),
cbc (18),
cgf(19),
mgw (20),
gmscServer (21),
iwf (22),
mnpSrf (23),
npdb (24),
rSgw (25),
ssf (26),
bs (27),
msc-Server (28)
GeneralObjectId ::= INTEGER
UserDefinedState ::= INTEGER
GeneralObjectPointer ::= ObjectInstance
GeneralObjectPointerList ::= SEQUENCE OF ObjectInstance
IRPNames::= SET OF ENUMERATED
notificationIRP
                 (1),
alarmIRP
              (2),
basicCmIRP
                 (3),
bulkCmIRP
                 (4),
genericNRM
                    (5),
cnNRM
                 (6),
utranNRM
                 (7),
geranNRM
                 (8)
SupportedIRPs ::= SET OF IRPNames
VsDataType ::= GraphicString
VsData ::= GraphicString
```

```
VsDataFormatVersion ::= GraphicString
IrpVersion ::= GraphicString
SupportedBCmIRPVersions ::= SET OF IrpVersion
UserDefinedNetworkType ::= GraphicString
SwVersion ::= GraphicString
GetBCmIRPVersionReply ::= SEQUENCE
{
versionNumbersList SupportedBCmIRPVersions,
status ErrorCauses
}
```

END -- of TS32-624TypeModule

Annex A (informative): Change history

	Change history						
Date	TSG #	TSG Doc.	CR	Rev		Old	New
Jun 2001	S_12	SP-010283			Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0
Sep 2001	S_13	SP-010478	001		Correction due to TS renumbering	4.0.0	4.1.0
Sep 2001	S_13	SP-010479	002		Change the attribute "systemTitle" from mandatory to optional	4.0.0	4.1.0
Dec 2001	S_14	SP-010648	003		Change to Read/Write the attribute "userDefinedState" in MOC "ManagementNode"	4.1.0	4.2.0

History

Document history				
V4.0.0	June 2001	Publication		
V4.1.0	September 2001	Publication		
V4.2.0	December 2001	Publication		