ETSI TS 132 623 V6.5.0 (2005-06)

Technical Specification

Digital cellular telecommunications system (Phase 2+);

Universal Mobile Telecommunications System (UMTS);

Telecommunication management;


Configuration Management (CM);

Generic network resources Integration Reference Point (IRP):

Common Object Request Broker Architecture (CORBA)

Solution Set (SS)

(3GPP TS 32.623 version 6.5.0 Release 6)



Reference
RTS/TSGS-0532623v650

Keywords
GSM, UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005. All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**TM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**TM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Contents

Intell	ectual Property Rights	2
Forev	vord	2
Forev	vord	Δ
	luction	
1	Scope	5
2	References	5
3	Definitions and abbreviations	6
3.1	Definitions	6
3.2	Abbreviations	6
4	Architectural features	6
4.1	Notifications	
4.2	Void	
4.3	Syntax for Distinguished Names	6
5	Mapping	7
5.1	General mappings	
5.2	Generic NRM Information Object Class (IOC) mapping.	
5.2.1	IOC SubNetwork	
5.2.2	IOC ManagedElement	
5.2.3	IOC MeContext	
5.2.4	IOC ManagementNode	
5.2.5	IOC VsDataContainer	
5.2.6	IOC ManagedFunction	
5.2.7	IOC IRPAgent	
5.2.8	IOC GenericIRP	9
5.2.9	IOC Top	9
5.2.10	IOC Link	9
5	Rules for NRM extensions	10
5.1	Allowed extensions	10
5.2	Extensions not allowed	10
A nne	ex A (normative): IDL specifications	11
A.1	IDL specification (file name "GenericNetworkResourcesIRPSystem.idl")	11
Anne	ex B (normative): IDL specifications	13
B.1	IDL specification (file name "GenericNetworkResourcesNRMDefs.idl")	13
A nn -	ex C (informative): Change history	10
Anne	cx C (miormative): Change history	18
Histo	ry	19

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

32.621:	"Configuration Management (CM); Generic network resources Integration Reference Point (IRP): Requirements".
32.622:	"Configuration Management (CM);Generic network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
32.623:	"Configuration Management (CM);Generic network resources Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)";
32.624:	"Configuration Management (CM);Generic network resources: Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".
32.625:	"Configuration Management (CM);Generic network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition".

1 Scope

The TS 32.62x-series (Generic Network Resources IRP) define an Integration Reference Point (IRP) through which an "IRPAgent" (typically an Element Manager or Network Element) can communicate Network Management related information to one or several "IRPManagers" (typically Network Managers).

This TS-family specifies a generic Network Resource Model, NRM (also referred to as a Management Information Model - MIM) with definitions of Information Object Classes (IOCs) and Managed Object Classes (MOCs).

The present document specifies the CORBA Solution Set.

This Solution Set specification is related to 3GPP TS 32.622 V6.3.X.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
 [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 32.622: "Telecommunication management; Configuration Management (CM); Generic network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [5] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [6] OMG Notification Service, Version 1.0.
- [7] OMG CORBA services: Common Object Services Specification, Update: November 22, 1996.
- [8] The Common Object Request Broker: Architecture and Specification (for specification of valid version, see [1]).
- [9] 3GPP TS 32.303: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
- [10] 3GPP TS 32.111-3: "Telecommunication management; Fault Management; Part 3: Alarm Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".

3 Definitions and abbreviations

3.1 **Definitions**

For terms and definitions please refer to 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.600 [3] and 3GPP TS 32.622 [4].

3.2 **Abbreviations**

For the purposes of the present document, the following abbreviations apply:

CORBA	Common Object Request Broker Architecture
DN	Distinguished Name
IS	Information Service
IDL	Interface Definition Language (OMG)
IRP	Integration Reference Point
MO	Managed Object
MOC	Managed Object Class
NRM	Network Resource Model
OMG	Object Management Group
SS	Solution Set

Architectural features 4

The overall architectural feature of Generic Network Resources IRP is specified in 3GPP TS 32.622 [4]. This clause specifies features that are specific to the CORBA SS.

Notifications 4.1

Notifications are sent according to the Notification IRP: CORBA SS (see 3GPP TS 32.303 [9]).

The contents of the Basic CM IRP notifications are defined in the present document.

4.2 Void

Syntax for Distinguished Names 4.3

The format of a Distinguished Name is defined in 3GPP TS 32.300 [5].

5 Mapping

5.1 General mappings

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MOReference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MOReferenceSet, which contains a sequence of MO references.

5.2 Generic NRM Information Object Class (IOC) mapping

This Solution Set supports reference attributes for relations other than containment relations between objects. Reference attributes are therefore introduced in each MOC where needed.

5.2.1 IOC SubNetwork

Mapping from NRM IOC SubNetwork attributes to SS equivalent MOC SubNetwork attributes

SS Attributes	SS Type	Qualifier
subNetworkId	string	Read-Only, M
dnPrefix	string	Read-Only, M
userLabel	string	Read-Write, M
userDefinedNetworkTy pe	string	Read-Only, M
setOfMcc	GenericNetworkRes ourcesIRPSystem:: AttributeTypes::Strin gSet	Read-Only, M (see note)
	dnPrefix userLabel userDefinedNetworkTy pe	dnPrefix string userLabel string userDefinedNetworkTy pe setOfMcc GenericNetworkRes ourcesIRPSystem:: AttributeTypes::Strin

5.2.2 IOC ManagedElement

Mapping from NRM IOC ManagedElement attributes and association roles to SS equivalent MOC ManagedElement attributes

NRM Attributes/Association roles	SS Attributes	SS Type	Qualifier
managedElementId	managedElementId	string	Read-Only, M
dnPrefix	dnPrefix	string	Read-Only, M
userLabel	userLabel	string	Read-Write, M
IocationName	locationName	string	Read-Only, M
vendorName	vendorName	string	Read-Only, M
userDefinedState	userDefinedState	string	Read-Write, M
managedElementType	managedElementTy pe	GenericNetworkResourcesNRMDef s::AttributeTypes::StringSet	Read-Only, M
managedBy	managedBy	GenericNetworkResourcesNRMDef s::AttributeTypes::MOReferenceSet	Read-Only, M
swVersion	swVersion	string	Read-Only, M

5.2.3 IOC MeContext

Mapping from NRM IOC MeContext attributes to SS equivalent MOC MeContext attributes

NRM Attributes of IOC MeContext in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
meContextId	meContextId	string	Read-Only, M
dnPrefix	dnPrefix	string	Read-Only, M

5.2.4 IOC ManagementNode

Mapping from NRM IOC ManagementNode attributes and association roles to SS equivalent MOC ManagementNode attributes

NRM Attributes/association roles of IOC ManagementNode in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
managementNodeld	managementNodel d	string	Read-Only, M
userLabel	userLabel	string	Read-Write, M
locationName	locationName	string	Read-Only, M
vendorName	vendorName	string	Read-Only, M
userDefinedState	userDefinedState	string	Read-Write, M
managedElements	managedElements	GenericNetworkResourcesNRMDef s::AttributeTypes::MOReferenceSet	Read-Only, M
swVersion	swVersion	string	Read-Only, M

5.2.5 IOC VsDataContainer

Mapping from NRM IOC VsDataContainer attributes and association roles to SS equivalent MOC VsDataContainer attributes

NRM Attributes/association roles of IOC VsDataContainer in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
vsDataContainerId	vsDataContainerId	string	Read-Only, M
vsDataType	vsDataType	string	Read-Only, M
vsData	vsData	any	Read-Write, M
vsDataFormatVersion	vsDataFormatVersion	string	Read-Only, M

5.2.6 IOC ManagedFunction

Mapping from NRM IOC ManagedFunction attributes and association roles to SS equivalent MOC ManagedFunction attributes

NRM Attributes/association roles of IOC ManagedFunction in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
userLabel	userLabel	string	Read-Write, M

5.2.7 IOC IRPAgent

Mapping from NRM IOC IRPAgent attributes to SS equivalent MOC IRPAgent attributes

NRM Attributes of IOC IRPAgent in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
irpAgentId	irpAgentId	string	Read-Only, M
systemDN	systemDN	string	Read-Only, M

5.2.8 IOC GenericIRP

This Information Object Class is provided for sub-classing only. Therefore no mapping for this class is provided in this document.

5.2.9 IOC Top

Mapping from NRM IOC Top attributes to SS equivalent attributes in all MOCs

NRM Attributes of IOC Top in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
objectClass	CLASS	string	Read-Only, M
objectInstance	No direct		
	mapping.		

5.2.10 IOC Link

Mapping from NRM IOC Link attributes to SS equivalent MOC IRPAgent attributes

NRM Attributes of IOC Top	SS Attributes	SS Type	Qualifier
in 3GPP TS 32.622 [4]			
linkld	linkld	string	Read-Only, M
objectClass (see note 1)	CLASS	string	Read-Only, M
objectInstance (see note 1)	No direct mapping		Read-Only, M
userLabel (see note 2)	userLabel	string	Read-Write, M
aEnd	aEnd	GenericNetworkResourcesIRPSystem::Attribut	Read-Only, M
		eTypes::MOReference	
zEnd	zEnd	GenericNetworkResourcesIRPSystem::Attribut	Read-Only, M
		eTypes::MOReference	
linkType	linkType	LinkTypeType	Read-Only, O
protocolName	protocolName	string	Read-Only, O
protocolVersion	protocolVersion	string	Read-Only, O

NOTE 1: This attribute is inherited from ${\tt ManagedFunction\ via\ Top}$

NOTE 2: This attribute is inherited from ManagedFunction

6 Rules for NRM extensions

This clause discusses how the models and IDL definitions provided in the present document can be extended for a particular implementation and still remain compliant with 3GPP SA5's specifications.

6.1 Allowed extensions

Vendor-specific MOCs may be supported. The vendor-specific MOCs may support new types of attributes. The 3GPP SA5-specified notifications may be issued referring to the vendor-specific MOCs and vendor-specific attributes. New MOCs shall be distinguishable from 3GPP SA5 MOCs by name. 3GPP SA5-specified and vendor-specific attributes may be used in vendor-specific MOCs. Vendor-specific attribute names shall be distinguishable from existing attribute names.

NRM MOCs may be subclassed. Subclassed MOCs shall maintain the specified behaviour of the 3GPP SA5's superior classes. They may add vendor-specific behaviour with vendor-specific attributes. When subclassing, naming attributes cannot be changed. The subclassed MOC shall support all attributes of its superior class. Vendor-specific attributes cannot be added to 3GPP SA5 NRM MOCs without subclassing.

When subclassing, the 3GPP SA5-specified containment rules and their specified cardinality shall still be followed. As an example, ManagementNode (or its subclasses) shall be contained under SubNetwork (or its subclasses).

Managed Object Instances may be instantiated as CORBA objects. This requires that the MOCs be represented in IDL. 3GPP SA5's NRM MOCs are not currently specified in IDL, but may be specified in IDL for instantiation or subclassing purposes. However, management information models should not require that IRPManagers access the instantiated managed objects other than through supported methods in the present document.

Extension rules related to notifications (Notification categories, Event Types, Extended Event Types etc.) are for further study.

6.2 Extensions not allowed

The IDL specifications in the present document cannot be edited or altered. Any additional IDL specifications shall be specified in separate IDL files.

IDL interfaces (note: not MOCs) specified in the present document may not be subclassed or extended. New interfaces may be defined with vendor-specific methods.

Annex A (normative): IDL specifications

A.1 IDL specification (file name "GenericNetworkResourcesIRPSystem.idl")

```
//File: GenericNetworkResourcesIRPSystem.idl
#ifndef _GENERIC_NETWORK_RESOURCES_IRP_SYSTEM_IDL_
#define GENERIC NETWORK RESOURCES IRP SYSTEM IDL
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
module GenericNetworkResourcesIRPSystem
 /**
  * The format of Distinguished Name (DN) is specified in "Name Convention
  * for Managed Objects (3GPP TS 32.300 [5])".
  */
 typedef string DN;
 /**
  * This module adds datatype definitions for types
  * used in the NRM which are not basic datatypes defined
  * already in CORBA.
 module AttributeTypes
   /**
    * An MO reference refers to an MO instance.
    * "otherMO" contains the distinguished name of the referred MO.
    * A conceptual "null" reference (meaning no MO is referenced)
    * is represented as an empty string ("").
```

```
*/
 struct MOReference
 {
   DN otherMO;
 };
 /**
  * MOReferenceSet represents a set of MO references.
  * This type is used to hold 0..n MO references.
  * A referred MO is not allowed to be repeated (therefore
  * it is denoted as a "Set")
 typedef sequence<MOReference> MOReferenceSet;
 /**
  * A set of strings.
 typedef sequence<string> StringSet;
 /**
  * A set of long.
 typedef sequence<long> LongSet;
};
```

#endif // _GENERIC_NETWORK_RESOURCES_IRP_SYSTEM_IDL_

};

Annex B (normative): IDL specifications

B.1 IDL specification (file name"GenericNetworkResourcesNRMDefs.idl")

```
//File: GenericNetworkResourcesNRMDefs.idl
#ifndef _GENERIC_NETWORK_RESOURCES_NRM_DEFS_IDL_
#define _GENERIC_NETWORK_RESOURCES_NRM_DEFS_IDL_
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
* This module defines constants for each MO class name and
* the attribute names for each defined MO class.
module GenericNetworkResourcesNRMDefs
{
   /**
    * Definitions for MO class Top
   interface Top
     // Attribute Names
     const string CLASS = "Top";
   };
    * Definitions for MO class SubNetwork
    */
   interface SubNetwork: Top
     const string CLASS = "SubNetwork";
     // Attribute Names
     //
```

```
const string subNetworkId = "subNetworkId";
 const string dnPrefix = "dnPrefix";
 const string userLabel = "userLabel";
 const string userDefinedNetworkType = "userDefinedNetworkType";
 const string setOfMcc = "setOfMcc";
};
/**
* Definitions for MO class ManagedElement
interface ManagedElement: Top
 const string CLASS = "ManagedElement";
 // Attribute Names
 //
 const string managedElementId = "managedElementId";
 const string dnPrefix = "dnPrefix";
 const string managedElementType = "managedElementType";
 const string userLabel = "userLabel";
 const string vendorName = "vendorName";
 const string userDefinedState ="userDefinedState";
 const string locationName ="locationName";
 const string managedBy = "managedBy";
 const string swVersion = "swVersion";
};
/**
* Definitions for MO class MeContext
interface MeContext: Top
 const string CLASS = "MeContext";
 // Attribute Names
 const string meContextId = "meContextId";
```

```
const string dnPrefix = "dnPrefix";
};
/**
* Definitions for MO class ManagementNode
interface ManagementNode: Top
 const string CLASS = "ManagementNode";
 // Attribute Names
 const string managementNodeId = "managementNodeId";
 const string userLabel = "userLabel";
 const string vendorName = "vendorName";
 const string userDefinedState = "userDefinedState";
 const string locationName = "locationName";
 const string managedElements = "managedElements";
 const string swVersion = "swVersion";
};
/**
* Definitions for abstract MO class ManagedFunction
interface ManagedFunction: Top
{
 const string CLASS = "ManagedFunction";
 // Attribute Names
 const string userLabel = "userLabel";
};
/**
* Definitions for MO class IRPAgent
```

```
interface IRPAgent: Top
  const string CLASS = "IRPAgent";
 // Attribute Names
 const string irpAgentId = "irpAgentId";
 const string systemDN = "systemDN";
};
/**
* Definitions for abstract MO class Link
* This inherits from ManagedFunction
* The attributes aEnd and zEnd are populated with the DNs
* of the entities associated via the link class.
* The aEnd takes the DN of the 1st entity in alphabetical order,
* the zEnd takes the 2nd entity in alphabetical order of the class
* names.
interface Link: ManagedFunction
 const string CLASS = "Link";
 // Attribute Names
  const string linkId = "linkId";
  const string aEnd = "aEnd";
  const string zEnd = "zEnd";
  const string linkType = "linkType";
 const string protocolName = "protocolName";
 const string protocolVersion = "protocolVersion";
};
/**
* Definitions for MO class VsDataContainer
interface VsDataContainer: Top
  const string CLASS = "VsDataContainer";
 // Attribute Names
```

```
//
     const string vsDataContainerId = "vsDataContainerId";
     const string vsDataType = "vsDataType";
     const string vsData = "vsData";
     const string vsDataFormatVersion = "vsDataFormatVersion";
   };
   /**
   * This module adds datatypes definitions for the Link Class
    * These attributes are not the basic datatypes already defined
   module LinkAttributeTypes
     enum LinkType
     {
      SIGNALLING,
      BEARER,
      OAM_AND_P,
      OTHER
     };
    typedef sequence <LinkType> LinkTypeType;
   };
};
#endif // _GENERIC_NETWORK_RESOURCES_NRM_DEFS_IDL_
```

Annex C (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New	
Jun 2001	SA_12	SP-010283			Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0	
Sep 2001	SA_13	SP-010479	0001		Missing Mapping table added and attribute qualifier corrected	4.0.0	4.1.0	
Dec 2001	SA_14	SP-010646	0002		Change type "integer" to "long" in the Generic Network Resources IRP: CORBA SS	4.1.0	4.2.0	
Dec 2001	SA_14	SP-010647	0003		Correction of Generic NRM CORBA Solution Set IDL definitions	4.1.0	4.2.0	
Sep 2002	SA_17	SP-020488	0004		Upgrade the NRM CORBA Solution Set to Rel-5	4.2.0	5.0.0	
Mar 2003	SA_19	SP-030141	0006		Replace Microsoft Word "" with straight Double Quotes - to avoid CORBA IDL Compilation Errors	5.0.0	5.1.0	
Dec 2003	SA_22	SP-030648	0007		Add SetofMcc attribute in Generic NRM IOCs for NRM alignment	5.1.0	6.0.0	
Mar 2004	SA_23	SP-040128	0009		Addition/correction of attributes for the managementScope association - Alignment with 32.622	6.0.0	6.1.0	
Jun 2004	SA_24	SP-040251	0011		Correction of legal values for managedElementType attribute	6.1.0	6.2.0	
Sep 2004	SA_25	SP-040567	0013		Correction in Rules for NRM extensions - Align with 32.622 (Generic NRM IS)	6.2.0	6.3.0	
Sep 2004	SA_25	SP-040581	0014		Add Inheritance in CORBA IDL	6.2.0	6.3.0	
Mar 2005	SA_27	SP-050046	0015		Add Link to generic NRM CORBA SS	6.3.0	6.4.0	
Jun 2005	SA_28	SP-050296	0016		Correction of IDL syntax error in GenericNetworkResourcesNRMDefs.idl	6.4.0	6.5.0	

History

Document history						
V6.3.0	September 2004	Publication				
V6.4.0	March 2005	Publication				
V6.5.0	June 2005	Publication				