ETSI TS 128 673 V12.0.0 (2014-10)



Universal Mobile Telecommunications System (UMTS); LTE;

Telecommunication management;
Home Node B (HNB) Subsystem (HNS)
Network Resource Model (NRM)
Integration Reference Point (IRP);
Solution Set (SS) definitions
(3GPP TS 28.673 version 12.0.0 Release 12)



Reference
RTS/TSGS-0528673vc00

Keywords
LTE, UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: <u>http://portal.etsi.org/chaircor/ETSI_support.asp</u>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "may not", "need", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intelle	lectual Property Rights	2
Forew	word	2
Moda	al verbs terminology	2
Forew	word	4
Introd	duction	4
1	Scope	5
2	References	5
3	Definitions and abbreviations	6
3.1	Definitions	6
3.2	Abbreviations	
4	Solution Set Definitions	
Anne	ex A (normative): CORBA Solution Set	8
A.0	General	8
A.1	Architectural features	
A.1.1 A.1.2	• · · · · · · · · · · · · · · · · · · ·	
A.2	Mapping	
A.2.1	General mappings	9
A.2.2 A.2.2.	\mathbf{J}	
A.2.2.	.2 IOC HNBProfile	9
A.2.2. A.2.2.		
A.2.2. A.2.2.		
A.3	Solution Set definitions	10
A.3.1		
A.3.2	IDL specification 'HnsNetworkResourcesNRMDefs.idl'	10
Anne	ex B (normative): XML Definitions	12
B.0	General	12
B.1	Architectural features	
B.1.1		
B.2	Mapping	
B.2.1 B.2.2	11 0	
B.3	Solution Set definitions	
B.3.1	XML definition structure	12
B.3.2 B.3.3	1 1	
	ex C (informative): Change history	
Histor	NTV	17

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project: Technical Specification Group Services and System Aspects; Telecommunication management; Configuration Management (CM); as identified below:

- 28.671: Telecommunication management; Home Node B Subsystem (HNS) Network Resource Model (NRM) Integration Reference Point (IRP); Requirements
- 28.672: Telecommunication management; Home Node B Subsystem (HNS) Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)
- 28.673: Telecommunication management; Home Node B (HNB) Subsystem (HNS) Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions

1 Scope

The present document is part of an Integration Reference Point (IRP) named HNS Network Resource Model (NRM) IRP, through which an IRPAgent can communicate configuration management information to one or several IRPManagers concerning HNS resources. The HNS NRM IRP comprises a set of specifications defining Requirements, a protocol neutral Information Service and one or more Solution Set(s).

The present document specifies the Solution Sets for the HNS NRM IRP.

This specification is related to 3GPP TS 28.672V12.0.X.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.

Solution Set (SS) definitions'.

• For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

the semie rec	case as me present accument
[1]	3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
[2]	3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
[3]	3GPP TS 32.102: "Telecommunication management; Architecture".
[4]	3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
[5]	3GPP TS 28.672: "Telecommunication management; Home Node B (HNB) Subsystem (HNS) Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)
[6]	3GPP TS 32.616: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP): Solution Set (SS) definitions".
[7]	3GPP TS 32.606: "Telecommunication management; Configuration Management (CM); Basic CM Integration Reference Point (IRP): Solution Set (SS) definitions".
[8]	W3C REC-xml11-20060816: "Extensible Markup Language (XML) 1.1 (Second Edition)".
[9]	Void
[10]	W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures.
[11]	W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes.
[12]	W3C REC-xml-names-20060816: "Namespaces in XML 1.1 (Second Edition)".
[13]	3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects"
[14]	3GPP TS 28.623: 'Generic Network Resource Model (NRM) Integration Reference Point (IRP);

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

For terms and definitions please refer to 3GPP TS 32.101 [2], 32.102 [3], 32.600 [4] and 32.772 [5].

XML file: See definition of [14].

XML document: See definition of [14].

XML declaration: See definition of [14].

XML element: See definition of [14].

empty XML element: See definition of [14].

XML content (of an XML element): See definition of [14].

XML start-tag: See definition of [14].

XML end-tag: See definition of [14].

XML empty-element tag: See definition of [14].

XML attribute specification: See definition of [14].

DTD: See definition of [14].

XML schema: See definition of [14].

XML namespace: See definition of [14].

XML complex type: See definition of [14].

XML element type: See definition of [14].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

CM Configuration Management

CORBA Common Object Request Broker Architecture

DN Distinguished Name
DTD Document Type Definition

HNB Home Node B

HNS Home Node B Subsystem
HNB-GW Home Node B Gateway
IDL Interface Definition Language
IRP Integration Reference Point

IS Information Service
MO Managed Object
MOC Managed Object Class
NRM Network Resource Model
OMG Object Management Group

SS Solution Set

XML eXtensible Markup Language

4 Solution Set Definitions

This specification defines the following 3GPP HNS NRM IRP Solution Set Definitions:

- 3GPP HNS NRM IRP CORBA SS (Annex A)
- 3GPP HNS NRM IRP XML Definitions (Annex B)

Annex A (normative): CORBA Solution Set

A.0 General

This annex contains the CORBA Solution Set for the IRP whose semantics is specified in HNS NRM IRP: Information Service (TS 32.772 [5]).

A.1 Architectural features

The overall architectural feature of HNS Network Resources IRP is specified in 3GPP TS 28.672 [5].

This clause specifies features that are specific to the CORBA SS.

A.1.1 Syntax for Distinguished Names

See clause A.1.1 of [14]

A.1.2 Rules for NRM extensions

See clause A.1.1 of [14].

A.2 Mapping

A.2.1 General mappings

See clause A.2.1 of [14].

A.2.2 Information Object Class (IOC) mapping

This SS supports reference attributes for relations other than containment relations between objects. Reference attributes are therefore introduced in each MOC where needed.

A.2.2.1 IOC HNBGWFunction

IS Attributes	SS Attributes	SS Type
id	hnbgwFunctionId	string
hnbgwld	hnbgwld	string
userLabel	userLabel	string
ipConfigInfo	ipConfigInfo	string
maxNbrHNBRegistered	maxNbrHNBRegistered	Integer
maxPacketCapability	maxPacketCapability	integer

A.2.2.2 IOC HNBProfile

IS Attributes	SS Attributes	SS Type
Id	hnbProfileId	string
userLabel	userLabel	string
Configuration	configuration	string
Criterion	criterion	string

A.2.2.3 IOC HMSFunction

IS Attributes	SS Attributes	SS Type
userLabel	userLabel	string

A.2.2.4 IOC luhSignLinkTp

IS Attributes	SS Attributes	SS Type
Id	iuhSignLinkTpId	string
userLabel	userLabel	string
farEndEntity	farEndEntity	string
sctpAssocLocalAddr	sctpAssocLocalAddr	string
sctpAssocRemoteAddr	sctpAssocRemoteAddr	string

A.2.2.5 IOC EP_luh

IS Attributes	SS Attributes	SS Type
Id	epluhld	string
userLabel	userLabel	string
farEndEntity	farEndEntity	string
farEndNEIPAddr	farEndNEIPAddr	string

A.3 Solution Set definitions

A.3.1 IDL definition structure

Clause A.3.2 defines the MO classes for the HNS NRM IRP.

A.3.2 IDL specification 'HnsNetworkResourcesNRMDefs.idl'

```
//File: HnsNetworkResourcesNRMDefs.idl
#ifndef _HNSNETWORKRESOURCESNRMDEFS_IDL_
#define _HNSNETWORKRESOURCESNRMDEFS_IDL_
#include "GenericNetworkResourcesNRMDefs.idl"
#pragma prefix "3gppsa5.org"
\ensuremath{^{\star}} This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
module HnsNetworkResourcesNRMDefs
       * Definitions for MO class HnbgwFunction
      interface HNBGWFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
         const string CLASS = "HNBGWFunction";
         // Attribute Names
         const string hnbgwFunctionId = "hnbgwFunctionId";
         const string hnbgwId = "hnbgwId";
         const string ipConfigInfo = "ipConfigInfo";
         const string maxNbrHNBRegistered = "maxNbrHNBRegistered";
         const string maxPacketCapability = "maxPacketCapability";
      };
       * Definitions for MO class IuhSignLinkTp
       */
      interface IuhSignLinkTp : GenericNetworkResourcesNRMDefs::EP_RP
         const string CLASS = "IuhSignLinkTp";
         // Attribute Names
         const string sctpAssocLocalAddr = "sctpAssocLocalAddr";
         const string sctpAssocRemoteAddr = "sctpAssocRemoteAddr";
       * Definitions for MO class EP_Iuh
         interface EP_Iuh : GenericNetworkResourcesNRMDefs::EP_RP
         const string CLASS= "EP_Iuh";
         // Attribute Names
         const string farEndNEIPAddr= "farEndNEIPAddr";
       * Definitions for MO class HNBProfile
      interface HNBProfile : GenericNetworkResourcesNRMDefs::ManagedFunction
         const string CLASS= "HNBProfile";
         // Attribute Names
         const string hnbProfileId = "hnbProfileId";
         const string configuration = "configuration";
         const string criterion = "criterion";
      };
```

```
/**
    * Definitions for MO class HMSFunction
    */
    interface HMSFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS= "HMSFunction";
        // Attribute Names
        //
     };
};
#endif //_HNSETWORKRESOURCESNRMDEFS_IDL_
```

Annex B (normative): XML Definitions

B.0 General

This annex contains the XML Definitions for the HNS NRM IRP as it applies to Itf-N, in accordance with HNS NRM IRP Information Service (TS 28.672 [5]).

The XML file formats are based on XML [8], XML Schema [10] [11] and XML Namespace [12] standards.

B.1 Architectural features

The overall architectural feature of HNS Network Resources IRP is specified in 3GPP TS 28.672 [5]. This clause specifies features that are specific to the Schema definitions.

B.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [13].

B.2 Mapping

B.2.1 General mapping

An IOC maps to an XML element of the same name as the IOC's name in the IS. An IOC attribute maps to a sub-element of the corresponding IOC's XML element, and the name of this sub-element is the same as the attribute's name in the IS.

B.2.2 Information Object Class (IOC) mapping

The mapping is not present in the current version of this specification.

B.3 Solution Set definitions

B.3.1 XML definition structure

Annex B.3.3 of the present document defines the NRM-specific XML schema hnsNrm.xsd for the HNS Network Resources IRP NRM defined in 3GPP TS 28.672 [5].

XML schema hnsNrm.xsd explicitly declares NRM-specific XML element types for the related NRM.

The definition of those NRM-specific XML element types complies with the generic mapping rules defined in 3GPP TS 32.616 [6].

B.3.2 Graphical Representation

The graphical representation is not present in the current version of this specification.

B.3.3 XML schema "hnsNrm.xsd"

```
<?xml version="1.1" encoding="UTF-8"?>
<!--
 3GPP TS 28.673 HNS Network Resources IRP
 Bulk CM Configuration data file NRM-specific XML schema
 hnsNrm.xsd
<schema
 targetNamespace=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.676#hnsNrm"
 elementFormDefault="qualified"
 xmlns="http://www.w3.org/2001/XMLSchema"
 xmlns:xn=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"
 xmlns:un=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.673#hnsNrm"
 xmlns:qn=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.656#geranNrm"
"http://www.3qpp.org/ftp/specs/archive/28_series/28.626#stateManagementIRP"
    <import namespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"</pre>
schemaLocation="genericNrm.xsd"/>
    <import namespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.656#geranNrm"</pre>
schemaLocation="geranNrm.xsd"/>
    <import namespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.626#stateManagementIRP"</pre>
schemaLocation="stateManagementIRP.xsd"/>
 <!-- HNS Network Resources IRP NRM attribute related XML types -->
 <!-- HNS network Resources IRP NRM class associated XML elements -->
 <element
   name="HNBGWFunction"
   substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass"
   <complexType>
     <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
             <all>
               <element name="hnbgwId" type="string"/>
               <element name="userLabel" type="string"/>
               <element name="iPConfigInfo" type="string"/>
               <element name="maxNbrHNBRegistered" type="integer"/>
<element name="maxPacketCapability" type="integer"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:VsDataContainer"/>
            <element ref="un:IuhSignLinkTp"/>
            <element ref="un:EP_Iuh"/>
          </choice>
        </sequence>
      </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="IuhSignLinkTp">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
             <all>
```

```
<element name="userLabel" type="string" minOccurs="0"/>
              <element name="farEndEntity" type="string" minOccurs="0"/>
<element name="sctpAssocLocalAddr" type="string"/>
              <element name="sctpAssocRemoteAddr" type="string"/>
            </all>
          </complexType>
        </element>
        <choice minOccurs="0" maxOccurs="unbounded">
          <element ref="xn:VsDataContainer"/>
         </choice>
       </sequence>
     </extension>
   </complexContent>
 </complexType>
</element>
<element name="EP_Iuh">
 <complexType>
   <complexContent>
     <extension base="xn:NrmClass">
       <sequence>
        <element name="attributes" minOccurs="0">
          <complexType>
            <all>
              <element name="userLabel" type="string" minOccurs="0"/>
              <element name="farEndEntity" type="string" minOccurs="0"/>
              <element name="farEndNEIPAddr" type="string" minOccurs="0"/>
            </all>
          </complexType>
        </element>
        <choice minOccurs="0" maxOccurs="unbounded">
          <element ref="xn:VsDataContainer"/>
        </choice>
       </sequence>
     </extension>
   </complexContent>
 </complexType>
</element>
<element name="HNBProfile">
 <complexType>
   <complexContent>
     <extension base="xn:NrmClass">
       <sequence>
        <element name="attributes" minOccurs="0">
          <complexType>
            <all>
              <element name="userLabel" type="string"/>
              <element name="configuration" type="string"/>
              <element name="criterion" type="string" minOccurs="0"/>
            </all>
          </complexType>
        </element>
       </sequence>
     </extension>
   </complexContent>
 </complexType>
</element>
<element name="HMSFunction">
 <complexType>
   <complexContent>
     <extension base="xn:NrmClass">
       <sequence>
        <element name="attributes" minOccurs="0">
          <complexType>
            <all>
              <element name="userLabel" type="string"/>
            </all>
          </complexType>
        </element>
        <choice minOccurs="0" maxOccurs="unbounded">
             <element ref="xn:VsDataContainer"/>
             <element ref="un:HNBProfile"/>
        </choice>
       </sequence>
```

</schema>

Annex C (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2014-06	SA#64	SP-140332	001	-	Upgrade W3C XML Schema version from 1.0 to 1.1	11.0.0	11.1.0
		SP-140360	002	-	remove the feature support statements		
2014-09	SA#65	SP-140560	003	-	Update the link from Solution Set to Information Service due to the end of 11.1.0 12		12.0.0
					Release 12		

History

Document history					
V12.0.0	Publication				