ETSI TS 132 626 V11.0.0 (2012-10)

Technical Specification

Digital cellular telecommunications system (Phase 2+);
Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Configuration Management (CM);
Generic network resources Integration Reference Point (IRP);
Solution Set (SS) definitions
(3GPP TS 32.626 version 11.0.0 Release 11)

Reference
RTS/TSGS-0532626vb00

Keywords
GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00　　　Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://ipr.etsi.org).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Contents

Intellectual Property Rights 2

Foreword...2

Foreword...4

Introduction 4

1 Scope 5

2 References 5

3 Definitions and abbreviations...6
3.1 Definitions 6
3.2 Abbreviations 7

4 Solution Set Definitions 7

Annex A (normative): CORBA Solution Set 8

A.1 Architectural features 8
A.1.1 Syntax for Distinguished Names 8
A.1.2 Rules for NRM extensions 8
A.1.2.1 Allowed extensions...8
A.1.2.2 Extensions not allowed 8

A.2 Mapping 9
A.2.1 General mapping 9
A.2.2 Information Object Class (IOC) mapping 9
A.2.2.1 IOC SubNetwork 9
A.2.2.2 IOC ManagedElement 9
A.2.2.3 IOC MeContext 10
A.2.2.4 IOC ManagementNode 10
A.2.2.5 IOC VsDataContainer 10
A.2.2.6 IOC ManagedFunction 10
A.2.2.7 IOC IRPAgent 10
A.2.2.8 IOC Top 11
A.2.2.9 IOC Link 11
A.2.2.10 IOC EP_RP 11

A.3 Solution Set definitions 12
A.3.1 IDL definition structure 12
A.3.2 IDL specification "GenericNetworkResourcesIRPSystem.idl" 12
A.3.3 IDL specification "GenericNetworkResourcesNRMDefs.idl" 14

Annex B (normative): XML Definitions 17

B.1 Architectural features 17
B.1.1 Syntax for Distinguished Names 17

B.2 Mapping 17
B.2.1 General mapping...17
B.2.2 Information Object Class (IOC) mapping 17

B.3 Solution Set definitions 18
B.3.1 XML definition structure..18
B.3.2 Graphical Representation 18
B.3.3 XML schema "genericNrm.xsd" 19

Annex C (informative): Change history 23

History 24

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x   the first digit:

1   presented to TSG for information;

2   presented to TSG for approval;

3   or greater indicates TSG approved document under change control.

y   the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z   the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

32.621:   Configuration Management (CM); Generic network resources Integration Reference Point (IRP); Requirements

32.622:   Configuration Management (CM); Generic network resources Integration Reference Point (IRP); Network Resource Model (NRM)

32.626:   Configuration Management (CM); Generic network resources Integration Reference Point (IRP); Solution Set (SS) definitions

1 Scope

The TS 32.62x-series (Generic Network Resources IRP) define an Integration Reference Point (IRP) through which an "IRPAgent" (typically an Element Manager or Network Element) can communicate Network Management related information to one or several "IRPManagers" (typically Network Managers).

This TS-family specifies a generic Network Resource Model, NRM (also referred to as a Management Information Model - MIM) with definitions of Information Object Classes (IOCs) and Managed Object Classes (MOCs).

The present document specifies the Solution Sets for the Generic NRM IRP.

These Solution Set specifications are related to 3GPP TS 32.622 V11.0.X [4].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.

- For a specific reference, subsequent revisions do not apply.

- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document.*

[1]   3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".

[2]   3GPP TS 32.102: "Telecommunication management; Architecture".

[3]   3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".

[4]   3GPP TS 32.622: "Telecommunication management; Configuration Management (CM); Generic network resources Integration Reference Point (IRP): Network Resource Model (NRM)".

[5]   3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".

[6]   3GPP TS 32.306: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP); Solution Set (SS) definitions".

[7]   3GPP TS 32.616: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Solution Set (SS) definitions".

[8]   W3C REC-xml-20001006: "Extensible Markup Language (XML) 1.0 (Second Edition)".

[9]   W3C REC-xmlschema-0-20010502: "XML Schema Part 0: Primer".

[10]   W3C REC-xmlschema-1-20010502: "XML Schema Part 1: Structures".

[11]   W3C REC-xmlschema-2-20010502: "XML Schema Part 2: Datatypes".

[12]   W3C REC-xml-names-19990114: "Namespaces in XML".

3 Definitions and abbreviations

3.1 Definitions

For terms and definitions please refer to 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.600 [3] and 3GPP TS 32.622 [4].

XML file: file containing an XML document

XML document: composed of the succession of an optional XML declaration followed by a root XML element

NOTE: See [8]; in the scope of the present document.

XML declaration: it specifies the version of XML being used

NOTE: See [8].

XML element: has a type, is identified by a name, may have a set of XML attribute specifications and is either composed of the succession of an XML start-tag followed by the XML content of the XML element followed by an XML end-tag, or composed simply of an XML empty-element tag; each XML element may contain other XML elements

NOTE: See [8].

empty XML element: having an empty XML content; an empty XML element still possibly has a set of XML attribute specifications; an empty XML element is either composed of the succession of an XML start-tag directly followed by an XML end-tag, or composed simply of an XML empty-element tag

NOTE: See [8].

XML content (of an XML element): empty if the XML element is simply composed of an XML empty-element tag; otherwise the part, possibly empty, of the XML element between its XML start-tag and its XML end-tag

XML start-tag: the beginning of a non-empty XML element is marked by an XML start-tag containing the name and the set of XML attribute specifications of the XML element

NOTE: See [8].

XML end-tag: the end of a non-empty XML element is marked by an XML end-tag containing the name of the XML element

NOTE: See [8].

XML empty-element tag: composed simply of an empty-element tag containing the name and the set of XML attribute specifications of the XML element.

NOTE: See [8].

XML attribute specification: has a name and a value

NOTE: See [8].

DTD: defines structure and content constraints to be respected by an XML document to be valid with regard to this DTD

NOTE: See [8].

XML schema: more powerful than a DTD, an XML schema defines structure and content constraints to be respected by an XML document to conform with this XML schema; through the use of XML namespaces several XML schemas can be used together by a single XML document; an XML schema is itself also an XML document that shall conform with the XML schema for XML schemas

NOTE: See [9], [10] and [11].

XML namespace: enables qualifying element and attribute names used in XML documents by associating them with namespaces identified by different XML schemas

    NOTE: See [12], in the scope of the present document.

XML complex type: defined in an XML schema; cannot be directly used in an XML document; can be the concrete type or the derivation base type for an XML element type or for another XML complex type; ultimately defines constraints for an XML element on its XML attribute specifications and/or its XML content

    NOTE: See [9], [10] and [11].

XML element type: declared by an XML schema; can be directly used in an XML document; as the concrete type of an XML element, directly or indirectly defines constraints on its XML attribute specifications and/or its XML content; can also be the concrete type or the derivation base type for another XML element type

    NOTE: See [9], [10] and [11].

For additional terms and definitions please refer to 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.600 [3] and 3GPP TS 32.622 [4].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM	Configuration Management
CORBA	Common Object Request Broker Architecture
DN	Distinguished Name
DTD	Document Type Definition
EDGE	Enhanced Data for GSM Evolution
GERAN	GSM/EDGE Radio Access Network
GSM	Global System for Mobile communication
IS	Information Service
IDL	Interface Definition Language (OMG)
IRP	Integration Reference Point
IS	Information Service
MO	Managed Object
MOC	Managed Object Class
NRM	Network Resource Model
OMG	Object Management Group
SS	Solution Set
UMTS	Universal Mobile Telecommunications System
UTRAN	Universal Terrestrial Radio Access Network
XML	eXtensible Markup Language

4 Solution Set Definitions

This specification defines the following 3GPP Generic NRM IRP Solution Set Definitions:

- 3GPP Generic NRM IRP CORBA SS (Annex A)

- 3GPP Generic NRM IRP XML Definitions (Annex B)

Annex A (normative):
CORBA Solution Set

This annex contains the CORBA Solution Set for the IRP whose semantics is specified in Generic NRM IRP: Information Service (TS 32.622 [4]).

A.1 Architectural features

The overall architectural feature of Generic Network Resources IRP is specified in 3GPP TS 32.622 [4]. This clause specifies features that are specific to the CORBA SS.

A.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

A.1.2 Rules for NRM extensions

This clause discusses how the models and IDL definitions provided in the present document can be extended for a particular implementation and still remain compliant with 3GPP SA5's specifications.

A.1.2.1 Allowed extensions

Vendor-specific MOCs may be supported. The vendor-specific MOCs may support new types of attributes. The 3GPP SA5-specified notifications may be issued referring to the vendor-specific MOCs and vendor-specific attributes. New MOCs shall be distinguishable from 3GPP SA5 MOCs by name. 3GPP SA5-specified and vendor-specific attributes may be used in vendor-specific MOCs. Vendor-specific attribute names shall be distinguishable from existing attribute names.

NRM MOCs may be subclassed. Subclassed MOCs shall maintain the specified behaviour of the 3GPP SA5's superior classes. They may add vendor-specific behaviour with vendor-specific attributes. When subclassing, naming attributes cannot be changed. The subclassed MOC shall support all attributes of its superior class. Vendor-specific attributes cannot be added to 3GPP SA5 NRM MOCs without subclassing.

When subclassing, the 3GPP SA5-specified containment rules and their specified cardinality shall still be followed. As an example, ManagementNode (or its subclasses) shall be contained under SubNetwork (or its subclasses).

Managed Object Instances may be instantiated as CORBA objects. This requires that the MOCs be represented in IDL. 3GPP SA5's NRM MOCs are not currently specified in IDL, but may be specified in IDL for instantiation or subclassing purposes. However, management information models should not require that IRPManagers access the instantiated managed objects other than through supported methods in the present document.

Extension rules related to notifications (Notification categories, Event Types, Extended Event Types etc.) are for further study.

A.1.2.2 Extensions not allowed

The IDL specifications in the present document cannot be edited or altered. Any additional IDL specifications shall be specified in separate IDL files.

IDL interfaces (note: not MOCs) specified in the present document may not be subclassed or extended. New interfaces may be defined with vendor-specific methods.

A.2 Mapping

A.2.1 General mapping

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MOReference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MOReferenceSet, which contains a sequence of MO references.

A.2.2 Information Object Class (IOC) mapping

This Solution Set supports reference attributes for relations other than containment relations between objects. Reference attributes are therefore introduced in each MOC where needed.

A.2.2.1 IOC SubNetwork

Mapping from NRM IOC SubNetwork attributes to SS equivalent MOC SubNetwork attributes

NRM Attributes of IOC SubNetwork in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
subNetworkId	subNetworkId	string	Read-Only, M
dnPrefix	dnPrefix	string	Read-Only, M
userLabel	userLabel	string	Read-Write, M
userDefinedNetworkType	userDefinedNetworkType	string	Read-Only, M
setOfMcc	setOfMcc	GenericNetworkResourcesIRPSystem::AttributeTypes::StringSet	Read-Only, M (see note)
NOTE: If there may be more than one MCC value in the SubNetwork instance, the attribute setOfMcc is mandatory. Otherwise it is optional. The attribute can always be in the IOC, but the value could be set to "none".			

A.2.2.2 IOC ManagedElement

Mapping from NRM IOC ManagedElement attributes and association roles to SS equivalent MOC ManagedElement attributes

NRM Attributes/Association roles	SS Attributes	SS Type	Qualifier
managedElementId	managedElementId	string	Read-Only, M
dnPrefix	dnPrefix	string	Read-Only, M
userLabel	userLabel	string	Read-Write, M
locationName	locationName	string	Read-Only, M
vendorName	vendorName	string	Read-Only, M
userDefinedState	userDefinedState	string	Read-Write, M
managedElementType	managedElementType	GenericNetworkResourcesIRPSystem::AttributeTypes::StringSet	Read-Only, M
managedBy	managedBy	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet	Read-Only, M
swVersion	swVersion	string	Read-Only, M

A.2.2.3   IOC MeContext

Mapping from NRM IOC MeContext attributes to SS equivalent MOC MeContext attributes

NRM Attributes of IOC MeContext in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
meContextId	meContextId	string	Read-Only, M
dnPrefix	dnPrefix	string	Read-Only, M

A.2.2.4   IOC ManagementNode

Mapping from NRM IOC ManagementNode attributes and association roles to SS equivalent MOC ManagementNode attributes

NRM Attributes/association roles of IOC ManagementNode in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
managementNodeId	managementNodeId	string	Read-Only, M
userLabel	userLabel	string	Read-Write, M
locationName	locationName	string	Read-Only, M
vendorName	vendorName	string	Read-Only, M
userDefinedState	userDefinedState	string	Read-Write, M
managedElements	managedElements	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet	Read-Only, M
swVersion	swVersion	string	Read-Only, M

A.2.2.5   IOC VsDataContainer

Mapping from NRM IOC VsDataContainer attributes and association roles to SS equivalent MOC VsDataContainer attributes

NRM Attributes/association roles of IOC VsDataContainer in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
vsDataContainerId	vsDataContainerId	string	Read-Only, M
vsDataType	vsDataType	string	Read-Only, M
vsData	vsData	any	Read-Write, M
vsDataFormatVersion	vsDataFormatVersion	string	Read-Only, M

A.2.2.6   IOC ManagedFunction

Mapping from NRM IOC ManagedFunction attributes and association roles to SS equivalent MOC ManagedFunction attributes

NRM Attributes/association roles of IOC ManagedFunction in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
userLabel	userLabel	string	Read-Write, M

A.2.2.7   IOC IRPAgent

Mapping from NRM IOC IRPAgent attributes to SS equivalent MOC IRPAgent attributes

NRM Attributes of IOC IRPAgent in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
irpAgentId	irpAgentId	string	Read-Only, M
systemDN	systemDN	string	Read-Only, M

A.2.2.8   IOC Top

Mapping from NRM IOC Top attributes to SS equivalent attributes in all MOCs

NRM Attributes of IOC Top in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
objectClass	CLASS	string	Read-Only, M
objectInstance	No direct mapping		

A.2.2.9   IOC Link

Mapping from NRM IOC Link attributes to SS equivalent MOC IRPAgent attributes

NRM Attributes of IOC Top in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
linkId	linkId	string	Read-Only, M
objectClass (see note 1)	CLASS	string	Read-Only, M
objectInstance (see note 1)	No direct mapping		Read-Only, M
userLabel (see note 2)	userLabel	string	Read-Write, M
aEnd	aEnd	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference	Read-Only, M
zEnd	zEnd	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference	Read-Only, M
linkType	linkType	LinkTypeType	Read-Only, O
protocolName	protocolName	string	Read-Only, O
protocolVersion	protocolVersion	string	Read-Only, O
NOTE 1: This attribute is inherited from **ManagedFunction via Top** NOTE 2: This attribute is inherited from **ManagedFunction**			

A.2.2.10 IOC EP_RP

Mapping from NRM IOC EP_RP attributes to SS equivalent MOC EP_RP attributes

NRM Attributes of IOC EP_RP in 3GPP TS 32.622 [4]	SS Attributes	SS Type	Qualifier
id	id	string	Read-Only, M
userLabel	userLabel	string	Read-Write, O
farEndEntity	farEndEntity	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference	Read-Only, M

A.3 Solution Set definitions

A.3.1 IDL definition structure

Clause A.3.2 defines the types which are used by the Generic NRM IRP.

Clause A.3.3 defines the MO classes for the Generic NRM IRP.

A.3.2 IDL specification "GenericNetworkResourcesIRPSystem.idl"

```
//File: GenericNetworkResourcesIRPSystem.idl
#ifndef _GENERIC_NETWORK_RESOURCES_IRP_SYSTEM_IDL_
#define _GENERIC_NETWORK_RESOURCES_IRP_SYSTEM_IDL_

// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"

module GenericNetworkResourcesIRPSystem
{
    /**
     * The format of Distinguished Name (DN) is specified in "Name Convention
     * for Managed Objects (3GPP TS 32.300 [5])".
     */
    typedef string DN;

    /**
     *  This module adds datatype definitions for types
     *  used in the NRM which are not basic datatypes defined
     *  already in CORBA.
     */
    module AttributeTypes
    {
        /**
         * An MO reference refers to an MO instance.
         * "otherMO" contains the distinguished name of the referred MO.
         * A conceptual "null" reference (meaning no MO is referenced)
         * is represented as an empty string ("").
         *
         */
        struct MOReference
        {
          DN otherMO;
        };

        /**
         * MOReferenceSet represents a set of MO references.
         * This type is used to hold 0..n MO references.
         * A referred MO is not allowed to be repeated (therefore
         * it is denoted as a "Set")
         */
        typedef sequence<MOReference> MOReferenceSet;

        /**
         *  A set of strings.
         */
        typedef sequence<string> StringSet;

        /**
         *  A set of long.
         */
        typedef sequence<long> LongSet;
        /*
         * The LinkListSet represents the Link_X_Y objects (or subclasses of
         * Link_X_Y objects) that have a relationship with this object instance.
         * Each Link_X_Y object models interface(s) between objects of class X and
         * Y. The object containing this attribute must either be a class of type X,
         * Y, XFunction, YFunction or a subclass of one of those classes. The
         * LinkListSet may be empty, or there may be no instances for a particular
```

```
        * Link_X_Y class name.
        */
        typedef MOReferenceSet LinkListSet;

    };

};

#endif // _GENERIC_NETWORK_RESOURCES_IRP_SYSTEM_IDL_
```

A.3.3   IDL specification "GenericNetworkResourcesNRMDefs.idl"

```
//File: GenericNetworkResourcesNRMDefs.idl
#ifndef _GENERIC_NETWORK_RESOURCES_NRM_DEFS_IDL_
#define _GENERIC_NETWORK_RESOURCES_NRM_DEFS_IDL_
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
/**
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module GenericNetworkResourcesNRMDefs
{
     /**
      *  Definitions for MO class Top
      */
     interface Top
     {
        // Attribute Names
        //
        const string CLASS = "Top";
     };
     /**
      *  Definitions for MO class SubNetwork
      */
     interface SubNetwork : Top
     {
        const string CLASS = "SubNetwork";
        // Attribute Names
        //
        const string subNetworkId = "subNetworkId";
        const string dnPrefix = "dnPrefix";
        const string userLabel = "userLabel";
        const string userDefinedNetworkType = "userDefinedNetworkType";
        const string setOfMcc = "setOfMcc";
     };

     /**
      *  Definitions for MO class ManagedElement
      */
     interface ManagedElement : Top
     {
        const string CLASS = "ManagedElement";
        // Attribute Names
        //
        const string managedElementId = "managedElementId";
        const string dnPrefix = "dnPrefix";
        const string managedElementType = "managedElementType";
        const string userLabel = "userLabel";
        const string vendorName = "vendorName";
        const string userDefinedState ="userDefinedState";
        const string locationName ="locationName";
        const string managedBy = "managedBy";
        const string swVersion = "swVersion";
     };

     /**
      *  Definitions for MO class MeContext
      */
     interface MeContext : Top
     {
        const string CLASS = "MeContext";
        // Attribute Names
        //
        const string meContextId = "meContextId";
        const string dnPrefix = "dnPrefix";
     };
     /**
      *  Definitions for MO class ManagementNode
      */
     interface ManagementNode : Top
     {
        const string CLASS = "ManagementNode";

        // Attribute Names
        //
```

ETSI

```
      const string managementNodeId = "managementNodeId";
      const string userLabel = "userLabel";
      const string vendorName = "vendorName";
      const string userDefinedState = "userDefinedState";
      const string locationName = "locationName";
      const string managedElements = "managedElements";
      const string swVersion = "swVersion";
   };


   /**
    *  Definitions for abstract MO class ManagedFunction
    *
    */
   interface ManagedFunction : Top
   {
      const string CLASS = "ManagedFunction";
      // Attribute Names
      //
      const string userLabel = "userLabel";
   };


   /**
    *  Definitions for MO class IRPAgent
    */
   interface IRPAgent : Top
   {
      const string CLASS = "IRPAgent";
      // Attribute Names
      //
      const string irpAgentId = "irpAgentId";
      const string systemDN = "systemDN";
   };
   /**
    *  Definitions for abstract MO class Link
    *  This inherits from ManagedFunction
    *  The attributes aEnd and zEnd are populated with the DNs
    *  of the entities associated via the link class.
    *  The aEnd takes the DN of the 1st entity in alphabetical order,
    *  the zEnd takes the 2nd entity in alphabetical order of the class
    *  names.
    */
   interface Link : ManagedFunction
   {
      const string CLASS = "Link";
      // Attribute Names
      //
      const string linkId = "linkId";
      const string aEnd = "aEnd";
      const string zEnd = "zEnd";
      const string linkType = "linkType";
      const string protocolName = "protocolName";
      const string protocolVersion = "protocolVersion";
   };
   /**
    *  Definitions for MO class VsDataContainer
    */
   interface VsDataContainer : Top
   {
      const string CLASS = "VsDataContainer";
      // Attribute Names
      //
      const string vsDataContainerId = "vsDataContainerId";
      const string vsDataType = "vsDataType";
      const string vsData = "vsData";
      const string vsDataFormatVersion = "vsDataFormatVersion";
   };
   /**
    *  Definitions for abstract MO class EP_RP
    */
   interface EP_RP : Top
   {
      const string CLASS = "EP_RP";
      // Attribute Names
      //
      const string farEndEntity = "farEndEntity";
      const string id = "id";
      const string userLabel = "userLabel";
   };      /**
```

```
        *  This module adds datatypes definitions for the Link Class
        *  These attributes are not the basic datatypes already defined
        */
      module LinkAttributeTypes
      {
         enum LinkType
          {
             SIGNALLING,
             BEARER,
             OAM_AND_P,
             OTHER
          };
         typedef sequence <LinkType> LinkTypeType;
      };
};
#endif // _GENERIC_NETWORK_RESOURCES_NRM_DEFS_IDL_
```

Annex B (normative):
XML Definitions

This annex contains the XML Definitions for the Generic NRM IRP as it applies to Itf-N, in accordance with Generic NRM IRP IS definitions [4].

B.1 Architectural features

The overall architectural feature of Generic Network Resources IRP is specified in 3GPP TS 32.622 [4].
This clause specifies features that are specific to the Schema definitions.

B.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

B.2 Mapping

B.2.1 General mapping

An IOC maps to an XML element of the same name as the IOC's name in the IS. An IOC attribute maps to a sub-element of the corresponding IOC's XML element, and the name of this sub-element is the same as the attribute's name in the IS.

B.2.2 Information Object Class (IOC) mapping

Not present in the current version of this specification.

B.3 Solution Set definitions

B.3.1 XML definition structure

The overall description of the file format of configuration data XML files is provided by 3GPP TS 32.616 [7].

Annex B.3.3 of the present document defines the NRM-specific XML schema `genericNrm.xsd` for the Generic Network Resources IRP NRM defined in 3GPP TS 32.622 [4].

XML schema `genericNrm.xsd` explicitly declares NRM-specific XML element types for the related NRM.

The definition of those NRM-specific XML element types complies with the generic mapping rules defined in 3GPP TS 32.616 [7], with the following exception: as defined in 3GPP TS 32.616 [7], the `vsData` XML element type has an empty XML content.

Additionally, XML schema `genericNrm.xsd` also provides the following global XML declarations and definitions:

- XML complex type `NrmClass`: derivation base type (see [9], [10] and [11]) for all NRM class associated XML element types (see 3GPP TS 32.616 [7]);

- XML element type `vsData`: derivation base type (see [9], [10] and [11]) for all vendor-specific XML element types (see 3GPP TS 32.616 [7]);

- XML element type `SubNetworkOptionallyContainedNrmClass`: substitution group head (see [9], [10] and [11]) for all XML element types associated to further NRM classes optionally contained under `SubNetwork` NRM class;

- XML element type `ManagedElementOptionallyContainedNrmClass`: substitution group head (see [9], [10] and [11]) for all XML element types associated to further NRM classes optionally contained under `ManagedElement` NRM class.

B.3.2 Graphical Representation

Not present in the current version of this specification.

B.3.3   XML schema "genericNrm.xsd"

```xml
<?xml version="1.0" encoding="UTF-8"?>

<!--
  3GPP TS 32.626 Generic Network Resources IRP
  Bulk CM Configuration data file NRM-specific XML schema
  genericNrm.xsd
-->

<schema
  targetNamespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.626#genericNrm"
  elementFormDefault="qualified"
  attributeFormDefault="unqualified"
  xmlns="http://www.w3.org/2001/XMLSchema"
  xmlns:xn="http://www.3gpp.org/ftp/specs/archive/32_series/32.626#genericNrm"
  xmlns:sp="http://www.3gpp.org/ftp/specs/archive/32_series/32.526#sonPolicyNrm"
>

  <!-- Base XML type for all NRM class associated XML elements -->

  <complexType name="NrmClass">
    <attribute name="id" type="string" use="required"/>
    <attribute name="modifier" use="optional">
      <simpleType>
        <restriction base="string">
          <enumeration value="create"/>
          <enumeration value="delete"/>
          <enumeration value="update"/>
        </restriction>
      </simpleType>
    </attribute>
  </complexType>

  <!-- Generic Network Resources IRP NRM attribute related XML types -->

  <simpleType name="dn">
    <restriction base="string">
      <maxLength value="400"/>
    </restriction>
  </simpleType>

  <complexType name="dnList">
    <sequence minOccurs="0" maxOccurs="unbounded">
      <element name="dn" type="xn:dn"/>
    </sequence>
  </complexType>

  <simpleType name="linkType">
    <list>
      <simpleType>
        <restriction base="string">
          <enumeration value="Signalling"/>
          <enumeration value="Bearer"/>
          <enumeration value="OAM_AND_P"/>
          <enumeration value="Other"/>
        </restriction>
      </simpleType>
    </list>
  </simpleType>

  <complexType name="linkListType">
    <sequence minOccurs="0" maxOccurs="unbounded">
      <element name="dn" type="xn:dn"/>
    </sequence>
  </complexType>

  <!-- Generic Network Resources IRP NRM class associated XML elements -->

  <element name="SubNetwork">
    <complexType>
      <complexContent>
        <extension base="xn:NrmClass">
          <sequence>
            <element name="attributes" minOccurs="0">
                  <complexType>
```

```
                  <all>
                       <element name="dnPrefix"/>
                   <element name="userLabel"/>
                   <element name="userDefinedNetworkType"/>
                       <element name="setOfMcc"/>
                 </all>
            </complexType>
           </element>
          <choice minOccurs="0" maxOccurs="unbounded">
           <element ref="xn:SubNetwork"/>
           <element ref="xn:ManagedElement"/>
           <element ref="xn:MeContext"/>
           <element ref="xn:ManagementNode"/>
           <element ref="xn:IRPAgent"/>
           <element ref="xn:SubNetworkOptionallyContainedNrmClass"/>
           <element ref="xn:VsDataContainer"/>
          </choice>
          <choice minOccurs="0" maxOccurs="1">
           <element ref="sp:ESPolicies"/>
          </choice>
         </sequence>
        </extension>
       </complexContent>
     </complexType>
 </element>

 <element name="ManagedElement">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
         <sequence>
          <element name="attributes" minOccurs="0">
               <complexType>
               <all>
                   <element name="dnPrefix"/>
                 <element name="managedElementType"/>
                 <element name="userLabel"/>
                 <element name="vendorName"/>
                 <element name="userDefinedState"/>
                 <element name="locationName"/>
                 <element name="swVersion"/>
                 <element name="managedBy" type="xn:dnList"/>
               </all>
             </complexType>
           </element>
          <choice minOccurs="0" maxOccurs="unbounded">
           <element ref="xn:IRPAgent"/>
           <element ref="xn:ManagedElementOptionallyContainedNrmClass"/>
           <element ref="xn:VsDataContainer"/>
          </choice>
         </sequence>
       </extension>
     </complexContent>
   </complexType>
 </element>
 <element name="MeContext">
   <complexType>
     <complexContent>
       <extension base="xn:NrmClass">
         <sequence>
          <element name="attributes" minOccurs="0">
               <complexType>
                 <all>
                  <element name="dnPrefix"/>
                 </all>
               </complexType>
             </element>
          <choice minOccurs="0" maxOccurs="unbounded">
           <element ref="xn:ManagedElement"/>
          </choice>
         </sequence>
       </extension>
     </complexContent>
   </complexType>
 </element>

 <element name="ManagementNode">
   <complexType>
```

```
      <complexContent>
        <extension base="xn:NrmClass">
          <sequence>
            <element name="attributes" minOccurs="0">
                <complexType>
                 <all>
                   <element name="userLabel"/>
                   <element name="vendorName"/>
                   <element name="locationName"/>
                   <element name="managedElements" type="xn:dnList"/>
                   <element name="swVersion"/>
                   <element name="userDefinedState"/>
                 </all>
               </complexType>
             </element>
            <choice minOccurs="0" maxOccurs="unbounded">
              <element ref="xn:IRPAgent"/>
              <element ref="xn:VsDataContainer"/>
            </choice>
          </sequence>
        </extension>
      </complexContent>
    </complexType>
</element>

<element name="IRPAgent">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
              <complexType>
               <all>
                 <element ref="xn:systemDN" " minOccurs="0"/>
               </all>
             </complexType>
           </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="VsDataContainer">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
              <complexType>
               <all>
                 <element name="vsDataType"/>
                 <element name="vsDataFormatVersion"/>
                 <element ref="xn:vsData"/>
               </all>
             </complexType>
           </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<!--
  IRPAgent IOC attributes
-->

<element name="systemDN" type="xn:dn"/>

<!--
  VsDataContainer NRM class vsData attribute associated empty XML element
-->

<complexType name="vsData"/>
<element name="vsData" type="xn:vsData"/>
```

```
<!--
  Abstract head XML element for all XML elements associated to further
  NRM classes optionally contained under SubNetwork NRM class
-->

<element
  name="SubNetworkOptionallyContainedNrmClass"
  type="xn:NrmClass"
  abstract="true"
/>

<!--
  Abstract head XML element for all XML elements associated to further
  NRM classes optionally contained under ManagedElement NRM class
-->

<element
  name="ManagedElementOptionallyContainedNrmClass"
  type="xn:NrmClass"
  abstract="true"
/>

</schema>
```

```
<!--
  Abstract head XML element for all XML elements associated to further
  NRM classes optionally contained under SubNetwork NRM class
-->
```

Annex C (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New
05-2010	SA-48	SP-100269	--	--	Presentation to SA for information and approval	--	---	1.0.0
06-2010	SA-48	--	--	--	Publication	--	1.0.0	10.0.0
09-2010	SA-49	SP-100489	001	--	Correct XML definitions to be aligned with IS	F	10.0.0	10.1.0
03-2011	SA-51	SP-110100	002	--	Add containment for object class ESPolicies - Align with 32.522 SON NRM IRP Information Service	F	10.1.0	10.2.0
09-2012	SA-57	-	-	-	Automatic upgrade from previous Release version 10.2.0	-	10.2.0	11.0.0

History

Document history		
V11.0.0	October 2012	Publication