## ETSI TS 129 282 V13.1.0 (2016-01)



Universal Mobile Telecommunications System (UMTS); LTE; Mobile IPv6 vendor specific option format and

usage within 3GPP (3GPP TS 29.282 version 13.1.0 Release 13)



# Reference RTS/TSGC-0429282vd10 Keywords LTE.UMTS

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<a href="http://portal.etsi.org/tb/status/status.asp">http://portal.etsi.org/tb/status/status.asp</a>

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

#### Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup>, **UMTS**<sup>TM</sup> and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**<sup>TM</sup> and **LTE**<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Foreword**

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <a href="http://webapp.etsi.org/key/queryform.asp">http://webapp.etsi.org/key/queryform.asp</a>.

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

## Contents

Intel	ellectual Property Rights	2
Fore	eword	2
	dal verbs terminology	
	eword	
1	Scope	5
2	•	
3	Definitions and abbreviations	5
3.1 3.2	Definitions	5
4	3GPP Mobile IPv6 Option	
4.1 4.2	General	6
Ann	nex A (informative): Change History	9
Hist	tory	10

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

#### where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

## 1 Scope

The present document specifies the format and usage of the Mobile IPv6 Vendor Specific Option [2] within the Third Generation Partnership Project.

### 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] IETF RFC 5094: "Mobile IPv6 Vendor Specific Option".
- [3] IANA Private Enterprise Numbers Registry, <a href="http://www.iana.org/assignments/enterprise-numbers">http://www.iana.org/assignments/enterprise-numbers</a>.
- [4] IETF RFC 6275: "Mobility Support in IPv6".
- [5] IETF RFC 5555: "Mobile IPv6 support for dual stack Hosts and Routers (DSMIPv6)".
- [6] IETF RFC 5213: "Proxy Mobile IPv6".
- [7] 3GPP TS 29.275: "Proxy Mobile IPv6 (PMIPv6) based Mobility and Tunnelling protocols; Stage 3".
- [8] 3GPP TS 24.327: "Mobility between 3GPP Wireless Local Area Network (WLAN) interworking (I-WLAN) and 3GPP systems; General Packet Radio System (GPRS) and 3GPP I-WLAN aspects; Stage 3".

## 3 Definitions and abbreviations

#### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

#### 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

## 4 3GPP Mobile IPv6 Option

#### 4.1 General

The 3GPP Mobile IPv6 Option is a Mobile IPv6 Vendor-Specific Option as defined by IETF RFC 5094 [2] using the Vendor-Id assigned to 3GPP. The 3GPP Mobile IPv6 Option is used to encode 3GPP Specific Information Elements within the protocols based on Mobile IPv6 (MIPv6) as defined by IETF RFC 6275 [4], such as the Dual Stack Mobile IPv6 (DSMIPv6) and Proxy Mobile IPv6 (PMIPv6) protocols respectively defined by IETF RFC 5555 [5] and IETF RFC 5213 [6].

#### 4.2 Format

The format of the 3GPP Mobile IPv6 Option is shown in table 4.2-1. The defined 3GPP Specific Information Elements are listed in table 4.2-2. The data format of a given 3GPP Specific Information Element (IE) is defined in the specification defining its usage, as indicated in table 4.2-2.

Bits								
Octets	8	7	6	5	4	3	2	1
1				Ту	ре			
2	Length							
3	Vendor Id (1 <sup>st</sup> Octet)							
4				ndor Id				
5				ndor Id				
6			Ve	ndor Id	(4 <sup>th</sup> Oc	tet)		
7				Sub-	Туре			
8			F	Reserve	d			М
9-n	3GPP Specific IE Data Fragment							

Figure 4.2-1: 3GPP Mobile IPv6 Option

Table 4.2-1: Fields in a 3GPP Mobile IPv6 Option

Field	Content	Reference
Туре	Value is decimal 19 the assigned value for the Vendor- Specific mobility option	RFC 5094 [2]
Length	An 8-bit field indicating the length of the option in octets excluding the Type and the Length fields. All other fields are included.	RFC 5094 [2]
Vendor ID	A 32-bit field. Value is set to the SMI Network Management Private Enterprise Number for 3GPP, which is decimal "10415".	IANA [3]
Sub-Type	Indicate the type of the 3GPP Specific Information Element encoded by the 3GPP Mobile IPv6 Option.	RFC 5094 [2]
Reserved	Value set to zero by sender and ignored by receiver.	Defined here
More 3GPP Specific IE Data Fragment (M) Flag	Value set to "1" if this instance of the 3GPP Mobile IPv6 Option is followed by another 3GPP Mobile IPv6 Option encoding the follow up 3GPP Specific IE data fragment that does not fit in this instance of the 3GPP Mobile IPv6 Option. Set to zero otherwise.	Defined here
3GPP Specific IE Data Fragment	The 3GPP Specific IE might be split over multiple 3GPP Mobile IPv6 Options in case the total length of the 3GPP Specific Information Element exceeds 248 bytes. This is the data fragment of the 3GPP Specific IE contained in this instance of the 3GPP Mobile IPv6 Option. The data fragment has a maximum length of 248 bytes.	Defined here

The syntax of the 3GPP specific information element allows appending extra octets. The receiver that does not support such appended octets shall ignore the appended octets in order to ensure backwards compatibility.

Table 4.2-2: Subtypes for 3GPP specific Information Elements

3GPP-specific IE Subtype	3GPP-specific Information Element	Reference		
1	Protocol Configuration Options.	3GPP TS 29.275 [7]		
2	3GPP Specific PMIPv6 Error Code.	3GPP TS 29.275 [7]		
3	PMIPv6 PDN GW IP Address.	3GPP TS 29.275 [7]		
4	PMIPv6 DHCPv4 Address Allocation Procedure Indication.	3GPP TS 29.275 [7]		
5	PMIPv6 Fully Qualified PDN Connection Set Identifier	3GPP TS 29.275 [7]		
6	PMIPv6 PDN type indication.	3GPP TS 29.275 [7]		
7	Charging ID	3GPP TS 29.275 [7]		
8	Selection Mode	3GPP TS 29.275 [7]		
9	I-WLAN Mobility Access Point Name (APN).	3GPP TS 24.327 [8]		
10	Charging Characteristics	3GPP TS 29.275 [7]		
11	Mobile Equipment Identity (MEI)	3GPP TS 29.275 [7]		
12	MSISDN	3GPP TS 29.275 [7]		
13	Serving Network	3GPP TS 29.275 [7]		
14	APN Restriction	3GPP TS 29.275 [7]		
15	Maximum APN Restriction	3GPP TS 29.275 [7]		
16	Unauthenticated IMSI	3GPP TS 29.275 [7]		
17	PDN Connection ID	3GPP TS 29.275 [7]		
18	PGW Back-Off Time	3GPP TS 29.275 [7]		
19	Signalling Priority Indication	3GPP TS 29.275 [7]		
20	Additional Protocol Configuration Options	3GPP TS 29.275 [7]		
21	Static IP Address Allocation Indication	3GPP TS 29.275 [7]		
22	MME/SGSN Identifier	3GPP TS 29.275 [7]		
23	End Marker Notification	3GPP TS 29.275 [7]		
24	Trusted WLAN Mode Indication	3GPP TS 29.275 [7]		
25	UE Time Zone	3GPP TS 29.275 [7]		
26	Access Network Identifier Timestamp	3GPP TS 29.275 [7]		
27	Logical Access ID	3GPP TS 29.275 [7]		
28	Origination Time Stamp	3GPP TS 29.275 [7]		
29	Maximum Wait Time	3GPP TS 29.275 [7]		
30	TWAN Capabilities	3GPP TS 29.275 [7]		

## Annex A (informative): Change History

	Change history						
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
03/2009	CT#43	CP-090057			V1.0.0 Approved in CT#43	1.0.0	8.0.0
06/2009	CT#44	CP-090290	0001		PMIP VSO Charging Characteristics	8.0.0	8.1.0
		CP-090290	0002	-	Registration of new 3GPP specific PMIPv6 IEs		
		CP-090290	0003	2	FQ-CSID		
09/2009	CT#45	CP-090538	0004	1	APN Restriction for PMIPv6	8.1.0	8.2.0
		CP-090538	0005	1	Handling future extensions of 3GPP Mobile IPv6 Options		
12/2009	CT#46	CP-090801	0007	-	Unauthenticated IMSI	8.2.0	9.0.0
			8000	1	Multiple PDN to the Same APN for PMIP-based Interfaces		
2011-03	-	-	-	-	Update to Rel-10 version (MCC)	9.0.0	10.0.0
2011-06	CT#52	CP-110369	0011	2	APN based congestion control	10.0.0	10.1.0
			0012	2	Low access priority indicator		
2011-12	CT#54	CP-110792	0015	3	Adding Additional Authentication Options IE	10.1.0	10.2.0
2012-09	CT#57	CP-120442	0019	2	Correction to IETF Draft for TS 29.282	10.2.0	10.3.0
2012-09	CT#57	CP-120460	0022	-	Correction to RFC Update for TS 29.282	10.3.0	11.0.0
2012-12	CT#58	CP-120729	0026	-	Static IP Address Allocation Indication	11.0.0	11.1.0
			0023	1	MME/SGSN Id		
2013-09	CT#61	CP-130464	0027	-	Addition of End Marker Notification information element	11.1.0	12.0.0
2014-03	CT#63	CP-140416	0028	1	Add Trusted WLAN Mode Indication IE	12.0.0	12.1.0
2014-06	CT#64	CP-140252	0029	1	UE Time Zone for PMIP	12.1.0	12.2.0
		CP-140252	0030	1	TWAN Identifier Timestamp for PMIP		
		CP-140252	0032	1	Add a 3GPP specific option for PMIP for new Line Identifier		
2015-09	CT#69	CP-150442	0033	-	Origination Time Stamp and Maximum Wait Time for PMIP	12.2.0	13.0.0
2015-12	CT#70	CP-150780	0034	-	Extensions for P-CSCF restoration for trusted and untrusted	13.0.0	13.1.0
					WLAN access		

## History

Document history					
V13.1.0 January 2016 Publication					