ETSI TS 129 510 V15.8.0 (2020-11)



5G; 5G System; Network function repository services; Stage 3 (3GPP TS 29.510 version 15.8.0 Release 15)



Reference RTS/TSGC-0429510vf80 Keywords 5G

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI. The content of the PDF version shall not be modified without the written authorization of ETSI. The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. 3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and

All rights reserved.

of the 3GPP Organizational Partners. oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and

of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights		
Legal	Notice	2
Modal	l verbs terminology	2
Forew	vord	8
Introd	luction	8
1	Scope	9
2	References	9
	Definitions and abbreviations	10
3.1	Definitions	
3.2	Abbreviations	
4	Overview	
5	Services Offered by the NRF	11
5.1	Introduction	
5.2	Nnrf_NFManagement Service	
5.2.1	Service Description	
5.2.2	Service Operations	
5.2.2.1	Introduction	12
5.2.2.2	8	
5.2.2.2		
5.2.2.2		
5.2.2.2		
5.2.2.3	1	
5.2.2.3		
5.2.2.3 5.2.2.4		
5.2.2.4 5.2.2.4		
5.2.2. 4 5.2.2.5		
5.2.2.5		
5.2.2.5		
5.2.2.5	1	
5.2.2.5	1	
5.2.2.5		
5.2.2.5		
5.2.2.5	Update of Subscription to NF Instances in a different PLMN	21
5.2.2.6	•	
5.2.2.6		
5.2.2.6		
5.2.2.6		
5.2.2.6		
5.2.2.7		
5.2.2.7 5.2.2.7		
5.2.2.7 5.2.2.7		
5.2.2. <i>1</i> 5.2.2.8		
5.2.2.8 5.2.2.8		
3.2.2.8 5.2.2.9		
5.2.2.9 5.2.2.9		
5.2.2.) 5.3	Nnrf_NFDiscovery Service	
5.3.1	Service Description	
5.3.2	Service Operations	
5.3.2.1		
5.3.2.2		

5.3.2.2.1	General	
5.3.2.2.2	Service Discovery in the same PLMN	
5.3.2.2.3	Service Discovery in a different PLMN	
5.3.2.2.4	Service Discovery with intermediate redirecting NRF	
5.3.2.2.5	Service Discovery with intermediate forwarding NRF	
5.4	Nnrf_AccessToken Service	
5.4.1	Service Description	
5.4.2	Service Operations	
5.4.2.1	Introduction	
5.4.2.2	Get (Access Token Request)	
5.4.2.2.1	General	
5.4.2.2.2	Access Token request with intermediate forwarding NRF	
5.4.2.2.3	Access Token request with intermediate redirecting NRF	33
6 Al	PI Definitions	34
6.1	Nnrf_NFManagement Service API	
6.1.1	API URI	
6.1.2	Usage of HTTP	
6.1.2.1	General	
6.1.2.2	HTTP Standard Headers	
6.1.2.2.1	General	
6.1.2.2.2	Content type	
6.1.2.2.3	Accept-Encoding	
6.1.2.3	HTTP custom headers	35
6.1.2.3.1	General	35
6.1.3	Resources	35
6.1.3.1	Overview	35
6.1.3.2	Resource: nf-instances (Store)	36
6.1.3.2.1	Description	36
6.1.3.2.2	Resource Definition	36
6.1.3.2.3	Resource Standard Methods	37
6.1.3.2.3.		
6.1.3.2.3.		
6.1.3.2.4	Resource Custom Operations	
6.1.3.3	Resource: nf-instance (Document)	
6.1.3.3.1	Description	
6.1.3.3.2	Resource Definition	
6.1.3.3.3	Resource Standard Methods	
6.1.3.3.3.		
6.1.3.3.3.		
6.1.3.3.3.		
6.1.3.3.3.		
6.1.3.4	Resource: subscriptions (Collection)	
6.1.3.4.1	Description	
6.1.3.4.2	Resource Definition	
6.1.3.4.3	Resource Standard Methods	
6.1.3.4.3. 6.1.3.5		
6.1.3.5.1	Resource: subscription (Document)	
	Description	
6.1.3.5.2 6.1.3.5.3	Resource Definition	
6.1.3.5.3 6.1.3.5.3.		
6.1.3.5.3.		
6.1.3.3.3. 6.1.4	Custom Operations without associated resources	
6.1.5	Notifications	
6.1.5.1	General	
6.1.5.1	NF Instance Status Notification	
6.1.5.2.1	Description	
6.1.5.2.1	Notification Definition	
6.1.6	Data Model	
6.1.6.1	General	
6.1.6.2	Structured data types	
U. I. U. Z	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	

6.1.6.2.1	Introduction	
6.1.6.2.2	Type: NFProfile	
6.1.6.2.3	Type: NFService	
6.1.6.2.4	Type: DefaultNotificationSubscription	
6.1.6.2.5	Type: IpEndPoint	55
6.1.6.2.6	Type: UdrInfo	55
6.1.6.2.7	Type: UdmInfo	56
6.1.6.2.8	Type: AusfInfo	56
6.1.6.2.9	Type: SupiRange	57
6.1.6.2.10	Type: IdentityRange	
6.1.6.2.11	Type: AmfInfo	
6.1.6.2.12	Type: SmfInfo	
6.1.6.2.13	Type: UpfInfo	
6.1.6.2.14	Type: SnssaiUpfInfoItem	
6.1.6.2.15	Type: DnnUpfInfoItem	
6.1.6.2.16	Type: SubscriptionData	
6.1.6.2.17	Type: NotificationData	
6.1.6.2.18	Void	
6.1.6.2.19	Type: NFServiceVersion	
6.1.6.2.20	Type: PcfInfo	
6.1.6.2.21	Type: BsfInfo	
6.1.6.2.22	Type: Ipv4AddressRange	
6.1.6.2.23	Type: Ipv6PrefixRange	
6.1.6.2.24	Type: InterfaceUpfInfoItem	
6.1.6.2.25	Type: UriList	
6.1.6.2.26	Type: N2InterfaceAmfInfo	
6.1.6.2.27	Type: TaiRange	
6.1.6.2.28	Type: TacRange	
6.1.6.2.29	Type: SnssaiSmfInfoItem	
6.1.6.2.30	Type: DnnSmfInfoItem	
6.1.6.2.31	Type: NrfInfo	
6.1.6.2.32	Type: ChfInfo	
6.1.6.2.33	Type: Chflino	
6.1.6.2.34	Type: PlmnRange	
6.1.6.2.35	Type: SubscrCond	
6.1.6.2.36	* *	
6.1.6.2.37	Type: NfInstanceCond	
6.1.6.2.38	Type: NfTypeCond	
6.1.6.2.39	Type: ServiceNameCond	
	Type: AmfCond	
6.1.6.2.40	Type: GuamiListCond	
6.1.6.2.41	Type: NetworkSliceCond	
6.1.6.2.42	Type: NfGroupCond	
6.1.6.2.43	Type: NotifCondition	
6.1.6.2.44	Type: PlmnSnssai	
6.1.6.3	Simple data types and enumerations	
6.1.6.3.1	Introduction	
6.1.6.3.2	Simple data types	
6.1.6.3.3	Enumeration: NFType	
6.1.6.3.4	Enumeration: NotificationType	
6.1.6.3.5	Enumeration: TransportProtocol	
6.1.6.3.6	Enumeration: NotificationEventType	
6.1.6.3.7	Enumeration: NFStatus	
6.1.6.3.8	Enumeration: DataSetId	
6.1.6.3.9	Enumeration: UPInterfaceType	
6.1.6.3.10	Relation Types	
6.1.6.3.10.1	General	
6.1.6.3.11	Enumeration: ServiceName	
6.1.6.3.12	Enumeration: NFServiceStatus	
6.1.7	Error Handling	
6.1.7.1	General	74
6.1.7.2	Protocol Errors	
6.1.7.3	Application Errors	74

6.1.8	Security	
6.2	Nnrf_NFDiscovery Service API	74
6.2.1	API URI	74
6.2.2	Usage of HTTP	74
6.2.2.1	General	
6.2.2.2	HTTP Standard Headers	
6.2.2.2.1	General	
6.2.2.2.2	Content type	
6.2.2.2.3	Cache-Control	
6.2.2.2.4	ETag	
6.2.2.2.5	If-None-Match	
6.2.2.3	HTTP custom headers	
6.2.2.3.1	General	
6.2.3	Resources	
6.2.3.1	Overview	
6.2.3.2 6.2.3.2.1	Resource: nf-instances (Store)	
6.2.3.2.1	Description	
6.2.3.2.2	Resource Definition	
6.2.3.2.3		
6.2.3.2.4	Resource Custom Operations	
6.2.4	Custom Operations without associated resources	
6.2.5	Notifications	
6.2.6	Data Model	
6.2.6.1	General	
6.2.6.2	Structured data types	
6.2.6.2.1	Introduction	
6.2.6.2.2	Type: SearchResult	84
6.2.6.2.3	Type: NFProfile	
6.2.6.2.4	Type: NFService	
6.2.6.3	Simple data types and enumerations	
6.2.6.3.1	Introduction	
6.2.6.3.2	Simple data types	
6.2.7	Error Handling	
6.2.7.1	General	
6.2.7.2	Protocol Errors	
6.2.7.3	Application Errors	
6.2.8 6.2.9	Security Features supported by the NFDiscovery service	
6.3	Nnrf_AccessToken Service API	وه
6.3.1	General.	
6.3.2	API URI	
6.3.3	Usage of HTTP	
6.3.3.1	General	
6.3.3.2	HTTP standard headers	
6.3.3.2.1	General	
6.3.3.2.2	Content type	90
6.3.3.3	HTTP custom headers	91
6.3.3.3.1	General	
6.3.4	Custom Operation without Associated Resources	
6.3.4.1	Overview	
6.3.4.2	Operation: Get (Access Token Request)	
6.3.4.2.1	Description	
6.3.4.2.2	Operation Definition	
6.3.5	Data Model	
6.3.5.1 6.3.5.2	General	
6.3.5.2.1	Introduction	
6.3.5.2.1	Type: AccessTokenReq	
6.3.5.2.3	Type: AccessTokenRsp	
6.3.5.2.4	Type: AccessTokenClaims	
6.3.5.3	Simple data types and enumerations	

6.3.5.3.1	Introduc	tion	95
6.3.5.3.2	Simple d	ata types	95
6.3.5.3.3		tion: GrantType	
6.3.5.4		escribing alternative data types or combinations of data types	
6.3.5.4.1		idience	
Annex A	A (normative):	OpenAPI specification	97
A.1	General		97
A.2	Nnrf_NFManagem	ent API	97
A.3		API	
A.4	Nnrf_AccessToken	API (NRF OAuth2 Authorization)	124
Annex I	3 (normative):	NF Profile changes in NFRegister and NFUpdate (NF Profile	
		Complete Replacement) responses	127
B.1	General	, <u>, , , , , , , , , , , , , , , , , , </u>	
Annex (C (informative):	Change history	128
History.			132

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

This clause is optional. If it exists, it is always the second unnumbered clause.

1 Scope

The present document specifies the stage 3 protocol and data model for the Nnrf Service Based Interface. It provides stage 3 protocol definitions and message flows, and specifies the API for each service offered by the NRF.

The 5G System stage 2 architecture and procedures are specified in 3GPP TS 23.501 [2] and 3GPP TS 23.502 [3].

The Technical Realization of the Service Based Architecture and the Principles and Guidelines for Services Definition are specified in 3GPP TS 29.500 [4] and 3GPP TS 29.501 [5].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1]	3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
[2]	3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
[3]	3GPP TS 23.502: "Procedures for the 5G System; Stage 2".
[4]	3GPP TS 29.500: "5G System; Technical Realization of Service Based Architecture; Stage 3".
[5]	3GPP TS 29.501: "5G System; Principles and Guidelines for Services Definition; Stage 3".
[6]	3GPP TS 29.518: "5G System; Access and Mobility Management Services; Stage 3".
[7]	3GPP TS 29.571: "5G System; Common Data Types for Service Based Interfaces; Stage 3".
[8]	ECMA-262: "ECMAScript® Language Specification", https://www.ecma-international.org/ecma-262/5.1/ .
[9]	IETF RFC 7540: "Hypertext Transfer Protocol Version 2 (HTTP/2)".
[10]	OpenAPI Initiative, "OpenAPI 3.0.0 Specification", https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.0.md .
[11]	IETF RFC 7807: "Problem Details for HTTP APIs".
[12]	3GPP TS 23.003: "Numbering, Addressing and Identification".
[13]	IETF RFC 6902: "JavaScript Object Notation (JSON) Patch".
[14]	IETF RFC 6901: "JavaScript Object Notation (JSON) Pointer".
[15]	3GPP TS 33.501: "Security architecture and procedures for 5G system".
[16]	IETF RFC 6749: "The OAuth 2.0 Authorization Framework".
[17]	IETF RFC 3986: "Uniform Resource Identifier (URI): Generic Syntax".
[18]	IETF RFC 4122: "A Universally Unique IDentifier (UUID) URN Namespace".
[19]	IETF RFC 7232: "Hypertext Transfer Protocol (HTTP/1.1): Conditional Requests".

[20]	IETF RFC 7234: "Hypertext Transfer Protocol (HTTP/1.1): Caching".
[21]	3GPP TS 29.244: "Interface between the Control Plane and the User Plane Nodes; Stage 3".
[22]	IETF RFC 8259: "The JavaScript Object Notation (JSON) Data Interchange Format".
[23]	IETF RFC 2782: "A DNS RR for specifying the location of services (DNS SRV)".
[24]	IETF RFC 7515: "JSON Web Signature (JWS)".
[25]	IETF RFC 7519: "JSON Web Token (JWT)".
[26]	W3C HTML 4.01 Specification, https://www.w3.org/TR/2018/SPSD-html401-20180327/ .
[27]	3GPP TS 23.527: "5G System; Restoration Procedures; Stage 2".
[28]	3GPP TS 29.513: "5G System; Policy and Charging Control signalling flows and QoS parameter mapping; Stage 3".
[29]	3GPP TS 38.413: "NG-RAN; NG Application Protocol (NGAP)".
[30]	IETF RFC 1952: "GZIP file format specification version 4.3".
[31]	3GPP TR 21.900: "Technical Specification Group working methods".
[32]	Void.
[33]	Void.
[34]	Void.
[35]	Void.
[36]	3GPP TS 29.503: "Unified Data Management Services".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

5GC 5G Core Network
CHF Charging Function
NF Network Function
NRF NF Repository Function

4 Overview

The Network Function (NF) Repository Function (NRF) is the network entity in the 5G Core Network (5GC) supporting the following functionality:

- Maintains the NF profile of available NF instances and their supported services;

- Allows other NF instances to subscribe to, and get notified about, the registration in NRF of new NF instances of a given type;
- Supports service discovery function. It receives NF Discovery Requests from NF instances, and provides the information of the available NF instances fulfilling certain criteria (e.g., supporting a given service).

Figures 4-1 shows the reference architecture for the 5GC, with focus on the NRF:




Figure 4-1: 5G System architecture

For the sake of clarity, the NRF is never depicted in reference point representation figures, given that the NRF interacts with every other NF in the 5GC. As an exception, in the roaming case, the reference point between the vNRF and the hNRF is named as N27. The reference point name of N27 is used only for representation purposes, but its functionality is included in the services offered by the Nnrf Service-Based Interface.

5 Services Offered by the NRF

5.1 Introduction

The NRF offers to other NFs the following services:

- Nnrf_NFManagement
- Nnrf_NFDiscovery
- Nnrf_AccessToken (OAuth2 Authorization)

5.2 Nnrf NFManagement Service

5.2.1 Service Description

The Nnrf_NFManagement service allows a Network Function Instance in the serving PLMN to register, update or deregister its profile in the NRF.

The Nnrf_NFManagement service also allows an NRF Instance to register, update or deregister its profile in another NRF in the same PLMN.

NOTE: Alternatively, other means such as OA&M can also be used to register, update or deregister NRF profile in another NRF.

It also allows an NF to subscribe to be notified of registration, deregistration and profile changes of NF Instances along with their NF services.

The NF profile consists of general parameters of the NF Instance, and also the parameters of the different NF Service Instances exposed by the NF Instance.

The PLMN of the NRF may comprise one or multiple PLMN IDs (i.e. MCC and MNC). An NRF configured with multiple PLMN IDs shall support registering, updating and deregistering the profile of Network Function Instances from any of these PLMN IDs.

The Nnrf_NFManagement service also allows retrieving a list of NF Instances currently registered in the NRF or the NF Profile of a given NF Instance.

5.2.2 Service Operations

5.2.2.1 Introduction

The services operations defined for the Nnrf_NFManagement service are as follows:

- NFRegister: It allows an NF Instance to register its NF profile in the NRF; it includes the registration of the general parameters of the NF Instance, together with the list of services exposed by the NF Instance. This service operation is not allowed to be invoked from an NRF in a different PLMN.
- NFUpdate: It allows an NF Instance to replace, or update partially, the parameters of its NF profile (including the parameters of the associated services) in the NRF; it also allows to add or delete individual services offered by the NF Instance. This service operation is not allowed to be invoked from an NRF in a different PLMN.
- NFDeregister: It allows an NF Instance to deregister its NF profile in the NRF, including the services offered by the NF Instance. This service operation is not allowed to be invoked from an NRF in a different PLMN.
- NFStatusSubscribe: It allows an NF Instance to subscribe to changes on the status of NF Instances registered in NRF. This service operation can be invoked by an NF Instance in a different PLMN (via the local NRF in that PLMN).
- NFStatusNotify: It allows the NRF to notify subscribed NF Instances of changes on the status of NF Instances. This service operation can be invoked directly between the NRF and an NF Instance in a different PLMN (without involvement of the local NRF in that PLMN).
- NFStatusUnsubscribe: It allows an NF Instance to unsubscribe to changes on the status of NF Instances registered in NRF. This service operation can be invoked by an NF Instance in a different PLMN (via the local NRF in that PLMN).
- NOTE 1: The "change of status" of the NFStatus service operations can imply a request to be notified of newly registered NF Instances in NRF, or to be notified of profile changes of a specific NF Instance, or to be notified of the deregistration of an NF Instance.
- NOTE 2: An NRF instance can also use the NFRegister, NFUpdate or NFDeregister service operations or OA&M system to register, update or deregister its profile in another NRF in the same PLMN.
- NFListRetrieval: It allows retrieving a list of NFs currently registered in the NRF. This service operation is not allowed to be invoked from an NRF in a different PLMN.
- NFProfileRetrieval: It allows retrieving the NF Profile of a given NF instance. This service operation is not allowed to be invoked from an NRF in a different PLMN.

The NFStatusSubscribe / NFstatusNotify / NFStatusUnsubscribe operations can be invoked by an NF Service Consumer (i.e., "source NF") requesting to be notified about events (registration, deregistration, profile change) related to an NF instance (i.e., "target NF") located in the same PLMN, or in a different PLMN.

In the description of these operations in clauses 5.2.2.5, 5.2.2.6 and 5.2.2.7, when the NF instances are located in the same PLMN, both source NF and target NF are said to be located in the "Serving PLMN" but, in the general case, the functionality is not restricted to the PLMN that is serving a given UE, and it shall be applicable as well to any scenario in which source NF and target NFs belong to the same PLMN.

When source NF and target NF are located in different PLMNs, the source NF is said to be in the "Serving PLMN", and the target NF (and the NRF where such NF is registered) is said to be in the "Home PLMN", similarly to the scenarios described in 3GPP TS 23.502 [3], but the functionality shall be equally applicable to any scenario between any pair of PLMNs (e.g. with the source NF in the Home PLMN and the target NF in the Serving PLMN).

5.2.2.2 NFRegister

5.2.2.2.1 General

This service operation is used:

- to register an NF in the NRF by providing the NF profile of the requesting NF to the NRF, and the NRF marks the requesting NF as available to be discovered by other NFs;
- to register services associated to an existing NF Instance;
- to register NRF information in another NRF, and this information is used for forwarding or redirecting service discovery request.

5.2.2.2.2 NF (other than NRF) registration to NRF




Figure 5.2.2.2.1: NF Instance Registration

1. The NF Service Consumer shall send a PUT request to the resource URI representing the NF Instance. The URI is determined by the NF Instance. The variable {nfInstanceID} represents an identifier, provided by the NF Service Consumer, that shall be globally unique inside the PLMN of the NRF where the NF is being registered. The format of the NF Instance ID shall be a Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 [18].

EXAMPLE: UUID version 4: "4947a69a-f61b-4bc1-b9da-47c9c5d14b64"

The payload body of the PUT request shall contain a representation of the NF Instance to be created.

2. On success, "201 Created" shall be returned, the payload body of the PUT response shall contain the representation of the created resource and the "Location" header shall contain the URI of the created resource. Additionally, the NRF returns a "heart-beat timer" containing the number of seconds expected between two consecutive heart-beat messages from an NF Instance to the NRF (see clause 5.2.2.3.2). The representation of the created resource may be a complete NF Profile or a NF Profile just including the mandatory attributes of the NF Profile and the attributes which the NRF added or changed (see Annex B).

If the registration of the NF instance fails at the NRF due to errors in the encoding of the NFProfile JSON object, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.

If the registration of the NF instance fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

The NRF shall allow the registration of a Network Function instance with any of the NF types described in clause 6.1.6.3.3, and it shall also allow registration of Network Function instances with custom NF types (e.g., NF type values not defined by 3GPP, or NF type values not defined by this API version).

NOTE: When registering a custom NF in NRF, it is recommended to use a NF type name that prevents collisions with other custom NF type names, or with NF types defined in the future by 3GPP. E.g., prefixing the custom NF type name with the string "CUSTOM_".

During the registration of a Network Function instance with a custom NF type, the NF instance may provide NF-specific data (in the "customInfo" attribute), that shall be stored by the NRF as part of the NF profile of the NF instance.

The NRF shall accept the registration of NF Instances containing Vendor-Specific attributes (see 3GPP TS 29.500 [4], clause 6.6.3), and therefore, it shall accept NF Profiles containing attributes whose type may be unknown to the NRF, and those attributes shall be stored as part of the NF's profile data in NRF.

5.2.2.2.3 NRF registration to another NRF

The procedure specified in clause 5.2.2.2.2 applies. Additionally:

- a) the registering NRF shall set the nfType to "NRF" in the nfProfile;
- b) the registering NRF shall set the nfService to contain "nnrf-disc" and "nnrf-nfm" in the nfProfile;
- c) the registering NRF may include nrfInfo which contains the information of udrInfo, udmInfo, ausfInfo, amfInfo, smfInfo, upfInfo, pcfInfo, bsfInfo and chfInfo in the nfProfile locally configured in the NRF or the NRF received during registration of other NFs, this means the registering NRF is able to provide service for discovery of NFs subject to that information;
- d) if the NRF receives an NF registration with the nfType set to "NRF", the NRF shall use the information contained in the nfProfile to target the registering NRF when forwarding or redirecting NF service discovery request.

5.2.2.3 NFUpdate

5.2.2.3.1 General

This service operation updates the profile of a Network Function previously registered in the NRF by providing the updated NF profile of the requesting NF to the NRF. The update operation may apply to the whole profile of the NF (complete replacement of the existing profile by a new profile), or it may apply only to a subset of the parameters of the profile (including adding/deleting/replacing services to the NF profile).

To perform a complete replacement of the NF Profile of a given NF Instance, the NF Service Consumer shall issue an HTTP PUT request, as shown in Figure 5.2.2.3.1-1:




Figure 5.2.2.3.1-1: NF Profile Complete Replacement

- 1. The NF Service Consumer shall send a PUT request to the resource URI representing the NF Instance. The payload body of the PUT request shall contain a representation of the NF Instance to be completely replaced in the NRF.
- 2a. On success, "200 OK" shall be returned, the payload body of the PUT response shall contain the representation of the replaced resource. The representation of the replaced resource may be a complete NF Profile or a NF Profile just including the mandatory attributes of the NF Profile and the attributes which the NRF added or changed (see Annex B).
- 2b. If the update of the NF instance fails at the NRF due to errors in the encoding of the NFProfile JSON object, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.
 - If the update of the NF instance fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

To perform a partial update of the NF Profile of a given NF Instance, the NF Service Consumer shall issue an HTTP PATCH request, as shown in Figure 5.2.2.3.1-2. This partial update shall be used to add/delete/replace individual parameters of the NF Instance, and also to add/delete/replace any of the services (and their parameters) offered by the NF Instance.



Figure 5.2.2.3.1-2: NF Profile Partial Update

- 1. The NF Service Consumer shall send a PATCH request to the resource URI representing the NF Instance. The payload body of the PATCH request shall contain the list of operations (add/delete/replace) to be applied to the NF Profile of the NF Instance; these operations may be directed to individual parameters of the NF Profile or to the list of services (and their parameters) offered by the NF Instances. In order to leave the NF Profile in a consistent state, all the operations specified by the PATCH request body shall be executed atomically.
- 2a. On success, "200 OK" shall be returned, the payload body of the PATCH response shall contain the representation of the replaced resource.
- 2b. If the NF Instance, identified by the "nfInstanceID", is not found in the list of registered NF Instances in the NRF's database, the NRF shall return "404 Not Found" status code with the ProblemDetails IE providing details of the error.

The NRF shall allow updating Vendor-Specific attributes (see 3GPP TS 29.500 [4], clause 6.6.3) that may exist in the NF Profile of a registered NF Instance.

5.2.2.3.2 NF Heart-Beat

Each NF that has previously registered in NRF shall contact the NRF periodically (heart-beat), by invoking the NFUpdate service operation, in order to show that the NF is still operative.

The time interval at which the NRF shall be contacted is deployment-specific, and it is returned by the NRF to the NF Service Consumer as a result of a successful registration.

When the NRF detects that a given NF has not updated its profile for a configurable amount of time (longer than the heart-beat interval), the NRF changes the status of the NF to SUSPENDED and considers that the NF and its services can no longer be discovered by other NFs via the NFDiscovery service. The NRF notifies NFs subscribed to receiving notifications of changes of the NF Profile that the NF status has been changed to SUSPENDED.

If the NRF modifies the heart-beat interval value of a given NF instance currently registered (e.g. as a result of an OA&M operation), it shall return the new value to the registered NF in the response of the next periodic heart-beat interaction received from that NF and, until then, the NRF shall apply the heart-beat check procedure according to the original interval value.



Figure 5.2.2.3.2-1: NF Heart-Beat

1. The NF Service Consumer shall send a PATCH request to the resource URI representing the NF Instance. The payload body of the PATCH request shall contain a "replace" operation on the "nfStatus" attribute of the NF Profile of the NF Instance, and set it to the value "REGISTERED" or "UNDISCOVERABLE".

In addition, the NF Service Consumer may also provide the load information of the NF, and/or the load information of the NF associated NF services.

- 2a. On success, the NRF should return "204 No Content"; the NRF may also answer with "200 OK" along with the full NF Profile, e.g. in cases where the NRF determines that the NF Profile has changed significantly since the last heart-beat, and wants to send the new profile to the NF Service Consumer (note that this alternative has bigger signalling overhead).
- 2b. If the NF Instance, identified by the "nfInstanceID", is not found in the list of registered NF Instances in the NRF's database, the NRF shall return "404 Not Found" status code with the ProblemDetails IE providing details of the error.

EXAMPLE:

5.2.2.4 NFDeregister

5.2.2.4.1 General

This service operation removes the profile of a Network Function previously registered in the NRF.

It is executed by deleting a given resource identified by a "NF Instance ID". The operation is invoked by issuing a DELETE request on the URI representing the specific NF Instance.




Figure 5.2.2.4.1-1: NF Instance Deregistration

- 1. The NF Service Consumer shall send a DELETE request to the resource URI representing the NF Instance. The request body shall be empty.
- 2a. On success, "204 No Content" shall be returned. The response body shall be empty.
- 2b. If the NF Instance, identified by the "nfInstanceID", is not found in the list of registered NF Instances in the NRF's database, the NRF shall return "404 Not Found" status code with the ProblemDetails IE providing details of the error.

5.2.2.5 NFStatusSubscribe

5.2.2.5.1 General

This service operation is used to:

- create a subscription so an NF Service Consumer can request to be notified when NF Instances of a given set, following certain filter criteria are registered/deregistered in NRF or when their profile is modified;
- create a subscription to a specific NF Instance so an NF Service Consumer can request to be notified when the profile of such NF Instance is modified or when the NF Instance is deregistered from NRF.

5.2.2.5.2 Subscription to NF Instances in the same PLMN

The subscription to notifications on NF Instances is executed creating a new individual resource under the collection resource "subscriptions". The operation is invoked by issuing a POST request on the URI representing the "subscriptions" resource.




Figure 5.2.2.5.2-1: Subscription to NF Instances in the same PLMN

 The NF Service Consumer shall send a POST request to the resource URI representing the "subscriptions" collection resource.

The request body shall include the data indicating the type of notifications that the NF Service Consumer is interested in receiving; it also contains a callback URI, where the NF Service Consumer shall be prepared to receive the actual notification from the NRF (see NFStatusNotify operation in 5.2.2.6) and it may contain a validity time, suggested by the NF Service Consumer, representing the time span during which the subscription is desired to be kept active.

The subscription request may also include additional parameters indicating the list of attributes (including Vendor-Specific attributes, see 3GPP TS 29.500 [4], clause 6.6.3) in the NF Profile to be monitored (or to be excluded from monitoring), in order to determine whether a notification from NRF should be sent, or not, when any of those attributes is changed in the profile.

The NF Service Consumer may request the creation of a subscription to a specific NF Instance, or to a set of NF Instances, where the set is determined according to different criteria specified in the request body, in the "subscrCond" attribute of the "SubscriptionData" object type (see clause 6.1.6.2.16).

The subscription shall be authorized, or rejected, by the NRF by checking the "reqNfType" and "reqNfFqdn" input attributes in the subscription request body (along with the contents of any optional Oauth2 access token provided in the API request) against the list of authorization attributes in the NF Profile of the target NF Instance to be monitored.

When the subscription request is for a set of NFs, the authorization attributes of the NF Instances in the set may differ, resulting in positive authorization of the subscription for only a part of the NF Instances in the set; in that case, the subscription to the set of NFs may be accepted by the NRF, but the NF Instances in the set that are not authorized for the NF Service Consumer that requested the subscription, shall not result in triggering any notification event from the NRF to the NF Service Consumer.

- 2a. On success, "201 Created" shall be returned. The response shall contain the data related to the created subscription, including the validity time, as determined by the NRF, after which the subscription becomes invalid. Once the subscription expires, if the NF Service Consumer wants to keep receiving status notifications, it shall create a new subscription in the NRF.
- 2b. If the creation of the subscription fails at the NRF due to errors in the SubscriptionData JSON object in the request body, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.

If the creation of the subscription fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

5.2.2.5.3 Subscription to NF Instances in a different PLMN

The subscription to notifications on NF Instances in a different PLMN is done by creating a resource under the collection resource "subscriptions", in the NRF of the Home PLMN.

For that, step 1 in clause 5.2.2.5.2 is executed (send a POST request to the NRF in the Serving PLMN); this request shall include the identity of the PLMN of the home NRF in the SubscriptionData parameter in the request body.

Then, steps 1-2 in Figure 5.2.2.5.3-1 are executed, between the NRF in the Serving PLMN and the NRF in the Home PLMN. In this step, the presence of the PLMN ID in the SubscriptionData parameter is not required. The NRF in the Home PLMN returns a subscriptionID identifying the created subscription.

Finally, step 2 in clause 5.2.2.5.2 is executed; a new subscriptionID shall be generated by the NRF in the Serving PLMN as indicated in step 2 of Figure 5.2.2.5.3-1, and shall be sent to the NF Service Consumer in the Serving PLMN.




Figure 5.2.2.5.3-1: Subscription to NF Instances in a different PLMN

1. The NRF in Serving PLMN shall send a POST request to the resource URI in the NRF in Home PLMN representing the "subscriptions" collection resource. The request body shall include the SubscriptionData as received by the NRF in Serving PLMN from the NF Service Consumer in the Serving PLMN (see 5.2.2.5.2),

containing the data about the type of notifications that the NF Service Consumer is interested in receiving and the callback URI where the NF Service Consumer shall be prepared to receive the notifications from the NRF (see NFStatusNotify operation in 5.2.2.6).

2a. On success, "201 Created" shall be returned. The NRF in Serving PLMN should not keep state for this created subscription and shall send to the NF Service Consumer in Serving PLMN (step 2 in 5.2.2.5.2) a subscriptionID that shall consist on the following structure: <MCC>+<MNC>+"-"+<OriginalSubscriptionID>

EXAMPLE: If the NRF in a Home PLMN (where MCC = 123, and MNC=456) creates a subscription with value "subs987654", the subscriptionID that the NRF in Serving PLMN would send to the NF Service Consumer in Serving PLMN is: "123456-subs987654"

2b. If the creation of the subscription fails at the NRF due to errors in the SubscriptionData JSON object in the request body, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.

If the creation of the subscription fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

5.2.2.5.4 Subscription to NF Instances with intermediate forwarding NRF

When multiple NRFs are deployed in one PLMN, an NF Instance can subscribe to changes of NF Instances registered in an NRF to which it is not directly interacting. The subscription message is forwarded by an intermediate NRF to which the subscribing NF instance is directly interacting.

For that, step 1 in clause 5.2.2.5.2 is executed (send a POST request to the NRF-1 in the Serving PLMN); this request shall include the SubscriptionData parameter in the request body.

Then, steps 1-4 in Figure 5.2.2.5.4-1 are executed between NF Service Consumer in Serving PLMN, NRF-1 in Serving PLMN and NRF-2 in Serving PLMN. In thest steps, NRF-1 sends the subscription request to a pre-configured NRF-2. NRF-2 requests corresponding NRF (e.g. the NF Service Producer registered NRF) and returns a subscriptionID identifying the created subscription and this subscriptionID is sent to the NF Service Consumer via NRF-1.

Finally, step 2 in clause 5.2.2.5.2 is executed; the subscriptionID shall be sent to the NF Service Consumer.




Figure 5.2.2.5.4-1: Subscription with intermediate forwarding NRF

- 1. NRF-1 receives a subscription request but does not have the information to fulfil the request. Then NRF-1 sends the subscription request to a pre-configured NRF-2.
- 2. Upon receiving a subscription request, based on the SubscriptionData contained in the subscription request (e.g.NF type) and locally stored information (see clause 5.2.2.2.3), NRF-2 shall identify the next hop NRF and forward the subscription request to that NRF (i.e. NF Service Producer registered NRF).
- 3a. On success, "201 Created" shall be returned by NRF-2.

- 3b. If the creation of the subscription fails, the NRF-2 shall return "4XX/5XX" response.
- 4a. NRF-1 forwards the success response to NF Service Consumer. The payload body of the POST response shall contain the representation describing the status of the request and the "Location" header shall be present and shall contain the URI of the created resource. The authority and/or deployment-specific string of the apiRoot of the created resource URI may differ from the authority and/or deployment-specific string of the apiRoot of the request URI received in the POST request.
- 4b. NRF-1 forwards the error response to NF Service Consumer.

5.2.2.5.5 Subscription to NF Instances with intermediate redirecting NRF

When multiple NRFs are deployed in one PLMN, an NF Instance can subscribe to changes of NF Instances registered in another NRF. The subscription message is redirected by a third NRF.

For that, step 1 in clause 5.2.2.5.2 is executed (send a POST request to the NRF-1 in the Serving PLMN); this request shall include the SubscriptionData parameter in the request body.

Then, steps 2-5 in Figure 5.2.2.5.5-1 are executed between NRF-1, NRF-2 and NRF-3.

Finally, step 2 in clause 5.2.2.5.2 is executed; the subscriptionID shall be sent to the NF Service Consumer.




Figure 5.2.2.5.5-1: Subscription to NF Instances with intermediate redirecting NRF

- 1. NF Service Consumer send a subscription request to NRF-1.
- 2. NRF-1 receives a subscription request but does not have the information to fulfil the request. Then NRF-1 sends the subscription request to a pre-configured NRF-2.
- 3. Upon receiving a subscription request, based on the SubscriptionData contained in the subscription request (e.g.NF type) and locally stored information (see clause 5.2.2.2.3), NRF-2 shall identify the next hop NRF, and redirect the subscription request by returning HTTP 307 Temporary Redirect response.
 - The 307 Temporary Redirect response shall contain a Location header field, the host part of the URI in the Location header field represents NRF-3.
- 4. Upon receiving 307 Temporary Redirect response, NRF-1 sends the subscription request to NRF-3 by using the URI contained in the Location header field of the 307 Temporary Redirect response.
- 5a. On success, "201 Created" shall be returned by NRF-3.
- 5b. If the creation of the subscription fails at the NRF-3, the NRF-3 shall return "4XX/5XX" response.
- 6a. On success, "201 Created" shall be forwarded to NF Service Consumer via NRF-1. The payload body of the POST response shall contain the representation describing the status of the request and the "Location" header shall be present and shall contain the URI of the created resource. The authority and/or deployment-specific string of the apiRoot of the created resource URI may differ from the authority and/or deployment-specific string of the apiRoot of the request URI received in the POST request.

6b. If the creation of the subscription fails, "4XX/5XX" shall be forwarded to NF Service Consumer via NRF-1.

5.2.2.5.6 Update of Subscription to NF Instances

The subscription to notifications on NF Instances may be updated to refresh the validity time, when this time is about to expire. The NF Service Consumer may request a new validity time to the NRF, and the NRF shall answer with the new assigned validity time, if the operation is successful.

This operation is executed by updating the resource identified by "subscriptionID". It is invoked by issuing an HTTP PATCH request on the URI representing the individual resource received in the Location header field of the "201 Created" response received during a successful subscription (see clause 5.2.2.5).




Figure 5.2.2.5.6-1: Subscription to NF Instances in the same PLMN

- 1. The NF Service Consumer shall send a PATCH request to the resource URI identifying the individual subscription resource. The payload body of the PATCH request shall contain a "replace" operation on the "validityTime" attribute of the SubscriptionData structure and shall contain a new suggested value for it; no other attribute of the resource shall be updated as part of this operation.
- 2a. On success, if the NRF accepts the extension of the lifetime of the subscription, and it accepts the requested value for the "validityTime" attribute, a response with status code "204 No Content" shall be returned.
- 2b. On success, if the NRF accepts the extension of the lifetime of the subscription, but it assigns a validity time different than the value suggested by the NF Service Consumer, a "200 OK" response code shall be returned. The response shall contain the new resource representation of the "subscription" resource, which includes the new validity time, as determined by the NRF, after which the subscription becomes invalid.
- 2c. If the update of the subscription fails at the NRF due to errors in the JSON Patch object in the request body, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.

If the update of the subscription fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

EXAMPLE:

5.2.2.5.7 Update of Subscription to NF Instances in a different PLMN

The update of subscription in a different PLMN is done by updating a subscription resource identified by a "subscriptionID".

For that, step 1 in clause 5.2.2.5.6 is executed (send a PATCH request to the NRF in the Serving PLMN); this request shall include the identity of the PLMN of the home NRF (MCC/MNC values) as a leading prefix of the susbcriptionID.

Then, steps 1-2 in Figure 5.2.2.5.7-1 are executed, between the NRF in the Serving PLMN and the NRF in the Home PLMN. In this step, the subscriptionID sent to the NRF in the Home PLMN shall not contain the identity of the PLMN

(i.e., it shall be the same subscriptionID value as originally generated by the NRF in the Home PLMN). The NRF in the Home PLMN returns a status code with the result of the operation.

Finally, step 2 in clause 5.2.2.5.7-2 is executed; a status code is returned to the NF Service Consumer in Serving PLMN in accordance to the result received from NRF in the Home PLMN.




Figure 5.2.2.5.7-1: Update of Subscription to NF Instances in a different PLMN

- 1. The NRF in Serving PLMN shall send a PATCH request to the resource URI representing the individual subscription. The payload body of the PATCH request shall contain a "replace" operation on the "validityTime" attribute of the SubscriptionData structure and shall contain a new suggested value for it;
- 2a. On success, if the NRF in the Home PLMN accepts the extension of the lifetime of the subscription, and it accepts the requested value for the "validityTime" attribute, a response with status code "204 No Content" shall be returned.
- 2b. On success, if the NRF in the Home PLMN accepts the extension of the lifetime of the subscription, but it assigns a validity time different than the value suggested by the NF Service Consumer, a "200 OK" response code shall be returned. The response shall contain the new resource representation of the "subscription" resource, which includes the new validity time, as determined by the NRF in the Home PLMN, after which the subscription becomes invalid.
- 2c. If the update of the subscription fails at the NRF due to errors in the JSON Patch object in the request body, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.

If the update of the subscription fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

5.2.2.6 NFStatusNotify

5.2.2.6.1 General

This service operation notifies each NF Service Consumer that was previously subscribed to receiving notifications of registration/deregistration of NF Instances, or notifications of changes of the NF profile of a given NF Instance. The notification is sent to a callback URI that each NF Service Consumer provided during the subscription (see NFStatusSubscribe operation in 5.2.2.5).

5.2.2.6.2 Notification from NRF in the same PLMN

The operation is invoked by issuing a POST request to each callback URI of the different subscribed NF Instances.




Figure 5.2.2.6.2-1: Notification from NRF in the same PLMN

1. The NRF shall send a POST request to the callback URI.

For notifications of newly registered NF Instances, the request body shall include the data associated to the newly registered NF, and its services, according to the criteria indicated by the NF Service Consumer during the subscription operation. These data shall contain the NFInstanceID of the NF Instance, an indication of the event being notified ("registration"), and the new profile data (including, among others, the services offered by the NF Instance).

For notifications of changes of the profile of a NF Instance, the request body shall include the NFInstancceID of the NF Instance whose profile was changed, an indication of the event being notified ("profile change"), and the new profile data.

For notifications of deregistration of the NF Instance from NRF, the request body shall include the NFInstanceID of the deregistered NF Instance, and an indication of the event being notified ("deregistration").

When an NF Service Consumer subscribes to a set of NFs (using the different subscription conditions specified in clause 6.1.6.2.35), a change in the profile of the monitored NF Instance may result in such NF becoming a part of the NF set (e.g., an NF Service Consumer subscribing to all NFs offering a given NF Service, and then, a certain NF Instance changes its profile by adding a new NF Service to its NF Profile); in such case, the NRF shall use the "profile change" event type in the notification.

- 2a. On success, "204 No content" shall be returned by the NF Service Consumer.
- 2b. If the NF Service Consumer does not consider the "nfStatusNotificationURI" as a valid notification URI (e.g., because the URI does not belong to any of the existing subscriptions created by the NF Service Consumer in the NRF), the NF Service Consumer shall return "404 Not Found" status code with the ProblemDetails IE providing details of the error.

5.2.2.6.3 Notification from NRF in a different PLMN

The operation is invoked by issuing a POST request to each callback URI of the different subscribed NF Instances.




Figure 5.2.2.6.3-1: Notification from NRF in a different PLMN

Steps 1 and 2 are identical to steps 1 and 2 in Figure 5.2.2.6.2-1.

It should be noted that the POST request shall be sent directly from the NRF in Home PLMN to the NF Service Consumer in Serving PLMN, without involvement of the NRF in Serving PLMN.

5.2.2.6.4 Notification for subscription via intermediate NRF




Figure 5.2.2.6.4-1: Notification for subscription via intermediate NRF

Step 0 is the NF Service Consumer creates a subscription to NRF-2 via intermediate NRF.

Steps 1 and 2 are identical to steps 1 and 2 in Figure 5.2.2.6.2-1.

The POST request shall be sent directly from NRF-2 to the NF Service Consumer without involvement of NRF-1.

5.2.2.7 NFStatusUnSubscribe

5.2.2.7.1 General

This service operation removes an existing subscription to notifications.

5.2.2.7.2 Subscription removal in the same PLMN

It is executed by deleting a given resource identified by a "subscriptionID". The operation is invoked by issuing a DELETE request on the URI representing the specific subscription received in the Location header field of the "201 Created" response received during a successful subscription (see clause 5.2.2.5).




Figure 5.2.2.7.2-1: Subscription removal in the same PLMN

- 1. The NF Service Consumer shall send a DELETE request to the resource URI representing the individual subscription. The request body shall be empty.
- 2a. On success, "204 No Content" shall be returned. The response body shall be empty.
- 2b. If the subscription, identified by the "subscriptionID", is not found in the list of active subscriptions in the NRF's database, the NRF shall return "404 Not Found" status code with the ProblemDetails IE providing details of the error.

5.2.2.7.3 Subscription removal in a different PLMN

The subscription removal in a different PLMN is done by deleting a resource identified by a "subscriptionID", in the NRF of the Home PLMN.

For that, step 1 in clause 5.2.2.7.2 is executed (send a DELETE request to the NRF in the Serving PLMN); this request shall include the identity of the PLMN of the home NRF (MCC/MNC values) as a leading prefix of the susbcriptionID (see clause 5.2.2.5.3).

Then, steps 1-2 in Figure 5.2.2.7.3-1 are executed, between the NRF in the Serving PLMN and the NRF in the Home PLMN. In this step, the subscriptionID sent to the NRF in the Home PLMN shall not contain the identity of the PLMN (i.e., it shall be the same subscriptionID value as originally generated by the NRF in the Home PLMN). The NRF in the Home PLMN returns a status code with the result of the operation.

Finally, step 2 in clause 5.2.2.7.2 is executed; a status code is returned to the NF Service Consumer in Serving PLMN in accordance to the result received from NRF in Home PLMN.




Figure 5.2.2.7.3-1: Subscription removal in a different PLMN

- 1. The NF Service Consumer shall send a DELETE request to the resource URI representing the individual subscription. The request body shall be empty.
- 2a. On success, "204 No Content" shall be returned. The response body shall be empty.
- 2b. If the subscription, identified by the "subscriptionID", is not found in the list of active subscriptions in the NRF's database, the NRF shall return "404 Not Found" status code with the ProblemDetails IE providing details of the error.

5.2.2.8 NFListRetrieval

5.2.2.8.1 General

This service operation allows the retrieval of a list of NF Instances that are currently registered in NRF. The operation may apply to the whole set of registered NF instances or only to a subset of the NF instances, based on a given NF type and/or maximum number of NF instances to be returned.




Figure 5.2.2.8.1-1: NF instance list retrieval

1. The NF Service Consumer shall send an HTTP GET request to the resource URI "nf-instances" collection resource. The optional input filter criteria for the retrieval request shall be included in query parameters.

- 2a. On success, "200 OK" shall be returned. The response body shall contain the URI (conforming to the resource URI structure as described in clause 5.2.2.9.1) of each registered NF in the NRF that satisfy the retrieval filter criteria (e.g., all NF instances of the same NF type), or an empty list if there are no NFs to return in the query result (e.g., because there are no registered NFs in the NRF, or because there are no matching NFs of the type specified in the "nf-type" query parameter, currently registered in the NRF).
- 2b. If the NF Service Consumer is not allowed to retrieve the registered NF instances, the NRF shall return "403 Forbidden" status code.

If the NF Instance list retrieval fails at the NRF due to errors in the input data in the URI query parameters, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.

If the discovery request fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

5.2.2.9 NFProfileRetrieval

5.2.2.9.1 General

This service operation allows the retrieval of the NF profile of a given NF instance currently registered in NRF.



Figure 5.2.2.9.1-1: NF profile retrieval

- 1. The NF Service Consumer shall send an HTTP GET request to the resource URI "nf-instances/{nfInstanceId}".
- 2a. On success, "200 OK" shall be returned. The response body shall contain the NF profile of the NF instance identified in the request.
- 2b. If the NF Service Consumer is not allowed to retrieve the NF profile of this specific registered NF instance, the NRF shall return "403 Forbidden" status code.

If the NF Profile retrieval fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

5.3 Nnrf NFDiscovery Service

5.3.1 Service Description

The Nnrf_NFDiscovery service allows a Network Function Instance to discover services offered by other Network Function Instances, by querying the local NRF.

It also allows an NRF in a PLMN to re-issue a discovery request towards an NRF in another PLMN (e.g., the HPLMN of a certain UE).

5.3.2 Service Operations

5.3.2.1 Introduction

The service operations defined for the Nnrf_NFDiscovery service are as follows:

- NFDiscover: It provides to the NF service consumer the IP address(es) or FQDN of the NF Instance(s) or NF Service(s) matching certain input criteria.

The NFDiscover operation can be invoked by an NF Service Consumer (i.e., "source NF") requesting to discover NF instances (i.e., "target NFs") located in the same PLMN, or in a different PLMN.

In the description of these operations in clause 5.3.2.2, when the NF instances are located in the same PLMN, both source NF and target NFs are said to be located in the "Serving PLMN" but, in the general case, the functionality is not restricted to the PLMN that is serving a given UE, and it shall be applicable as well to any scenario in which source NF and target NFs belong to the same PLMN.

When source NF and target NFs are located in different PLMNs, the source NF is said to be in the "Serving PLMN", and the target NFs (and the NRF where they are registered) are said to be in the "Home PLMN", similarly to the scenarios described in 3GPP TS 23.502 [3], but the functionality shall be equally applicable to any scenario between any pair of PLMNs (e.g. with the source NF in the Home PLMN and the target NF in the Serving PLMN).

5.3.2.2 NFDiscover

5.3.2.2.1 General

This service operation discovers the set of NF Instances (and their associated NF Service Instances), represented by their NF Profile, that are currently registered in NRF and satisfy a number of input query parameters.

Before a service consumer invokes this service operation, it shall consider if it is possible to reuse the results from a previous searching (service discovery).

The service consumer should reuse the previous result if input query parameters in the new service discovery request are the same as used for the previous search and the validity period of the result is not expired.

The service consumer may consider reusing the previous result if the attributes as required for the new query is also part of NF profile of the candidates NFs from a previous query. In such case, when the results of a previous query are reused, the service consumer need consider that the results, e.g. in terms of the number of discovered NFs, can be different than the potential results obtained after performing a new query.

5.3.2.2.2 Service Discovery in the same PLMN

This service operation is executed by querying the "nf-instances" resource. The request is sent to an NRF in the same PLMN of the NF Service Consumer.




Figure 5.3.2.2.1: Service Discovery Request in the same PLMN

- 1. The NF Service Consumer shall send an HTTP GET request to the resource URI "nf-instances" collection resource. The input filter criteria for the discovery request shall be included in query parameters.
- 2a. On success, "200 OK" shall be returned. The response body shall contain a validity period, during which the search result can be cached by the NF Service Consumer, and an array of NF Profile objects, that satisfy the search filter criteria (e.g., all NF Instances offering a certain NF Service name).
- 2b. If the NF Service Consumer is not allowed to discover the NF services for the requested NF type provided in the query parameters, the NRF shall return "403 Forbidden" response.

If the discovery request fails at the NRF due to errors in the input data in the URI query parameters, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.

If the discovery request fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

The NF Profile objects returned in a successful result shall contain generic data of each NF Instance, applicable to any NF type, and it may also contain NF-specific data, for those NF Instances belonging to a specific type (e.g., the attribute "udrInfo" is typically present in the NF Profile when the type of the NF Instance takes the value "UDR"). In addition, the attribute "customInfo", may be present in the NF Profile for those NF Instances with custom NF types.

For those NF Instances, the "customInfo" attribute shall be returned by NRF, if available, as part of the NF Profiles returned in the discovery response.

The NRF shall also include, in the returned NF Profile objects, the Vendor-Specific attributes (see 3GPP TS 29.500 [4], clause 6.6.3) that may have been provided by the registered NF Instances.

5.3.2.2.3 Service Discovery in a different PLMN

The service discovery in a different PLMN is done by querying the "nf-instances" resource in the NRF of the Home PLMN.

For that, step 1 in clause 5.3.2.2.2 is executed (send a GET request to the NRF in the Serving PLMN); this request shall include the identity of the PLMN of the home NRF in a query parameter of the URI.

Then, steps 1-2 in Figure 5.3.2.2.3-1 are executed, between the NRF in the Serving PLMN and the NRF in the Home PLMN. In this step, the presence of the PLMN ID of the Home NRF in the query parameter of the URI is not required. The NRF in the Home PLMN returns a status code with the result of the operation. The NRF in the Serving PLMN shall be configured with a telescopic FQDN (see 3GPP TS 23.003 [12] and 3GPP TS 29.500 [4]) of the NRF in the Home PLMN.

NOTE: This is required for the NRF in the serving PLMN to route the NF discovery request to the NRF in the HPLMN through a SEPP in the serving PLMN and the SEPP to terminate the TLS connection with a wildcard certificate.

Finally, step 2 in clause 5.3.2.2.2 is executed; a status code is returned to the NF Service Consumer in Serving PLMN in accordance to the result received from NRF in Home PLMN.




Figure 5.3.2.2.3-1: Service Discovery in a different PLMN

Steps 1 and 2 are similar to steps 1 and 2 in Figure 5.3.2.2.2-1, by replacing the originator of the service invocation with the NRF in Serving PLMN, and the recipient of the service invocation with the NRF in the Home PLMN.

5.3.2.2.4 Service Discovery with intermediate redirecting NRF

When multiple NRFs are deployed in one PLMN, one NRF may query the "nf-instances" resource in a different NRF so as to fulfil the service discovery request from a NF service consumer. The query between these two NRFs is redirected by a third NRF.




Figure 5.3.2.2.4-1: Service Discovery with intermediate redirecting NRF

- 1. NRF-1 receives a service discovery request but does not have the information to fulfil the request. Then NRF-1 sends the service discovery request to a pre-configured NRF-2.
- 2a. Upon receiving a service discovery request, based on the information contained in the service discovery request (e.g. the "supi" query parameter in the URI) and locally stored information NRF-2 shall identify the next hop NRF (see clause 5.2.2.2.3), and redirect the service discovery request by returning HTTP 307 Temporary Redirect response. The locally stored information in NRF-2 may:
 - a) be preconfigured; or
 - b) registered by other NRFs (see clause 5.2.2.2.3).

The 307 Temporary Redirect response shall contain a Location header field, the host part of the URI in the Location header field represents NRF-3.

- 2b. if NRF-2 does not have enough information to redirect the service discovery request, then it responds with 404 Not Found, and the rest of the steps are omitted.
- 3. Upon receiving 307 Temporary Redirect response, NRF-1 sends the service discovery request to NRF-3 by using the URI contained in the Location header field of the 307 Temporary Redirect response.
- 4a. Upon success, NRF-3 returns the search result.
- 4b. If the NF Service Consumer is not allowed to discover the NF services for the requested NF type provided in the query parameters, the NRF shall return "403 Forbidden" response.

If the discovery request fails at the NRF due to errors in the input data in the URI query parameters, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.

If the discovery request fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

5.3.2.2.5 Service Discovery with intermediate forwarding NRF

When multiple NRFs are deployed in one PLMN, one NRF may query the "nf-instances" resource in a different NRF so as to fulfil the service discovery request from a NF service consumer. The query between these two NRFs is forwarded by a third NRF.




Figure 5.3.2.2.5-1: Service Discovery with intermediate forwarding NRF

- 1. NRF-1 receives a service discovery request but does not have the information to fulfil the request. Then NRF-1 sends the service discovery request to a pre-configured NRF-2.
- 2a. Upon receiving a service discovery request, based on the information contained in the service discovery request (e.g. the "supi" query parameter in the URI) and locally stored information, NRF-2 shall identify the next hop NRF (see clause 5.2.2.2.3), and forward the service discovery request to that NRF (i.e. NRF-3 in this example), by replacing the originator of the service invocation with NRF-2, and the recipient of the service invocation with NRF-3. The locally stored information in NRF-2 may:
 - a) be preconfigured; or
 - b) registered by other NRFs (see clause 5.2.2.2.3).
- 2b. if NRF-2 does not have enough information to forward the service discovery request, then it responds with 404 Not Found, and the rest of the steps are omitted.
- 3a. Upon success, NRF-3 returns the search result.
- 3b. If the NF Service Consumer is not allowed to discover the NF services for the requested NF type provided in the query parameters, the NRF shall return "403 Forbidden" response.

If the discovery request fails at the NRF due to errors in the input data in the URI query parameters, the NRF shall return "400 Bad Request" status code with the ProblemDetails IE providing details of the error.

If the discovery request fails at the NRF due to NRF internal errors, the NRF shall return "500 Internal Server Error" status code with the ProblemDetails IE providing details of the error.

- 4a. NRF-2 forwards the success response to NRF-1.
- 4b. NRF-2 forwards the error response to NRF-1.

NOTE: It is not assumed that there can only be two NRF hierarchies, i.e. the NRF-3 can go on to forward the service discovery request to another NRF.

5.4 Nnrf_AccessToken Service

5.4.1 Service Description

The NRF offers an Nnrf_AccessToken service (used for OAuth2 authorization, see IETF RFC 6749 [16]), following the "Client Credentials" authorization grant, as specified in 3GPP TS 33.501 [15]. It exposes a "Token Endpoint" where the Access Token Request service can be requested by NF Service Consumers.

5.4.2 Service Operations

5.4.2.1 Introduction

The services operations defined for the Nnrf_AccessToken service are as follows:

- Access Token Request (i.e. Nnrf AccessToken Get)

5.4.2.2 Get (Access Token Request)

5.4.2.2.1 General

This service operation is used by an NF Service Consumer to request an OAuth2 access token from the authorization server (NRF).




Figure 5.4.2.2.1-1: Access Token Request

1. The NF Service Consumer shall send a POST request to the "Token Endpoint", as described in IETF RFC 6749 [16], clause 3.2. The "Token Endpoint" URI shall be:

{nrfApiRoot}/oauth2/token

where {nrfApiRoot} represents the concatenation of the "scheme" and "authority" components of the NRF, as defined in IETF RFC 3986 [17].

The OAuth 2.0 Access Token Request includes in the body of the HTTP POST request shall contain:

- An OAuth2 grant type set to "client_credentials";
- The "scope" parameter indicating the names of the NF Services that the NF Service Consumer is trying to access (i.e., the expected NF service names);
- The NF Instance Id of the the NF Service Consumer requesting the OAuth2.0 access token, if this is an access token request for a specific NF Service Producer;
- NF type of the NF Service Consumer, if this is an access token request not for a specific NF Service Producer;
- NF type of the expected NF Service Producer, if this is an access token request for a specific NF Service Producer;
- The NF Instance Id of the expected NF Service Producer, if this is an access token request for a specific NF Service Producer;
- Home and Serving PLMN IDs, if this is an access token request for use in roaming scenarios (see clause 13.4.1.2 of 3GPP TS 33.501 [15]).

The NF Service Consumer shall use TLS for mutual authentication with the NRF in order to access this endpoint, if the PLMN uses protection at the transport layer. Otherwise the NF Service Consumer shall use NDS or physical security to mutually authenticate with the NRF as specified in clause 13.3.1 of 3GPP TS 33.501 [15].

- 2. On success, "200 OK" shall be returned, the payload body of the POST response shall contain the requested access token and the token type set to value "Bearer". The response in addition:
 - should contain the expiration time for the token as indicated in IETF RFC 6749 [16] unless the expiration time of the token is made available by other means (e.g. deployment-specific documentation); and
 - shall contain the NF service name(s) of the requested NF service producer(s), if it is different from the scope included in the access token request (see IETF RFC 6749 [16]).

The access token shall be a JSON Web Token (JWT) as specified in IETF RFC 7519 [25]. The access token returned by the NRF shall include the claims encoded as a JSON object as specified in clause 6.3.5.2.4 and then digitally signed using JWS as specified in IETF RFC 7515 [24] and in clause 13.4.1 of 3GPP TS 33.501 [15].

The digitally signed access token shall be converted to the JWS Compact Serialization encoding as a string as specified in clause 7.1 of IETF RFC 7515 [24].

If the access token request fails at the NRF, the NRF shall return "400 Bad Request" status code, including in the response payload a JSON object that provides details about the specific error that occurred.

5.4.2.2.2 Access Token request with intermediate forwarding NRF

When multiple NRFs are deployed in one PLMN, one NRF may request an OAuth2 access token to a different NRF so as to fulfil the Access Token Request from a NF service consumer. The acces token request between these two NRFs is forwarded by a third NRF in this case.

For this, step 1 in clause 5.4.2.2.1 is executed (send a POST request to NRF-1 in the Serving PLMN); this request shall include the OAuth 2.0 Access Token Request in the request body.

Then, steps 1-4 in Figure 5.4.2.2.2-1 hereinafter are executed between NRF-1in Serving PLMN, NRF-2 in Serving PLMN and NRF-3 in Serving PLMN.

Finally, step 2 in clause 5.4.2.2.1 is executed, the Access Token Response containing the requested access token, the token type and additional attributes shall be sent to the NF Service Consumer.




Figure 5.4.2.2.1: Access Token Request with intermediate forwarding NRF

- 1. NRF-1 receives an Access token request but does not have the information to fulfil the request. Then NRF-1 sends the Access token request to a pre-configured NRF-2.
- 2a. Upon reception of the Access token request and based on the information contained in the Acces token request and locally stored information, NRF-2 shall identify the next hop NRF (see clause 5.2.2.2.3), and forward the Access token request to that NRF (i.e. NRF-3 in this example) by replacing the originator of the service invocation with NRF-2, and the recipient of the service invocation with NRF-3. The locally stored information in NRF-2 may:
 - a) be preconfigured; or
 - b) registered by other NRFs (see clause 5.2.2.2.3).
- 2b. if NRF-2 does not have enough information to forward the Access token request, then it responds with 404 Not Found, and the rest of the steps are omitted.

- 3a. Upon success, NRF-3 shall return a "200 OK" status code, including in the response payload the Access token response containing the requested access token, the token type and additional attributes.
- 3b. Upon failure, NRF-3 shall return "400 Bad Request" status code, including in the response payload a JSON object that provides details about the specific error(s) that occurred.
- 4a. NRF-2 forwards the success response to NRF-1.
- 4b. NRF-2 forwards the error response to NRF-2.

NOTE: It is not assumed that there can only be two NRF hierarchies, i.e. the NRF-3 can go on and forward the Access token request request to another NRF.

5.4.2.2.3 Access Token request with intermediate redirecting NRF

When multiple NRFs are deployed in one PLMN, one NRF may request an OAuth2 access token to a different NRF so as to fulfil the Access Token Request from a NF service consumer. The access token request between these two NRFs is redirected by a third NRF in this case.

For this, step 1 in clause 5.4.2.2.1 is executed (send a POST request to NRF-1 in the Serving PLMN); this request shall include the OAuth 2.0 Access Token Request in the request body

Then, steps 1-4 in Figure 5.4.2.2.3-1 hereinafter are executed between NRF-1in Serving PLMN, NRF-2 in Serving PLMN and NRF-3 in Serving PLMN.

Finally, step 2 in clause 5.4.2.2.1 is executed, the Access token response containing the requested access token, the token type and additional attributes shall be sent to the NF Service Consumer.




Figure 5.4.2.2.3-1: Access Token Request with intermediate redirecting NRF

- 1. NRF-1 receives an Access token request but does not have the information to fulfil the request. Then NRF-1 sends the Access token request to a pre-configured NRF-2.
- 2a. Upon reception of the Access token requestand based on the information contained in the Acces token request and locally stored information, NRF-2 shall identify the next hop NRF (see clause 5.2.2.2.3), and redirect the Access token request by returning HTTP "307 Temporary Redirect" response. The locally stored information in NRF-2 may:
 - a) be preconfigured; or
 - b) registered by other NRFs (see clause 5.2.2.2.3).

The "307 Temporary Redirect" response shall contain a Location header field, the host part of the URI in the Location header field represents NRF-3.

- 2b. if NRF-2 does not have enough information to forward the Access token request, then it responds with "404 Not Found", and the rest of the steps are omitted.
- 3. Upon reception of "307 Temporary Redirect" response, NRF-1 sends the Acces token request to NRF-3 by using the URI contained in the Location header field of the "307 Temporary Redirect" response.

- 4a. Upon success, NRF-3shall return a "200 OK" status code including in the response payload the Access token response containing the requested access token, the token type and additional attributes.
- 4b. Upon failure, the NRF-3 shall return "400 Bad Request" status code, including in the response payload a JSON object that provides details about the specific error(s) that occurred.

6 API Definitions

6.1 Nnrf_NFManagement Service API

6.1.1 API URI

URIs of this API shall have the following root:

{apiRoot}/{apiName}/{apiVersion}/

where "apiRoot" is defined in clause 4.4.1 of 3GPP TS 29.501 [5], the "apiName" shall be set to "nnrf-nfm" and the "apiVersion" shall be set to "v1" for the current version of this specification.

6.1.2 Usage of HTTP

6.1.2.1 General

HTTP/2, as defined in IETF RFC 7540 [9], shall be used as specified in clause 5 of 3GPP TS 29.500 [4].

HTTP/2 shall be transported as specified in clause 5.3 of 3GPP TS 29.500 [4].

HTTP messages and bodies for the Nnrf_NFManagement service shall comply with the OpenAPI [10] specification contained in Annex A.

6.1.2.2 HTTP Standard Headers

6.1.2.2.1 General

The mandatory standard HTTP headers as specified in clause 5.2.2.2 of 3GPP TS 29.500 [4] shall be supported.

6.1.2.2.2 Content type

The following content types shall be supported:

- JSON, as defined in IETF RFC 8259 [22], shall be used as content type of the HTTP bodies specified in the present specification as indicated in clause 5.4 of 3GPP TS 29.500 [4].
- The Problem Details JSON Object (IETF RFC 7807 [11]). The use of the Problem Details JSON object in a HTTP response body shall be signalled by the content type "application/problem+json".
- JSON Patch (IETF RFC 6902 [13]). The use of the JSON Patch format in a HTTP request body shall be signalled by the content type "application/json-patch+json".
- The 3GPP hypermedia format as defined in 3GPP TS 29.501 [5]. The use of the 3GPP hypermedia format in a HTTP response body shall be signalled by the content type "application/3gppHal+json".

6.1.2.2.3 Accept-Encoding

The NRF should support gzip coding (see IETF RFC 1952 [30]) in HTTP requests and responses and indicate so in the Accept-Encoding header, as described in clause 6.9 of 3GPP TS 29.500 [4].

NF Service Consumers of the NFManagement API should support gzip coding in HTTP requests and responses and they should support gzip coding in the reception of notification requests sent by the NRF.

6.1.2.3 HTTP custom headers

6.1.2.3.1 General

In this release of this specification, no custom headers specific to the Nnrf_NFManagement service are defined. For 3GPP specific HTTP custom headers used across all service-based interfaces, see clause 5.2.3 of 3GPP TS 29.500 [4].

6.1.3 Resources

6.1.3.1 Overview

The structure of the Resource URIs of the NFManagement service is shown in figure 6.1.3.1-1.




Figure 6.1.3.1-1: Resource URI structure of the NFManagement API

Table 6.1.3.1-1 provides an overview of the resources and applicable HTTP methods.

Table 6.1.3.1-1: Resources and methods overview

Resource name	Resource URI	HTTP method or custom operation	Description
nf-instances (Store)	{apiRoot}/nnrf-nfm/v1/nf-instances	GET	Read a collection of NF Instances.
		OPTIONS	Discover the communication options supported by the NRF for this resource.
nf-instance (Document)	{apiRoot}/nnrf-nfm/v1/nf-instances/{nfInstanceID}	GET	Read the profile of a given NF Instance.
		PUT	Register in NRF a new NF Instance, or replace the profile of an existing NF Instance, by providing an NF profile.
		PATCH	Modify the NF profile of an existing NF Instance.
		DELETE	Deregister from NRF a given NF Instance.
subscriptions (Collection)	{apiRoot}/nnrf-nfm/v1/subscriptions	POST	Creates a new subscription in NRF to newly registered NF Instances.
subscription (Document)	{apiRoot}/nnrf- nfm/v1/subscriptions/{subscriptionID}	PATCH	Updates an existing subscription in NRF.
		DELETE	Deletes an existing subscription from NRF.
Notification Callback	{nfStatusNotificationUri}	POST	Notify about newly created NF Instances, or about changes of the profile of a given NF Instance.

6.1.3.2 Resource: nf-instances (Store)

6.1.3.2.1 Description

This resource represents a collection of the different NF instances registered in the NRF.

This resource is modelled as the Store resource archetype (see clause C.3 of 3GPP TS 29.501 [5]).

6.1.3.2.2 Resource Definition

Resource URI: {apiRoot}/nnrf-nfm/v1/nf-instances

This resource shall support the resource URI variables defined in table 6.1.3.2.2-1.

Table 6.1.3.2.2-1: Resource URI variables for this resource

Name	Definition
apiRoot	See clause 6.1.1

6.1.3.2.3 Resource Standard Methods

6.1.3.2.3.1 GET

This method retrieves a list of all NF instances currently registered in the NRF. This method shall support the URI query parameters specified in table 6.1.3.2.3.1-1.

Table 6.1.3.2.3.1-1: URI query parameters supported by the GET method on this resource

Name	Data type	Р	Cardinality	Description
nf-type	NFType	0	01	The type of NF to restrict the list of returned NF Instances.
limit	integer	0	01	Maximum number of items to be returned in this query.

This method shall support the request data structures specified in table 6.1.3.2.3.1-2 and the response data structures and response codes specified in table 6.1.3.2.3.1-3.

Table 6.1.3.2.3.1-2: Data structures supported by the GET Request Body on this resource

Data type	Р	Cardinality	Description
n/a			

Table 6.1.3.2.3.1-3: Data structures supported by the GET Response Body on this resource

Data ty	/pe	Р	Cardinality	Response codes	Description
UriList		M	1	200 OK	The response body contains a "_links" object containing the URI of each registered NF in the NRF, or an empty object if there are no NFs to return in the query result (e.g., because there are no registered NFs in the NRF, or because there are no matching NFs of the type specified in the "nf-type" query parameter, currently registered in the NRF).
	OTE: The mandatory HTTP error status codes for the GET method listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [4] other than those specified in the table above also apply, with a ProblemDetails data type (see clause 5.2.7 of 3GPP TS 29.500 [4]).				

6.1.3.2.3.2 OPTIONS

This method queries the communication options supported by the NRF (see clause 6.9 of 3GPP TS 29.500 [4]). This method shall support the URI query parameters specified in table 6.1.3.2.3.2-1.

Table 6.1.3.2.3.2-1: URI query parameters supported by the OPTIONS method on this resource

Name	Data type	Р	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 6.1.3.2.3.2-2 and the response data structures and response codes specified in table 6.1.3.2.3.2-3.

Table 6.1.3.2.3.2-2: Data structures supported by the OPTIONS Request Body on this resource

Data type	Р	Cardinality	Description
n/a			

Table 6.1.3.2.3.2-3: Data structures supported by the OPTIONS Response Body on this resource

Data type	Р	Cardinality	Response	Description
			codes	
n/a	M	1	200 OK	
ProblemDetails	M	1	405 Method Not	
			Allowed	
ProblemDetails	М	1	501 Not Implemented	
	·			· · · · · · · · · · · · · · · · · · ·

NOTE: The mandatory HTTP error status codes for the OPTIONS method listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [4] other than those specified in the table above also apply, with a ProblemDetails data type (see clause 5.2.7 of 3GPP TS 29.500 [4]).

6.1.3.2.4 Resource Custom Operations

There are no resource custom operations for the Nnrf_NFManagement service in this release of the specification.

6.1.3.3 Resource: nf-instance (Document)

6.1.3.3.1 Description

This resource represents a single NF instance.

6.1.3.3.2 Resource Definition

Resource URI: {apiRoot}/nnrf-nfm/v1/nf-instances/{nfInstanceID}

This resource shall support the resource URI variables defined in table 6.1.3.3.2-1.

Table 6.1.3.3.2-1: Resource URI variables for this resource

Name	Definition
apiRoot	See clause 6.1.1
nfInstanceID	Represents a specific NF Instance

6.1.3.3.3 Resource Standard Methods

6.1.3.3.3.1 GET

This method retrieves the NF Profile of a given NF instance.

This method shall support the URI query parameters specified in table 6.1.3.3.3.1-1.

Table 6.1.3.3.3.1-1: URI query parameters supported by the GET method on this resource

Name	Data type	Р	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 6.1.3.3.3.1-2 and the response data structures and response codes specified in table 6.1.3.3.3.1-3.

Table 6.1.3.3.3.1-2: Data structures supported by the GET Request Body on this resource

Data type	Р	Cardinality	Description
n/a			

Table 6.1.3.3.3.1-3: Data structures supported by the GET Response Body on this resource

Data t	type	Р	Cardinality	Response codes	Description	
NFProfile		M	1	200 OK	The response body contains the profile of a given NF Instance.	
NOTE:	, and the state of					

6.1.3.3.3.2 PUT

This method registers a new NF instance in the NRF, or replaces completely an existing NF instance.

This method shall support the URI query parameters specified in table 6.1.3.3.3.2-1.

Table 6.1.3.3.3.2-1: URI query parameters supported by the PUT method on this resource

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 6.1.3.3.3.2-2 and the response data structures and response codes specified in table 6.1.3.3.3.2-3.

Table 6.1.3.3.3.2-2: Data structures supported by the PUT Request Body on this resource

Data type	Р	Cardinality	Description
NFProfile	M	1	Profile of the NF Instance to be registered, or
			completely replaced, in NRF.

Table 6.1.3.3.3.2-3: Data structures supported by the PUT Response Body on this resource

Data type	Р	Cardinality	Response codes	Description
NFProfile	М	1	200 OK	This case represents the successful replacement of an existing NF Instance profile.
				Upon success, a response body is returned containing the replaced profile of the NF Instance.
NFProfile	M	1	201 Created	This case represents the successful registration of a new NF Instance.
				Upon success, a response body is returned
				containing the newly created NF Instance profile; also, the HTTP response shall include
				a "Location" HTTP header that contains the resource URI of the created NF Instance.
				od listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [4]
			above also apply, wi	th a ProblemDetails data type (see clause 5.2.7
i of 3GPI	P TS 29.500	[4]).		

6.1.3.3.3.3 PATCH

This method updates partially the profile of a given NF instance.

This method shall support the URI query parameters specified in table 6.1.3.3.3.3-1.

Table 6.1.3.3.3.3-1: URI query parameters supported by the PATCH method on this resource

Name	Data type	Р	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 6.1.3.3.3.3-2 and the response data structures and response codes specified in table 6.1.3.3.3.3-3.

Table 6.1.3.3.3.3-2: Data structures supported by the PATCH Request Body on this resource

Data type	Р	Cardinality	Description
PatchDocument	M	1	It contains the list of changes to be made to
			the profile of the NF Instance, according to
			the JSON PATCH format specified in
			IETF RFC 6902 [13].

Table 6.1.3.3.3.3-3: Data structures supported by the PATCH Response Body on this resource

Data type	Р	Cardinality	Response codes	Description
NFProfile	М	1	200 OK	Upon success, a response body is returned containing the updated profile of the NF Instance.
n/a			204 No Content	Successful response sent when there is no need to provide a full updated profile of the NF Instance (e.g., in the Heart-Beat operation response described in clause 5.2.2.3.2).
NOTE: The mandatory HTTP error status codes for the PATCH method listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [4] other than those specified in the table above also apply, with a ProblemDetails data type (see clause 5.2.7 of 3GPP TS 29.500 [4]).				

6.1.3.3.3.4 DELETE

This method deregisters an existing NF instance from the NRF.

This method shall support the URI query parameters specified in table 6.1.3.3.3.4-1.

Table 6.1.3.3.3.4-1: URI query parameters supported by the DELETE method on this resource

Name	Data type	Р	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 6.1.3.3.3.4-2 and the response data structures and response codes specified in table 6.1.3.3.3.4-3.

Table 6.1.3.3.3.4-2: Data structures supported by the DELETE Request Body on this resource

Data type	Р	Cardinality	Description
n/a			

Table 6.1.3.3.3.4-3: Data structures supported by the DELETE Response Body on this resource

Data	type	Р	Cardinality	Response codes	Description	
n/a				204 No Content		
NOTE:	NOTE: The mandatory HTTP error status codes for the DELETE method listed in Table 5.2.7.1-1 of					
	3GPP TS 29.500 [4] other than those specified in the table above also apply, with a ProblemDetails data					
	type (see clause 5.2.7 of 3GPP TS 29.500 [4]).					

6.1.3.4 Resource: subscriptions (Collection)

6.1.3.4.1 Description

This resource represents a collection of subscriptions of NF Instances to newly registered NF Instances.

6.1.3.4.2 Resource Definition

Resource URI: {apiRoot}/nnrf-nfm/v1/subscriptions

This resource shall support the resource URI variables defined in table 6.1.3.4.2-1.

Table 6.1.3.4.2-1: Resource URI variables for this resource

Name	Definition
apiRoot	See clause 6.1.1

6.1.3.4.3 Resource Standard Methods

6.1.3.4.3.1 POST

This method creates a new subscription. This method shall support the URI query parameters specified in table 6.1.3.4.3.1-1.

Table 6.1.3.4.3.1-1: URI query parameters supported by the POST method on this resource

Name	Data type	Р	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 6.1.3.4.3.1-2 and the response data structures and response codes specified in table 6.1.3.4.3.1-3.

Table 6.1.3.4.3.1-2: Data structures supported by the POST Request Body on this resource

Data type	P	Cardinality	Description
SubscriptionData	М		The request body contains the input parameters for the subscription. These parameters include, e.g.: - Target NF type - Target Service Name - Callback URI of the Requester NF

Table 6.1.3.4.3.1-3: Data structures supported by the POST Response Body on this resource

Data type	Р	Cardinality	Response codes	Description
SubscriptionData	M	1	201 Created	This case represents the successful creation of a subscription.
				Upon success, the HTTP response shall include a "Location" HTTP header that contains the resource URI of the created resource.
other tha		cified in the table		listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [4] a ProblemDetails data type (see clause 5.2.7

6.1.3.5 Resource: subscription (Document)

6.1.3.5.1 Description

This resource represents an individual subscription of a given NF Instance to newly registered NF Instances.

6.1.3.5.2 Resource Definition

Resource URI: {apiRoot}/nnrf-nfm/v1/subscriptions/{subscriptionID}

This resource shall support the resource URI variables defined in table 6.1.3.5.2-1.

Table 6.1.3.5.2-1: Resource URI variables for this resource

Name	Definition
apiRoot	See clause 6.1.1
subscriptionID	Represents a specific subscription

6.1.3.5.3 Resource Standard Methods

6.1.3.5.3.1 DELETE

This method terminates an existing subscription. This method shall support the URI query parameters specified in table 6.1.3.5.3.1-1.

Table 6.1.3.5.3.1-1: URI query parameters supported by the DELETE method on this resource

Name	Data type	Р	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 6.1.3.5.3.1-2 and the response data structures and response codes specified in table 6.1.3.5.3.1-3.

Table 6.1.3.5.3.1-2: Data structures supported by the DELETE Request Body on this resource

Data type	Р	Cardinality	Description
n/a			

Table 6.1.3.5.3.1-3: Data structures supported by the DELETE Response Body on this resource

Data t	Data type P		Cardinality Response		Description		
				codes			
n/a				204 No Content			
NOTE:	NOTE: The mandatory HTTP error status codes for the PUT method listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [4]						
	other than those specified in the table above also apply, with a ProblemDetails data type (see clause 5.2.7						
	of 3GPP TS 29.500 [4]).						

6.1.3.5.3.2 PATCH

This method updates an existing subscription. This method shall support the URI query parameters specified in table 6.1.3.5.3.2-1.

Table 6.1.3.5.3.2-1: URI query parameters supported by the PATCH method on this resource

Name	Data type	Р	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 6.1.3.5.3.2-2 and the response data structures and response codes specified in table 6.1.3.5.3.2-3.

Table 6.1.3.5.3.2-2: Data structures supported by the PATCH Request Body on this resource

Data type	Р	Cardinality	Description
array(PatchItem)	М		It contains the list of changes to be made to the profile of the NF Instance, according to the JSON PATCH format specified in IETF RFC 6902 [13].

Table 6.1.3.5.3.2-3: Data structures supported by the PATCH Response Body on this resource

Data type	Р	Cardinality	Response codes	Description
SubscriptionData	М	1	200 OK	
n/a			204 No Content	

6.1.4 Custom Operations without associated resources

There are no custom operations defined without any associated resources for the Nnrf_NFManagement service in this release of the specification.

6.1.5 Notifications

6.1.5.1 General

This clause specifies the notifications provided by the Nnrf_NFManagement service.

The delivery of notifications shall be supported as specified in clause 6.2 of 3GPP TS 29.500 [4] for Server-initiated communication.

Table 6.1.5.1-1: Notifications overview

Notification	Resource URI	HTTP method or custom operation	Description (service operation)
	{nfStatusNotificationUri} (NF Service Consumer provided callback reference)	POST	Notify about registrations / deregistrations or profile changes of NF Instances

6.1.5.2 NF Instance Status Notification

6.1.5.2.1 Description

The NF Service Consumer provides a callback URI for getting notified about NF Instances status events, the NRF shall notify the NF Service Consumer, when the conditions specified in the subscription are met.

6.1.5.2.2 Notification Definition

The POST method shall be used for NF Instance Status notification and the URI shall be the callback reference provided by the NF Service Consumer during the subscription to this notification.

Resource URI: {nfStatusNotificationUri}

Support of URI query parameters is specified in table 6.1.5.2.2-1.

Table 6.1.5.2.2-1: URI query parameters supported by the POST method

Name	Data type	Р	Cardinality	Description
n/a				

Support of request data structures is specified in table 6.1.5.2.2-2, and support of response data structures and response codes is specified in table 6.1.5.2-3.

Table 6.1.5.2.2-2: Data structures supported by the POST Request Body

Data type	Р	Cardinality	Description
NotificationData	М	1	Representation of the NF Instance status notification.

Table 6.1.5.2.2-3: Data structures supported by the POST Response Body

Data	type	Р	Cardinality	Response	Description	
				codes		
N/A				204 No	This case represents a successful notification of the NF	
				Content	Instance status event.	
NOTE: The mandatory HTTP error status codes for the PUT method listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [4]						
other than those specified in the table above also apply, with a ProblemDetails data type (see clause 5.2.7						
	of 3GPP TS 29.500 [4]).					

6.1.6 Data Model

6.1.6.1 General

This clause specifies the application data model supported by the API.

Table 6.1.6.1-1 specifies the data types defined for the Nnrf service based interface protocol.

Table 6.1.6.1-1: Nnrf_NFManagement specific Data Types

Data type	Clause defined	Description
NFProfile	6.1.6.2.2	
NFService	6.1.6.2.3	
DefaultNotificationSubscription	6.1.6.2.4	Data structure for specifying the notifications the NF service
		subscribes by default along with callback URI.
IpEndPoint	6.1.6.2.5	-
UdrInfo	6.1.6.2.6	
UdmInfo	6.1.6.2.7	
AusfInfo	6.1.6.2.8	
SupiRange	6.1.6.2.9	
IdentityRange	6.1.6.2.10	
AmfInfo	6.1.6.2.11	
SmfInfo	6.1.6.2.12	
UpfInfo	6.1.6.2.13	Information related to UPF
SnssaiUpfInfoItem	6.1.6.2.14	
DnnUpfInfoltem	6.1.6.2.15	
SubscriptionData	6.1.6.2.16	
NotificationData	6.1.6.2.17	
NFServiceVersion	6.1.6.2.19	Contains the version details of an NF service.
PcfInfo	6.1.6.2.20	
BsfInfo	6.1.6.2.21	
Ipv4AddressRange	6.1.6.2.22	
Ipv6PrefixRange	6.1.6.2.23	
InterfaceUpfInfoltem	6.1.6.2.24	
UriList	6.1.6.2.25	
N2InterfaceAmfInfo	6.1.6.2.26	AMF N2 interface information
TaiRange	6.1.6.2.27	
TacRange	6.1.6.2.28	
SnssaiSmfInfoltem	6.1.6.2.29	
DnnSmfInfoItem	6.1.6.2.30	
NrfInfo	6.1.6.2.31	
ChfInfo	6.1.6.2.32	
ChfServiceInfo	6.1.6.2.33	
PlmnRange	6.1.6.2.34	
SubscrCond	6.1.6.2.35	
NfInstanceIdCond	6.1.6.2.36	
NfTypeCond	6.1.6.2.37	
ServiceNameCond	6.1.6.2.38	
AmfCond	6.1.6.2.39	
GuamiListCond	6.1.6.2.40	
NetworkSliceCond	6.1.6.2.41	
NfGroupCond	6.1.6.2.42	
NotifCondition	6.1.6.2.43	
PlmnSnssai	6.1.6.2.44	
Fqdn	6.1.6.3.2	
NFType	6.1.6.3.3	
NotificationType	6.1.6.3.4	
TransportProtocol	6.1.6.3.5	
NotificationEventType	6.1.6.3.6	
NFStatus	6.1.6.3.7	
DataSetId	6.1.6.3.8	
UPInterfaceType	6.1.6.3.9	
ServiceName	6.1.6.3.11	
NFServiceStatus	6.1.6.3.12	

Table 6.1.6.1-2 specifies data types re-used by the Nnrf service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the Nnrf service based interface.

Table 6.1.6.1-2: Nnrf_NFManagement re-used Data Types

Data type	Reference	Comments
N1MessageClass	3GPP 29.518 [6]	The N1 message type
N2InformationClass	3GPP 29.518 [6]	The N2 information type
IPv4Addr	3GPP TS 29.571 [7]	
IPv6Addr	3GPP TS 29.571 [7]	
IPv6Prefix	3GPP TS 29.571 [7]	
Uri	3GPP TS 29.571 [7]	
Dnn	3GPP TS 29.571 [7]	
SupportedFeatures	3GPP TS 29.571 [7]	
Snssai	3GPP TS 29.571 [7]	
Plmnld	3GPP TS 29.571 [7]	
Guami	3GPP TS 29.571 [7]	
Tai	3GPP TS 29.571 [7]	
NfInstanceId	3GPP TS 29.571 [7]	
LinksValueSchema	3GPP TS 29.571 [7]	3GPP Hypermedia link
UriScheme	3GPP TS 29.571 [7]	
AmfName	3GPP TS 29.571 [7]	
DateTime	3GPP TS 29.571 [7]	
Dnai	3GPP TS 29.571 [7]	
Changeltem	3GPP TS 29.571 [7]	
DiameterIdentity	3GPP TS 29.571 [7]	
AccessType	3GPP TS 29.571 [7]	
NfGroupId	3GPP TS 29.571 [7]	Network Function Group Id
AmfRegionId	3GPP TS 29.571 [7]	
AmfSetId	3GPP TS 29.571 [7]	
PduSessionType	3GPP TS 29.571 [7]	

6.1.6.2 Structured data types

6.1.6.2.1 Introduction

This clause defines the structures to be used in resource representations.

6.1.6.2.2 Type: NFProfile

Table 6.1.6.2.2-1: Definition of type NFProfile

Attribute name	Data type	Р	Cardinality	Description
nfInstanceId	NfInstanceId	М	1	Unique identity of the NF Instance.
nfType	NFType	М	1	Type of Network Function
nfStatus	NFStatus	М	1	Status of the NF Instance (NOTE 5)
heartBeatTimer	integer	С	01	Time in seconds expected between 2 consecutive heart-beat messages from an NF Instance to the NRF. It may be included in the registration request. When present in the request it shall contain the heartbeat time proposed by the NF service consumer.
				It shall be included in responses from NRF to registration requests (PUT) or in NF profile updates (PUT or PATCH). If the proposed heartbeat time is acceptable by the NRF based on the local configuration, it shall use the same value as in the registration request; otherwise the NRF shall override the value using a preconfigured value.
plmnList	array(Plmnld)	С	1N	PLMN(s) of the Network Function (NOTE 7). This IE shall be present if this information is available for the NF. If not provided, PLMN ID(s) of the PLMN of the NRF are assumed for the NF.
sNssais	array(Snssai)	0	1N	S-NSSAIs of the Network Function. If not provided, the NF can serve any S-NSSAI. When present this IE represents the list of S-NSSAIs supported in all the PLMNs listed in the plmnList IE. (NOTE 11)
perPlmnSnssaiList	array(PlmnSnssai)	0	1N	This IE may be included when the list of S-NSSAIs supported by the NF for each PLMN it is supporting is different. When present, this IE shall include the S-NSSAIs supported by the Network Function for each PLMN supported by the Network Function. When present, this IE shall override sNssais IE. (NOTE 9) (NOTE 11)
nsiList	array(string)	0	1N	NSI identities of the Network Function. If not provided, the NF can serve any NSI.
fqdn	Fqdn	С	01	FQDN of the Network Function (NOTE 1) (NOTE 2). For AMF, the FQDN registered with the NRF shall be that of the AMF Name (see 3GPP 23.003 [12] clause 28.3.2.5).
interPlmnFqdn	Fqdn	С	01	If the NF needs to be discoverable by other NFs in a different PLMN, then an FQDN that is used for inter-PLMN routing as specified in 3GPP 23.003 [12] shall be registered with the NRF (NOTE 8).
				A change of this attribute shall result in triggering a "NF_PROFILE_CHANGED" notification from NRF towards subscribing NFs located in a different PLMN, but the new value shall be notified as a change of the "fqdn" attribute.
ipv4Addresses	array(Ipv4Addr)	С	1N	IPv4 address(es) of the Network Function (NOTE 1) (NOTE 2)
ipv6Addresses	array(Ipv6Addr)	С	1N	IPv6 address(es) of the Network Function (NOTE 1) (NOTE 2)
allowedPlmns	array(Plmnld)	0	1N	PLMNs allowed to access the NF instance. If not provided, any PLMN is allowed to access the NF.
				A change of this attribute shall not trigger a "NF_PROFILE_CHANGED" notification from NRF, and this attribute shall not be included in profile change notifications to subscribed NFs.

Г 			1	<u> </u>
allowedNfTypes	array(NFType)	0	1N	Type of the NFs allowed to access the NF instance.
				If not provided, any NF type is allowed to access the NF.
				A change of this attribute shall not trigger a
				"NF_PROFILE_CHANGED" notification from NRF,
				and this attribute shall not be included in profile
				change notifications to subscribed NFs.
allowedNfDomains	array(string)	0	1N	Pattern (regular expression according to the ECMA-
				262 dialect [8]) representing the NF domain names
				allowed to access the NF instance.
				If not provided, any NF domain is allowed to access
				the NF.
				A change of this attribute shall not trigger a
				"NF_PROFILE_CHANGED" notification from NRF,
				and this attribute shall not be included in profile
	(0 ")		4 11	change notifications to subscribed NFs.
allowedNssais	array(Snssai)	0	1N	S-NSSAI of the allowed slices to access the NF
				instance. If not provided, any slice is allowed to access the
				NF.
				A sharp of this attains to shall not trigger
				A change of this attribute shall not trigger a "NF_PROFILE_CHANGED" notification from NRF,
				and this attribute shall not be included in profile
				change notifications to subscribed NFs.
priority	integer	0	01	Priority (relative to other NFs of the same type) in the
priority	lintogor		01	range of 0-65535, to be used for NF selection; lower
				values indicate a higher priority. If priority is also
				present in the nfServiceList parameters, those will
				have precedence over this value. (NOTE 4).
				The NRF may overwrite the received priority value
				when exposing an NFProfile with the
	:		0.4	Nnrf_NFDiscovery service.
capacity	integer	0	01	Static capacity information in the range of 0-65535,
				expressed as a weight relative to other NF instances of the same type; if capacity is also present in the
				infServiceList parameters, those will have
				precedence over this value. (NOTE 4).
load	integer	0	01	Dynamic load information, ranged from 0 to 100,
				indicates the current load percentage of the NF.
locality	string	0	01	Operator defined information about the location of
				the NF instance (e.g. geographic location, data center) (NOTE 3)
udrInfo	UdrInfo	0	01	Specific data for the UDR (ranges of SUPI, group ID
			0.4)
udmInfo	UdmInfo	0	01	Specific data for the UDM (ranges of SUPI, group ID)
ausfInfo	AusfInfo	0	01	Specific data for the AUSF (ranges of SUPI, group
amfInfo	Amfinfo		0.1	ID)
smfInfo	AmfInfo SmfInfo	0	01	Specific data for the AMF (AMF Set ID,) Specific data for the SMF (DNN's,)
upfInfo	UpfInfo	0	01	Specific data for the SMF (DNN's,) Specific data for the UPF (S-NSSAI, DNN, SMF
•	·			serving area, interface)
pcfInfo	PcfInfo	0	01	Specific data for the PCF
bsfInfo	BsfInfo	0	01	Specific data for the BSF
chfInfo	ChfInfo	0	01	Specific data for the CHF
nrfInfo	NrfInfo	0	01	Specific data for the NRF
customInfo	object	0	01	Specific data for custom Network Functions
recoveryTime	DateTime	0	01	Timestamp when the NF was (re)started (NOTE 5) (NOTE 6)
			1	[(INOTE 0)

nfServicePersistence	boolean	0	01	If present, and set to true, it indicates that the different service instances of a same NF Service in this NF instance, supporting a same API version, are capable to persist their resource state in shared storage and therefore these resources are available after a new NF service instance supporting the same API version is selected by a NF Service Consumer (see 3GPP 23.527 [27]). Otherwise, it indicates that the NF Service Instances of a same NF Service are not capable to share resource state inside the NF Instance.
nfServices	array(NFService)	0	1N	List of NF Service Instances. It shall include the services produced by the NF that can be discovered by other NFs, if any. (NOTE 11)
nfProfileChangesSuppo rtInd	boolean	0	01	NF Profile Changes Support Indicator. See Annex B. This IE may be present in the NFRegister or NFUpdate (NF Profile Complete Replacement) request and shall be absent in the response. true: the NF Service Consumer supports receiving NF Profile Changes in the response. false (default): the NF Service Consumer does not support receiving NF Profile Changes in the response. Write-Only: true
nfProfileChangesInd	boolean	0	01	NF Profile Changes Indicator. See Annex B. This IE shall be absent in the request to the NRF and may be included by the NRF in NFRegister or NFUpdate (NF Profile Complete Replacement) response. true: the NF Profile contains NF Profile changes. false (default): complete NF Profile. Read-Only: true
defaultNotificationSubsc riptions	array(DefaultNotif icationSubscriptio n)	0	1N	Notification endpoints for different notification types. (NOTE 10)

- NOTE 1: At least one of the addressing parameters (fqdn, ipv4address or ipv6adress) shall be included in the NF Profile. If the NF supports the NF services with "https" URI scheme (i.e use of TLS is mandatory), then the FQDN shall be provided in the NF Profile or the NF Service profile (see clause 6.1.6.2.3). See NOTE 1 of Table 6.1.6.2.3-1 for the use of these parameters. If multiple ipv4 addresses and/or ipv6 addresses are included in the NF Profile, the NF Service Consumer of the discovery service shall select one of these addresses randomly, unless operator defined local policy of IP address selection, in order to avoid overload for a specific ipv4 address and/or ipv6 address.
- NOTE 2: If the type of Network Function is UPF, the addressing information is for the UPF N4 interface.
- NOTE 3: A requester NF may use this information to select a NF instance (e.g. a NF instance preferably located in the same data center).
- NOTE 4: The capacity and priority parameters, if present, are used for NF selection and load balancing. The priority and capacity attributes shall be used for NF selection in the same way that priority and weight are used for server selection as defined in IETF RFC 2782 [23].
- NOTE 5: The NRF shall notify NFs subscribed to receiving notifications of changes of the NF profile, if the NF recoveryTime or the nfStatus is changed. See clause 6.2 of 3GPP 23.527 [27].
- NOTE 6: A requester NF may consider that all the resources created in the NF before the NF recovery time have been lost. This may be used to detect a restart of a NF and to trigger appropriate actions, e.g. release local resources. See clause 6.2 of 3GPP 23.527 [27].
- NOTE 7: A NF may register multiple PLMN IDs in its profile within a PLMN comprising multiple PLMN IDs. If so, all the attributes of the NF Profile shall apply to each PLMN ID registered in the plmnList. As an exception, attributes including a PLMN ID, e.g. IMSI-based SUPI ranges, TAIs and GUAMIs, are specific to one PLMN ID and the NF may register in its profile multiple occurrences of such attributes for different PLMN IDs (e.g. the UDM may register in its profile SUPI ranges for different PLMN IDs).
- NOTE 8: Other NFs are in a different PLMN if they belong to none of the PLMN ID(s) configured for the PLMN of the NRF.
- NOTE 9: This is for the use case where an NF (e.g. AMF) supports multiple PLMNs and the slices supported in each PLMN are different. See clause 9.2.6.2 of 3GPP TS 38.413 [29].
- NOTE 10: If notification endpoints are present both in the profile of the NF instance (NFProfile) and in some of its NF Services (NFService) for a same notification type, the notification endpoint(s) of the NF Services shall be used for this notification type.
- NOTE 11: If a change of this attribute triggers a notification from NRF of type "NF_PROFILE_CHANGED", and the changed data is sent as a set of incremental changes of the NFProfile (i.e. as a list of "Changeltem", see clause 6.1.6.2.17), those changes shall be sent as a complete replacement of the entire array attribute, and not as individual changes of specific array elements).

6.1.6.2.3 Type: NFService

Table 6.1.6.2.3-1: Definition of type NFService

Attribute name	Data type	Р	Cardinality	Description
serviceInstanceId	string	М	1	Unique ID of the service instance within a given NF Instance
serviceName	ServiceName	М	1	Name of the service instance (e.g. "nudm-sdm")
versions	array(NFService Version)	M	1N	The API versions supported by the NF Service and if available, the corresponding retirement date of the NF Service. The different array elements shall have distinct unique values for "apiVersionInUri", and consequently, the values of "apiFullVersion" shall have a unique first digit version number.
scheme	UriScheme	М	1	URI scheme (e.g. "http", "https")
nfServiceStatus	NFServiceStatus	М	1	Status of the NF Service Instance (NOTE 3)
fqdn	Fqdn	0	01	FQDN of the NF Service Instance (NOTE 1) (NOTE 8)
interPlmnFqdn	Fqdn	0	01	If the NF service needs to be discoverable by other NFs in a different PLMN, then an FQDN that is used for inter PLMN routing as specified in 3GPP 23.003 [12] may be registered with the NRF (NOTE 1) (NOTE 6). A change of this attribute shall result in triggering a
				"NF_PROFILE_CHANGED" notification from NRF towards subscribing NFs located in a different PLMN, but the new value shall be notified as a change of the "fqdn" attribute.
ipEndPoints	array(IpEndPoint)	0	1N	IP address(es) and port information of the Network Function (including IPv4 and/or IPv6 address) where the service is listening for incoming service requests (NOTE 1) (NOTE 7).
apiPrefix	string	0	01	Optional path segment(s) used to construct the {apiRoot} variable of the different API URIs, as described in 3GPP 29.501 [5], clause 4.4.1
defaultNotificationSubsc riptions	array(DefaultNotif icationSubscription)	0	1N	Notification endpoints for different notification types.
allowedPlmns	array(Plmnld)	0	1N	PLMNs allowed to access the service instance (NOTE 5).
				The absence of this attribute indicates that any PLMN is allowed to access the service instance.
				When included, the allowedPlmns attribute needs not include the PLMN ID(s) registered in the plmnList attribute of the NF Profile, i.e. the PLMN ID(s) registered in the NF Profile shall be considered to be allowed to access the service instance.
				A change of this attribute shall not trigger a "NF_PROFILE_CHANGED" notification from NRF, and this attribute shall not be included in profile change notifications to subscribed NFs.
allowedNfTypes	array(NFType)	0	1N	Type of the NFs allowed to access the service instance (NOTE 5).
				The absence of this attribute indicates that any NF type is allowed to access the service instance.
				A change of this attribute shall not trigger a "NF_PROFILE_CHANGED" notification from NRF, and this attribute shall not be included in profile change notifications to subscribed NFs.

allowedNfDomains	array(string)	0	1N	Pattern (regular expression according to the ECMA- 262 dialect [8]) representing the NF domain names allowed to access the service instance (NOTE 5). The absence of this attribute indicates that any NF domain is allowed to access the service instance. A change of this attribute shall not trigger a "NF_PROFILE_CHANGED" notification from NRF, and this attribute shall not be included in profile change notifications to subscribed NFs.
allowedNssais	array(Snssai)	0	1N	S-NSSAI of the allowed slices to access the service instance (NOTE 5). The absence of this attribute indicates that any slice is allowed to access the service instance. A change of this attribute shall not trigger a "NF_PROFILE_CHANGED" notification from NRF, and this attribute shall not be included in profile change notifications to subscribed NFs.
priority	integer	0	01	Priority (relative to other services of the same type) in the range of 0-65535, to be used for NF Service selection; lower values indicate a higher priority. (NOTE 2). The NRF may overwrite the received priority value when exposing an NFProfile with the Nnrf_NFDiscovery service.
capacity	integer	0	01	Static capacity information in the range of 0-65535, expressed as a weight relative to other services of the same type. (NOTE 2).
load	integer	0	01	Dynamic load information, ranged from 0 to 100, indicates the current load percentage of the NF Service.
recoveryTime	DateTime	0	01	Timestamp when the NF service was (re)started (NOTE 3) (NOTE 4)
chfServiceInfo	ChfServiceInfo	0	01	Specific data for a CHF service instance
supportedFeatures	SupportedFeatur es	0	01	Supported Features of the NF Service instance

- NOTE 1: The NF Service Consumer will construct the API URIs of the service using:
 - for intra-PLMN signalling: the FQDN and IP addresses related attributes present in the NF Service Profile, if any, otherwise the FQDN and IP addresses related attributes present in the NF Profile.
 - for inter-PLMN signalling: the interPlmnFqdn present in the NF Service Profile, if any, otherwise the interPlmnFqdn present in the NF Profile. See Table 6.2.6.2.4-1.
- NOTE 2: The capacity and priority parameters, if present, are used for NF selection and load balancing. The priority and capacity attributes shall be used for NF selection in the same way that priority and weight are used for server selection as defined in IETF RFC 2782 [23].
- NOTE 3: The NRF shall notify NFs subscribed to receiving notifications of changes of the NF profile, if the recoveryTime or the nfServiceStatus is changed. See clause 6.2 of 3GPP 23.527 [27].
- NOTE 4: A requester NF subscribed to NF status changes may consider that all the resources created in the NF service before the NF service recovery time have been lost. This may be used to detect a restart of a NF service and to trigger appropriate actions, e.g. release local resources. See clause 6.2 of 3GPP 23.527 [27].
- NOTE 5: If this attribute is present in the NFService and in the NF profile, the attribute from the NFService shall prevail. The absence of this attribute in the NFService and in the NFProfile indicates that there is no corresponding restriction to access the service instance. If this attribute is absent in the NF Service, but it is present in the NF Profile, the attribute from the NF Profile shall be applied.
- NOTE 6: Other NFs are in a different PLMN if they belong to none of the PLMN ID(s) configured for the PLMN of the
- NOTE 7: If multiple ipv4 addresses and/or ipv6 addresses are included in the NF Service, the NF Service Consumer of the discovery service shall select one of these addresses randomly, unless operator defined local policy of IP address selection, in order to avoid overload for a specific ipv4 address and/or ipv6 address.
- NOTE 8: If the URI scheme registered for the NF service is "https" then FQDN shall be provided in the NF Service profile or in NF Profile (see clause 6.1.6.2.2).

6.1.6.2.4 Type: DefaultNotificationSubscription

Table 6.1.6.2.4-1: Definition of type DefaultNotificationSubscription

Attribute name	Data type	Р	Cardinality	Description
notificationType	NotificationType	М	1	Type of notification for which the corresponding
				callback URI is provided.
callbackUri	Uri	M	1	The callback URI.
n1MessageClass	N1MessageClass	С	01	If the notification type is N1_MESSAGES, this IE shall be present and shall identify the class of N1 messages to be notified.
n2InformationClass	N2InformationCla ss	С	01	If the notification type is N2_INFORMATION, this IE shall be present and shall identify the class of N2 information to be notified.

6.1.6.2.5 Type: IpEndPoint

Table 6.1.6.2.5-1: Definition of type IpEndPoint

Attribute name	Data type	Р	Cardinality	Description
ipv4Address	Ipv4Addr	C	01	IPv4 address (NOTE 1)
ipv6Address	lpv6Addr	С	01	IPv6 address (NOTE 1)
transport	TransportProtocol	0	01	Transport protocol
port	integer	0	01	Port number (NOTE 2)

NOTE 1: At most one occurrence of either ipv4Address or ipv6Address shall be included in this data structure.

NOTE 2: If the port number is absent from the ipEndPoints attribute, the NF service consumer shall use the default HTTP port number, i.e. TCP port 80 for "http" URIs or TCP port 443 for "https" URIs as specified in IETF RFC 7540 [9] when invoking the service.

6.1.6.2.6 Type: UdrInfo

Table 6.1.6.2.6-1: Definition of type UdrInfo

Attribute name	Data type	Р	Cardinality	Description
groupId	NfGroupId	0	01	Identity of the UDR group that is served by the UDR instance. If not provided, the UDR instance does not pertain to any UDR group. (NOTE 1)
supiRanges	array(SupiRange)	0	1N	List of ranges of SUPI's whose profile data is available in the UDR instance (NOTE 1)
gpsiRanges	array(IdentityRan ge)	0	1N	List of ranges of GPSIs whose profile data is available in the UDR instance (NOTE 1)
externalGroupIdentifiers Ranges	array(IdentityRan ge)	0	1N	List of ranges of external groups whose profile data is available in the UDR instance (NOTE 1)
supportedDataSets	array(DataSetId)	0	1N	List of supported data sets in the UDR instance. If not provided, the UDR supports all data sets.

NOTE 1: If none of these parameters are provided, the UDR can serve any external group and any SUPI or GPSI managed by the PLMN of the UDR instance. If "supiRanges", "gpsiRanges" and "externalGroupIdentifiersRanges" attributes are absent, and "groupId" is present, the SUPIs / ExternalGroups served by this UDR instance is determined by the NRF (see 3GPP TS 23.501 [2], clause 6.2.6.2).

6.1.6.2.7 Type: UdmInfo

Table 6.1.6.2.7-1: Definition of type UdmInfo

Attribute name	Data type	Р	Cardinality	Description
groupId	NfGroupId	0	01	Identity of the UDM group that is served by the UDM
				instance.
				If not provided, the UDM instance does not pertain to
				any UDM group.
				(NOTE 1)
supiRanges	array(SupiRange)	0	1N	List of ranges of SUPIs whose profile data is
				available in the UDM instance (NOTE 1)
gpsiRanges	array(IdentityRan	0	1N	List of ranges of GPSIs whose profile data is
	ge)			available in the UDM instance (NOTE 1)
externalGroupIdentifiers	array(IdentityRan	0	1N	List of ranges of external groups whose profile data
Ranges	ge)			is available in the UDM instance (NOTE 1)
routingIndicators	array(string)	0	1N	List of Routing Indicator information that allows to
				route network signalling with SUCI (see
				3GPP 23.003 [12]) to the UDM instance.
				If not provided, the UDM can serve any Routing
				Indicator.
				Pattern: '^[0-9]{1,4}\$'

NOTE 1: If none of these parameters are provided, the UDM can serve any external group and any SUPI or GPSI managed by the PLMN of the UDM instance. If "supiRanges", "gpsiRanges" and "externalGroupIdentifiersRanges" attributes are absent, and "groupId" is present, the SUPIs / GPSIs / ExternalGroups served by this UDM instance is determined by the NRF (see 3GPP TS 23.501 [2], clause 6.2.6.2).

6.1.6.2.8 Type: AusfInfo

Table 6.1.6.2.8-1: Definition of type AusfInfo

Attribute name	Data type	Р	Cardinality	Description	
groupId	NfGroupId	0	01	Identity of the AUSF group. If not provided, the AUSF instance does not pertain to any AUSF group. (NOTE)	
supiRanges	array(SupiRange)	0	1N	List of ranges of SUPIs that can be served by the AUSF instance. (NOTE)	
routingIndicators	array(string) O 1N List of Routing Indicator information that allows to route network signalling with SUCI (see 3GPP 23.003 [12]) to the AUSF instance. If not provided, the AUSF can serve any Routing Indicator. Pattern: '\[\frac{1}{9} - 9\] \{1,4\}\\$'				
NOTE: If none of these parameters are provided, the AUSF can serve any SUPI managed by the PLMN of the AUSF instance. If "supiRanges" attribute is absent, and "groupId" is present, the SUPIs served by this AUSF instance is determined by the NRF (see 3GPP TS 23.501 [2], clause 6.2.6.2).					

6.1.6.2.9 Type: SupiRange

Table 6.1.6.2.9-1: Definition of type SupiRange

Attribute name	Data type	Р	Cardinality	Description
start	string	0	01	First value identifying the start of a SUPI range, to be used when the range of SUPI's can be represented as a numeric range (e.g., IMSI ranges). This string shall consist only of digits. Pattern: "\[0-9]+\$"
end	string	0	01	Last value identifying the end of a SUPI range, to be used when the range of SUPI's can be represented as a numeric range (e.g. IMSI ranges). This string shall consist only of digits. Pattern: "^[0-9]+\$"
pattern	string	0	01	Pattern (regular expression according to the ECMA-262 dialect [8]) representing the set of SUPI's belonging to this range. A SUPI value is considered part of the range if and only if the SUPI string fully matches the regular expression.
NOTE: Either the start	and end attributes.	or the	e pattern attrib	belonging to this range. A SUP part of the range if and only if the

EXAMPLE 1: IMSI range. From: 123 45 6789040000 To: 123 45 6789059999 (i.e., 20,000 IMSI numbers)

JSON: { "start": "123456789040000", "end": "123456789059999" }

IMSI range. From: 123 45 6789040000 To: 123 45 6789049999 (i.e., 10,000 IMSI numbers) EXAMPLE 2:

JSON: { "pattern": "^imsi-12345678904[0-9]{4}\$" }, or JSON: { "start": "123456789040000", "end": "123456789049999" }

NAI range. "smartmeter-{factoryID}@company.com" where "{factoryID}" can be any string. EXAMPLE 3:

JSON: { "pattern": "^nai-smartmeter-.+@company\.com\$" }

6.1.6.2.10 Type: IdentityRange

Table 6.1.6.2.10-1: Definition of type IdentityRange

Attribute name	Data type	P	Cardinality	Description
start	string	0	01	First value identifying the start of an identity range, to be used when the range of identities can be represented as a numeric range (e.g., MSISDN ranges). This string shall consist only of digits. Pattern: "^[0-9]+\$"
end	string	0	01	Last value identifying the end of an identity range, to be used when the range of identities can be represented as a numeric range (e.g. MSISDN ranges). This string shall consist only of digits. Pattern: "^[0-9]+\$"
pattern	String	0	01	Pattern (regular expression according to the ECMA-262 dialect [8]) representing the set of identities belonging to this range. An identity value is considered part of the range if and only if the identity string fully matches the regular expression. To be used when identity is External Identifier or External Group Identifier or MSISDN.
NOTE: Either the st	art and end attributes	s, or th	e pattern attrik	oute, shall be present.

6.1.6.2.11 Type: AmfInfo

Table 6.1.6.2.11-1: Definition of type AmfInfo

Attribute name	Data type	Р	Cardinality	Description
amfRegionId	AmfRegionId	М	1	AMF region identifier
amfSetId	AmfSetId	М	1	AMF set identifier.
guamiList	array(Guami)	Μ	1N	List of supported GUAMIs
taiList	array(Tai)	0	1N	The list of TAIs the AMF can serve. It may contain the non-3GPP access TAI. The absence of this attribute and the taiRangeList attribute indicate that the AMF can be selected for any TAI in the serving network.
taiRangeList	array(TaiRange)	0	1N	The range of TAIs the AMF can serve. The absence of this attribute and the taiList attribute indicate that the AMF can be selected for any TAI in the serving network.
backupInfoAmfFailure	array(Guami)	0	1N	List of GUAMIs for which the AMF acts as a backup for AMF failure
backupInfoAmfRemoval	array(Guami)	0	1N	List of GUAMIs for which the AMF acts as a backup for planned AMF removal
n2InterfaceAmfInfo	N2InterfaceAmfIn fo	0	01	N2 interface information of the AMF. This information needs not be sent in NF Discovery responses. It may be used by the NRF to update the DNS for AMF discovery by the 5G Access Network. The procedures for updating the DNS are out of scope of this specification.

6.1.6.2.12 Type: SmfInfo

Table 6.1.6.2.12-1: Definition of type SmfInfo

Attribute name	Data type	Р	Cardinality	Description
sNssaiSmfInfoList	array(sNssaiSmfl nfoltem)	М	1N	List of parameters supported by the SMF per S-NSSAI.
taiList	array(Tai)	0	1N	The list of TAIs the SMF can serve. It may contain the non-3GPP access TAI. The absence of this attribute and the taiRangeList attribute indicate that the SMF can be selected for any TAI in the serving network.
taiRangeList	array(TaiRange)	0	1N	The range of TAIs the SMF can serve. It may contain the non-3GPP access' TAI. The absence of this attribute and the taiList attribute indicate that the SMF can be selected for any TAI in the serving network.
pgwFqdn	Fqdn	0	01	The FQDN of the PGW if the SMF is a combined SMF/PGW-C.
accessType	array(AccessTyp e)	С	12	If included, this IE shall contain the access type (3GPP_ACCESS and/or NON_3GPP_ACCESS) supported by the SMF. If not included, it shall be assumed the both access types are supported.

6.1.6.2.13 Type: UpfInfo

Table 6.1.6.2.13-1: Definition of type UpfInfo

Attribute name	Data type	Р	Cardinality	Description
sNssaiUpfInfoList	array(SnssaiUpfI nfoltem)	М	1N	List of parameters supported by the UPF per S-NSSAI
smfServingArea	array(string)	0	1N	The SMF service area(s) the UPF can serve. If not provided, the UPF can serve any SMF service area.
interfaceUpfInfoList	array(InterfaceUp fInfoltem)	0	1N	List of User Plane interfaces configured on the UPF. When this IE is provided in the NF Discovery response, the NF Service Consumer (e.g. SMF) may use this information for UPF selection.
iwkEpsInd	boolean	0	01	Indicates whether interworking with EPS is supported by the UPF. true: Supported false (default): Not Supported
pduSessionTypes	array(PduSessio nType)	0	1N	List of PDU session type(s) supported by the UPF. The absence of this attribute indicates that the UPF can be selected for any PDU session type.

6.1.6.2.14 Type: SnssaiUpfInfoItem

Table 6.1.6.2.14-1: Definition of type SnssaiUpfInfoltem

Attribute name	Data type	Р	Cardinality	Description
sNssai	Snssai	М	1	Supported S-NSSAI
dnnUpfInfoList	array(DnnUpfInfo Item)	М	1N	List of parameters supported by the UPF per DNN

6.1.6.2.15 Type: DnnUpfInfoItem

Table 6.1.6.2.15-1: Definition of type DnnUpfInfoltem

Attribute name	Data type	Р	Cardinality	Description
dnn	Dnn	М	1	Supported DNN
dnaiList	array(Dnai)	0	1N	List of Data network access identifiers supported by the UPF for this DNN. The absence of this attribute indicates that the UPF can be selected for this DNN for any DNAI.
pduSessionTypes	array(PduSessio nType)	0	1N	List of PDU session type(s) supported by the UPF for a specific DNN. The absence of this attribute indicates that the UPF can be selected for this DNN for any PDU session type supported by the UPF (see clause 6.1.6.2.13).
ipv4AddressRanges	array(Ipv4Addres sRange)	0	1N	List of ranges of static IPv4 addresses handled by UPF.
ipv6PrefixRanges	array(Ipv6PrefixR ange)	0	1N	List of ranges of static IPv6 prefixes handled by the UPF.

6.1.6.2.16 Type: SubscriptionData

Table 6.1.6.2.16-1: Definition of type SubscriptionData

Attribute name	Data type	Р	Cardinality	Description
nfStatusNotificationUri	Uri	М	1	Callback URI where the NF Service Consumer will receive the notifications from NRF.
subscrCond	SubscrCond	0	01	If present, this attributed shall contain the conditions identifying the set of NF Instances whose status is requested to be monitored. If this attribute is not present, it means that the NF Service Consumer requests a subscription to all NFs in the NRF (NOTE 1).
subscriptionId	string	С	01	Subscription ID for the newly created resource. This parameter shall be absent in the request to the NRF and shall be included by NRF in the response to the subscription creation request. Read-Only: true
validityTime	DateTime	С	01	Time instant after which the subscription becomes invalid. This parameter may be sent by the client, as a hint to the server, but it shall be always sent back by the server (regardless of the presence of the attribute in the request) in the response to the subscription creation request.
reqNotifEvents	array(Notification EventType)	0	1N	If present, this attribute shall contain the list of event types that the NF Service Consumer is interested in receiving. If this attribute is not present, it means that
reqNfType	NFType	0	01	notifications for all event types are requested. If included, this IE shall contain the NF type of the NF Service Consumer that is requesting the creation of the subscription. The NRF shall use it for authorizing the request, in the same way as the "requester-nf-type" is used in the NF Discovery service (see Table 6.2.3.2.3.1-1).
				When the subscription is for a set of NF Instances, the subscription may be accepted by NRF, but it shall only generate notifications from NF Instances whose authorization parameters allow the NF Service Consumer to access their services (NOTE 2).
reqNfFqdn	Fqdn	0	01	If included, this IE shall contain the FQDN of the NF Service Consumer that is requesting the creation of the subscription. The NRF shall use it for authorizing the request, in the same way as the "requester-nf-instance-fqdn" is used in the NF Discovery service (see Table 6.2.3.2.3.1-1).
				When the subscription is for a set of NF Instances, the subscription may be accepted by NRF, but it shall only generate notifications from NF Instances whose authorization parameters allow the NF Service Consumer to access their services (NOTE 2).
reqSnssais	array(Snssai)	0	01	If included, this IE shall contain the list of S-NSSAIs of the NF Service Consumer that is requesting the creation of the subscription. The NRF shall use it for authorizing the request, in the same way as the "requester-snssais" is used in the NF Discovery service (see Table 6.2.3.2.3.1-1).
				When the subscription is for a set of NF Instances, the subscription may be accepted by NRF, but it shall only generate notifications from NF Instances whose authorization parameters allow the NF Service Consumer to access their services (NOTE 2).
plmnld	Plmnld	0	01	If present, this attribute contains the target PLMN ID of the NF Instance(s) whose status is requested to be monitored.

notifCondition	NotifCondition	0	01	If present, this attribute contains the conditions that trigger a notification from NRF; this attribute shall only be present if the NF Service Consumer has subscribed to changes on the NF Profile (i.e., regNotifEvents contains the value
				"NF_PROFILE_CHANGED", or reqNotifEvents attribute is absent).
				If this attribute is absent, it means that the NF Service Consumer does not indicate any restriction, or condition, on which attributes of the NF Profile
				shall trigger a notification from NRF. (NOTE 3).

- NOTE 1: The "subscription to all NFs" may be quite demanding in terms of resources in NRF and also in terms of network traffic of the resulting notifications, so it should be authorized by NRF under very strict policies (e.g. only to a specific requesting NF, as indicated by reqNfType and reqNfFqdn attributes).
- NOTE 2: The authorization parameters in NF Profile are those used by NRF to determine whether a given NF Instance / NF Service Instance can be discovered by an NF Service Consumer in order to consume its offered services (e.g. "allowedNfTypes", "allowedNfDomains", etc.).
- NOTE 3: If the attributes to be monitored or excluded from monitoring, included as part of the "notifCondition" attribute, refer to a specific element of an array (e.g. they refer to a specific array index of the "nfServices" attribute of the NFProfile), the NRF shall apply the same condition to all elements of the same array.

6.1.6.2.17 Type: NotificationData

Table 6.1.6.2.17-1: Definition of type NotificationData

Attribute name	Data type	Р	Cardinality	Description
event	NotificationEventType	М	1	Notification type. It shall take the values "NF_REGISTERED", "NF_DEREGISTERED" OR "NF_PROFILE_CHANGED".
nfInstanceUri	Uri	М	1	Uri of the NF Instance (see clause 6.1.3.3.2) associated to the notification event.
nfProfile	NFProfile	С	01	New NF Profile or Updated NF Profile; it shall be present when the notification type is "NF_REGISTERED" or "NF_PROFILE_CHANGED".
profileChanges	array(Changeltem)	С	1N	List of changes on the profile of the NF Instance associated to the notification event; it may be present when the notification type is "NF_PROFILE_CHANGED" (see NOTE 1, NOTE 2).

- NOTE 1: If "event" attribute takes the value "NF_PROFILE_CHANGED", then either "nfProfile" or "profileChanges" attributes shall be present, but not both.
- NOTE 2: For those array attributes explicitly indicated in the NFProfile data type definition (see clause 6.1.6.2.2), the NRF shall notify about NF Profile changes affecting those attributes as a complete replacement of the whole array (i.e. it shall not notify about changes of individual array elements).

EXAMPLE: Notification payload sent from NRF when an NF Instance has changed its profile by updating the value of the "recoveryTime" attribute of its NF Profile, and updated any attribute of any of its NF Service Instances:

6.1.6.2.18 Void

6.1.6.2.19 Type: NFServiceVersion

Table 6.1.6.2.19-1: Definition of type NFServiceVersion

Attribute name	Data type	Р	Cardinality	Description
apiVersionInUri	string	M	1	Version of the service instance to be used in the
				URI for accessing the API (e.g. "v1").
apiFullVersion	string	M	1	Full version number of the API as specified in
				clause 4.3.1 of 3GPP 29.501 [5].
expiry	DateTime	0	01	Expiry date and time of the NF service. This
				represents the planned retirement date as
				specified in clause 4.3.1.5 of 3GPP 29.501 [5].

6.1.6.2.20 Type: PcfInfo

Table 6.1.6.2.20-1: Definition of type PcfInfo

Attribute name	Data type	Р	Cardinality	Description
dnnList	array(Dnn)	0	1N	DNNs supported by the PCF.
				If not provided, the PCF can serve any DNN.
supiRanges	array(SupiRange)	0	1N	List of ranges of SUPIs that can be served by the
				PCF instance. If not provided, the PCF can serve
				any SUPI.
rxDiamHost	DiameterIdentity	С	01	This IE shall be present if the PCF supports Rx
				interface.
				When present, this IE shall indicate the Diameter
				host of the Rx interface for the PCF.
rxDiamRealm	DiameterIdentity	С	01	This IE shall be present if the PCF supports Rx
				interface.
				When present, this IE shall indicate the Diameter
				realm of the Rx interface for the PCF.

6.1.6.2.21 Type: BsfInfo

Table 6.1.6.2.21-1: Definition of type BsfInfo

Attribute name	Data type	Р	Cardinality	Description
ipv4AddressRanges	array(Ipv4Addres	0	1N	List of ranges of IPv4 addresses handled by BSF.
	sRange)			If not provided, the BSF can serve any IPv4 address.
dnnList	array(Dnn)	0	1N	List of DNNs handled by the BSF
				If not provided, the BSF can serve any DNN.
ipDomainList	array(string)	0	1N	List of IPv4 address domains, as described in clause
				6.2 of 3GPP 29.513 [28], handled by the BSF.
				If not provided, the BSF can serve any IP domain.
ipv6PrefixRanges	array(Ipv6PrefixR	0	1N	List of ranges of IPv6 prefixes handled by the BSF.
	ange)			If not provided, the BSF can serve any IPv6 prefix.

6.1.6.2.22 Type: Ipv4AddressRange

Table 6.1.6.2.22-1: Definition of type IPv4AddressRange

Attribute name	Data type	Р	Cardinality	Description
start	lpv4Addr	М	1	First value identifying the start of an IPv4 address
				range
end	lpv4Addr	M	1	Last value identifying the end of an IPv4 address
				range

6.1.6.2.23 Type: Ipv6PrefixRange

Table 6.1.6.2.23-1: Definition of type IPv6PrefixRange

Attribute name	Data type	Р	Cardinality	Description
start	Ipv6Prefix	М	1	First value identifying the start of an IPv6 prefix
				range
end	Ipv6Prefix	М	1	Last value identifying the end of an IPv6 prefix range

6.1.6.2.24 Type: InterfaceUpfInfoltem

Table 6.1.6.2.24-1: Definition of type InterfaceUpfInfoltem

Attribute name	Data type	Р	Cardinality	Description	
interfaceType	UPInterfaceType	М	1	User Plane interface type	
ipv4EndpointAddresses	array(Ipv4Addr)	С	1N	Available endpoint IPv4 address(es) of the User Plane interface (NOTE 1)	
ipv6EndpointAddresses	array(Ipv6Addr)	С	1N	Available endpoint IPv6 address(es) of the User Plane interface (NOTE 1)	
endpointFqdn	Fqdn	С	01	FQDN of available endpoint of the User Plane interface (NOTE 1)	
networkInstance string O 01 Network Instance (See 3GPP 29.244 [21]) associated to the User Plane interface					
NOTE 1: At least one of the addressing parameters (ipv4address, ipv6adress or endpointFqdn) shall be included in					

the InterfaceUpfInfoltem.

6.1.6.2.25 Type: UriList

Table 6.1.6.2.25-1: Definition of type UriList

Attribute name	Data type	Р	Cardinality	Description
_links	map(LinksValueS	0	1N	See clause 4.9.4 of 3GPP TS 29.501 [5] for the
	chema)			description of the members.

6.1.6.2.26 Type: N2InterfaceAmfInfo

Table 6.1.6.2.26-1: Definition of type N2InterfaceAmfInfo

Attribute name	Data type	Р	Cardinality	Description			
ipv4EndpointAddress	array(Ipv4Addr)	С	1N	Available AMF endpoint IPv4 address(es) for N2			
				(see NOTE 1)			
ipv6EndpointAddress	array(Ipv6Addr)	С	1N	Available AMF endpoint IPv6 address(es) for N2			
(see NOTE 1)							
amfName O 01 AMF Name							
NOTE 1: At least one of the addressing parameters (ipv4address or ipv6adress) shall be included.							

6.1.6.2.27 Type: TaiRange

Table 6.1.6.2.27-1: Definition of type TaiRange

Attribute name	Data type	Р	Cardinality	Description
plmnld	Plmnld	М	1	PLMN ID related to the TacRange.
tacRangeList	array(TacRange)	М	1N	The range of the TACs

6.1.6.2.28 Type: TacRange

Table 6.1.6.2.28-1: Definition of type TacRange

used when the range of TAC's can be represer as a hexadecimal range (e.g., TAC ranges). 3-c string identifying a tracking area code, each character in the string shall take a value of "0" to """ to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the TAC shall appear first in the string, and the character representing the 4 leas significant bit of the TAC shall appear last in the string. Pattern: "^([A-Fa-f0-9]{6}]\section*" end string O 01 Last value identifying the end of a TAC range, to used when the range of TAC's can be represer as a hexadecimal range (e.g. TAC ranges). 3-c string identifying a tracking area code, each character in the string shall take a value of "0" to """ to "F" and shall represent 4 bits. The most significant character representing the 4 most significant character representing the 4 most significant bits of the TAC shall appear first in the string, and the character representing the 4 leas significant bit of the TAC shall appear last in the string. Pattern: "^([A-Fa-f0-9]{4}][A-Fa-f0-9]{6})\section*" pattern: "^([A-Fa-f0-9]{4}][A-Fa-f0-9]{6})\section*"	Attribute name	Data type	Р	Cardinality	Description
end string O 01 Last value identifying the end of a TAC range, to used when the range of TAC's can be represed as a hexadecimal range (e.g. TAC ranges). 3-ostring identifying a tracking area code, each character in the string shall take a value of "0" to "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the TAC shall appear first in the string, and the character representing the 4 lead significant bit of the TAC shall appear last in the string. Pattern: "^([A-Fa-f0-9]{4} [A-Fa-f0-9]{6})\$" pattern string O 01 Pattern (regular expression according to the ECC)	start	string	0	01	character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the TAC shall appear first in the string, and the character representing the 4 least significant bit of the TAC shall appear last in the string.
	end	string	0	01	Last value identifying the end of a TAC range, to be used when the range of TAC's can be represented as a hexadecimal range (e.g. TAC ranges). 3-octet string identifying a tracking area code, each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent 4 bits. The most significant character representing the 4 most significant bits of the TAC shall appear first in the string, and the character representing the 4 least significant bit of the TAC shall appear last in the string.
belonging to this range. A TAC value is consider		J	_		Pattern (regular expression according to the ECMA-262 dialect [8]) representing the set of TAC's belonging to this range. A TAC value is considered part of the range if and only if the TAC string fully matches the regular expression.

EXAMPLE 1: TAC range. From: 543000 To: 5433E7 (i.e., 1000 TAC numbers)

JSON: { "start": "543000", "end": "5433E7" }

EXAMPLE 2: TAC range. From: 54E000 To: 54EFFF (i.e., 4096 TAC numbers)

JSON: { "pattern": "^54E[0-9a-fA-F]{3}\$" }, or JSON: { "start": "54E000", "end": "54EFFF" }

6.1.6.2.29 Type: SnssaiSmfInfoItem

Table 6.1.6.2.29-1: Definition of type SnssaiSmfInfoltem

Attribute name	Data type	Р	Cardinality	Description
sNssai	Snssai	М	1	Supported S-NSSAI
dnnSmfInfoList	array(DnnSmfInfo Item)	М	1N	List of parameters supported by the SMF per DNN

6.1.6.2.30 Type: DnnSmfInfoltem

Table 6.1.6.2.30-1: Definition of type DnnSmfInfoltem

Attribute name	Data type	Р	Cardinality	Description
dnn	Dnn	М	1	Supported DNN

6.1.6.2.31 Type: NrfInfo

Table 6.1.6.2.31-1: Definition of type NrfInfo

Attribute name	Data type	Р	Cardinality	Description
servedUdrInfo	map(UdrInfo)	0	1N	This attribute contains all the udrInfo attributes
				locally configured in the NRF or the NRF received
				during NF registration. The key of the map is the
				nfInstanceId of which the udrInfo belongs to.
servedUdmInfo	map(UdmInfo)	0	1N	This attribute contains all the udmInfo attributes
				locally configured in the NRF or the NRF received
				during NF registration. The key of the map is the
				nfInstanceId of which the udmInfo belongs to.
servedAusfInfo	map(AusfInfo)	0	1N	This attribute contains all the ausfInfo attributes
				locally configured in the NRF or the NRF received
				during NF registration. The key of the map is the
				nfInstanceId of which the ausfInfo belongs to.
servedAmfInfo	map(AmfInfo)	0	1N	This attribute contains all the amfInfo attributes
				locally configured in the NRF or the NRF received
				during NF registration. The key of the map is the
				nfInstanceId of which the amfInfo belongs to.
servedSmfInfo	map(SmfInfo)	0	1N	This attribute contains all the smfInfo attributes
				locally configured in the NRF or the NRF received
				during NF registration. The key of the map is the
				nfInstanceId of which the smfInfo belongs to.
servedUpfInfo	map(UpfInfo)	0	1N	This attribute contains all the upfInfo attributes
				locally configured in the NRF or the NRF received
				during NF registration. The key of the map is the
				nfInstanceId of which the upfInfo belongs to.
servedPcfInfo	map(PcfInfo)	0	1N	This attribute contains all the pcfInfo attributes locally
				configured in the NRF or the NRF received during
				NF registration. The key of the map is the
				nfInstanceId of which the pcfInfo belongs to.
servedBsfInfo	map(BsfInfo)	0	1N	This attribute contains all the bsfInfo attributes locally
				configured in the NRF or the NRF received during
				NF registration. The key of the map is the
				nfInstanceId of which the bsfInfo belongs to.
servedChfInfo	Map(ChfInfo)	0	1N	This attribute contains all the bsfInfo attributes locally
				configured in the NRF or the NRF received during
				NF registration. The key of the map is the
				nfInstanceId of which the chfInfo belongs to.

NOTE: The absence of these parameters means the NRF is able to serve any NF discovery request.

6.1.6.2.32 Type: ChfInfo

Table 6.1.6.2.32-1: Definition of type ChfInfo

Attribute name	Data type	Р	Cardinality	Description
supiRangeList	array(SupiRange)	0	1N	List of ranges of SUPIs that can be served by the CHF instance. If not provided, the CHF can serve any SUPI.
gpsiRangeList	array(IdentityRan ge)	0	1N	List of ranges of GPSI that can be served by the CHF instance. If not provided, the CHF can serve any GPSI.
plmnRangeList	array(PlmnRange)	0	1N	List of ranges of PLMNs (including the PLMN IDs of the CHF instance) that can be served by the CHF instance. If not provided, the CHF can serve any PLMN.

6.1.6.2.33 Type: ChfServiceInfo

Table 6.1.6.2.33-1: Definition of type ChfServiceInfo

Attribute name	Data type	Р	Cardinality	Description
primaryChfServiceInsta	string	С	01	This IE shall be present if the CHF service instance
nce				serves as a secondary CHF instance of another
				primary CHF service instance. When present, it shall
				be set to the serviceInstanceId of the primary CHF
				service instance.
				This IE shall be absent if the
				secondaryChfServiceInstance is present.
secondaryChfServiceIns	string	С	01	This IE shall be present if the CHF service instance
tance				serves as a primary CHF instance of another
				secondary CHF service instance. When present, it
				shall be set to the serviceInstanceId of the
				secondary CHF service instance.
				This IE shall be absent if the
				primaryChfServiceInstance is present.

6.1.6.2.34 Type: PlmnRange

Table 6.1.6.2.34-1: Definition of type PlmnRange

Attribute name	Data type	Р	Cardinality	Description
start	string	0	01	First value identifying the start of a PLMN range. The string shall be encoded as follows: <mcc><mnc> Pattern: '^[0-9]{3}[0-9]{2,3}\$'</mnc></mcc>
end	string	0	01	Last value identifying the end of a PLMN range. The string shall be encoded as follows: <mcc><mnc> Pattern: '^[0-9]{3}[0-9]{2,3}\$'</mnc></mcc>
pattern NOTE: Fither the start	string	0	01	Pattern (regular expression according to the ECMA-262 dialect [8]) representing the set of PLMNs belonging to this range. A PLMN value is considered part of the range if and only if the PLMN string (formatted as <mcc><mnc>) fully matches the regular expression.</mnc></mcc>

EXAMPLE 1: PLMN range. MCC 123, any MNC

JSON: { "start": "12300", "end": "123999" }

EXAMPLE 2: PLMN range. MCC 123, MNC within range 45 to 49

JSON: { "pattern": "^1234[5-9]\$" }, or JSON: { "start": "12345", "end": "12349" }

EXAMPLE 3: PLMN range. MCC within range 123 to 257, any MNC

JSON: { "start": "12300", "end": "257999" }

6.1.6.2.35 Type: SubscrCond

Table 6.1.6.2.35-1: Definition of type SubscrCond as a list of mutually exclusive alternatives

Data type	Cardinality	Description
NfInstanceIdCond	1	Subscription to a given NF Instance
NfTypeCond	1	Subscription to a set of NF Instances, identified by
		their NF Type
ServiceNameCond	1	Subscription to a set of NF Instances that offer a
		certain service name
AmfCond	1	Subscription to a set of NF Instances (AMFs),
		belonging to a certain AMF Set and/or belonging to a certain AMF Region.
GuamiListCond	1	Subscription to a set of NF Instances (AMFs),
		identified by their Guamis.
NetworkSliceCond	1	Subscription to a set of NF Instances, identified by
		S-NSSAI(s) and NSI ID(s).
NfGroupCond	1	Subscription to a set of NF Instances, identified by a
		NF (UDM, AUSF or UDR) Group Identity.

6.1.6.2.36 Type: NfInstanceCond

Table 6.1.6.2.36-1: Definition of type NfInstanceCond

Attribute name	Data type	Р	Cardinality	Description
nflnstanceld	NfInstanceId	М	1	NF Instance ID of the NF Instance whose status is
				requested to be monitored.

6.1.6.2.37 Type: NfTypeCond

Table 6.1.6.2.37-1: Definition of type NfTypeCond

Attril	bute name	Data type	Р	Cardinality	Description	
nfType		NFType	М	1	NF type of the NF Instances whose status is	
					requested to be monitored.	
NOTE:	NOTE: This type shall not contain the attribute "nfGroupId", to avoid that this type has a matching definition with					
	"NfGroupCond" type.					

6.1.6.2.38 Type: ServiceNameCond

Table 6.1.6.2.38-1: Definition of type ServiceNameCond

Attribute name	Data type	Р	Cardinality	Description
serviceName	ServiceName	M	1	Service name offered by the NF Instances whose
				status is requested to be monitored.

6.1.6.2.39 Type: AmfCond

Table 6.1.6.2.39-1: Definition of type AmfCond

Attrib	oute name	Data type	Р	Cardinality	Description	
amfSetId		AmfSetId	С	1	AMF Set ID of the NF Instances (AMF) whose status	
					is requested to be monitored.	
amfRegio	nld	AmfRegionId	С	1	AMF Region ID of the NF Instances (AMF) whose	
					status is requested to be monitored.	
NOTE 1:	NOTE 1: At least amfSetId or amfRegionId shall be present; if both the amfRegionId and amfSetId attributes are					
	present in the	Subscription Data,	this inc	dicates a subso	cription for notifications satisfying both attributes (i.e.	
	notifications for NFs from that amfRegionId and amfSetId).					
NOTE 2:	The PLMN ID of the AMF Region and AMF Set of the NF Instances (AMF) whose status is requested to be					
	monitored may be indicated in the plmnld attribute in the SubscriptionData.					

6.1.6.2.40 Type: GuamiListCond

Table 6.1.6.2.40-1: Definition of type GuamiListCond

Attribute name	Data type	Р	Cardinality	Description
guamiList	array(Guami)	М	1N	Guamis of the NF Instances (AMFs) whose status is
				requested to be monitored.

6.1.6.2.41 Type: NetworkSliceCond

Table 6.1.6.2.41-1: Definition of type NetworkSliceCond

Attribute name	Data type	Р	Cardinality	Description
snssaiList	array(Snssai)	М	1N	S -NSSAIs of the NF Instances whose status is
				requested to be monitored.
nsiList	array(string)	0	1N	NSI IDs of the NF Instances whose status is
				requested to be monitored.

6.1.6.2.42 Type: NfGroupCond

Table 6.1.6.2.42-1: Definition of type NfGroupCond

Attribute name	Data type	Р	Cardinality	Description
nfType	string	М	1	NF type (UDM, AUSF or UDR) of the NF Instances
				whose status is requested to be monitored.
nfGroupId	NfGroupId	М	1	Group ID of the NF Instances whose status is
				requested to be monitored.

6.1.6.2.43 Type: NotifCondition

Table 6.1.6.2.43-1: Definition of type NotifCondition

Attribute name	Data type	Р	Cardinality	Description
monitoredAttributes	array(string)	C	1N	List of JSON Pointers of attributes in the NF Profile.
				If this attribute is present, the NRF shall send notification only for changes in the attributes included in this list (see NOTE 1).
unmonitoredAttributes	array(string)	С	1N	List of JSON Pointers of attributes in the NF Profile.
				If this attribute is present, the NRF shall send notification for changes on any attribute, except for those included in this list (see NOTE 1).
NOTE 1: Attributes "mon	nitoredAttributes" an	d "un	monitoredAttri	butes" shall not be included simultaneously

EXAMPLE 1: The following JSON object would represent a monitoring condition where the client requests to be notified of all changes on the NF Profile, except "load" attribute.

```
{
    "unmonitoredAttributes": [ "/load" ]
}
```

EXAMPLE 2: The following JSON object would represent a monitoring condition where the client requests to be notified only of changes on attribute "nfStatus":

```
{
    "monitoredAttributes": [ "/nfStatus" ]
}
```

6.1.6.2.44 Type: PlmnSnssai

Table 6.1.6.2.44-1: Definition of type PlmnSnssai

Attribute name	Data type	Р	Cardinality	Description
plmnld	Plmnld	М	1	PLMN ID for which list of supported S-NSSAI(s) is provided.
sNssaiList	array(Snssai)	М	1N	The specific list of S-NSSAIs supported by the given PLMN.

6.1.6.3 Simple data types and enumerations

6.1.6.3.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

6.1.6.3.2 Simple data types

The simple data types defined in table 6.1.6.3.2-1 shall be supported.

Table 6.1.6.3.2-1: Simple data types

Type Name	Type Definition	Description
Fqdn	string	FQDN (Fully Qualified Domain Name)

6.1.6.3.3 Enumeration: NFType

The enumeration NFType represents the different types of Network Functions that can be found in the 5GC.

Table 6.1.6.3.3-1: Enumeration NFType

Enumeration value	Description
"NRF"	Network Function: NRF
"UDM"	Network Function: UDM
"AMF"	Network Function: AMF
"SMF"	Network Function: SMF
"AUSF"	Network Function: AUSF
"NEF"	Network Function: NEF
"PCF"	Network Function: PCF
"SMSF"	Network Function: SMSF
"NSSF"	Network Function: NSSF
"UDR"	Network Function: UDR
"LMF"	Network Function: LMF
"GMLC"	Network Function: GMLC
"5G_EIR"	Network Function: 5G-EIR
"SEPP"	Network Function: SEPP
"UPF"	Network Function: UPF
"N3IWF"	Network Function: N3IWF
"AF"	Network Function: AF
"UDSF"	Network Function: UDSF
"BSF"	Network Function: BSF
"CHF"	Network Function: CHF
"NWDAF"	Network Function: NWDAF

6.1.6.3.4 Enumeration: NotificationType

Table 6.1.6.3.4-1: Enumeration NotificationType

Enumeration value	Description
"N1_MESSAGES"	Notification of N1 messages
"N2_INFORMATION"	Notification of N2 information
"LOCATION_NOTIFICATION"	Notification of Location Information by AMF towards NF Service Consumers (e.g GMLC)
"DATA_REMOVAL_NOTIFICATION"	Notification of Data Removal by UDR (e.g., removal of UE registration data upon subscription withdrawal)
"DATA_CHANGE_NOTIFICATION"	Notification of Data Changes by UDR

6.1.6.3.5 Enumeration: TransportProtocol

Table 6.1.6.3.5-1: Enumeration TransportProtocol

Enumeration value	Description
"TCP"	Transport protocol: TCP

6.1.6.3.6 Enumeration: NotificationEventType

Table 6.1.6.3.6-1: Enumeration NotificationEventType

Enumeration value	Description
"NF_REGISTERED"	The NF Instance has been registered in NRF
"NF_DEREGISTERED"	The NF Instance has been deregistered from NRF
"NF PROFILE CHANGED"	The profile of the NF Instance has been modified

6.1.6.3.7 Enumeration: NFStatus

Table 6.1.6.3.7-1: Enumeration NFStatus

Enumeration value	Description
"REGISTERED"	The NF Instance is registered in NRF and can be discovered by other NFs.
"SUSPENDED"	The NF Instance is registered in NRF but it is not operative and cannot be discovered by other NFs. This status may result from a NF Heart-Beat failure (see clause 5.2.2.3.2) or a NF failure and may trigger restoration procedures (see clause 6.2 of 3GPP 23.527 [27]).
"UNDISCOVERABLE"	The NF instance is registered in NRF, is operative but cannot be discovered by other NFs. This status may be set by the NF e.g. in shutting down scenarios where the NF is still able to process requests for existing resources or sessions but cannot accept new resource creation or session establishment.

6.1.6.3.8 Enumeration: DataSetId

The enumeration DataSetId represents the different types of data sets supported by an UDR instance.

Table 6.1.6.3.8-1: Enumeration DataSetId

Enumeration value	Description
"SUBSCRIPTION"	Data set: Subscription data
"POLICY"	Data set: Policy data
"EXPOSURE"	Data set: Structured data for exposure
"APPLICATION"	Data set: Application data

6.1.6.3.9 Enumeration: UPInterfaceType

Table 6.1.6.3.9-1: Enumeration UPInterfaceType

Enumeration value	Description
"N3"	User Plane Interface: N3
"N6"	User Plane Interface: N6
"N9"	User Plane Interface: N9

6.1.6.3.10 Relation Types

6.1.6.3.10.1 General

This clause describes the possible relation types defined within NRF API. See clause 4.7.5.2 of 3GPP TS 29.501 [5] for the description of the relation types.

Table 6.1.6.3.10.1-1: supported registered relation types

Relation Name	
self	
item	

6.1.6.3.11 Enumeration: ServiceName

Table 6.1.6.3.11-1: Enumeration ServiceName

Enumeration value	Description				
"nnrf-nfm"	Nnrf_NFManagement Service offered by the NRF				
"nnrf-disc"	Nnrf_NFDiscovery Service offered by the NRF				
"nudm-sdm"	Nudm_SubscriberDataManagement Service offered by the UDM				
"nudm-uecm"	Nudm_UEContextManagement Service offered by the UDM				
"nudm-ueau"	Nudm_UEAuthentication Service offered by the UDM				
"nudm-ee"	Nudm_EventExposure Service offered by the UDM				
"nudm-pp"	Nudm_ParameterProvision Service offered by the UDM				
"namf-comm"	Namf_Communication Service offered by the AMF				
"namf-evts"	Namf_EventExposure Service offered by the AMF				
"namf-mt"	Namf_MT Service offered by the AMF				
"namf-loc"	Namf_Location Service offered by the AMF				
"nsmf-pdusession"	Nsmf_PDUSession Service offered by the SMF				
"nsmf-event-exposure"	Nsmf_EventExposure Service offered by the SMF				
"nausf-auth"	Nausf_UEAuthentication Service offered by the AUSF				
"nausf-sorprotection"	Nausf_SoRProtection Service offered by the AUSF				
"nausf-upuprotection"	Nausf_UPUProtection Service offered by the AUSF				
"nnef-pfdmanagement"	Nnef_PFDManagement offered by the NEF				
"npcf-am-policy-control"	Npcf_AMPolicyControl Service offered by the PCF				
"npcf-smpolicycontrol"	Npcf_SMPolicyControl Service offered by the PCF				
"npcf-policyauthorization"	Npcf_PolicyAuthorization Service offered by the PCF				
"npcf-bdtpolicycontrol"	Npcf_BDTPolicyControl Service offered by the PCF				
"npcf-eventexposure"	Npcf_EventExposure Service offered by the PCF				
"npcf-ue-policy-control"	Npcf_UEPolicyControl Service offered by the PCF				
"nsmsf-sms"	Nsmsf_SMService Service offered by the SMSF				
"nnssf-nsselection"	Nnssf_NSSelection Service offered by the NSSF				
"nnssf-nssaiavailability"	Nnssf_NSSAIAvailability Service offered by the NSSF				
"nudr-dr"	Nudr_DataRepository Service offered by the UDR				
"nlmf-loc"	Nlmf_Location Service offered by the LMF				
"n5g-eir-eic"	N5g-eir_EquipmentIdentityCheck Service offered by the 5G-EIR				
"nbsf-management"	Nbsf_Management Service offered by the BSF				
"nchf-spendinglimitcontrol"	Nchf_SpendingLimitControl Service offered by the CHF				
"nchf-convergedcharging"	Nchf_Converged_Charging Service offered by the CHF				
"nnwdaf-eventssubscription"	Nnwdaf_EventsSubscription Service offered by the NWDAF				
"nnwdaf-analyticsinfo"	Nnwdaf_AnalyticsInfo Service offered by the NWDAF				
NOTE: The services defined in this table are those defined by 3GPP NFs in 5GC; however, in order to					
	red by standard and custom NFs, the NRF shall also accept the				
registration of NF Services w	ith other service names.				

6.1.6.3.12 Enumeration: NFServiceStatus

Table 6.1.6.3.12-1: Enumeration NFServiceStatus

Enumeration value	Description
"REGISTERED"	The NF Service Instance is registered in NRF and can be discovered by other NFs.
"SUSPENDED"	The NF Service Instance is registered in NRF but it is not operative and cannot be discovered by other NFs. This status may result from a NF Service failure and may trigger restoration procedures (see clause 6.2 of 3GPP 23.527 [27]).
"UNDISCOVERABLE"	The NF Service instance is registered in NRF, is operative but cannot be discovered by other NFs. This status may be set by the NF e.g. in shutting down scenarios where the NF service is still able to process requests for existing resources or sessions but cannot accept new resource creation or session establishment.

6.1.7 Error Handling

6.1.7.1 General

HTTP error handling shall be supported as specified in clause 5.2.4 of 3GPP TS 29.500 [4].

6.1.7.2 Protocol Errors

Protocol errors handling shall be supported as specified in clause 5.2.7 of 3GPP TS 29.500 [4].

6.1.7.3 Application Errors

The application errors defined for the Nnrf_NFManagement service are listed in Table 6.1.7.3-1.

Table 6.1.7.3-1: Application errors

Application Error	HTTP status code	Description

6.1.8 Security

As indicated in 3GPP TS 33.501 [15], the access to the Nnrf_NFManagement API may be authorized by means of the OAuth2 protocol (see IETF RFC 6749 [16]), using the "Client Credentials" authorization grant, where the NRF plays the role of the authorization server.

If Oauth2 authorization is used, an NF Service Consumer, prior to consuming services offered by the Nnrf_NFManagement API, shall obtain a "token" from the authorization server, by invoking the Access Token Request service, as described in clause 5.4.2.2.

NOTE: When multiple NRFs are deployed in a network, the NRF used as authorization server is the same NRF where the Nnrf_NFManagement service is invoked by the NF Service Producer.

The Nnrf_NFManagement API defines scopes for OAuth2 authorization as specified in 3GPP TS 33.501 [15]; it defines a single scope consisting on the name of the service (i.e., "nnrf-nfm"), and it does not define any additional scopes at resource or operation level.

6.2 Nnrf_NFDiscovery Service API

6.2.1 API URI

URIs of this API shall have the following root:

{apiRoot}/{apiName}/{apiVersion}/

where "apiRoot" is defined in clause 4.4.1 of 3GPP TS 29.501 [5], the "apiName" shall be set to "nnrf-disc" and the "apiVersion" shall be set to "v1" for the current version of this specification.

6.2.2 Usage of HTTP

6.2.2.1 General

HTTP/2, as defined in IETF RFC 7540 [9], shall be used as specified in clause 5 of 3GPP TS 29.500 [4].

HTTP/2 shall be transported as specified in clause 5.3 of 3GPP TS 29.500 [4].

HTTP messages and bodies for the Nnrf_NFDiscovery service shall comply with the OpenAPI [10] specification contained in Annex A.

6.2.2.2 HTTP Standard Headers

6.2.2.2.1 General

The mandatory standard HTTP headers as specified in clause 5.2.2.2 of 3GPP TS 29.500 [4] shall be supported.

6.2.2.2.2 Content type

The following content types shall be supported:

- The JSON format (IETF RFC 8259 [22]). The use of the JSON format shall be signalled by the content type "application/json". See also clause 5.4 of 3GPP TS 29.500 [4].
- The Problem Details JSON Object (IETF RFC 7807 [11]). The use of the Problem Details JSON object in a HTTP response body shall be signalled by the content type "application/problem+json".

6.2.2.2.3 Cache-Control

A "Cache-Control" header should be included in HTTP responses, as described in IETF RFC 7234 [20], clause 5.2. It shall contain a "max-age" value, indicating the amount of time in seconds after which the received response is considered stale; this value shall be the same as the content of the "validityPeriod" element described in clause 6.2.6.2.2.

6.2.2.2.4 ETag

An "ETag" (entity-tag) header should be included in HTTP responses, as described in IETF RFC 7232 [19], clause 2.3. It shall contain a server-generated strong validator, that allows further matching of this value (included in subsequent client requests) with a given resource representation stored in the server or in a cache.

6.2.2.2.5 If-None-Match

An NF Service Consumer should issue conditional GET request towards NRF, by including an If-None-Match header in HTTP requests, as described in IETF RFC 7232 [19], clause 3.2, containing one or several entity tags received in previous responses for the same resource.

6.2.2.3 HTTP custom headers

6.2.2.3.1 General

In this release of this specification, no custom headers specific to the Nnrf_NFDiscovery service are defined. For 3GPP specific HTTP custom headers used across all service-based interfaces, see clause 5.2.3 of 3GPP TS 29.500 [4].

6.2.3 Resources

6.2.3.1 Overview

The structure of the Resource URIs of the NFDiscovery service is shown in figure 6.2.3.1-1.




Figure 6.2.3.1-1: Resource URI structure of the NFDiscovery API

Table 6.2.3.1-1 provides an overview of the resources and applicable HTTP methods.

Table 6.2.3.1-1: Resources and methods overview

Resource name	Resource URI	HTTP method or custom operation	Description
nf-instances (Store)	{apiRoot}/nnrf-disc/v1/nf-instances	GET	Retrieve a collection of NF Instances according to certain filter criteria.

6.2.3.2 Resource: nf-instances (Store)

6.2.3.2.1 Description

This resource represents a collection of the different NF instances registered in the NRF.

This resource is modelled as the Store resource archetype (see clause C.3 of 3GPP TS 29.501 [5]).

6.2.3.2.2 Resource Definition

Resource URI: {apiRoot}/nnrf-disc/v1/nf-instances

This resource shall support the resource URI variables defined in table 6.1.3.2.2-1.

Table 6.2.3.2.2-1: Resource URI variables for this resource

Name	Definition			
apiRoot	See clause 6.1.1			

6.2.3.2.3 Resource Standard Methods

6.2.3.2.3.1 GET

This operation retrieves a list of NF Instances, and their offered services, currently registered in the NRF, satisfying a number of filter criteria, such as those NF Instances offering a certain service name, or those NF Instances of a given NF type (e.g., AMF).

Table 6.2.3.2.3.1-1: URI query parameters supported by the GET method on this resource

Name	Data type	Р	Cardi nality	Description	Applicab ility
target-nf- type	NFType	М	1	This IE shall contain the NF type of the NF Service Producer being discovered.	_
requester- nf-type	NFType	М	1	This IE shall contain the NF type of the NF Service Consumer that is invoking the Nnrf_NFDiscovery service.	
service- names	array(Service Name)	0	1N	If included, this IE shall contain an array of service names for which the NRF is queried to provide the list of NF profiles. The NRF shall return the NF profiles that have at least one NF service matching the NF service names in this list. The NF service names returned by the NRF shall be an interclause of the NF service names requested and the NF service names registered in the NF profile. If not included, the NRF shall return all the NF service names registered in the NF profile.	
requester- nf-instance- fqdn	Fqdn	0	01	If included, this IE shall contain the FQDN of the NF Service Consumer that is invoking the Nnrf_NFDiscovery service. The NRF shall use this to return only those NF profiles that include at least one NF service containing an entry in the "allowedNfDomains" list (see clause 6.1.6.2.3) that matches the domain of the requester NF.	
target-plmn- list	array(Pimnid)	С	1N	This IE shall be included when NF services in a different PLMN, or NF services of specific PLMN ID(s) in a same PLMN comprising multiple PLMN IDs, need to be discovered. When included, this IE shall contain the PLMN ID of the target NF. If more than one PLMN ID is included, NFs from any PLMN ID present in the list matches the query parameter. For inter-PLMN service discovery, at most 1 PLMN ID shall be included in the list; it shall be included in the service discovery from the NF in the source PLMN sent to the NRF in the same	
requester-	array(Plmnld	С	1N	PLMN, while it may be absent in the service discovery request sent from the source NRF to the target NRF. In such case, if the NRF receives more than 1 PLMN ID, it shall only consider the first element of the array, and ignore the rest. This IE shall be included when NF services in a different PLMN	
plmn-list)		11	need to be discovered. When included, this IE shall contain the PLMN ID(s) of the requester NF.	
target-nf- instance-id	NfInstanceId		01	Identity of the NF instance being discovered.	
target-nf- fqdn	Fqdn		01	FQDN of the target NF instance being discovered.	
hnrf-uri	Uri	С	01	If included, this IE shall contain the API URI of the NFDiscovery Service (see clause 6.2.1) of the home NRF. It shall be included if the NF Service Consumer has previously received such API URI to be used for service discovery (e.g., from the NSSF in the home PLMN).	
snssais	array(Snssai)		1N	If included, this IE shall contain the list of S-NSSAIs that are served by the NF Instances being discovered. The NRF shall return those NF profiles of NF Instances that have at least one of the S-NSSAIs in this list. The S-NSSAIs included in the NF profiles of NF Instances returned by the NRF shall be an interclause of the S-NSSAIs requested and the S-NSSAIs supported by those NF Instances. (NOTE 5).	
requester- snssais	array(Snssai)	0	1N	If included, this IE shall contain the list of S-NSSAI of the requester NF. The NRF shall use this to return only those NF profiles of NF Instances allowing to be discovered from at least one network slice identified by this IE, according to the "allowedNssais" list in the NF Profile and NF Service (see clause 6.1.6.2.2 and 6.1.6.2.3).	

nlmr	orrov/DirectO	\sim	4 NI	If included this IT shall sentein the list of C NOCAL that are	!
plmn- specific- snssai-list	array(PImnS nssai)		1N	If included, this IE shall contain the list of S-NSSAI that are served by the NF service being discovered for the corresponding PLMN provided. The NRF shall use this to identify the NF services that have registered their support for the S-NSSAIs for the corresponding PLMN given. The NRF shall return the NF profiles that have at least one per PLMN S-NSSAI entry matching the PLMN specific S-NSSAIs provided in this list. The per PLMN list of S-NSSAIs included in the NF profile returned by the NRF shall be an interclause of the list requested and the list registered in the NF profile.	
nsi-list	array(string)		1N	If included, this IE shall contain the list of NSI IDs that are served by the services being discovered.	
dnn	Dnn	0	01	If included, this IE shall contain the DNN for which NF services serving that DNN is discovered. DNN may be included if the target NF type is "BSF", "SMF" or "UPF". If the Snssai(s) are also included, the NF services serving the DNN shall be available in the network slice(s) identified by the Snssai(s).	
smf-serving- area	string	0	01	If included, this IE shall contain the serving area of the SMF. It may be included if the target NF type is "UPF".	
tai	Tai	0	01	Tracking Area Identity.	
amf-region- id	AmfRegionId		01	AMF Region Identity.	
amf-set-id	AmfSetId	0	01	AMF Set Identity.	
guami	Guami	0	01	Guami used to search for an appropriate AMF. (NOTE 1)	
supi	Supi	0	01	If included, this IE shall contain the SUPI of the requester UE to search for an appropriate NF. SUPI may be included if the target NF type is e.g. "PCF", "CHF", "AUSF", "UDM" or "UDR".	
ue-ipv4- address	lpv4Addr	0	01	The IPv4 address of the UE for which a BSF needs to be discovered.	
ip-domain	string	0	01	The IPv4 address domain of the UE for which a BSF needs to be discovered.	
ue-ipv6- prefix	Ipv6Prefix	0	01	The IPv6 prefix of the UE for which a BSF needs to be discovered.	
pgw-ind	boolean	0	01	When present, this IE indicates whether a combined SMF/PGW-C or a standalone SMF needs to be discovered. true: A combined SMF/PGW-C is requested to be discovered; false: A standalone SMF is requested to be discovered. (See NOTE 2)	
pgw	Fqdn	0	01	If included, this IE shall contain the PGW FQDN which is received by the AMF from the MME to find the combined SMF/PGW.	
gpsi	Gpsi		01	If included, this IE shall contain the GPSI of the requester UE to search for an appropriate NF. GPSI may be included if the target NF type is "CHF", "UDM" or "UDR".	
external- group- identity	ExtGroupId	0	01	If included, this IE shall contain the external group identifier of the requester UE to search for an appropriate NF. This may be included if the target NF type is "UDM" or "UDR".	
data-set	DataSetId	0	01	Indicates the data set to be supported by the NF to be discovered. May be included if the target NF type is "UDR".	
routing- indicator	string		01	Routing Indicator information that allows to route network signalling with SUCI (see 3GPP 23.003 [12]) to an AUSF and UDM instance capable to serve the subscriber. May be included if the target NF type is "AUSF" or "UDM".	
group-id-list	array(NfGrou pld)		1N	Identity of the group(s) of the NFs of the target NF type to be discovered. May be included if the target NF type is "UDR", "UDM" or "AUSF".	
dnai-list	array(Dnai)	0	1N	If included, this IE shall contain the Data network access identifiers. It may be included if the target NF type is "UPF".	

upf-iwk-eps- ind	boolean	0	01	When present, this IE indicates whether a UPF supporting interworking with EPS needs to be discovered.	
				true: A UPF supporting interworking with EPS is requested to be discovered;	
				false: A UPF not supporting interworking with EPS is requested to be discovered. (NOTE 3)	
chf- supported- plmn	Plmnld	0	01	If included, this IE shall contain the PLMN ID that a CHF supports (i.e., in the PlmnRange of ChfInfo attribute in the NFProfile). This IE may be included when the target NF type is "CHF".	
preferred- locality	string		01	Preferred target NF location (e.g. geographic location, data center). When present, the NRF shall prefer NF profiles with a locality attribute that matches the preferred-locality. The NRF may return additional NFs in the response not matching the preferred target NF location, e.g. if no NF profile is found matching the preferred target NF location. The NRF should set a lower priority for any additional NFs on the response not matching the preferred target NF location than those matching the preferred target NF location.	
access-type	AccessType		01	If included, this IE shall contain the Access type which is required to be supported by the target Network Function (i.e. SMF).	
supported- features	SupportedFe atures	0	01	List of features required to be supported by the target Network Function. This IE may be present only if the service-names attribute is present and if it contains a single service-name, or if the target Network Function does not support any service. It shall be ignored by the NRF otherwise. (NOTE 4)	
required- features	array(Suppor tedFeatures)	0	1N	List of features required to be supported by the target Network Function, as defined by the supportedFeatures attribute in NFService (see clauses 6.1.6.2.3 and 6.2.6.2.4). This IE may be present only if the service-names attribute is present. When present, the required-features attribute shall contain as many entries as the number of entries in the service-names attribute. The n th entry in the required-features attribute shall correspond to the n th entry in the service-names attribute. An entry corresponding to a service for which no specific feature is required shall be encoded as "0".	Query- Params- Ext1
complex- query	ComplexQue ry		01	This query parameter is used to override the default logical relationship of query parameters.	Complex- Query
limit	integer	0	01	Maximum number of NFProfiles to be returned in the response.	Query- Params- Ext1
max- payload- size	integer	0	01	Maximum payload size (before compression, if any) of the response, expressed in kilo octets. When present, the NRF shall limit the number of NF profiles returned in the response such as to not exceed the maximum payload size indicated in the request. Default = 124. Maximum = 2000 (i.e. 2 Mo).	Query- Params- Ext1
pdu- session- types	array(PduSe ssionType)	0	1N	List of the PDU session type (s) requested to be supported by the target Network Function (i.e UPF).	Query- Params- Ext1

- NOTE 1: If this parameter is present and no AMF supporting the requested GUAMI is available due to AMF Failure or planned AMF removal, the NRF shall return in the response AMF instances acting as a backup for AMF failure or planned AMF removal respectively for this GUAMI. The NRF can detect if an AMF has failed, using the Heartbeat procedure. The NRF will receive a de-registration request from an AMF performing a planned removal.
- NOTE 2: If the combined SMF/PGW-C is requested to be discovered, the NRF shall return in the response the SMF instances registered with the SmfInfo containing pgwFgdn.
- NOTE 3: If a UPF supporting interworking with EPS is requested to be discovered, the NRF shall return in the response the UPF instances registered with the upfInfo containing iwkEpsInd set to true.
- NOTE 4: This attribute has a different semantic than what is defined in clause 6.6.2 of 3GPP TS 29.500 [4], i.e. it is not used to signal optional features of the Nnrf_NFDiscovery Service API supported by the requester NF.
- NOTE 5: An S-NSSAI value used in discovery request query parameters shall be considered as matching the S-NSAAI value in the NF Profile of a given NF Instance if both the SST and SD components are identical (i.e. an S-NSSAI value where SD is absent, shall not be considered as matching an S-NSSAI where SD is present, regardless if SST is equal in both).

The default logical relationship among the query parameters is logical "AND", i.e. all the provided query parameters shall be matched, with the exception of the "preferred-locality" query (see Table 6.2.3.2.3.1-1).

The NRF may support the Complex query expression as defined in 3GPP TS 29.501 [5] for the NF Discovery service. If the "complexQuery" query parameter is included, then the logical relationship among the query parameters contained in "complexQuery" query parameter is as defined in 3GPP TS 29.571 [7].

A NRF not supporting Complex query expression shall reject a NF service discovery request including a complexQuery parameter, with a ProblemDetails IE including the cause attribute set to INVALID_QUERY_PARAM and the invalidParams attribute indicating the complexQuery parameter.

This method shall support the request data structures specified in table 6.1.3.2.3.1-2 and the response data structures and response codes specified in table 6.1.3.2.3.1-3.

Table 6.2.3.2.3.1-2: Data structures supported by the GET Request Body on this resource

Data type	P	Cardinality	Description
n/a			

Table 6.2.3.2.3.1-3: Data structures supported by the GET Response Body on this resource

Data type	Р	Cardinality	Response codes	Description
SearchResult	М	1	200 OK	The response body contains the result of the search over the list of registered NF Instances.
n/a			307 Temporary Redirect	The response shall be used when the intermediate NRF redirects the service discovery request. The NRF shall include in this response a Location header field containing a URI pointing to the resource located on the redirect target NRF.
ProblemDetails	М	1	400 Bad Request	The response body contains the error reason of the request message.
ProblemDetails	M	1	403 Forbidden	This response shall be returned if the NF Service Consumer is not allowed to discover the NF Service(s) being queried.
ProblemDetails	М	1	500 Internal Server Error	The response body contains the error reason of the request message.

6.2.3.2.4 Resource Custom Operations

There are no resource custom operations for the Nnrf_NFDiscovery service in this release of the specification.

6.2.4 Custom Operations without associated resources

There are no custom operations defined without any associated resources for the Nnrf_NFDiscovery service in this release of this specification.

6.2.5 Notifications

There are no notifications defined for the Nnrf_NFDiscovery service in this release of the specification.

6.2.6 Data Model

6.2.6.1 General

This clause specifies the application data model supported by the API.

Table 6.2.6.1-1 specifies the data types defined for the Nnrf service based interface protocol.

Table 6.2.6.1-1: Nnrf_NFDiscovery specific Data Types

Data type	Clause defined	Description
SearchResult	6.2.6.2.2	
NFProfile	6.2.6.2.3	
NFService	6.2.6.2.4	

Table 6.2.6.1-2 specifies data types re-used by the Nnrf service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the Nnrf service based interface.

Table 6.2.6.1-2: Nnrf_NFDiscovery re-used Data Types

Data type	Reference	Comments
Snssai	3GPP TS 29.571 [7]	
Plmnld	3GPP TS 29.571 [7]	
Dnn	3GPP TS 29.571 [7]	
Tai	3GPP TS 29.571 [7]	
SupportedFeatures	3GPP TS 29.571 [7]	
NfInstanceId	3GPP TS 29.571 [7]	
Uri	3GPP TS 29.571 [7]	
Gpsi	3GPP TS 29.571 [7]	
GroupId	3GPP TS 29.571 [7]	
Guami	3GPP TS 29.571 [7]	
IPv4Addr	3GPP TS 29.571 [7]	
IPv6Addr	3GPP TS 29.571 [7]	
UriScheme	3GPP TS 29.571 [7]	
Dnai	3GPP TS 29.571 [7]	
NfGroupId	3GPP TS 29.571 [7]	Identifier of a NF Group
PduSessionType	3GPP TS 29.571 [7]	
ExtGroupId	3GPP TS 29.503 [36]	
DefaultNotificationSubscription	3GPP TS 29.510	See clause 6.1.6.2.4
IPEndPoint	3GPP TS 29.510	See clause 6.1.6.2.5
NFType	3GPP TS 29.510	See clause 6.1.6.3.3
UdrInfo	3GPP TS 29.510	See clause 6.1.6.2.6
UdmInfo	3GPP TS 29.510	See clause 6.1.6.2.7
AusfInfo	3GPP TS 29.510	See clause 6.1.6.2.8
SupiRange	3GPP TS 29.510	See clause 6.1.6.2.9
AmfInfo	3GPP TS 29.510	See clause 6.1.6.2.11
SmfInfo	3GPP TS 29.510	See clause 6.1.6.2.12
UpfInfo	3GPP TS 29.510	See clause 6.1.6.2.13
PcfInfo	3GPP TS 29.510	See clause 6.1.6.2.20
BsfInfo	3GPP TS 29.510	See clause 6.1.6.2.21
ChfInfo	3GPP TS 29.510	See clause 6.1.6.2.32
ChfServiceInfo	3GPP TS 29.510	See clause 6.1.6.2.33
NFServiceVersion	3GPP TS 29.510	See clause 6.1.6.2.19
PlmnSnssai	3GPP TS 29.510	See clause 6.1.6.2.44
NFStatus	3GPP TS 29.510	See clause 6.1.6.3.7
DataSetId	3GPP TS 29.510	See clause 6.1.6.3.8
ServiceName	3GPP TS 29.510	See clause 6.1.6.3.11
NFServiceStatus	3GPP TS 29.510	See clause 6.1.6.3.12

6.2.6.2 Structured data types

6.2.6.2.1 Introduction

This clause defines the structures to be used in resource representations.

6.2.6.2.2 Type: SearchResult

Table 6.2.6.2.2-1: Definition of type SearchResult

Attribute name	Data type	Р	Cardinality	Description
validityPeriod	integer	M	1	It shall contain the time in seconds during which the discovery result is considered valid and can be cached by the NF Service Consumer. This value shall be the same as the value contained in the "max-age" parameter of the "Cache-Control" header field sent in the HTTP response.
nfInstances	array(NFProfile)	M	0N	It shall contain an array of NF Instance profiles, matching the search criteria indicated by the query parameters of the discovery request. An empty array means there is no NF instance that can match the search criteria.
nrfSupportedFeatures	SupportedFeatur es	С	01	Features supported by the NRF for the NFDiscovery service (see clause 6.2.9). This IE should be present if the NRF supports at least one feature.

6.2.6.2.3 Type: NFProfile

Table 6.2.6.2.3-1: Definition of type NFProfile

Attribute name	Data type	Р	Cardinality	Description
nflnstanceld	NfInstanceId	М	1	Unique identity of the NF Instance.
nfType	NFType	М	1	Type of Network Function
nfStatus	NFStatus	М	1	Status of the NF Instance
plmnList	array(PlmnId)	С	1N	PLMN(s) of the Network Function (NOTE 5). This IE
	,			shall be present if this information is available for the
				NF. If this information was not provided by the NF
				during registration, the NRF should return the list of
				PLMN ID(s) of the PLMN of the NRF. If this IE is
				absent in the response, PLMN ID(s) of the PLMN of
				the NRF are assumed for the NF.
sNssais	array(Snssai)	0	1N	S-NSSAIs of the Network Function.
B. 6	(5)			If not provided, the NF can serve any S-NSSAI.
perPlmnSnssaiList	array(PlmnSnssai	0	1N	The per-PLMN list of S-NSSAI(s) supported by the
nsiList)	_	1 N	Network Function. List of NSIs of the Network Function.
nsilist	array(string)	0	1N	
fqdn	Fqdn	С	01	If not provided, the NF can serve any NSI. FQDN of the Network Function (NOTE 1, NOTE 3)
ipv4Addresses	array(lpv4Addr)	С	1N	IPv4 address(es) of the Network Function (NOTE 1)
ipv6Addresses	array(Ipv6Addr)	С	1N	IPv6 address(es) of the Network Function (NOTE 1)
capacity	integer	0	01	Static capacity information in the range of 0-65535,
Capacity	integer		01	expressed as a weight relative to other NF instances
				of the same type; if capacity is also present in the
				nfServiceList parameters, those will have
				precedence over this value. (See NOTE 2)
load	integer	0	01	Latest known load information of the NF ranged from
				0 to 100 in percentage (See NOTE 4)
locality	string	0	01	Operator defined information about the location of
				the NF instance (e.g. geographic location, data
				center)
priority	integer	0	01	Priority (relative to other NFs of the same type) in the
				range of 0-65535, to be used for NF selection; lower
				values indicate a higher priority. If priority is also
				present in the nfServiceList parameters, those will
udrinfo	Lidrinfo	_	0.1	have precedence over this value. (See NOTE 2)
udrInfo udmInfo	UdrInfo UdmInfo	0	01	Specific data for the UDR (ranges of SUPI,) Specific data for the UDM
ausfinfo	AusfInfo	0	01	Specific data for the AUSF
amfInfo	AmfInfo	0	01	Specific data for the AMF (AMF Set ID,)
smfInfo	smfInfo	0	01	Specific data for the SMF (DNN's,)
upfInfo	UpfInfo	ō	01	Specific data for the UPF (S-NSSAI, DNN, SMF
артто	Opiniio		01	serving area,)
pcfInfo	PcfInfo	0	01	Specific data for the PCF
bsfInfo	BsfInfo	0	01	Specific data for the BSF
chfInfo	ChfInfo	0	01	Specific data for the CHF
customInfo	object	0	01	Specific data for custom Network Functions
recoveryTime	DateTime	0	01	Timestamp when the NF was (re)started
nfServicePersistence	boolean	0	01	If present, and set to true, it indicates that the
				different service instances of a same NF Service in
				the NF instance, supporting a same API version, are
				capable to persist their resource state in shared
				storage and therefore these resources are available
				after a new NF service instance supporting the same
				API version is selected by a NF Service Consumer
			1	(see 3GPP 23.527 [27]).
			1	Otherwise, it indicates that the NF Service Instances
				of a same NF Service are not capable to share
				resource state inside the NF Instance.
nfServices	array(NFService)	0	1N	List of NF Service Instances
defaultNotificationSubsc	array(DefaultNotif	Ō	1N	Notification endpoints for different notification types.
riptions	icationSubscriptio	1	1	(NOTE 6)
	n)			<u> </u>
				

- NOTE 1: At least one of the addressing parameters (fqdn, ipv4address or ipv6adress) shall be included in the NF Profile. See NOTE 1 of Table 6.2.6.2.4-1 for the use of these parameters. If multiple ipv4 addresses and/or ipv6 addresses are included in the NF Profile, the NF Service Consumer shall select one of these addresses randomly, unless operator defined local policy of IP address selection, in order to avoid overload for a specific ipv4 address and/or ipv6 address.
- NOTE 2: The capacity and priority parameters, if present, are used for NF selection and load balancing. The priority and capacity attributes shall be used for NF selection in the same way that priority and weight are used for server selection as defined in IETF RFC 2782 [23].
- NOTE 3: If the requester-plmn in the query parameter is different from the PLMN of the discovered NF, then the fqdn attribute value shall contain the interPlmnFqdn value registered by the NF during NF registration (see clause 6.1.6.2.2). The requester-plmn is different from the PLMN of the discovered NF if it belongs to none of the PLMN ID(s) configured for the PLMN of the NRF.
- NOTE 4: The usage of the load parameter by the NF service consumer is implementation specific, e.g. be used for NF selection and load balancing, together with other parameters.
- NOTE 5: An NF may register multiple PLMN IDs in its profile within a PLMN comprising multiple PLMN IDs. If so, all the attributes of the NF Profile shall apply to each PLMN ID registered in the plmnList. As an exception, attributes including a PLMN ID, e.g. IMSI-based SUPI ranges, TAIs and GUAMIs, are specific to one PLMN ID and the NF may register in its profile multiple occurrences of such attributes for different PLMN IDs (e.g. the UDM may register in its profile SUPI ranges for different PLMN IDs).
- NOTE 6: If notification endpoints are present both in the profile of the NF instance (NFProfile) and in some of its NF Services (NFService) for a same notification type, the notification endpoint(s) of the NF Services shall be used for this notification type.

6.2.6.2.4 Type: NFService

Table 6.2.6.2.4-1: Definition of type NFService

	1 able 0.2.0.2	.4-1	. Dennidon	of type NFService
Attribute name	Data type	Р	Cardinality	Description
serviceInstanceId	string	M	1	Unique ID of the service instance within a given NF Instance
serviceName	ServiceName	М	1	Name of the service instance (e.g. "udm-sdm")
versions	array(NFServiceVe rsion)	M	1N	The API versions supported by the NF Service and if available, the corresponding retirement date of the NF Service. The different array elements shall have distinct unique values for "apiVersionInUri", and consequently, the values of "apiFullVersion" shall have a unique first digit version number.
scheme	UriScheme	M	1	URI scheme (e.g. "http", "https")
nfServiceStatus	NFServiceStatus	М	1	Status of the NF Service Instance
fqdn	string	0	01	FQDN of the NF Service Instance (see NOTE 1, NOTE 3)
ipEndPoints	array(IpEndPoint)	0	1N	IP address(es) and port information of the Network Function (including IPv4 and/or IPv6 address) where the service is listening for incoming service requests (see NOTE 1, NOTE 5, NOTE 6)
apiPrefix	string	0	01	Optional path segment(s) used to construct the {apiRoot} variable of the different API URIs, as described in 3GPP 29.501 [5], clause 4.4.1 (optional deployment-specific string that starts with a "/" character)
defaultNotificationSubsc riptions	array(DefaultNotific ationSubscription)	0	1N	Notification endpoints for different notification types.
capacity	integer		01	Static capacity information in the range of 0-65535, expressed as a weight relative to other services of the same type. (See NOTE 2)
load	integer	0	01	Latest known load information of the NF Service, ranged from 0 to 100 in percentage. (See NOTE 4)
priority	integer	0	01	Priority (relative to other services of the same type) in the range of 0-65535, to be used for NF Service selection; lower values indicate a higher priority. (See NOTE 2)
recoveryTime	DateTime	0	01	Timestamp when the NF service was (re)started
chfServiceInfo	ChfServicefInfo		01	Specific data for the CHF service instance
supportedFeatures	SupportedFeatures		01	Supported Features of the NF Service instance
if any, otherwis	N signalling: the FQDI se the FQDN and IP a	N an ddre	d IP addressesses related a	Is of the service using: es related attributes present in the NF Service Profile, attributes present in the NF Profile. IF Service Profile, if any, otherwise the FQDN present

- for inter-PLMN signalling: the FQDN present in the NF Service Profile, if any, otherwise the FQDN present in the NF Profile (see NOTE 3).
- NOTE 2: The capacity and priority parameters, if present, are used for service selection and load balancing. The priority and capacity attributes shall be used for NF selection in the same way that priority and weight are used for server selection as defined in IETF RFC 2782 [23].
- NOTE 3: If the requester-plmn in the query parameter is different from the PLMN of the discovered NF Service, then the fqdn attribute value, if included shall contain the interPlmnFqdn value registered by the NF Service during NF registration (see clause 6.1.6.2.3). The requester-plmn is different from the PLMN of the discovered NF Service if it belongs to none of the PLMN ID(s) configured for the PLMN of the NRF.
- NOTE 4: The usage of the load parameter by the NF service consumer is implementation specific, e.g. be used for NF service selection and load balancing, together with other parameters.
- NOTE 5: If the ipEndPoints attribute is absent in the NF Service and NF Profile, the NF service consumer shall use the fqdn attribute value for DNS query and if the NF service consumer does not receive a port number during the DNS query it shall use the default HTTP port number, i.e. TCP port 80 for "http" URIs or TCP port 443 for "https" URIs as specified in IETF RFC 7540 [9] when invoking the service.
- NOTE 6: If multiple ipv4 addresses and/or ipv6 addresses are included in the NF Service, the NF Service Consumer shall select one of these addresses randomly, unless operator defined local policy of IP address selection, in order to avoid overload for a specific ipv4 address and/or ipv6 address.

6.2.6.3 Simple data types and enumerations

6.2.6.3.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

6.2.6.3.2 Simple data types

The simple data types defined in table 6.2.6.3.2-1 shall be supported.

Table 6.2.6.3.2-1: Simple data types

Type Name	Type Definition	Description

6.2.7 Error Handling

6.2.7.1 General

HTTP error handling shall be supported as specified in clause 5.2.4 of 3GPP TS 29.500 [4].

6.2.7.2 Protocol Errors

Protocol errors handling shall be supported as specified in clause 5.2.7 of 3GPP TS 29.500 [4].

6.2.7.3 Application Errors

The application errors defined for the Nnrf_NFDiscovery service are listed in Table 6.2.7.3-1.

Table 6.2.7.3-1: Application errors

Application Error	HTTP status code	Description

6.2.8 Security

As indicated in 3GPP TS 33.501 [15], the access to the Nnrf_NFDiscovery API may be authorized by means of the OAuth2 protocol (see IETF RFC 6749 [16]), using the "Client Credentials" authorization grant, where the NRF plays the role of the authorization server.

If Oauth2 authorization is used, an NF Service Consumer, prior to consuming services offered by the Nnrf_NFDiscovery API, shall obtain a "token" from the authorization server, by invoking the Access Token Request service, as described in clause 5.4.2.2.

NOTE: When multiple NRFs are deployed in a network, the NRF used as authorization server is the same NRF where the Nnrf_NFDiscovery service is invoked by the NF Service Consumer.

The Nnrf_NFDiscovery API defines scopes for OAuth2 authorization as specified in 3GPP TS 33.501 [15]; it defines a single scope consisting on the name of the service (i.e., "nnrf-disc"), and it does not define any additional scopes at resource or operation level.

6.2.9 Features supported by the NFDiscovery service

The syntax of the supportedFeatures attribute is defined in clause 5.2.2 of 3GPP TS 29.571 [7].

The following features are defined for the Nnrf_NFDiscovery service.

Table 6.2.9-1: Features of supportedFeatures attribute used by Nnrf_NFDiscovery service

Feature Number	Feature	Description
1	Complex-Query	Support of Complex Query expression (see clause 6.2.3.2.3.1)
2	Query-Params- Ext1	Support of the following query parameters: - limit - max-payload-size - required-features - pdu-session-types

Feature number: The order number of the feature within the supportedFeatures attribute (starting with 1). Feature: A short name that can be used to refer to the bit and to the feature.

Description: A clear textual description of the feature.

6.3 Nnrf_AccessToken Service API

6.3.1 General

This API reuses the API endpoints and input / output parameters specified in IETF RFC 6749 [16] as a custom operation without resources. Hence this clause does not follow the 3GPP API specification guidelines described in 3GPP TS 29.501 [5].

6.3.2 API URI

URIs of this API shall have the following root:

{nrfApiRoot}/oauth2/

where {nrfApiRoot} represents the concatenation of the "scheme" and "authority" components of the NRF, as defined in IETF RFC 3986 [17].

6.3.3 Usage of HTTP

6.3.3.1 General

HTTP/2, as defined in IETF RFC 7540 [9], shall be used as specified in clause 5 of 3GPP TS 29.500 [4].

HTTP/2 shall be transported as specified in clause 5.3 of 3GPP TS 29.500 [4].

HTTP messages and bodies this API shall comply with the OpenAPI [10] specification contained in Annex A.

6.3.3.2 HTTP standard headers

6.3.3.2.1 General

The HTTP headers as specified in clause 4.4 of IETF RFC 6749 [16] shall be supported, with the exception that there shall not be "Authorization" HTTP request header in the access token request.

6.3.3.2.2 Content type

The following content types shall be supported:

- The x-www-form-urlencoded format (see clause 17.13.4.1 of W3C HTML 4.01 Specification [26]). The use of the x-www-form-urlencoded format shall be signalled by the content type "application/x-www-form-urlencoded".
- The JSON format (IETF RFC 8259 [22]). The use of the JSON format shall be signalled by the content type "application/json". See also clause 5.4 of 3GPP TS 29.500 [4].

6.3.3.3 HTTP custom headers

6.3.3.3.1 General

In this release of this specification, no custom headers specific to the OAuth2.0 Authorization Service API are defined. For 3GPP specific HTTP custom headers used across all service-based interfaces, see clause 5.2.3 of 3GPP TS 29.500 [4].

6.3.4 Custom Operation without Associated Resources

6.3.4.1 Overview

The /token endpoint as specified in IETF RFC 6749 [16] shall be supported. The "token endpoint" URI shall be:

{nrfApiRoot}/oauth2/token

where {nrfApiRoot} is defined in clause 6.3.2.

Table 6.3.4.1-1 provides an overview of the endpoints and applicable HTTP methods.

Table 6.3.4.1-1: Custom operations without associated resources

Custom operation URI	Mapped HTTP method	Description
{nrfApiRoot}/oauth2/token	POST	Access token request for obtaining OAuth2.0
		access token. This operation maps to
		Nnrf_AccessToken_Get service operation.

6.3.4.2 Operation: Get (Access Token Request)

6.3.4.2.1 Description

This custom operation represents the process for issuing the OAuth2.0 access token.

6.3.4.2.2 Operation Definition

This operation returns an OAuth 2.0 access token based on the input parameters provided. This custom operation shall use the HTTP POST method.

This method shall support the request data structures specified in table 6.3.4.2.2-1 and the response data structures and response codes specified in table 6.3.4.2.2-2. The data structure used for the POST request body shall be using x-www-urlencoded format as specified in clause 17.13.4.1 of W3C HTML 4.01 Specification [26].

Table 6.3.4.2.2-1: Data structures supported by the POST Request Body on this endpoint

Data type	Р	Cardinality	Description
AccessTokenReq	М	1	This IE shall contain the request information for the access token
			request.

Table 6.3.4.2.2-2: Data structures supported by the POST Response Body on this endpoint

Data type	Р	Cardinality	Response	Description
			codes	
AccessTokenRsp	M	1	200 OK	This IE shall contain the access token response information.
AccessTokenErr	М	1		See IETF RFC 6749 [16] clause 5.2.

6.3.5 Data Model

6.3.5.1 General

This clause specifies the application data model supported by the API.

Table 6.3.5.1-1 specifies the data types defined for the OAuth 2.0 Authorization Service API. The AccessTokenReq data structure shall be converted to the content type "application/x-www-urlencoded" when the OAuth 2.0 Access Token Request is invoked.

Table 6.3.5.1-1: OAuth 2.0 Authorization service specific Data Types

Data type	Clause defined	Description	
AccessTokenReq	6.3.5.2.2	Data type for carrying information related to access token request.	
AccessTokenRsp	6.3.5.2.3	Data type for carrying information related to access token	
		response.	
AccessTokenClaims	6.3.5.2.4	The claims data structure for the access token.	
Audience	6.3.5.4.1	Data type for the audience of the access token.	

Table 6.3.5.1-2 specifies data types re-used by the OAuth 2.0 Authorization service from other specifications, including a reference to their respective specifications and when needed, a short description of their use.

Table 6.3.5.1-2: OAuth 2.0 Authorization service re-used Data Types

Data type	Reference	Comments
NfInstanceId	3GPP TS 29.571 [7]	
Plmnld	3GPP TS 29.571 [7]	PLMN ID
NFType	3GPP TS 29.510	See clause 6.1.6.3.3
Snssai	3GPP TS 29.571 [7]	

6.3.5.2 Structured data types

6.3.5.2.1 Introduction

This clause defines the structures to be used in the APIs.

6.3.5.2.2 Type: AccessTokenReq

Table 6.3.5.2.2-1: Definition of type AccessTokenReq

Attribute name	Data type	Р	Cardinality	Description	
grant_type	GrantType	М	1	This IE shall contain the grant type as "client_credentials"	
nflnstanceld	NfInstanceId	М	1	This IE shall contain the NF instance id of the NF service consumer.	
nfType	NFType	С	01	This IE shall be included when the access token request is for an NF type and not for a specific NF NF service instance. When present, this IE shall contain the NF type of the NF service consumer.	
targetNfType	NFType	С	01	This IE shall be included when the access token request is for an NF type and not for a specific NF / NF service instance. When present, this IE shall contain the NF type of the NF service producer.	
scope	string	M	1	This IE shall contain the NF service name(s) of the NF service producer(s), separated by whitespaces, as described in IETF RFC 6749 [16], clause 3.3.	
				The service name(s) included in this attribute shall be any of the services defined in the ServiceName enumerated type (see clause 6.1.6.3.11). pattern: '^([a-zA-Z0-9]+)([a-zA-Z0-9]+)*\$'	
				See NOTE 2.	
targetNfInstanceId	NfInstanceId	С	01	This IE shall be included, if available and if it is an access token request for a specific NF Service Producer. When present this IE shall contain the NF Instance ID of the specific NF Service Producer for which the access token is requested.	
requesterPlmn	Plmnld	С	01	This IE shall be included when the NF service consumer in one PLMN requests a service access authorization for an NF service producer from a different PLMN. When present, this IE shall contain the PLMN ID of	
targetPlmn	Plmnld	С	01	the requester NF service consumer. This IE shall be included when the NF service consumer in one PLMN requests a service access	
				authorization for an NF service producer from a different PLMN. When present, this IE shall contain the PLMN ID of the target PLMN (i.e., PLMN ID of the NF service producer).	
targetSnssaiList	array(Snssai)	0	1N	This IE may be included during an access token request for an NF type and not for a specific NF / NF service instance. When present, this IE shall contain the list of S-NSSAIs of the NF Service Producer.	
targetNsiList	array(string)	0	1N	This IE may be included during an access token request for an NF type and not for a specific NF / NF service instance. When present, this IE shall contain the list of NSIs of the NF Service Producer.	

NOTE 1: This data structure shall not be treated as a JSON object. It shall be treated as a key, value pair data structure to be encoded using x-www-urlencoded format as specified in clause 17.13.4.1 of W3C HTML 4.01 Specification [26].

NOTE 2: Though scope attribute is optional as per IETF RFC 6749 [16], it is mandatory for 3GPP as per 3GPP TS 33.501 [15].

6.3.5.2.3 Type: AccessTokenRsp

Table 6.3.5.2.3-1: Definition of type AccessTokenRsp

Attribute name	Data type	Р	Cardinality	Description	
access_token	string	M	1	This IE shall contain JWS Compact Serialized representation of the JWS signed JSON object containing AccessTokenClaims (see clause 6.3.5.2.4).	
token_type	string	М	1	This IE shall contain the token type, set to value "Bearer".	
expires_in	integer	С	01	This IE when present shall contain the number of seconds after which the access token is considered to be expired. As indicated in IETF RFC 6749 [16], this attribute should be included, unless the expiration time of the token is made available by other means (e.g. deployment-specific documentation).	
scope	string	C	01	This IE when present shall contain the NF service name(s) of the NF service producer(s), separated by whitespaces, as described in IETF RFC 6749 [16], clause 3.3. The service name(s) included in this attribute shall be any of the services defined in the ServiceName enumerated type (see clause 6.1.6.3.11). As indicated in IETF RFC 6749 [16], this attribute shall be present if it is different than the scope included in the access token request; if it is the same as the requested scope, this attribute may be absent. pattern: '^([a-zA-Z0-9]+)([a-zA-Z0-9]+)*\$'	

6.3.5.2.4 Type: AccessTokenClaims

Table 6.3.5.2.4-1: Definition of type AccessTokenClaims

Attribute name	Data type	Р	Cardinality	Description	
iss	NfInstanceId	М	1	This IE shall contain NF instance id of the NRF., corresponding to the standard "Issuer" claim described in IETF RFC 7519 [25], clause 4.1.1	
sub	NfInstanceId	M	1	This IE shall contain the NF instance ID of the NF service consumer, corresponding to the standard "Subject" claim described in IETF RFC 7519 [25], clause 4.1.2.	
aud	Audience	M	1	This IE shall contain the NF service producer's NF instance ID(s) (if the exact NF instance(s) of the NF service producer is known) or the NF type of NF service producers for which the claim is applicable, corresponding to the standard "Audience" claim described in IETF RFC 7519 [25], clause 4.1.3.	
scope	string	M	1	This IE shall contain the name of the NF services for which the access_token is authorized for use; this claim corresponds to a private claim, as described in IETF RFC 7519 [25], clause 4.3. pattern: '^([a-zA-Z0-9]+)([a-zA-Z0-9]+)*\$'	
ехр	integer	М	1	This IE shall contain the expiration time after which the access_token is considered to be expired, corresponding to the standard "Expiration Time" claim described in IETF RFC 7519 [25], clause 4.1.4.	
consumerPlmnId	PlmnId	С	01	This IE shall be included if the NRF supports providing PLMN ID of the NF service consumer in the access token claims, to be interpreted for subject (sub IE), as specified in clause 13.4.1.2 of 3GPP TS 33.501 [15]. If an NF service producer that receives this IE in the token included in the authorization header does not understand this IE, it shall be ignored.	
producerPlmnId	Plmnld	С	01	This IE shall be included if the NRF supports providing PLMN ID of the NF service producer in the access token claims, to be interpretted for audience (aud IE), as specified in clause 13.4.1.2 of 3GPP TS 33.501 [15]. If an NF service producer that receives this IE in the token included in the authorization header does not understand this IE, it shall be ignored.	
producerSnssaiList	array(Snssai)	0	1N	This IE may be included if the NRF supports providing list of S-NSSAIs of the NF service producer in the access token claims.	
producerNsiList	array(string)	0	1N	This IE may be included if the NRF supports providing list of NSIs of the NF service producer in the access token claims.	

6.3.5.3 Simple data types and enumerations

6.3.5.3.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

6.3.5.3.2 Simple data types

There are no specific simple data types defined in this version of this API. For the re-used data types from other specifications see clause 6.3.5.1

6.3.5.3.3 Enumeration: GrantType

Table 6.3.5.3.3-1: Enumeration GrantType

Enumeration value	Description		
"client_credentials"	Represents the Client Credentials grant type.		

6.3.5.4 Data types describing alternative data types or combinations of data types

6.3.5.4.1 Type: Audience

Table 6.3.5.4.1-1: Definition of type Audience as a list of "non-exclusive alternatives"

Data type	Cardinality	Description	Applicability
NFType	1	NF type	
array(NfInstanceId)	1N	Array of NF Instance Ids	

Annex A (normative): OpenAPI specification

A.1 General

This Annex specifies the formal definition of the Nnrf Service API(s). It consists of OpenAPI 3.0.0 specifications, in YAML format.

This Annex takes precedence when being discrepant to other parts of the specification with respect to the encoding of information elements and methods within the API(s).

NOTE 1: The semantics and procedures, as well as conditions, e.g. for the applicability and allowed combinations of attributes or values, not expressed in the OpenAPI definitions but defined in other parts of the specification also apply.

Informative copies of the OpenAPI specification files contained in this 3GPP Technical Specification are available on the public 3GPP file server in the following locations (see clause 5B of the 3GPP TR 21.900 [31] for further information):

- https://www.3gpp.org/ftp/Specs/archive/OpenAPI/<Release>/, and
- https://www.3gpp.org/ftp/Specs/<Plenary>/<Release>/OpenAPI/.

NOTE 2: To fetch the OpenAPI specification file after CT#83 plenary meeting for Release 15 in the above links <Plenary> must be replaced with the date the CT Plenary occurs, in the form of year-month (yyyy-mm), e.g. for CT#83 meeting <Plenary> must be replaced with value "2019-03" and <Release> must be replaced with value "Rel-15".

A.2 Nnrf_NFManagement API

```
openapi: 3.0.0
info:
  version: '1.0.4'
  title: 'NRF NFManagement Service'
  description: |
   NRF NFManagement Service.
    © 2020, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
   All rights reserved.
   url: '{apiRoot}/nnrf-nfm/v1'
    variables:
      apiRoot:
        default: https://example.com
        description: apiRoot as defined in clause 4.4 of 3GPP TS 29.501
security:
  - {}
  - oAuth2ClientCredentials:
      - nnrf-nfm
paths:
  /nf-instances:
      summary: Retrieves a collection of NF Instances
      operationId: GetNFInstances
      tags:
        - NF Instances (Store)
      parameters:
        - name: nf-type
          in: query
         description: Type of NF
          required: false
            $ref: '#/components/schemas/NFType'
        - name: limit
          in: query
          description: How many items to return at one time
          required: false
          schema:
            type: integer
      responses:
```

```
'200':
          description: Expected response to a valid request
          content:
            application/3gppHal+json:
              schema:
                type: object
                properties:
                  _links:
                    type: object
                    description: 'List of the URI of NF instances. It has two members whose names
are item and self. The item one contains an array of URIs.'
                    additionalProperties:
                      $ref: 'TS29571_CommonData.yaml#/components/schemas/LinksValueSchema'
                minProperties: 1
        '400':
          $ref: 'TS29571 CommonData.vaml#/components/responses/400'
        '401':
          $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
          $ref: 'TS29571_CommonData.yaml#/components/responses/403'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
        '406':
          $ref: 'TS29571_CommonData.yaml#/components/responses/406'
        '411':
          $ref: 'TS29571_CommonData.yaml#/components/responses/411'
        '413':
          $ref: 'TS29571_CommonData.yaml#/components/responses/413'
        '415':
          $ref: 'TS29571 CommonData.yaml#/components/responses/415'
        '429':
          $ref: 'TS29571_CommonData.yaml#/components/responses/429'
        500:
          $ref: 'TS29571_CommonData.yaml#/components/responses/500'
        '501':
          $ref: 'TS29571_CommonData.yaml#/components/responses/501'
          $ref: 'TS29571 CommonData.vaml#/components/responses/503'
        default:
          $ref: 'TS29571_CommonData.yaml#/components/responses/default'
      summary: Discover communication options supported by NRF for NF Instances
      operationId: OptionsNFInstances
      tags:
        - NF Instances (Store)
      responses:
        '200':
          description: OK
          headers:
           Accept-Encoding:
             description: Accept-Encoding, described in IETF RFC 7694
             schema:
               type: string
        '400':
          $ref: 'TS29571_CommonData.yaml#/components/responses/400'
        '401':
          $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
          $ref: 'TS29571_CommonData.yaml#/components/responses/403'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
        '405':
          $ref: 'TS29571_CommonData.yaml#/components/responses/405'
        '429':
          $ref: 'TS29571_CommonData.yaml#/components/responses/429'
        '500':
          $ref: 'TS29571_CommonData.yaml#/components/responses/500'
        501:
          $ref: 'TS29571_CommonData.yaml#/components/responses/501'
        '503':
          $ref: 'TS29571_CommonData.yaml#/components/responses/503'
        default:
          $ref: 'TS29571_CommonData.yaml#/components/responses/default'
  /nf-instances/{nfInstanceID}:
      summary: Read the profile of a given NF Instance
      operationId: GetNFInstance
      tags:
```

```
- NF Instance ID (Document)
parameters:
  - name: nfInstanceID
    in: path
    description: Unique ID of the NF Instance
    required: true
    schema:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
responses:
  '200':
   description: Expected response to a valid request
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/NFProfile'
  '400':
    $ref: 'TS29571_CommonData.yaml#/components/responses/400'
  '401':
    $ref: 'TS29571_CommonData.yaml#/components/responses/401'
  '403':
    $ref: 'TS29571_CommonData.yaml#/components/responses/403'
  '404':
    $ref: 'TS29571_CommonData.yaml#/components/responses/404'
    $ref: 'TS29571 CommonData.vaml#/components/responses/406'
  '411':
    $ref: 'TS29571_CommonData.yaml#/components/responses/411'
    $ref: 'TS29571_CommonData.yaml#/components/responses/413'
  '415':
    $ref: 'TS29571_CommonData.yaml#/components/responses/415'
    $ref: 'TS29571_CommonData.yaml#/components/responses/429'
  '500':
    $ref: 'TS29571_CommonData.yaml#/components/responses/500'
  '501':
    $ref: 'TS29571_CommonData.yaml#/components/responses/501'
  '503':
    $ref: 'TS29571_CommonData.yaml#/components/responses/503'
  default:
    $ref: 'TS29571_CommonData.yaml#/components/responses/default'
summary: Register a new NF Instance
operationId: RegisterNFInstance
tags:
  - NF Instance ID (Document)
parameters:

    name: nfInstanceID

    in: path
    required: true
    description: Unique ID of the NF Instance to register
    schema:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
  - name: Content-Encoding
    in: header
    description: Content-Encoding, described in IETF RFC 7231
    schema:
     type: string
requestBody:
  content:
    application/json:
      schema:
        $ref: '#/components/schemas/NFProfile'
 required: true
responses:
  '200':
    description: OK (Profile Replacement)
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/NFProfile'
    headers:
      Accept-Encoding:
        description: Accept-Encoding, described in IETF RFC 7694
        schema:
          type: string
  '201':
    description: Expected response to a valid request
```

```
content:
           application/json:
             schema:
               $ref: '#/components/schemas/NFProfile'
         headers:
           Location:
             description: 'Contains the URI of the newly created resource, according to the
required: true
             schema:
               type: string
           Accept-Encoding:
             description: Accept-Encoding, described in IETF RFC 7694
               type: string
        '400':
         $ref: 'TS29571_CommonData.yaml#/components/responses/400'
        '401':
         $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
         $ref: 'TS29571 CommonData.yaml#/components/responses/403'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
         $ref: 'TS29571 CommonData.vaml#/components/responses/411'
        '413':
         $ref: 'TS29571_CommonData.yaml#/components/responses/413'
         $ref: 'TS29571_CommonData.yaml#/components/responses/415'
        '429':
         $ref: 'TS29571_CommonData.yaml#/components/responses/429'
         $ref: 'TS29571_CommonData.yaml#/components/responses/500'
        '501':
         $ref: 'TS29571_CommonData.yaml#/components/responses/501'
        '503':
         $ref: 'TS29571_CommonData.yaml#/components/responses/503'
        default:
         $ref: 'TS29571_CommonData.yaml#/components/responses/default'
   patch:
      summary: Update NF Instance profile
     operationId: UpdateNFInstance
     tags:
        - NF Instance ID (Document)
     parameters:
        - name: nfInstanceID
         in: path
         required: true
         description: Unique ID of the NF Instance to update
           $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
      requestBody:
        content:
         application/json-patch+json:
           schema:
             type: array
             items:
               $ref: 'TS29571_CommonData.yaml#/components/schemas/PatchItem'
             minItems: 1
       required: true
      responses:
        '200':
         description: Expected response to a valid request
         content:
           application/json:
             schema:
               $ref: '#/components/schemas/NFProfile'
         description: Expected response with empty body
        '400':
          $ref: 'TS29571_CommonData.yaml#/components/responses/400'
        '403':
         $ref: 'TS29571_CommonData.yaml#/components/responses/403'
        '404':
         $ref: 'TS29571_CommonData.yaml#/components/responses/404'
        '411':
         $ref: 'TS29571_CommonData.yaml#/components/responses/411'
        '413':
```

```
$ref: 'TS29571_CommonData.yaml#/components/responses/413'
        '415':
         $ref: 'TS29571_CommonData.yaml#/components/responses/415'
        '429':
         $ref: 'TS29571_CommonData.yaml#/components/responses/429'
         $ref: 'TS29571_CommonData.yaml#/components/responses/500'
        501:
         $ref: 'TS29571_CommonData.yaml#/components/responses/501'
        '503':
         $ref: 'TS29571_CommonData.yaml#/components/responses/503'
        default:
         \verb| $ref: 'TS29571_CommonData.yaml#/components/responses/default'| \\
    delete:
      summary: Deregisters a given NF Instance
      operationId: DeregisterNFInstance
      tags:
        - NF Instance ID (Document)
     parameters:
        - name: nfInstanceID
         in: path
         required: true
          description: Unique ID of the NF Instance to deregister
         schema:
           $ref: 'TS29571 CommonData.vaml#/components/schemas/NfInstanceId'
      responses:
        '204':
         description: Expected response to a successful deregistration
         $ref: 'TS29571 CommonData.vaml#/components/responses/400'
        '401':
         $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
         $ref: 'TS29571 CommonData.yaml#/components/responses/403'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
         $ref: 'TS29571_CommonData.yaml#/components/responses/411'
        '429':
          $ref: 'TS29571_CommonData.yaml#/components/responses/429'
        '500':
         $ref: 'TS29571_CommonData.yaml#/components/responses/500'
        '501':
         $ref: 'TS29571_CommonData.yaml#/components/responses/501'
         $ref: 'TS29571_CommonData.yaml#/components/responses/503'
        default:
         \verb| $ref: 'TS29571_CommonData.yaml\#/components/responses/default'| \\
  /subscriptions:
     summary: Create a new subscription
      operationId: CreateSubscription
        - Subscriptions (Collection)
     requestBody:
       content:
         application/json:
            schema:
              $ref: '#/components/schemas/SubscriptionData'
       required: true
      responses:
        '201':
         description: Expected response to a valid request
         content:
            application/json:
              schema:
                $ref: '#/components/schemas/SubscriptionData'
         headers:
            Location:
              description: 'Contains the URI of the newly created resource, according to the
structure: {apiRoot}/nnrf-nfm/v1/subscriptions/{subscriptionId}'
              required: true
              schema:
                type: string
        '400':
          $ref: 'TS29571_CommonData.yaml#/components/responses/400'
         $ref: 'TS29571_CommonData.yaml#/components/responses/401'
```

'403':

```
$ref: 'TS29571_CommonData.yaml#/components/responses/403'
      '404':
       $ref: 'TS29571_CommonData.yaml#/components/responses/404'
      '411':
       $ref: 'TS29571_CommonData.yaml#/components/responses/411'
      '413':
       $ref: 'TS29571_CommonData.yaml#/components/responses/413'
      '415':
       $ref: 'TS29571_CommonData.yaml#/components/responses/415'
       $ref: 'TS29571_CommonData.yaml#/components/responses/429'
      500:
       $ref: 'TS29571_CommonData.yaml#/components/responses/500'
       $ref: 'TS29571_CommonData.yaml#/components/responses/501'
      '503':
       $ref: 'TS29571_CommonData.yaml#/components/responses/503'
     default:
       $ref: 'TS29571_CommonData.yaml#/components/responses/default'
   callbacks:
     onNFStatusEvent:
        '{$request.body#/nfStatusNotificationUri}':
         post:
           parameters:
              - name: Content-Encoding
               in: header
               description: Content-Encoding, described in IETF RFC 7231
               schema:
                 type: string
           requestBody:
             description: Notification Payload
              content:
                application/json:
                 schema:
                   $ref: '#/components/schemas/NotificationData'
           responses:
              '204':
               description: Expected response to a successful callback processing
               headers:
                 Accept-Encoding:
                   description: Accept-Encoding, described in IETF RFC 7694
                   schema:
                     type: string
              '400':
               $ref: 'TS29571_CommonData.yaml#/components/responses/400'
              '401':
                $ref: 'TS29571_CommonData.yaml#/components/responses/401'
              '403':
               $ref: 'TS29571_CommonData.yaml#/components/responses/403'
              '404':
               $ref: 'TS29571_CommonData.yaml#/components/responses/404'
              14111:
                $ref: 'TS29571_CommonData.yaml#/components/responses/411'
               $ref: 'TS29571_CommonData.yaml#/components/responses/413'
              '415':
                $ref: 'TS29571_CommonData.yaml#/components/responses/415'
               $ref: 'TS29571_CommonData.yaml#/components/responses/429'
              '500':
                $ref: 'TS29571_CommonData.yaml#/components/responses/500'
                $ref: 'TS29571_CommonData.yaml#/components/responses/501'
              503:
                $ref: 'TS29571_CommonData.yaml#/components/responses/503'
              default:
               $ref: 'TS29571_CommonData.yaml#/components/responses/default'
/subscriptions/{subscriptionID}:
 patch:
   summary: Updates a subscription
   operationId: UpdateSubscription
   tags:
     - Subscription ID (Document)
   parameters:
     - name: subscriptionID
       in: path
       required: true
```

```
description: Unique ID of the subscription to update
      schema:
       type: string
       pattern: '^([0-9]{5,6}-)?[^-]+$'
  requestBody:
   content:
     application/json-patch+json:
       schema:
          type: array
            $ref: 'TS29571_CommonData.yaml#/components/schemas/PatchItem'
   required: true
  responses:
    '200':
     description: Expected response to a valid request
     content:
        application/json:
          schema:
           $ref: '#/components/schemas/SubscriptionData'
    '204':
     description: No Content
    '400':
      $ref: 'TS29571_CommonData.yaml#/components/responses/400'
     $ref: 'TS29571 CommonData.vaml#/components/responses/403'
    '404':
     $ref: 'TS29571_CommonData.yaml#/components/responses/404'
    '411':
     $ref: 'TS29571_CommonData.yaml#/components/responses/411'
    '413':
     $ref: 'TS29571_CommonData.yaml#/components/responses/413'
     $ref: 'TS29571 CommonData.yaml#/components/responses/415'
    '429':
      $ref: 'TS29571_CommonData.yaml#/components/responses/429'
    '500':
     $ref: 'TS29571_CommonData.yaml#/components/responses/500'
    '501':
     $ref: 'TS29571_CommonData.yaml#/components/responses/501'
    '503':
      $ref: 'TS29571_CommonData.yaml#/components/responses/503'
   default:
     $ref: 'TS29571_CommonData.yaml#/components/responses/default'
delete:
  summary: Deletes a subscription
  operationId: RemoveSubscription
  taqs:
    - Subscription ID (Document)
  parameters:
    - name: subscriptionID
     in: path
     required: true
     description: Unique ID of the subscription to remove
       type: string
       pattern: '^([0-9]{5,6}-)?[^-]+$'
  responses:
    '204':
     description: Expected response to a successful subscription removal
     $ref: 'TS29571_CommonData.yaml#/components/responses/400'
    '401':
     $ref: 'TS29571_CommonData.yaml#/components/responses/401'
    '403':
     $ref: 'TS29571_CommonData.yaml#/components/responses/403'
    '404':
     $ref: 'TS29571_CommonData.yaml#/components/responses/404'
    '411':
     $ref: 'TS29571 CommonData.yaml#/components/responses/411'
    '413':
      $ref: 'TS29571_CommonData.yaml#/components/responses/413'
    '415':
     $ref: 'TS29571_CommonData.yaml#/components/responses/415'
    '429':
     $ref: 'TS29571_CommonData.yaml#/components/responses/429'
      $ref: 'TS29571_CommonData.yaml#/components/responses/500'
    '501':
```

```
$ref: 'TS29571_CommonData.yaml#/components/responses/501'
          $ref: 'TS29571_CommonData.yaml#/components/responses/503'
        default:
          $ref: 'TS29571_CommonData.yaml#/components/responses/default'
components:
 securitySchemes:
    oAuth2ClientCredentials:
      type: oauth2
      flows:
       clientCredentials:
          tokenUrl: '/oauth2/token'
          scopes:
            nnrf-nfm: Access to the Nnrf_NFManagement API
 schemas:
   NFProfile:
      type: object
      required:
       - nfInstanceId
        - nfType
        - nfStatus
      anyOf:
        - required: [ fqdn ]
- required: [ ipv4Addresses ]
        - required: [ ipv6Addresses ]
      properties:
        nfInstanceId:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
        nfType:
         $ref: '#/components/schemas/NFType'
        nfStatus:
         $ref: '#/components/schemas/NFStatus'
        heartBeatTimer:
         type: integer
        plmnList:
          type: array
          items:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
          minItems: 1
        sNssais:
          type: array
          items:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
          minItems: 1
        perPlmnSnssaiList:
          type: array
          items:
            $ref: '#/components/schemas/PlmnSnssai'
          minItems: 1
        nsiList:
          type: array
          items:
            type: string
          minItems: 1
        fqdn:
          $ref: '#/components/schemas/Fqdn'
        interPlmnFqdn:
          $ref: '#/components/schemas/Fqdn'
        ipv4Addresses:
          type: array
          items:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
          minItems: 1
        ipv6Addresses:
          type: array
          items:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Addr'
          minItems: 1
        allowedPlmns:
          type: array
          items:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
          minItems: 1
        allowedNfTypes:
          type: array
            $ref: '#/components/schemas/NFType'
          minItems: 1
```

```
allowedNfDomains:
     type: array
     items:
       type: string
     minItems: 1
   allowedNssais:
     type: array
     items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
     minItems: 1
   priority:
     type: integer
     minimum: 0
     maximum: 65535
    capacity:
     type: integer
     minimum: 0
     maximum: 65535
   load:
     type: integer
     minimum: 0
     maximum: 100
    locality:
     type: string
    udrInfo:
     $ref: '#/components/schemas/UdrInfo'
    udmInfo:
     $ref: '#/components/schemas/UdmInfo'
    ausfInfo:
     $ref: '#/components/schemas/AusfInfo'
    amfInfo:
     $ref: '#/components/schemas/AmfInfo'
    smfInfo:
     $ref: '#/components/schemas/SmfInfo'
    upfInfo:
      $ref: '#/components/schemas/UpfInfo'
    pcfInfo:
     $ref: '#/components/schemas/PcfInfo'
   bsfInfo:
     $ref: '#/components/schemas/BsfInfo'
    chfInfo:
     $ref: '#/components/schemas/ChfInfo'
   nrfInfo:
     $ref: '#/components/schemas/NrfInfo'
   customInfo:
     type: object
    recoveryTime:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
    nfServicePersistence:
     type: boolean
     default: false
   nfServices:
     type: array
      items:
       $ref: '#/components/schemas/NFService'
     minItems: 1
   nfProfileChangesSupportInd:
     type: boolean
     default: false
     writeOnly: true
   nfProfileChangesInd:
     type: boolean
     default: false
     readOnly: true
    defaultNotificationSubscriptions:
      type: array
      items:
       $ref: '#/components/schemas/DefaultNotificationSubscription'
NFService:
  type: object
  required:
    - serviceInstanceId
    - serviceName
   - versions
    - scheme
    - nfServiceStatus
 properties:
   serviceInstanceId:
```

```
type: string
    serviceName:
     $ref: '#/components/schemas/ServiceName'
    versions:
      type: array
      items:
        $ref: '#/components/schemas/NFServiceVersion'
     minItems: 1
    scheme:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/UriScheme'
    nfServiceStatus:
     $ref: '#/components/schemas/NFServiceStatus'
    fqdn:
      $ref: '#/components/schemas/Fqdn'
    interPlmnFqdn:
     $ref: '#/components/schemas/Fqdn'
    ipEndPoints:
      type: array
     items:
        $ref: '#/components/schemas/IpEndPoint'
     minItems: 1
    apiPrefix:
      type: string
    defaultNotificationSubscriptions:
     type: array
      items:
        $ref: '#/components/schemas/DefaultNotificationSubscription'
     minItems: 1
    allowedPlmns:
     type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
     minItems: 1
    allowedNfTypes:
      type: array
      items:
        $ref: '#/components/schemas/NFType'
     minItems: 1
    allowedNfDomains:
     type: array
      items:
       type: string
     minItems: 1
    allowedNssais:
      type: array
     items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
     minItems: 1
    priority:
     type: integer
     minimum: 0
     maximum: 65535
    capacity:
      type: integer
     minimum: 0
     maximum: 65535
    load:
     type: integer
     minimum: 0
     maximum: 100
    {\tt recoveryTime:}
     $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
    chfServiceInfo:
     $ref: '#/components/schemas/ChfServiceInfo'
    supportedFeatures:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/SupportedFeatures'
NFType:
  anyOf:
    - type: string
     enum:
        - NRF
        - UDM
        - AMF
        - SMF
        - AUSF
        - NEF
        - PCF
        - SMSF
```

```
- NSSF
        - UDR
        - LMF
        - GMLC
        - 5G_EIR
        - SEPP
        - UPF
        - N3IWF
        - AF
        - UDSF
        - BSF
        - CHF
       - NWDAF
    - type: string
Fqdn:
 type: string
IpEndPoint:
  type: object
  properties:
   ipv4Address:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
    ipv6Address:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Addr'
    transport:
     $ref: '#/components/schemas/TransportProtocol'
    port:
     type: integer
     minimum: 0
     maximum: 65535
SubscriptionData:
  type: object
  required:
    - nfStatusNotificationUri
    - subscriptionId
  properties:
   nfStatusNotificationUri:
     type: string
    subscrCond:
     oneOf:
        - $ref: '#/components/schemas/NfInstanceIdCond'
        - $ref: '#/components/schemas/NfTypeCond'
        - $ref: '#/components/schemas/ServiceNameCond'
        - $ref: '#/components/schemas/AmfCond'
        - $ref: '#/components/schemas/GuamiListCond'
        - $ref: '#/components/schemas/NetworkSliceCond'
        - $ref: '#/components/schemas/NfGroupCond
    subscriptionId:
     type: string
      pattern: '^([0-9]{5,6}-)?[^-]+$'
     readOnly: true
    validityTime:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
    reqNotifEvents:
      type: array
      items:
        $ref: '#/components/schemas/NotificationEventType'
     minItems: 1
    plmnId:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
    notifCondition:
       $ref: '#/components/schemas/NotifCondition'
    reqNfType:
     $ref: '#/components/schemas/NFType'
    reaNfFadn:
     $ref: '#/components/schemas/Fqdn'
    reqSnssais:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
     minItems: 1
NfInstanceIdCond:
 type: object
 required:
    - nfInstanceId
  properties:
    nfInstanceId:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
NfTypeCond:
```

```
type: object
  required:

    nfType

  not:
   required: [ nfGroupId ]
  properties:
   nfType:
      $ref: '#/components/schemas/NFType'
ServiceNameCond:
  type: object
  required:
    - serviceName
 properties:
    serviceName:
     $ref: '#/components/schemas/ServiceName'
AmfCond:
  type: object
  anyOf:
    - required: [ amfSetId ]
    - required: [ amfRegionId ]
  properties:
    amfSetId:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/AmfSetId'
    amfRegionId:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/AmfRegionId'
GuamiListCond:
  type: object
  required:
   - guamiList
 properties:
    guamiList:
      type: array
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Guami'
NetworkSliceCond:
  type: object
  required:
    - snssaiList
  properties:
    snssaiList:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
    nsiList:
      type: array
      items:
        type: string
NfGroupCond:
  type: object
  required:
    - nfType
    - nfGroupId
  properties:
    nfType:
     type: string
      enum:
        - UDM
        - AUSF
        - UDR
    nfGroupId:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/NfGroupId'
NotifCondition:
  type: object
  not:
    required: [ monitoredAttributes, unmonitoredAttributes ]
  properties:
    monitoredAttributes:
     type: array
      items:
        type: string
      minItems: 1
    unmonitoredAttributes:
      type: array
      items:
        type: string
      minItems: 1
UdrInfo:
  type: object
```

```
properties:
    groupId:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/NfGroupId'
    supiRanges:
     type: array
      items:
        $ref: '#/components/schemas/SupiRange'
     minItems: 1
    gpsiRanges:
      type: array
      items:
        $ref: '#/components/schemas/IdentityRange'
     minItems: 1
    externalGroupIdentifiersRanges:
     type: array
     items:
        $ref: '#/components/schemas/IdentityRange'
     minItems: 1
    supportedDataSets:
     type: array
      items:
        $ref: '#/components/schemas/DataSetId'
     minItems: 1
SupiRange:
 type: object
 properties:
    start:
     type: string
     pattern: '^[0-9]+$'
    end:
     type: string
     pattern: '^[0-9]+$'
   pattern:
     type: string
IdentityRange:
  type: object
 properties:
   start:
     type: string
     pattern: '^[0-9]+$'
    end:
     type: string
     pattern: '^[0-9]+$'
   pattern:
     type: string
DataSetId:
 anyOf:
    - type: string
     enum:
       - SUBSCRIPTION
       - POLICY
       - EXPOSURE
        - APPLICATION
    - type: string
UdmInfo:
  type: object
  properties:
   groupId:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/NfGroupId'
    supiRanges:
     type: array
      items:
       $ref: '#/components/schemas/SupiRange'
     minItems: 1
    gpsiRanges:
      type: array
      items:
        $ref: '#/components/schemas/IdentityRange'
     minItems: 1
    externalGroupIdentifiersRanges:
      type: array
      items:
        $ref: '#/components/schemas/IdentityRange'
     minItems: 1
    routingIndicators:
      type: array
      items:
        type: string
```

```
pattern: '^[0-9]{1,4}$'
      minItems: 1
AusfInfo:
  type: object
  properties:
    groupId:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/NfGroupId'
    supiRanges:
      type: array
      items:
        $ref: '#/components/schemas/SupiRange'
      minItems: 1
    routingIndicators:
      type: array
      items:
       type: string
        pattern: '^[0-9]{1,4}$'
      minItems: 1
AmfInfo:
  type: object
  required:
    - amfSetId
    - amfRegionId
    - guamiList
  properties:
    amfSetId:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/AmfSetId'
    amfRegionId:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/AmfRegionId'
    quamiList:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Guami'
      minItems: 1
    taiList:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Tai'
      minItems: 1
    taiRangeList:
      type: array
      items:
        $ref: '#/components/schemas/TaiRange'
      minItems: 1
    backupInfoAmfFailure:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Guami'
      minItems: 1
    backupInfoAmfRemoval:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Guami'
      minItems: 1
    n2InterfaceAmfInfo:
      $ref: '#/components/schemas/N2InterfaceAmfInfo'
SmfInfo:
  type: object
  required:
    - sNssaiSmfInfoList
  properties:
    sNssaiSmfInfoList:
     type: array
      items:
        $ref: '#/components/schemas/SnssaiSmfInfoItem'
      minItems: 1
    taiList:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Tai'
      minItems: 1
    taiRangeList:
      type: array
      items:
        $ref: '#/components/schemas/TaiRange'
      minItems: 1
    pgwFqdn:
      $ref: '#/components/schemas/Fqdn'
```

```
accessType:
     type: array
     items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/AccessType'
     minItems: 1
SnssaiSmfInfoItem:
 type: object
 required:
    - sNssai
    - dnnSmfInfoList
 properties:
    sNssai:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
    dnnSmfInfoList:
     type: array
     items:
        $ref: '#/components/schemas/DnnSmfInfoItem'
     minItems: 1
DnnSmfInfoItem:
 type: object
 required:
    - dnn
 properties:
   dnn:
     $ref: 'TS29571 CommonData.yaml#/components/schemas/Dnn'
UpfInfo:
 type: object
 required:
   - sNssaiUpfInfoList
 properties:
    sNssaiUpfInfoList:
     type: array
     items:
        $ref: '#/components/schemas/SnssaiUpfInfoItem'
     minItems: 1
    smfServingArea:
     type: array
     items:
        type: string
     minItems: 1
    interfaceUpfInfoList:
     type: array
     items:
        $ref: '#/components/schemas/InterfaceUpfInfoItem'
     minItems: 1
    iwkEpsInd:
     type: boolean
     default: false
    pduSessionTypes:
     type: array
     items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/PduSessionType'
     minItems: 1
SnssaiUpfInfoItem:
 type: object
 required:
    - sNssai
    - dnnUpfInfoList
 properties:
    sNssai:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
    dnnUpfInfoList:
     type: array
      items:
        $ref: '#/components/schemas/DnnUpfInfoItem'
     minItems: 1
DnnUpfInfoItem:
  type: object
  required:
    - dnn
 properties:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/Dnn'
    dnaiList:
      type: array
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Dnai'
     minItems: 1
```

```
pduSessionTypes:
     type: array
     items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/PduSessionType'
     minItems: 1
    ipv4AddressRanges:
     type: array
     items:
        $ref: '#/components/schemas/Ipv4AddressRange'
     minItems: 1
    ipv6PrefixRanges:
      type: array
      items:
        $ref: '#/components/schemas/Ipv6PrefixRange'
     minItems: 1
InterfaceUpfInfoItem:
  type: object
 required:
   - interfaceType
 properties:
    \verb|interfaceType:|\\
      $ref: '#/components/schemas/UPInterfaceType'
    ipv4EndpointAddresses:
     type: array
     items:
       $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
     minItems: 1
    ipv6EndpointAddresses:
      type: array
     items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Addr'
     minItems: 1
    endpointFqdn:
        $ref: '#/components/schemas/Fqdn'
   networkInstance:
     type: string
UPInterfaceType:
 anyOf:
    - type: string
     enum:
       - N3
        - N6
       - N9
    - type: string
PcfInfo:
 type: object
 properties:
    dnnList:
      type: array
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Dnn'
     minItems: 1
    supiRanges:
     type: array
     items:
        $ref: '#/components/schemas/SupiRange'
     minItems: 1
    rxDiamHost:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/DiameterIdentity'
    rxDiamRealm:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/DiameterIdentity'
BsfInfo:
 type: object
 properties:
    dnnList:
     type: array
       $ref: 'TS29571_CommonData.yaml#/components/schemas/Dnn'
     minItems: 1
    ipDomainList:
      type: array
      items:
       type: string
     minItems: 1
    ipv4AddressRanges:
      type: array
      items:
        $ref: '#/components/schemas/Ipv4AddressRange'
```

```
minItems: 1
          ipv6PrefixRanges:
              type: array
              items:
                   $ref: '#/components/schemas/Ipv6PrefixRange'
              minItems: 1
ChfInfo:
     type: object
     properties:
         supiRangeList:
              type: array
              items:
                   $ref: '#/components/schemas/SupiRange'
              minItems: 1
         gpsiRangeList:
              type: array
              items:
                   $ref: '#/components/schemas/IdentityRange'
              minItems: 1
         plmnRangeList:
              type: array
              items:
                   $ref: '#/components/schemas/PlmnRange'
              minItems: 1
Ipv4AddressRange:
     type: object
     properties:
         start:
                   $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
          end:
                   $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
Ipv6PrefixRange:
     type: object
     properties:
          start:
                   $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Prefix'
                   $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Prefix'
DefaultNotificationSubscription:
     type: object
     required:
         - notificationType
          - callbackUri
     properties:
         notificationType:
              $ref: '#/components/schemas/NotificationType'
          callbackUri:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/Uri'
          nlMessageClass:
              $ref: 'TS29518_Namf_Communication.yaml#/components/schemas/N1MessageClass'
         n2InformationClass:
              \verb| $ref: 'TS29518_Namf_Communication.yaml#/components/schemas/N2InformationClass'| | TS29518_Namf_Communication.yaml#/components/schemas/N2InformationClass'| | TS29518_Namf_CommunicationClass'| | TS29518_Namf_Commu
NotificationType:
     anyOf:
          - type: string
              enum:
                   - N1_MESSAGES
                   - N2_INFORMATION
                   - LOCATION_NOTIFICATION
                  - DATA REMOVAL NOTIFICATION
                   - DATA_CHANGE_NOTIFICATION
          - type: string
TransportProtocol:
     anyOf:
          - type: string
             enum:
                  - TCP
          - type: string
NotificationEventType:
     anyOf:
          - type: string
              enum:
                  - NF_REGISTERED
                   - NF_DEREGISTERED
                  - NF_PROFILE_CHANGED
          - type: string
NotificationData:
     type: object
```

```
required:
    - event
- nfInstanceUri
  allOf:
    # Condition: If 'event' takes value 'NF_PROFILE_CHANGED',
    # then either 'nfProfile' or 'profileChanges' (but not both) must be present
    - anyOf:
      - not:
         properties:
            event:
              type: string
              enum:
                - NF_PROFILE_CHANGED
      - oneOf:
          - required: [ nfProfile ]
          - required: [ profileChanges ]
    # Condition: If 'event' takes value 'NF_REGISTERED',
    # then 'nfProfile' must be present
    - anyOf:
      - not:
          properties:
            event:
              type: string
               - NF_REGISTERED
      - required: [ nfProfile ]
  properties:
      $ref: '#/components/schemas/NotificationEventType'
    nfInstanceUri:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Uri'
    nfProfile:
      allOf:
        - $ref: '#/components/schemas/NFProfile'
        - not:
            required: [ interPlmnFqdn ]
        - not:
           required: [ allowedPlmns ]
        - not:
            required: [ allowedNfTypes ]
           required: [ allowedNfDomains ]
        - not:
            required: [ allowedNssais ]
        - properties:
            nfServices:
              type: array
              items:
                allOf:
                  - $ref: '#/components/schemas/NFService'
                      required: [ interPlmnFqdn ]
                  - not:
                      required: [ allowedPlmns ]
                  - not:
                      required: [ allowedNfTypes ]
                  - not:
                      required: [ allowedNfDomains ]
                  - not:
                      required: [ allowedNssais ]
    profileChanges:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/ChangeItem'
      minItems: 1
NFStatus:
  anyOf:
    - type: string
      enum:
        - REGISTERED
        - SUSPENDED
        - UNDISCOVERABLE
    - type: string
NFServiceVersion:
```

```
type: object
  required:
    - apiVersionInUri
    - apiFullVersion
  properties:
    apiVersionInUri:
      type: string
    apiFullVersion:
     type: string
    expiry:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
ServiceName:
  anyOf:
    - type: string
      enum:
       - nnrf-nfm
        - nnrf-disc
        - nudm-sdm
        - nudm-uecm
        - nudm-ueau
        - nudm-ee
        - nudm-pp
        - namf-comm
        - namf-evts
        - namf-mt
        - namf-loc
        - nsmf-pdusession
        - nsmf-event-exposure
        - nausf-auth
        - nausf-sorprotection
        - nausf-upuprotection
        - nnef-pfdmanagement
        - npcf-am-policy-control
        - npcf-smpolicycontrol
        - npcf-policyauthorization
        - npcf-bdtpolicycontrol
        - npcf-eventexposure
        - npcf-ue-policy-control
        - nsmsf-sms
        - nnssf-nsselection
        - nnssf-nssaiavailability
        - nudr-dr
        - nlmf-loc
        - n5g-eir-eic
        - nbsf-management
        - nchf-spendinglimitcontrol
        - nchf-convergedcharging
        - nnwdaf-eventssubscription
        - nnwdaf-analyticsinfo
    - type: string
N2InterfaceAmfInfo:
  type: object
  properties:
    ipv4EndpointAddress:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
      minItems: 1
    ipv6EndpointAddress:
      type: array
      items:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Addr'
      minItems: 1
    amfName:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/AmfName'
NFServiceStatus:
  anyOf:
    - type: string
      enum:
        - REGISTERED
        - SUSPENDED
        - UNDISCOVERABLE
    - type: string
TaiRange:
  type: object
  required:
    - plmnId
    - tacRangeList
```

```
properties:
    plmnId:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
    tacRangeList:
      type: array
      items:
        $ref: '#/components/schemas/TacRange'
      minItems: 1
TacRange:
  type: object
  properties:
    start:
      type: string
      pattern: '^([A-Fa-f0-9]{4}|[A-Fa-f0-9]{6})$'
     type: string
      pattern: '^([A-Fa-f0-9]{4}|[A-Fa-f0-9]{6})$'
    pattern:
     type: string
ChfServiceInfo:
  type: object
  not:
    required: [ primaryChfServiceInstance, secondaryChfServiceInstance ]
  properties:
    primaryChfServiceInstance:
     type: string
    secondaryChfServiceInstance:
     type: string
PlmnRange:
  type: object
  properties:
    start:
      type: string
      pattern: '^[0-9]{3}[0-9]{2,3}$'
    end:
      type: string
      pattern: '^[0-9]{3}[0-9]{2,3}$'
    pattern:
     type: string
NrfInfo:
  type: object
  properties:
    servedUdrInfo:
      type: object
      additionalProperties:
        $ref: '#/components/schemas/UdrInfo'
     minProperties: 1
    servedUdmInfo:
      type: object
      additionalProperties:
        $ref: '#/components/schemas/UdmInfo'
     minProperties: 1
    servedAusfInfo:
      type: object
      additionalProperties:
        $ref: '#/components/schemas/AusfInfo'
      minProperties: 1
    servedAmfInfo:
      type: object
      additionalProperties:
        $ref: '#/components/schemas/AmfInfo'
      minProperties: 1
    servedSmfInfo:
      type: object
      additionalProperties:
        $ref: '#/components/schemas/SmfInfo'
      minProperties: 1
    servedUpfInfo:
      type: object
      additionalProperties:
        $ref: '#/components/schemas/UpfInfo'
      minProperties: 1
    servedPcfInfo:
      type: object
      additionalProperties:
        $ref: '#/components/schemas/PcfInfo'
      minProperties: 1
    servedBsfInfo:
```

```
type: object
          additionalProperties:
            $ref: '#/components/schemas/BsfInfo'
          minProperties: 1
        servedChfInfo:
          type: object
          additionalProperties:
            $ref: '#/components/schemas/ChfInfo'
          minProperties: 1
    PlmnSnssai:
      type: object
      required:
        - plmnId
        - sNssaiList
      properties:
        plmnId:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
        sNssaiList:
          type: array
          items:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
          minItems: 1
externalDocs:
  description: 3GPP TS 29.510 V15.7.0; 5G System; Network Function Repository Services; Stage 3
  url: 'http://www.3gpp.org/ftp/Specs/archive/29_series/29.510/'
```

A.3 Nnrf_NFDiscovery API

```
openapi: 3.0.0
  version: '1.0.4'
  title: 'NRF NFDiscovery Service'
  description:
   NRF NFDiscovery Service.
    © 2019, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
   All rights reserved.
servers:
  - url: '{apiRoot}/nnrf-disc/v1'
   variables:
      apiRoot:
        default: https://example.com
        description: apiRoot as defined in clause 4.4 of 3GPP TS 29.501
security:
  - {}
  - oAuth2ClientCredentials:
      - nnrf-disc
paths:
  /nf-instances:
   get:
      summary: Search a collection of NF Instances
      operationId: SearchNFInstances
      tags:
       - NF Instances (Store)
      parameters:
        - name: target-nf-type
          in: query
          description: Type of the target NF
          required: true
          schema:
            $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFType'
        - name: requester-nf-type
          in: query
          description: Type of the requester NF
          required: true
          schema:
           $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFType'
        - name: service-names
          in: query
          description: Names of the services offered by the NF
          schema:
            type: array
            items:
              $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/ServiceName'
            minItems: 1
            uniqueItems: true
          style: form
```

```
explode: false
- name: requester-nf-instance-fqdn
 in: query
 description: FQDN of the requester NF
 schema:
   $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/Fqdn'
- name: target-plmn-list
 in: query
 description: Id of the PLMN of the target NF
 content:
   application/json:
     schema:
       type: array
       items:
         $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
       minItems: 1
- name: requester-plmn-list
 in: query
 description: Id of the PLMN where the NF issuing the Discovery request is located
 content:
   application/json:
     schema:
       type: array
       items:
         $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
       minItems: 1
- name: target-nf-instance-id
 in: query
 description: Identity of the NF instance being discovered
 schema:
   $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
- name: target-nf-fqdn
 in: query
 description: FQDN of the NF instance being discovered
 schema:
   $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/Fqdn'
- name: hnrf-uri
 in: query
 description: Uri of the home NRF
 schema:
   $ref: 'TS29571_CommonData.yaml#/components/schemas/Uri'
- name: snssais
 in: query
 description: Slice info of the target NF
   application/json:
     schema:
       type: array
       items:
         $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
       minItems: 1
- name: requester-snssais
 in: query
 description: Slice info of the requester NF
 content:
   application/json:
     schema:
       type: array
       items:
         $ref: 'TS29571 CommonData.yaml#/components/schemas/Snssai'
       minItems: 1
- name: plmn-specific-snssai-list
 in: query
 description: PLMN specific Slice info of the target NF
 content:
   application/json:
     schema:
       type: array
       items:
         minItems: 1
- name: dnn
 in: query
 description: Dnn supported by the BSF, SMF or UPF
   $ref: 'TS29571_CommonData.yaml#/components/schemas/Dnn'
- name: nsi-list
 in: query
```

```
description: NSI IDs that are served by the services being discovered
 schema:
   type: array
   items:
     type: string
   minItems: 1
 style: form
 explode: false
- name: smf-serving-area
 in: query
 schema:
   type: string
- name: tai
 in: query
 description: Tracking Area Identity
 content:
   application/json:
     schema:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Tai'
- name: amf-region-id
 in: query
 description: AMF Region Identity
   $ref: 'TS29571_CommonData.yaml#/components/schemas/AmfRegionId'
- name: amf-set-id
 in: query
 description: AMF Set Identity
   $ref: 'TS29571_CommonData.yaml#/components/schemas/AmfSetId'
- name: quami
 in: query
 description: Guami used to search for an appropriate AMF
 content:
   application/json:
     schema:
       $ref: 'TS29571_CommonData.yaml#/components/schemas/Guami'
- name: supi
 in: query
 description: SUPI of the user
 schema:
   $ref: 'TS29571_CommonData.yaml#/components/schemas/Supi'
- name: ue-ipv4-address
 in: query
 description: IPv4 address of the UE
   $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
- name: ip-domain
 in: query
 description: IP domain of the UE, which supported by BSF
   type: string
- name: ue-ipv6-prefix
 in: query
 description: IPv6 prefix of the UE
   $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Prefix'
- name: pgw-ind
 in: query
 description: Combined PGW-C and SMF or a standalone SMF
 schema:
   type: boolean
- name: pgw
 in: query
 description: PGW FQDN of a combined PGW-C and SMF
 schema:
   $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/Fqdn'
- name: gpsi
 in: query
 description: GPSI of the user
 schema:
   $ref: 'TS29571_CommonData.yaml#/components/schemas/Gpsi'
- name: external-group-identity
 in: query
 description: external group identifier of the user
   $ref: 'TS29503_Nudm_SDM.yaml#/components/schemas/ExtGroupId'
- name: data-set
 in: query
```

```
description: data set supported by the NF
   $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/DataSetId'
- name: routing-indicator
 in: query
 description: routing indicator in SUCI
 schema:
   type: string
   pattern: '^[0-9]{1,4}$'
- name: group-id-list
 in: query
 description: Group IDs of the NFs being discovered
 schema:
   type: array
   items:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/NfGroupId'
   minItems: 1
 style: form
 explode: false
- name: dnai-list
 in: query
 description: Data network access identifiers of the NFs being discovered
   type: array
   items:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/Dnai'
   minItems: 1
 style: form
 explode: false
- name: pdu-session-types
 in: query
 description: list of PDU Session Type required to be supported by the target NF
 schema:
   type: array
   items:
     $ref: 'TS29571_CommonData.yaml#/components/schemas/PduSessionType'
   minItems: 1
 style: form
 explode: false
- name: supported-features
 in: query
 description: Features required to be supported by the target NF
 schema:
   $ref: 'TS29571_CommonData.yaml#/components/schemas/SupportedFeatures'
- name: upf-iwk-eps-ind
 in: query
 description: UPF supporting interworking with EPS or not
 schema:
   type: boolean
- name: chf-supported-plmn
 in: query
 description: PLMN ID supported by a CHF
 content:
   application/json:
     schema:
       $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
- name: preferred-locality
 description: preferred target NF location
 schema:
   type: string
- name: access-type
 in: query
 description: AccessType supported by the target NF
 schema:
   $ref: 'TS29571_CommonData.yaml#/components/schemas/AccessType'
- name: limit
 in: query
 description: Maximum number of NFProfiles to return in the response
 required: false
 schema:
   type: integer
   minimum: 1
- name: required-features
 in: query
 description: Features required to be supported by the target NF
 schema:
   type: array
```

```
$ref: 'TS29571_CommonData.yaml#/components/schemas/SupportedFeatures'
          minItems: 1
        style: form
        explode: false
      - name: complex-query
       in: query
       description: the complex query condition expression
        content:
          application/json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ComplexQuery'
      - name: max-payload-size
       in: query
       description: Maximum payload size of the response expressed in kilo octets
       required: false
       schema:
          type: integer
          maximum: 2000
         default: 124
      - name: If-None-Match
        in: header
        description: Validator for conditional requests, as described in IETF RFC 7232, 3.2
       schema:
         type: string
    responses:
      '200':
       description: Expected response to a valid request
       content:
         application/ison:
            schema:
             $ref: '#/components/schemas/SearchResult'
       headers:
          Cache-Control:
            description: Cache-Control containing max-age, described in IETF RFC 7234, 5.2
            schema:
             type: string
          ETag:
            description: Entity Tag containing a strong validator, described in IETF RFC 7232, 2.3
            schema:
             type: string
      '307':
       description: Temporary Redirect
       headers:
            description: 'The URI pointing to the resource located on the redirect target NRF'
            required: true
            schema:
              type: string
      '400':
       $ref: 'TS29571_CommonData.yaml#/components/responses/400'
       401':
        $ref: 'TS29571_CommonData.yaml#/components/responses/401'
      '403':
       $ref: 'TS29571_CommonData.yaml#/components/responses/403'
      '404':
       $ref: 'TS29571_CommonData.yaml#/components/responses/404'
      '406':
       $ref: 'TS29571_CommonData.yaml#/components/responses/406'
      '411':
       $ref: 'TS29571_CommonData.yaml#/components/responses/411'
      '413':
       $ref: 'TS29571_CommonData.yaml#/components/responses/413'
      '415':
       $ref: 'TS29571_CommonData.yaml#/components/responses/415'
      '429':
        $ref: 'TS29571_CommonData.yaml#/components/responses/429'
       $ref: 'TS29571 CommonData.yaml#/components/responses/500'
      '501':
        $ref: 'TS29571_CommonData.yaml#/components/responses/501'
       $ref: 'TS29571_CommonData.yaml#/components/responses/503'
      default:
       $ref: 'TS29571_CommonData.yaml#/components/responses/default'
securitySchemes:
 oAuth2ClientCredentials:
```

```
type: oauth2
    flows:
      clientCredentials:
        tokenUrl: '/oauth2/token'
        scopes:
         nnrf-disc: Access to the Nnrf_NFDiscovery API
schemas:
  SearchResult:
    type: object
    required:
     - nfInstances
    properties:
     validityPeriod:
        type: integer
     nfInstances:
        type: array
        items:
          $ref: '#/components/schemas/NFProfile'
      nrfSupportedFeatures:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/SupportedFeatures'
  NFProfile:
    type: object
    required:
     - nfInstanceId
      - nfType
      - nfStatus
    properties:
      nfInstanceId:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
      nfType:
        $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFType'
      nfStatus:
        $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFStatus'
      plmnList:
        type: array
        items:
         $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
        minItems: 1
      sNssais:
        type: array
        items:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
        minItems: 1
      perPlmnSnssaiList:
        type: array
        items:
          $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/PlmnSnssai'
        minItems: 1
      nsiList:
        type: array
        items:
         type: string
        minItems: 1
        $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/Fqdn'
      ipv4Addresses:
        type: array
        items:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv4Addr'
        minItems: 1
      ipv6Addresses:
        type: array
        items:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Ipv6Addr'
        minTtems: 1
      capacity:
        type: integer
        minimum: 0
        maximum: 65535
      load:
        type: integer
        minimum: 0
       maximum: 100
      locality:
        type: string
      priority:
        type: integer
        minimum: 0
```

```
maximum: 65535
       udrInfo:
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/UdrInfo'
       udmInfo:
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/UdmInfo'
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/AusfInfo'
       amfInfo:
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/AmfInfo'
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/SmfInfo'
       upfInfo:
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/UpfInfo'
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/PcfInfo'
       bsfInfo:
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/BsfInfo'
       chfInfo:
        $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/ChfInfo'
       customInfo:
         type: object
       recoveryTime:
         $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
       nfServicePersistence:
         type: boolean
         default: false
       nfServices:
         type: array
         items:
           $ref: '#/components/schemas/NFService'
         minItems: 1
       defaultNotificationSubscriptions:
         type: array
         items:
           $ref:
'TS29510_Nnrf_NFManagement.yaml#/components/schemas/DefaultNotificationSubscription'
   NFService:
     type: object
     required:
       - serviceInstanceId
       - serviceName
       - versions
       - scheme
       - nfServiceStatus
     properties:
       serviceInstanceId:
         type: string
       serviceName:
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/ServiceName'
       versions:
         type: array
         items:
           $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFServiceVersion'
         minItems: 1
       scheme:
         $ref: 'TS29571_CommonData.yaml#/components/schemas/UriScheme'
       nfServiceStatus:
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFServiceStatus'
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/Fqdn'
       ipEndPoints:
         type: array
         items:
           $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/IpEndPoint'
         minTtems: 1
       apiPrefix:
         type: string
       defaultNotificationSubscriptions:
         type: array
         items:
           $ref:
'TS29510_Nnrf_NFManagement.yaml#/components/schemas/DefaultNotificationSubscription'
         minItems: 1
       capacity:
         type: integer
         minimum: 0
         maximum: 65535
       load:
```

```
type: integer
         minimum: 0
         maximum: 100
       priority:
         type: integer
         minimum: 0
         maximum: 65535
        recoveryTime:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
        chfServiceInfo:
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/ChfServiceInfo'
        supportedFeatures:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/SupportedFeatures'
externalDocs:
 description: 3GPP TS 29.510 V15.6.0; 5G System; Network Function Repository Services; Stage 3
 url: 'http://www.3gpp.org/ftp/Specs/archive/29_series/29.510/'
```

A.4 Nnrf_AccessToken API (NRF OAuth2 Authorization)

```
openapi: 3.0.0
info:
  version: '1.0.3'
  title: 'NRF OAuth2'
  description:
   NRF OAuth2 Authorization.
    © 2019, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
    All rights reserved.
paths:
  /oauth2/token:
   post:
      summary: Access Token Request
      operationId: AccessTokenRequest
      tags:
        - Access Token Request
      requestBody:
        content:
          application/x-www-form-urlencoded:
            schema:
              $ref: '#/components/schemas/AccessTokenReq'
        required: true
      responses:
        '200':
          description: Successful Access Token Request
            application/json:
              schema:
                $ref: '#/components/schemas/AccessTokenRsp'
          headers:
            Cache-Control:
              $ref: '#/components/headers/cache-control'
            Pragma:
             $ref: '#/components/headers/pragma'
          description: Temporary Redirect
        '400':
          description: Error in the Access Token Request
            application/ison:
              schema:
                $ref: '#/components/schemas/AccessTokenErr'
          headers:
            Cache-Control:
              $ref: '#/components/headers/cache-control'
            Pragma:
              $ref: '#/components/headers/pragma'
        '401':
          $ref: 'TS29571_CommonData.yaml#/components/responses/401'
        '403':
          $ref: 'TS29571_CommonData.yaml#/components/responses/403'
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
          $ref: 'TS29571_CommonData.yaml#/components/responses/411'
        '413':
          $ref: 'TS29571_CommonData.yaml#/components/responses/413'
        '415':
          $ref: 'TS29571_CommonData.yaml#/components/responses/415'
```

```
'429':
          $ref: 'TS29571_CommonData.yaml#/components/responses/429'
        '500':
          $ref: 'TS29571_CommonData.yaml#/components/responses/500'
        '501':
          $ref: 'TS29571_CommonData.yaml#/components/responses/501'
          $ref: 'TS29571_CommonData.yaml#/components/responses/503'
        default:
          $ref: 'TS29571_CommonData.yaml#/components/responses/default'
components:
  headers:
    cache-control:
      required: true
      schema:
       type: string
       enum:
         - no-store
   pragma:
      required: true
      schema:
        type: string
        enum:
         - no-cache
  schemas:
   AccessTokenReq:
      type: object
      required:
       - grant_type
       - nfInstanceId
       - scope
      properties:
       grant_type:
          type: string
          enum:
            - client_credentials
        nfInstanceId:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
        nfType:
          $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFType'
        targetNfType:
         $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFType'
        scope:
          type: string
          pattern: '^([a-zA-Z0-9_-]+)( [a-zA-Z0-9_-]+)*$'
        targetNfInstanceId:
         $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
        requesterPlmn:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
         $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
        targetSnssaiList:
          type: array
          items:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
          minItems: 1
        targetNsiList:
          type: array
          items:
            type: string
          minItems: 1
    AccessTokenRsp:
      type: object
      required:
        - access_token
        - token_type
      properties:
       access token:
          type: string
          description: JWS Compact Serialized representation of JWS signed JSON object
(AccessTokenClaims)
       token_type:
         type: string
          enum:
            - Bearer
        expires_in:
         type: integer
        scope:
```

```
pattern: '^([a-zA-Z0-9_-]+)( [a-zA-Z0-9_-]+)*$'
   AccessTokenClaims:
      type: object
      required:
       - iss
        - sub
       - aud
        - scope
        - exp
      properties:
        iss:
         $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
         $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
        aud:
          anyOf:
            -
- $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFType'
            - type: array
              items:
                $ref: 'TS29571_CommonData.yaml#/components/schemas/NfInstanceId'
              minItems: 1
        scope:
          type: string
          pattern: '^([a-zA-Z0-9_-]+)( [a-zA-Z0-9_-]+)*$'
        exp:
         type: integer
        consumerPlmnId:
         $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
        producerPlmnId:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
        producerSnssaiList:
          type: array
          items:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
          minItems: 1
       producerNsiList:
          type: array
          items:
            type: string
          minItems: 1
    AccessTokenErr:
      type: object
      required:
       - error
      properties:
        error:
          type: string
          enum:
           - invalid_request
            - invalid_client
           - invalid_grant
            - unauthorized_client
            - unsupported_grant_type
            - invalid_scope
        error_description:
          type: string
        error_uri:
          type: string
externalDocs:
  description: 3GPP TS 29.510 V15.5.0; 5G System; Network Function Repository Services; Stage 3
  url: 'http://www.3gpp.org/ftp/Specs/archive/29_series/29.510/'
```

Annex B (normative): NF Profile changes in NFRegister and NFUpdate (NF Profile Complete Replacement) responses

B.1 General

In the NFRegister and NFUpdate (NF Profile Complete Replacement) service operations, a NF Service Consumer may indicate to the NRF that it supports receiving NF Profile changes in the response from the NRF, by including the nfProfileChangesSupportInd attribute set to "true" in the NFProfile it registers to or replaces in the NRF.

The NRF may return NF Profile changes, instead of the complete NF Profile, in NFRegister or NFUpdate (NF Profile Complete Replacement) responses, if the NF Service Consumer indicated corresponding support in the request. When doing so, the NRF shall include in the NF Profile returned in the response:

- attributes that are mandatory to include in the NF Profile; if an optional IE is included (e.g. nfServices), attributes that are mandatory to include in this optional IE (e.g. serviceInstanceId) shall also be included;
- optional or conditional IEs that have been changed or added by the NRF; and
- the nfProfileChangesInd IE set to "true", indicating that the returned profile contains NF profile changes.

EXAMPLE 1: The NRF does not change the NF Profile received in the request.

The NRF response contains a NFProfile with just the following IEs:

- nfInstanceId, nfType, nfStatus; and
- nfProfileChangesInd IE set to "true".

EXAMPLE 2: The NRF modifies or adds the heartbeatTimer attribute to the NF Profile received in the request.

The NRF response contains a NFProfile with just the following IEs:

- nfInstanceId, nfType, nfStatus;
- heartbeatTimer with NRF chosen value;
- nfProfileChangesInd IE set to "true".

Annex C (informative): Change history

Date	Meeting	TDoc.	CR	Rev	Cat	Subject/Comment	New
2017-10	CT4#80	C4-175271				Initial draft	0.1.0
2017-10	CT4#80	C4-175395				Incorporation of agreed pCRs from CT4#80: C4- 175109, C4-175272, C4-175274, C4-175363	0.2.0
2017-12	CT4#81	C4-176438				Incorporation of agreed pCRs from CT4#81: C4- 176184, C4-176278, C4-176280, C4-176281, C4-	0.3.0
2018-01	CT4#82	C4-181392				Incorporation of agreed pCRs from CT4#82: C4- 181348, C4-181351	0.4.0
2018-03	CT4#83	C4-182435				Incorporation of agreed pCRs from CT4#83: C4- 182098, C4-182327, C4-182328, C4-182365, C4-	0.5.0
						182413	
2018-04	CT4#84	C4-183517				Incorporation of agreed pCRs from CT4#84: C4- 183450, C4-183451, C4-183452, C4-183487, C4- 183488, C4-183490, C4-183491	0.6.0
2018-05	CT4#85	C4-184625				Incorporation of agreed pCRs from CT4#85: C4- 184207, C4-184208, C4-184280, C4-184466, C4-184469, C4- 184478, C4-184517, C4-184519, C4-184545, C4- 184595, C4-184596, C4-184597, C4-184600, C4- 184615, C4-184616, C4-184626	0.7.0
2018-06	CT#80	CP-181105				Presented for information and approval	1.0.0
2018-06	CT#80					Approved in CT#80.	15.0.0
2018-09	CT#81	CP-182012	0001	2	F 	Implementing the Indirect Delivery method for the GET method to retrieve NF instances	15.1.0
2018-09	CT#81	CP-182093	0003	3	F	Defining the range of the priority and capacity attributes and aligning their usage with SRV RFC 2782	15.1.0
2018-09	CT#81	CP-182060	0004	-	F	Corrections to descriptions, references and SUPI parameter in Discovery Request	15.1.0
2018-09	CT#81	CP-182047	0006	2	F	SubscriptionData	15.1.0
2018-09	CT#81	CP-182045	0008	2	F	Error Cases	15.1.0
2018-09	CT#81	CP-182060	0009	2	F	Heart Beat Procedure	15.1.0
2018-09	CT#81	CP-182060	0010	1	В	Vendor-Specific NF Types	15.1.0
2018-09	CT#81	CP-182044	0011	3	F	Presence condition of service discovery query parameters	15.1.0
2018-09	CT#81	CP-182060	0012	4	F	Description of Inter-PLMN scenarios	15.1.0
2018-09	CT#81	CP-182060	0013	1	F	NF Service Versions	15.1.0
2018-09	CT#81	CP-182060	0014	1	В	Custom Headers	15.1.0
2018-09	CT#81	CP-182060	0015	1	F	Overall Clean-up	15.1.0
2018-09	CT#81	CP-182060	0016	-	<u>F</u>	Formatting of query parameters	15.1.0
2018-09	CT#81	CP-182060	0017	-	F	Editorial corrections	15.1.0
2018-09	CT#81	CP-182060	0018	2	F	Backup AMF	15.1.0
2018-09	CT#81	CP-182060 CP-182060	0020	1 -	B F	NF Service Names	15.1.0 15.1.0
2018-09 2018-09	CT#81	CP-182060 CP-182060	0023	3		CHF as service consumer	15.1.0
2018-09	CT#81	CP-182060	0024	2	<u>В</u> В	Hierarchical NF discovery in recursion mode Hierarchical NF discovery in iteration mode	15.1.0
2018-09	CT#81	CP-182060	0025	-	F	Correction of Allowed NF Domains	15.1.0
2018-09	CT#81	CP-182060	0020		F	Correction of BsfInfo data type	15.1.0
2018-09	CT#81	CP-182161	0027	1	F	IPv6 Prefix for NF / NF Service Address	15.1.0
2018-09	CT#81	CP-182060	0030	1	<u>.</u> В	NF Set Id	15.1.0
2018-09	CT#81	CP-182060	0031	1	F	URI Scheme	15.1.0
2018-09	CT#81	CP-182060	0032	2	В	NRF service registration	15.1.0
2018-09	CT#81	CP-182060	0034	2	F	Discovery of combined SMF and PGW-C	15.1.0
2018-09	CT#81	CP-182163	0035	3	F	Support TAI Range for AMF/SMF and SUPI Range for PCF	15.1.0
2018-09	CT#81	CP-182060	0036	1	F	SUPI Range for PCF	15.1.0
2018-09	CT#81	CP-182164	0037	3	F	Scope for OAuth 2.0 Access Token Request	15.1.0
2018-09	CT#81	CP-182060	0039	1	F	Corrections to NotificationData and "supi" parameter in Discovery Request	15.1.0
2018-09	CT#81	CP-182060	0040	1	F	Group ID in Discovery Request	15.1.0
2018-09	CT#81	CP-182060	0041	1	F	Registering multiple Routing Indicators	15.1.0
2018-09	CT#81	CP-182060	0045	-	<u>F</u>	Description of Structured data types	15.1.0
2018-09	CT#81	CP-182060	0046	1	<u>F</u>	Service names in Discovery Request	15.1.0
2018-09	CT#81	CP-182060	0047	1	F	Resource structure presentation	15.1.0
2018-09	CT#81	CP-182060	0048	-	В	Default Notifications for UDM	15.1.0
2018-09	CT#81	CP-182060	0049	-	F	Cell ID in Discovery Request	15.1.0
2018-09	CT#81	CP-182046	0050	2	<u>F</u> F	NRF Subscription Data	15.1.0
	CT#81	CP-182060 CP-182060	0051 0052	1	F	AMF Discovery by 5G-AN Detecting NF Failure and Restart using the NRF	15.1.0 15.1.0
2018-09	CT#91	1 2 1 T 1 OZ UOU	10032				10.1.0
2018-09 2018-09	CT#81			2	R	NRF Subscription Lifespan	15 1 0
2018-09 2018-09 2018-09	CT#81	CP-182060	0053	2	B F	NRF Subscription Lifespan NRF servers clause in OpenAPI	15.1.0 15.1.0
2018-09 2018-09				1 2	B F	NRF Subscription Lifespan NRF servers clause in OpenAPI Default port number	15.1.0 15.1.0 15.1.0

0040.00	OT#0:	OD 400000	0050			ADI Vanc'es Hadete	45.4.0
	CT#81	CP-182060	0058	-	<u> </u>	API Version Update	15.1.0
2018-12	CT#82	CP-183018 CP-183018	0060	4	F	Heartbeat Timer	15.2.0 15.2.0
2018-12	CT#82 CT#82		0061	2	F	Location Header	
2018-12		CP-183018	0062 0063	1	F	NF Profile Addressing Parameters NRF Notifications	15.2.0
2018-12	CT#82 CT#82	CP-183018 CP-183018	0064	-	F		15.2.0 15.2.0
2018-12 2018-12	CT#82	CP-183018	0065	1	F	Oauth2 Corrections Regular Expression Patterns	15.2.0
2018-12	CT#82	CP-183183	0066	5	F	Subscription Data	15.2.0
2018-12	CT#82	CP-183147	0067	2	F	UPF selection based on DNAI	15.2.0
2018-12	CT#82	CP-183018	0067	5	F	CHF registration and selection	15.2.0
2018-12	CT#82	CP-183018	0069	1	F	Clarify the NRF management functionality in the case	15.2.0
				_	-	of hierarchical NRFs	
2018-12	CT#82	CP-183149	0070	5	F	OAuth2.0 Service Alignments and Corrections	15.2.0
2018-12	CT#82	CP-183150	0071	1	F	HTTP Basic Authentication For OAuth2.0 Access Token Request	15.2.0
2018-12	CT#82	CP-183018	0072	1	F	Multiple PLMNs support	15.2.0
2018-12	CT#82	CP-183018	0075	2	F	NFService attribute in NFProfile	15.2.0
2018-12	CT#82	CP-183018	0076	1	F	Corrections of ServiceName enumeration	15.2.0
2018-12	CT#82	CP-183018	0077	4	F	Indicating support of EPS interworking in UPF Profile	15.2.0
2018-12	CT#82	CP-183018	0079	2	F	Cardinality	15.2.0
2018-12	CT#82	CP-183018	0081	-	F	APIRoot Clarification	15.2.0
2018-12	CT#82	CP-183018	0082	2	F	Clarification on the reuse of the previous search results	15.2.0
2018-12	CT#82	CP-183018	0083	1	F	NF profile detail for hierarchical NRF	15.2.0
2018-12	CT#82	CP-183235	0084	3	F	Complex query	15.2.0
2018-12	CT#82	CP-183152	0087	1	F	SMF discovery based on S-NSSAI and DNN	15.2.0
2018-12	CT#82	CP-183153	0088	2	F	CHF discovery based on GPSI and SUPI	15.2.0
2018-12	CT#82	CP-183146	0089	3	F	Add access type in SMF selection	15.2.0
2018-12	CT#82	CP-183018	0090	2	F	Hierarchical subscription with intermediate forwarding	15.2.0
2018-12	CT#82	CP-183018	0091	2	F	NRF Hierarchical subscription with intermediate redirecting NRF	15.2.0
2018-12	CT#82	CP-183018	0093	1	F	Notifications for subscriptions via intermediate NRF	15.2.0
2018-12	CT#82	CP-183018	0096	1	F	DNN and IP Domain in BSF Info	15.2.0
2018-12	CT#82	CP-183018	0097	1	F	PCF Information	15.2.0
2018-12	CT#82	CP-183018	0100	-	F	NF Service FQDN	15.2.0
2018-12	CT#82	CP-183018	0101	_	F	NRF Corrections	15.2.0
2018-12	CT#82	CP-183018	0102	1	F	Notification Data	15.2.0
2018-12	CT#82	CP-183181	0103	2	F	NRF Oauth Scopes	15.2.0
2018-12	CT#82	CP-183182	0104	1	F	NRF Subscription Handling	15.2.0
2018-12	CT#82	CP-183018	0105	÷	F	NF Profile Change Notification	15.2.0
2018-12	CT#82	CP-183171	0107	-	F	UDM Group ID	15.2.0
2018-12	CT#82	CP-183018	0108	2	F	Preferred target NF Location in Discovery Request	15.2.0
2018-12	CT#82	CP-183018	0109	1	F	Telescopic FQDN for HNRF	15.2.0
2018-12	CT#82	CP-183184	0112	1	F	Description of NF instances/NF profile retrieval	15.2.0
	CT#82	CP-183018	0113	-		Content of the Subscription to notification response	15.2.0
2018-12	CT#82	CP-183018	0115	-	F	Adding new services in ServiceName enumeration	15.2.0
2018-12	CT#82	CP-183018	0116	-	F	NF Profile Service Instances	15.2.0
2018-12	CT#82	CP-183018	0117	-	F	API Version	15.2.0
2018-12	CT#82	CP-183180	0118	1	F	ExternalDocs Update	15.2.0
2019-03	CT#83	CP-190023	0119	1	F	AmfRegionId and AmfSetId	15.3.0
2019-03	CT#83	CP-190023	0120	1	F	Interpretation of absence of IEs in NF Profile	15.3.0
2019-03	CT#83	CP-190023	0121	1	F	Usage of FQDN and IP address related attributes from NF / NF Service profiles	15.3.0
2019-03	CT#83	CP-190023	0122	1	F	AMF Region and AMF Set in PLMNs supporting multiple PLMN Ids	15.3.0
2019-03	CT#83	CP-190023	0123	1	F	Encoding of GUAMI query parameter in NFDiscover Request	15.3.0
2019-03	CT#83	CP-190023	0124	1	F	Status for operative NF (service) not discoverable by other NFs	15.3.0
2019-03	CT#83	CP-190023	0126	1	F	Limiting the number of NFProfiles returned in NFDiscover response	15.3.0
2019-03 2019-03	CT#83 CT#83	CP-190023 CP-190155	0127 0128	2	F	Maximum payload size of NFDiscover Response NF Profile Changes in NF Register / NFUpdate	15.3.0 15.3.0
2019-03	CT#83	CP-190023	0129	1	F	Response supported-features query parameter of NFDiscover	15.3.0
2010.02	CT#02	CD 100022	0120	1		Request OpenAPI Corrections	15 2 0
2019-03	CT#83	CP-190023	0130	1	F	OpenAPI Corrections	15.3.0
2019-03	CT#83	CP-190023	0132	1	F	Oauth2 Token Claims	15.3.0
2019-03	CT#83	CP-190023	0133	1	F	Oauth2 Token Type	15.3.0
2019-03	CT#83	CP-190023	0134	2	F F	Authorization Attributes of NF Profile	15.3.0
2019-03 2019-03	CT#83 CT#83	CP-190023 CP-190023	0135 0136			Features of NF Discovery service	15.3.0
		11.10~100023	10136		F	Subscription Authorization for Sets of NFs	15.3.0

2019-03	CT#83	CP-190023	0137	1	F	S-NSSAI per PLMN	15.3.0
2019-03	CT#83	CP-190023	0137	4	F	UPF selection based on PDUSessionType	15.3.0
2019-03	CT#83	CP-190039	0139	2	F	Service Names in URI Query Parameters	15.3.0
2019-03	CT#83	CP-190103	0140	1	F	GMLC URI for Namf_Location EventNotify	15.3.0
2019-03	CT#83	CP-190023	0140	1	F	Corrections on complex query	15.3.0
2019-03	CT#83	CP-190023	0141	1	F	NRF Notifications	15.3.0
2019-03	CT#83	CP-190023	0142	1	F	NRF Heart-Beat	15.3.0
2019-03	CT#83	CP-190023	0143	-	F	Addition of new Service Name	15.3.0
2019-03	CT#83	CP-190023	0144	-	F	API version update	15.3.0
2019-03	CT#84	CP-190023	0145	3	F	PLMN ID in Access Token Claims	15.4.0
2019-06	CT#84	CP-191034 CP-191034	0146	1	F		15.4.0
2019-06	CT#84	CP-191034 CP-191034	0147	3	F	Content encodings supported in HTTP requests Correct the condition of the FQDN parameter of	15.4.0
2019-06			0156	3	-	NFProfile and NFService	
2019-06	CT#84	CP-191034	0159	1	F	NRF Service Description	15.4.0
2019-06	CT#84	CP-191034	0161	1	F	Slice Info in NRF	15.4.0
2019-06	CT#84	CP-191034	0162	1	F	Subscription Conditions	15.4.0
2019-06	CT#84	CP-191034	0163	1	F	Vendor-Specific IEs in NF Profile	15.4.0
2019-06	CT#84	CP-191034	0165	2	F	Target PLMN List in Inter-PLMN Service Discovery	15.4.0
2019-06	CT#84	CP-191034	0167	2	F	Storage of OpenAPI specification files	15.4.0
2019-06	CT#84	CP-191034	0170	-	F	Corrections on NFStatusUnSubscribe operation to take	15.4.0
						into account multiple NRFs	
2019-06	CT#84	CP-191034	0171	1	F	Corrections on UpdateSubscription operation to take into account multiple NRFs	15.4.0
2019-06	CT#84	CP-191034	0174	4	F	Corrections on Nnrf_AccessToken Service for multiple NRFs	15.4.0
2019-06	CT#84	CP-191034	0176	-	F	LowerCamel Correction in Data Structures	15.4.0
2019-06	CT#84	CP-191034	0177	-	F	Removal of Basic Authentication	15.4.0
2019-06	CT#84	CP-191034	0178	1	F	Location header in redirect response	15.4.0
2019-06	CT#84	CP-191034	0185	2	F	Add HTTP error codes in 29.510	15.4.0
2019-09	CT#85	CP-192108	0192	4	F	Add selection mechanism for multiple IP addresses in NFProfile	15.4.0
2019-06	CT#84	CP-191034	0194	2	F	Add retrieval of the NF profile using the URI	15.4.0
2019-06	CT#84	CP-191034	0195	1	F	Add the update of subscription in a different PLMN	15.4.0
2019-06	CT#84	CP-191034	0198	1	F	PLMN-IDs in Discovery Response	15.4.0
2019-06	CT#84	CP-191034	0202	-	F	Copyright Note in YAML files	15.4.0
2019-06	CT#84	CP-191034	0206	-	F	3GPP TS 29.510 API version update	15.4.0
2019-09	CT#85	CP-192107	0214	-	F	Expiration Time of AccessTokenClaims	15.5.0
2019-09	CT#85	CP-192107	0221	-	F	Slice Information in Access Token Claims	15.5.0
2019-09	CT#85	CP-192248	0225	5	F	Support of Static IP Address	15.5.0
2019-09	CT#85	CP-192107	0230	-	F	Authorization Attributes in NF Service	15.5.0
2019-09	CT#85	CP-192119	0241	-	F	3GPP TS 29.510 API version update	15.5.0
2019-10	200	1	5=11			Corrupted references fixed	15.5.1
2019-12	CT#86	CP-193031	0270	-	F	External Group ID	15.6.0
2019-12	CT#86	CP-193031	0271	-	F	S-NSSAI Discovery Parameter	15.6.0
2019-12	CT#86	CP-193043	0272	_	F	3GPP TS 29.510 API version update	15.6.0
2020-07	CT#88	CP-201022	0339	_	F	Requester-snssais	15.7.0
2020-07	CT#88	CP-201182	0358	3	F	NRF Notifications	15.7.0
2020-07	CT#88	CP-2011022	0367	-	F	3GPP TS 29.510 API version update	15.7.0
2020-07 2020-09	CT#88 CT#89	CP-201022 CP-202043	0367 0388	1	F	NF Group ID	15.7.0 15.8.0

History

Document history						
V15.0.0	September 2018	Publication				
V15.1.0	October 2018	Publication				
V15.2.0	April 2019	Publication				
V15.3.0	April 2019	Publication				
V15.4.0	July 2019	Publication				
V15.5.0	October 2019	Publication (withdrawn)				
V15.5.1	October 2019	Publication				
V15.6.0	January 2020	Publication				
V15.7.0	July 2020	Publication				
V15.8.0	November 2020	Publication				