## ETSI TS 132 603 V6.3.1 (2005-04)

Technical Specification

Digital cellular telecommunications system (Phase 2+);

**Universal Mobile Telecommunications System (UMTS)**;

**Telecommunication management;** 

**Configuration Management (CM);** 

**Basic CM Integration Reference Point (IRP):** 

**Common Object Request Broker Architecture (CORBA)** 

**Solution Set (SS)** 

(3GPP TS 32.603 version 6.3.1 Release 6)



Reference
RTS/TSGS-0532603v631

Keywords
GSM, UMTS

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<a href="http://portal.etsi.org/tb/status/status.asp">http://portal.etsi.org/tb/status/status.asp</a></a>

#### **Copyright Notification**

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005. All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup> and **UMTS**<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**<sup>TM</sup> and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Foreword**

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <a href="http://webapp.etsi.org/key/queryform.asp">http://webapp.etsi.org/key/queryform.asp</a>.

## Contents

Intell	lectual Property Rights	2
Fore	word	2
Fore	word	4
Intro	oduction	4
1	Scope	5
2	References	5
3	Definitions and abbreviations	6
3.1 3.2	Definitions	
4	IRP document version number string	6
5 5.1 5.2	Architectural features	6
6 6.1 6.2 6.3	Mapping  General mappings  Operation mapping  Operation parameter mapping	7 7
7	Void	10
Anno	ex A (normative): CORBA IDL, Access Protocol	11
A.1	IDL specification (file name "BasicCMIRPConstDefs.idl")	11
A.2	IDL specification (file name "BasicCMIRPSystem.idl")	15
Anno	ex B (informative): Change history	24
Histo	ory	25

#### **Foreword**

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

#### Introduction

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project: Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

32.601:	"Configuration Management (CM); Basic CM Integration Reference Point (IRP); Requirements".
32.602:	"Configuration Management (CM); Basic CM Integration Reference Point (IRP): Information

Service (SS)".

32.603: "Configuration Management (CM); Basic CM Integration Reference Point (IRP): Common

Object Request Broker Architecture (CORBA) Solution Set (SS)".

32.604: "Configuration Management (CM); Basic CM Integration Reference Point (IRP) Common

Management Information Protocol (CMIP) Solution Set (SS)".

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

### 1 Scope

The purpose of this *Basic Configuration Management (CM) IRP: CORBA Solution Set* is to define the mapping of the Basic CM IRP: IS (see 3GPP TS 32.602 [4]) to the protocol specific details necessary for implementation of this IRP in a CORBA/IDL environment.

This document defines NRM independent data types and methods.

This Solution Set specification is related to 3G TS 32.602 V6.1.X.

#### 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 32.602: "Telecommunication management; Configuration Management (CM); Basic CM Integration Reference Point (IRP) Information Service (IS)".
- [5] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [6] OMG Notification Service, Version 1.0.
- [7] OMG CORBA services: Common Object Services Specification, Update: November 22, 1996.
- [8] The Common Object Request Broker: Architecture and Specification (for specification of valid version, see [1]).
- [9] 3GPP TS 32.303: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
- [10] 3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP) management; Information Service (IS)".
- [11] 3GPP TS 32.663: "Telecommunication management; Configuration Management (CM); Kernel CM Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".

#### 3 Definitions and abbreviations

#### 3.1 Definitions

For terms and definitions please refer to 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.600 [3] and 3GPP TS 32.602 [4].

#### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CORBA Common Object Request Broker Architecture
DN Distinguished Name
IS Information Service
IDL Interface Definition Language (OMG)
IRP Integration Reference Point
MO Managed Object

MOC Managed Object Class
NRM Network Resource Model
OMG Object Management Group

SS Solution Set

## 4 IRP document version number string

The IRP document version number (sometimes called "IRPVersion" or "SS version number") string is used to identify this specification. The string is derived using a rule described in 3GPP TS 32.312: [10].

This string (or sequence of strings, if more than one version is supported) is returned in getBasicCmIRPVersion method.

### 5 Architectural features

The overall architectural feature of Basic Configuration Management IRP is specified in 3GPP TS 32.602 [4]. This clause specifies features that are specific to the CORBA SS.

#### 5.1 Filter language

The filter language used in the SS is the Extended Trader Constraint Language (see OMG Notification Service [6]). IRPAgents may throw a FilterComplexityLimit exception when a given filter is too complex. However, for 3GPP Release 99 an "empty filter" shall be used i.e. a filter that satisfies all MOs of a scoped search (this does not affect the filter for notifications as defined in the Notification IRP – see 3GPP TS 32.303 [9]).

### 5.2 Syntax for Distinguished Names and Versions

The format of a Distinguished Name is defined in 3GPP TS 32.300 [5].

The version of this IRP is represented as a string (see also clause 4).

## 6 Mapping

### 6.1 General mappings

The IS parameter name managedObjectInstance is mapped into DN.

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MOReference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MOReferenceSet, which contains a sequence of MO references.

If a reference attribute is changed, an Attribute Value Change notification (see TS 32.663 [11]) is emitted.

### 6.2 Operation mapping

The Basic CM IRP: IS (see 3GPP TS 32.602 [4]) defines semantics of operation visible across the Basic Configuration Management IRP. Table 1 indicates mapping of these operations to their equivalents defined in this SS.

IS Operation (3GPP TS 32.602 [4])	SS Method	Qualifier
getMoAttributes	BasicCmIrpOperations::find_managed_objects	M
	BasicCmInformationIterator::next_basicCmInformations	
getContainment	BasicCmIrpOperations::find_managed_objects	0
	BasicCmInformationIterator::next_basicCmInformations	
getIRPVersion (see note)	get_basicCm_IRP_version	M
cancelOperation	BasicCmInformationIterator::destroy	0
createMo	BasicCmIrpOperations::create_managed_object	0
deleteMo	BasicCmIrpOperations::delete_managed_objects	0
setMoAttributes	BasicCmIrpOperations::modify_managed_objects	0
getOperationProfile (see note)	get_basicCm_IRP_operation_profile	0
getNotificationProfile (see note)	get_basicCm_IRP_notification_profile	0
NOTE: This operation is of IOC	ManagedGenericIRP specified in [10]. The IOC BasicCmIRP of [4] in	herits from it.

**Table 1: Mapping from IS Operation to SS equivalents** 

### 6.3 Operation parameter mapping

The Basic CM IRP: IS (see 3GPP TS 32.602 [4]) defines semantics of parameters carried in operations across the Basic Configuration Management IRP. Tables 2 through 8 indicate the mapping of these parameters, as per operation, to their equivalents defined in this SS.

The SS operation find\_managed\_objects is equivalent to the IS operation getMoAttributes when called with ResultContents set to NAMES\_AND\_ATTRIBUTES. Iterating the BasicCmInformationIterator is used to fetch the result.

Table 2: Mapping from IS getMoAttributes parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
invokeldentifier	- (No equivalence)	-
invokeldentifierOut	Return value of type BasicCmInformationIterator	M
baseObjectInstance	in DN baseObject	M
scope	in SearchControl searchControl (SearchControl.type and SearchControl.level)	M
filter	in SearchControl searchControl (SearchControl.filter)	M
attributeListIn	in AttributeNameSet requestedAttributes	M
managedObjectClass managedObjectInstance attributeListOut	Return value of type BasicCmInformationIterator - parameter out ResultSet fetchedElements of method next_basicCmInformations	M
status	Exceptions: FindManagedObjects, ManagedGenericIRPSystem::InvalidParameter, UndefinedMOException, IllegalDNFormatException, UndefinedScopeException, IllegalScopeTypeException, IllegalScopeLevelException, IllegalFilterFormatException, FilterComplexityLimit	M

The SS operation find\_managed\_objects is equivalent to the IS operation getContainment when called with ResultContents set to NAMES. Iterating the BasicCmInformationIterator is used to fetch the result.

Table 3: Mapping from IS getContainment parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
invokeldentifier	- (No equivalence)	-
invokeldentifierOut	Return value of type BasicCmInformationIterator	M
baseObjectInstance	in DN baseObject	M
scope	in SearchControl searchControl (SearchControl.type and SearchControl.level)	0
Not specified in IS	in SearchControl searchControl (SearchControl.filter)	M
containment	Return value of type BasicCmInformationIterator - parameter out ResultSet fetchedElements of method next_basicCmInformations	M
status	Exceptions: FindManagedObjects, ManagedGenericIRPSystem::OperationNotSupported, ManagedGenericIRPSystem::ParameterNotSupported, ManagedGenericIRPSystem::InvalidParameter, ManagedGenericIRPSystem::ValueNotSupported, UndefinedMOException, IllegalDNFormatException, UndefinedScopeException, IllegalScopeTypeException, IllegalScopeLevelException, IllegalFilterFormatException, FilterComplexityLimit	M

Table 4: Mapping from IS getIRPVersion parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
versionNumberSet	Return value of type ManagedGenericIRPConstDefs::VersionNumberSet	M
status	Exceptions:	M
	GetBasicCmIRPVersion	

Table 5: Mapping from IS cancelOperation parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
invokeldentifier	- (Not applicable, the BasicCmInformationIterator instance identifies the ongoing	M
	operation)	
status	Exceptions:	M
	ManagedGenericIRPSystem::OperationNotSupported,	
	DestroyException	

Table 6: Mapping from IS createMo parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
managedObjectClass	in DN objectName	M
managedObjectInstance		
referenceObjectInstance	in DN referenceObject	0
attributeListIn	inout MoAttributeSet attributes	M
attributeListOut		
status	out AttributeErrorSeq attributeErrors	M
	Exceptions:	
	CreateManagedObject,	
	ManagedGenericIRPSystem::OperationNotSupported,	
	ManagedGenericIRPSystem::ParameterNotSupported,	
	ManagedGenericIRPSystem::InvalidParameter,	
	UndefinedMOException,	
	IllegalDNFormatException,	
	DuplicateMO,	
	CreateNotAllowed,	
	ObjectClassMismatch,	
	NoSuchObjectClass,	
	ParentObjectDoesNotExist	

Table 7: Mapping from IS deleteMo parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
baseObjectInstance	in DN baseObject	M
scope	in SearchControl searchControl (SearchControl.type and SearchControl.level)	М
filter	in SearchControl searchControl (SearchControl.filter)	M
deletionList	Return value of type DeleteResultIterator - parameter out ResultSet fetchedElements of method next_basicCmInformations	М
status	Return value of type DeleteResultIterator - parameter out DeleteErrorSeq fetchedDeleteErrors of method next_deleteErrors  Exceptions: DeleteManagedObjects, ManagedGenericIRPSystem::OperationNotSupported, ManagedGenericIRPSystem::InvalidParameter, UndefinedMoException, IllegalDNFormatException, UndefinedScopeException, IllegalScopeTypeException, IllegalScopeLevelException, IllegalFilterFormatException, FilterComplexityLimit	M

Table 8: Mapping from IS setMoAttributes parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
baseObjectInstance	in DN baseObject	M
scope	in SearchControl searchControl (SearchControl.type and SearchControl.level)	M
filter	in SearchControl searchControl (SearchControl.filter)	M
modificationList	in AttributeModificationSet modifications	M
modificationListOut	Return value of type ModifyResultIterator - parameter out ResultSet fetchedElements of method next_basicCmInformations	M
status	Return value of type ModifyResultIterator - parameter out ModifyAttributeErrorsSeq fetchedModifyErrors of method next_modifyErrors Exceptions: ModifyManagedObjects, ManagedGenericIRPSystem::OperationNotSupported, ManagedGenericIRPSystem::InvalidParameter, UndefinedMoException, IllegalDNFormatException, UndefinedScopeException, IllegalScopeTypeException, IllegalScopeLevelException, IllegalFilterFormatException, FilterComplexityLimit	M

Table 9: Mapping from IS getOperationProfile parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
irpVersion	ManagedGenericIRPConstDefs::VersionNumber basicCm_IRP_version	M
operationNameProfile, operationParameterProfile	Return value of type ManagedGenericIRPConstDefs::MethodList	М
status	GetBasicCmIRPOperationProfile,	M
	ManagedGenericIRPSystem::OperationNotSupported, ManagedGenericIRPSystem::InvalidParameter	

Table 10: Mapping from IS getNotificationProfile parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
irpVersion	ManagedGenericIRPConstDefs::VersionNumber basicCm_IRP_version	M
notificationNameProfile,	Return value of type ManagedGenericIRPConstDefs::MethodList	M
notificationParameterProfile		
status	Exceptions:	M
	GetBasicCmIRPNotificationProfile,	
	ManagedGenericIRPSystem::OperationNotSupported,	
	ManagedGenericIRPSystem::InvalidParameter	

## 7 Void

## Annex A (normative): CORBA IDL, Access Protocol

## A.1 IDL specification (file name "BasicCMIRPConstDefs.idl")

```
// File: BasicCMIRPConstDefs.idl
#ifndef _BASICCMIRPCONSTDEFS_IDL_
#define _BASICCMIRPCONSTDEFS_IDL_
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
/* ## Module: BasicCMIRPConstDefs
This module contains commonly used definitions for BasicCMIRP.
______
* /
module BasicCMIRPConstDefs
{
   /**
   * Defines the name of a Managed Object Class
  typedef string MOClass;
   /**
   * The format of Distinguished Name (DN) is specified in 3GPP TS 32.300
    * "Name Conventions for Managed Objects".
  typedef string DN;
   * Defines the name of an attribute of a Managed Object
  typedef string MOAttributeName;
   * Defines the value of an attribute of a Managed Object in form of a CORBA
   * Any. Apart from basic datatypes already defined in CORBA, the allowed
    * attribute value types are defined in the AttributeTypes module.
  typedef any MOAttributeValue;
   /**
    * In this version the only allowed filter value is "TRUE" i.e. a filter that
    * matches everything.
  typedef string FilterType;
    /**
    * ResultContents is used to tell how much information to get back
     * from the find_managed_objects operation.
     * NAMES: Used to get only Distinguished Name
```

```
for MOs.
           The name contains both the MO class
           and the names of all superior objects in the naming
           tree.
  * NAMES_AND_ATTRIBUTES: Used to get both NAMES plus
  * MO attributes (all or selected).
  * /
 enum ResultContents
   NAMES,
   NAMES_AND_ATTRIBUTES
 };
 /**
 * ScopeType defines the kind of scope to use in a search
  * together with SearchControl.level, in a SearchControl value.
  * SearchControl.level is always >= 0. If a level is bigger than the
  * depth of the tree there will be no exceptions thrown.
  * BASE_ONLY: level ignored, just return the base object.
  * BASE_NTH_LEVEL: return all subordinate objects that are on "level"
  * distance from the base object, where 0 is the base object.
  * BASE_SUBTREE: return the base object and all of its subordinates
  * down to and including the nth level.
  * BASE_ALL: level ignored, return the base object and all of it's
  * subordinates.
 * /
enum ScopeType
   BASE_ONLY,
   BASE_NTH_LEVEL,
   BASE_SUBTREE,
   BASE_ALL
 };
 /**
 * SearchControl controls the find_managed_object search,
 * and contains:
 * the type of scope ("type" field),
  * the level of scope ("level" field), level 0 means the "baseObject",
      level 1 means baseobject including its sub-ordinates etc..
  * the filter ("filter" field),
  * the result type ("contents" field).
  * The type, level and contents fields are all mandatory.
  * The filter field contains the filter expression.
    The string "TRUE" indicates "no filter",
  * i.e. a filter that matches everything.
  * /
struct SearchControl
   ScopeType type;
   unsigned long level;
   FilterType filter;
   ResultContents contents;
 };
 * Represents an attribute: "name" is the attribute name
  * and "value" is the attribute value.
  * /
struct MOAttribute
```

```
MOAttributeName name;
  MOAttributeValue value;
};
typedef sequence <MOAttribute> MOAttributeSet;
struct Result
   DN mo;
   MOAttributeSet attributes;
 };
typedef sequence <Result> ResultSet;
 * AttributeErrorCategory defines the categories of errors, related to
 * attributes, that can occur during creation or modification of MOs.
 * NO SUCH ATTRIBUTE: The specified attribute does not exist.
  * INVALID_ATTRIBUTE_VALUE: The specified attribute value is not valid.
  * MISSING_ATTRIBUTE_VALUE: An attribute value is required but none was
    provided and no default value is defined for the attribute.
  * INVALID_MODIFY_OPERATOR: The specified modify operator is not valid
    (e.g. operator ADD_VALUES applied to a non multi-valued attribute
     or operator SET_TO_DEFAULT applied where no default value is defined).
  * MODIFY_NOT_ALLOWED: The modification of the attribute is not allowed.
  * MODIFY_FAILED: The modification failed because of an unspecified reason.
enum AttributeErrorCategory
   NO_SUCH_ATTRIBUTE,
   INVALID_ATTRIBUTE_VALUE,
   MISSING_ATTRIBUTE_VALUE,
   INVALID_MODIFY_OPERATOR,
   MODIFY_NOT_ALLOWED,
   MODIFY_FAILED
};
 * DeleteErrorCategory defines the categories of errors that can occur
 * during deletion of MOs.
 * SUBORDINATE_OBJECT: The MO cannot be deleted due to subordinate MOs.
 * DELETE NOT ALLOWED: The deletion of the MO is not allowed.
 * DELETE FAILED: The deletion failed because of an unspecified reason.
 * /
enum DeleteErrorCategory
   SUBORDINATE OBJECT,
   DELETE NOT ALLOWED,
   DELETE FAILED
};
 * AttributeError represents an error, related to an attribute, that occured
 * during creation or modification of MOs.
  * It contains:
  * - the name of the indicted attribute ("name" field),
  * - the category of the error ("error" field),
  * - optionally, the indicted attribute value ("value" field),
  * - optionally, additional details on the error ("reason" field).
  * /
```

```
struct AttributeError
  MOAttributeName name;
  AttributeErrorCategory error;
  MOAttributeValue value;
  string reason;
};
typedef sequence <AttributeError> AttributeErrorSeq;
/**
 \mbox{\ensuremath{^{\star}}} DeleteError represents an error that occured during deletion of MOs.
 * It contains:
 * - the distinguished name of the indicted MO ("objectName" field),
 * - the category of the error ("error" field),
 * - optionally, additional details on the error ("reason" field).
 * /
struct DeleteError
   DN objectName;
  DeleteErrorCategory error;
  string reason;
};
typedef sequence <DeleteError> DeleteErrorSeq;
/**
 * ModifyAttributeErrors represents errors that occured during
 * modification of attributes of a MO.
 * It contains:
 * - the distinguished name of the indicted MO ("objectName" field),
 * - a sequence containing the attribute errors ("errors" field).
* /
struct ModifyAttributeErrors
  DN objectName;
  AttributeErrorSeq errors;
};
typedef sequence <ModifyAttributeErrors> ModifyAttributeErrorsSeq;
typedef sequence <MOAttributeName> AttributeNameSet;
/**
 * ModifyOperator defines the way in which an attribute value is to be
 * applied to an attribute in a modification of MO attributes.
 * REPLACE: replace the current value with the provided value
 * ADD VALUES: for a multi-valued attribute, add the provided values to the
   current list of values
 * REMOVE VALUES: for a multi-valued attribute, remove the provided values
   from the current list of values
 * SET_TO_DEFAULT: set the attribute to its default value
enum ModifyOperator
  REPLACE,
  ADD_VALUES,
  REMOVE_VALUES,
  SET_TO_DEFAULT
};
/**
```

```
* AttributeModification defines an attribute value and the way it is to
* be applied to an attribute in a modification of MO attributes.
* It contains:
    * - the name of the attribute to modify ("name" field),
    * - the value to apply to this attribute ("value" field),
    * - the way the attribute value is to be applied to the attribute
    * ("operator" field).
    */
struct AttributeModification
{
    MOAttributeName name;
    MOAttributeValue value;
    ModifyOperator operator;
};
typedef sequence <AttributeModification> AttributeModificationSet;

};
#endif // _BASICCMIRPCONSTDEFS_IDL_
```

## A.2 IDL specification (file name "BasicCMIRPSystem.idl")

```
// File: BasicCMIRPSystem.idl
#ifndef _BASICCMIRPSYSTEM_IDL_
#define _BASICCMIRPSYSTEM_IDL_
#include "ManagedGenericIRPConstDefs.idl"
#include "ManagedGenericIRPSystem.idl"
#include "BasicCMIRPConstDefs.idl"
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
module BasicCmIRPSystem
    exception IllegalFilterFormatException {
      string reason;
    exception IllegalDNFormatException {
      string reason;
    };
    exception IllegalScopeTypeException {
      string reason;
    exception IllegalScopeLevelException {
       string reason;
    };
    exception UndefinedMOException {
       string reason;
   exception UndefinedScopeException {
       string reason;
   exception FilterComplexityLimit {
      string reason;
   };
```

```
exception DuplicateMO {};
exception CreateNotAllowed {};
exception ObjectClassMismatch {};
exception NoSuchObjectClass {
  BasicCMIRPConstDefs::MOClass objectClass;
};
 exception ParentObjectDoesNotExist {};
 \mbox{\scriptsize \star} System otherwise fails to complete the operation. System can provide
 * reason to qualify the exception. The semantics carried in reason
 * is outside the scope of this IRP.
exception NextBasicCmInformations { string reason; };
exception NextDeleteErrors { string reason; };
exception NextModifyErrors { string reason; };
exception DestroyException { string reason; };
exception GetBasicCmIRPVersion { string reason; };
exception GetBasicCmIRPOperationProfile { string reason; };
exception GetBasicCmIRPNotificationProfile { string reason; };
exception FindManagedObjects { string reason; };
exception CreateManagedObject { string reason; };
exception DeleteManagedObjects { string reason; };
exception ModifyManagedObjects { string reason; };
 /**
  The BasicCmInformationIterator is used to iterate through a snapshot of
   Managed Object Information when IRPManager invokes find_managed_objects.
   IRPManager uses it to pace the return of Managed Object Information.
  IRPAgent controls the life-cycle of the iterator. However, a destroy
   operation is provided to handle the case where IRPManager wants to stop
   the iteration procedure before reaching the last iteration.
 interface BasicCmInformationIterator
    /**
     This method returns between 1 and "how_many" Managed Object information.
      The IRPAgent may return less than "how many" items even if there are
      more items to return. "how many" must be non-zero. Return TRUE if there
      may be more Managed Object information to return. Return FALSE if there
      are no more Managed Object information to be returned.
      If FALSE is returned, the IRPAgent will automatically destroy the
       iterator.
      @parm how_many how many elements to return in the "fetchedElements" out
      parameter.
      @parm fetchedElements the elements.
      @returns A boolean indicating if any elements are returned.
       "fetchedElements" is empty when the BasicCmInformationIterator is
       empty.
     * /
     boolean next_basicCmInformations (
         in unsigned short how_many,
         out BasicCMIRPConstDefs::ResultSet fetchedElements
```

```
)
   raises (
        NextBasicCmInformations,
        ManagedGenericIRPSystem::InvalidParameter,
         ManagedGenericIRPSystem::OperationNotSupported);
    / * *
   This method destroys the iterator.
   void destroy ()
    raises (
         DestroyException,
         ManagedGenericIRPSystem::OperationNotSupported);
}; // end of BasicCmInformationIterator
/**
 The DeleteResultIterator is used to iterate through the list of deleted MOs
  when IRPManager invokes method "delete managed objects".
  IRPManager uses it to pace the return of Managed Object Information.
 IRPAgent controls the life-cycle of the iterator. However, a destroy
  operation is provided to handle the case where IRPManager wants to stop
  the iteration procedure before reaching the last iteration.
interface DeleteResultIterator : BasicCmInformationIterator
   /**
    Inherited method "next_basicCmInformations" has the same behaviour as
     for interface BasicCmInformationIterator, except that:
     - The Managed Object information returned in parameter
       "fetchedElements" contains only the DNs of the deleted MOs
       (no attributes are returned).
     - If FALSE is returned, the IRPAgent will not automatically destroy the
       iterator.
   / * *
    This method returns between 0 and "how_many" deletion errors. The
     IRPAgent may return less than "how_many" items even if there are more
     items to return. "how_many" must be non-zero. Return TRUE if there are
     more deletion errors to return. Return FALSE if there are no more
     deletion errors to be returned.
     If FALSE is returned and last call to inherited method
     "next_basicCmInformations" also returned FALSE (i.e. no more Managed
     Object information to be returned), the IRPAgent will automatically
     destroy the iterator.
     @parm how_many: how many deletion errors to return in the
     "fetchedDeleteErrors" out parameter.
     @parm fetchedDeleteErrors: the deletion errors.
    @returns: a boolean indicating if any deletion errors are returned.
   boolean next_deleteErrors (
        in unsigned short how_many,
        out BasicCMIRPConstDefs::DeleteErrorSeq fetchedDeleteErrors
    raises (
```

```
NextDeleteErrors,
       ManagedGenericIRPSystem::InvalidParameter);
}; // end of DeleteResultIterator
/**
The ModifyResultIterator is used to iterate through the list of modified
 MOs when IRPManager invokes method "modify_managed_objects".
 IRPManager uses it to pace the return of Managed Object Information.
IRPAgent controls the life-cycle of the iterator. However, a destroy
 operation is provided to handle the case where IRPManager wants to stop
 the iteration procedure before reaching the last iteration.
interface ModifyResultIterator : BasicCmInformationIterator
   /**
    Inherited method "next basicCmInformations" has the same behaviour as
     for interface BasicCmInformationIterator, except that:
     - The Managed Object information returned in parameter
       "fetchedElements" contains DNs and attributes of the modified MOs.
     - If FALSE is returned, the IRPAgent will not automatically destroy the
       iterator.
    This method returns between 0 and "how_many" modification errors. The
    IRPAgent may return less than "how_many" items even if there are more
    items to return. "how_many" must be non-zero. Return TRUE if there are
    more modification errors to return. Return FALSE if there are no more
    modification errors to be returned.
     If FALSE is returned and last call to inherited method
     "next_basicCmInformations" also returned FALSE (i.e. no more Managed
    Object information to be returned), the IRPAgent will automatically
    destroy the iterator.
     @parm how_many: how many modification errors to return in the
     "fetchedModifyErrors" out parameter.
    @parm fetchedModifyErrors: the modification errors.
    @returns: a boolean indicating if any modification errors are returned.
    * /
   boolean next modificationErrors (
        in unsigned short how many,
        out BasicCMIRPConstDefs::ModifyAttributeErrorsSeq
           fetchedModifyErrors
   raises (
       NextModifyErrors,
       ManagedGenericIRPSystem::InvalidParameter);
}; // end of ModifyResultIterator
 * The BasicCmIrpOperations interface.
 * Supports a number of Resource Model versions.
interface BasicCmIrpOperations
```

```
/**
 * Get the version(s) of the interface
 \mbox{\tt *} @raises GetBasicCmIRPVersion when the system for some reason
   can not return the supported versions.
 * @returns all supported versions.
 * /
ManagedGenericIRPConstDefs::VersionNumberSet get_basicCm_IRP_version()
  raises (GetBasicCmIRPVersion);
/**
 * Return the operation profile for a specific Basic CM IRP version.
 * @raises GetBasicCmIRPOperationProfile when the system for some reason
   cannot return the supported operations and parameters.
 * @returns the list of all supported operations and their supported
    parameters for the specified version.
 * /
ManagedGenericIRPConstDefs::MethodList get basicCm IRP operation profile
    in ManagedGenericIRPConstDefs::VersionNumber basicCm IRP version
raises (
    GetBasicCmIRPOperationProfile,
    ManagedGenericIRPSystem::OperationNotSupported,
   ManagedGenericIRPSystem::InvalidParameter);
 * Return the notification profile for a specific Basic CM IRP version.
 * @raises GetBasicCmIRPNotificationProfile when the system for some
   reason cannot return the supported notifications and parameters.
 * @returns the list of all supported notifications and their supported
   parameters for the specified version.
 * /
ManagedGenericIRPConstDefs::MethodList
   get_basicCm_IRP_notification_profile (
        in ManagedGenericIRPConstDefs::VersionNumber basicCm_IRP_version
)
raises (
    GetBasicCmIRPNotificationProfile,
    ManagedGenericIRPSystem::OperationNotSupported,
    ManagedGenericIRPSystem::InvalidParameter);
 * Performs a containment search, using a SearchControl to
 * control the search and the returned results.
 * All MOs in the scope constitute a set that the filter works on.
 * The result BasicCmInformationIterator contains all matched MOs,
 * with the amount of detail specified in the SearchControl.
 * For the special case when no managed objects are matched in
 * find_managed_objects, the BasicCmInformationIterator will be returned.
 * Executing the next basicCmInformations in the
 * BasicCmInformationIterator will return FALSE for
 * completion.
 * @parm baseObject The start MO in the containment tree.
 * @parm searchControl the SearchControl to use.
 * @parm requestedAttributes defines which attributes to get.
    If this parameter is empty (""), all attributes shall
    be returned. In this version this is the only supported semantics.
    Note that this argument is only
```

```
relevant if ResultContents in the search control is
     specifed to NAMES_AND_ATTRIBUTES.
 * @raises ManagedGenericIRPSystem::ValueNotSupported if a valid but
 * unsupported parameter value is passed. E.g. the contents
 * field in the searchcontrol parameter contains the value NAMES and
 * the optional getContainment IS operation is not supported.
 \mbox{\tt *} @raises UndefinedMOException The MO does not exist.
 * @raises IllegalDNFormatException The dn syntax string is
 * malformed.
 * @raises IllegalScopeTypeException The ScopeType in scope contains
 * an illegal value.
 * @raises IllegalScopeLevelException The scope level is negative
 * (<0).
 * @raises IllegalFilterFormatException The filter string is
 * malformed.
 * @raises FilterComplexityLimit if the filter syntax is correct,
    but the filter is too complex to be processed by the IRP agent.
 * @see SearchControl
 * @see BasicCmInformationIterator
BasicCmInformationIterator find_managed_objects(
    in BasicCMIRPConstDefs::DN baseObject,
    in BasicCMIRPConstDefs::SearchControl searchControl,
    in BasicCMIRPConstDefs::AttributeNameSet requestedAttributes)
raises (
    FindManagedObjects,
    ManagedGenericIRPSystem::ParameterNotSupported,
    ManagedGenericIRPSystem::InvalidParameter,
   ManagedGenericIRPSystem::ValueNotSupported,
   ManagedGenericIRPSystem::OperationNotSupported,
   UndefinedMOException,
    IllegalDNFormatException,
   UndefinedScopeException,
    IllegalScopeTypeException,
    IllegalScopeLevelException,
    IllegalFilterFormatException,
    FilterComplexityLimit);
 * Performs the creation of a MO instance in the MIB maintained
 * by the IRPAgent.
 * @parm objectName: the distinguished name of the MO to create.
 * @parm referenceObject: the distinguished name of a reference MO.
 * @parm attributes: in input, initial attribute values for the MO to
   create; in output, actual attribute values of the created MO.
 * @parm attributeErrors: errors, related to attributes, that caused the
    creation of the MO to fail.
 * @raises ManagedGenericIRPSystem::OperationNotSupported: The operation
    is not supported.
 * @raises ManagedGenericIRPSystem::ParameterNotSupported: An optional
   parameter is not supported.
 * @raises ManagedGenericIRPSystem::InvalidParameter: An invalid
   parameter value has been provided.
 * @raises UndefinedMOException: The MO does not exist.
 * @raises IllegalDNFormatException: The DN syntax string is malformed.
 * @raises DuplicateMO: A MO already exist with the same DN as the one
     to create.
 \mbox{\tt *} @raises CreateNotAllowed: The creation of the MO is not allowed.
 * @raises ObjectClassMismatch: The object class of the MO to create does
```

```
not match with the object class of the provided reference MO.
 * @raises NoSuchObjectClass: The class of the object to create is not
   recognized.
 * @raises ParentObjectDoesNotExist: The parent MO instance of the
  ManagedEntity specified to be created does not exist.
 * /
void create_managed_object (
    in BasicCMIRPConstDefs::DN objectName,
    in BasicCMIRPConstDefs::DN referenceObject,
    inout BasicCMIRPConstDefs::MOAttributeSet attributes,
    out BasicCMIRPConstDefs::AttributeErrorSeq attributeErrors
raises (
    CreateManagedObject,
    ManagedGenericIRPSystem::OperationNotSupported,
    ManagedGenericIRPSystem::ParameterNotSupported,
    ManagedGenericIRPSystem::InvalidParameter,
    UndefinedMOException,
    IllegalDNFormatException,
   DuplicateMO,
    CreateNotAllowed,
    ObjectClassMismatch,
   NoSuchObjectClass,
   ParentObjectDoesNotExist);
/ * *
 * Performs the deletion of one or more MO instances from the MIB
 * maintained by the IRPAgent, using a SearchControl to control the
 * instances to be deleted.
 * All MOs in the scope constitute a set that the filter works on.
 * All matched MOs will be deleted by this operation.
 * The returned DeleteResultIterator is used to retrieve the DNs of the
 * MOs deleted and the errors that may have occurred preventing deletion
 * of some MOs.
 * For the special case when no managed objects are matched in
 * delete_managed_objects, the DeleteResultIterator will be returned.
 * Executing the next_basicCmInformations in the DeleteResultIterator
 * will return FALSE for completion.
 * @parm baseObject: the start MO in the containment tree.
 * @parm searchControl: the SearchControl to use; field "contents" has no
    meaning here and shall be ignored.
 @returns: a DeleteResultIterator (see above).
 * @raises ManagedGenericIRPSystem::OperationNotSupported: The operation
    is not supported.
 * @raises ManagedGenericIRPSystem::InvalidParameter: An invalid
    parameter value has been provided.
 * @raises UndefinedMOException: The MO does not exist.
 * @raises IllegalDNFormatException: The DN syntax string is malformed.
 * @raises IllegalScopeTypeException: The ScopeType in scope contains
    an illegal value.
 * @raises IllegalScopeLevelException: The scope level is negative (<0).
 * @raises IllegalFilterFormatException: The filter string is malformed.
 * @raises FilterComplexityLimit: The filter syntax is correct,
    but the filter is too complex to be processed by the IRPAgent.
 * /
DeleteResultIterator delete_managed_objects (
    in BasicCMIRPConstDefs::DN baseObject,
    in BasicCMIRPConstDefs::SearchControl searchControl
)
raises (
```

```
DeleteManagedObjects,
    ManagedGenericIRPSystem::OperationNotSupported,
    ManagedGenericIRPSystem::InvalidParameter,
    UndefinedMOException,
    IllegalDNFormatException,
    UndefinedScopeException,
    IllegalScopeTypeException,
    IllegalScopeLevelException,
    IllegalFilterFormatException,
    FilterComplexityLimit);
 * Performs the modification of MO attributes. One or more MOs attributes
 * may be modified according to a SearchControl.
 * All MOs in the scope constitute a set that the filter works on.
 * All matched MOs will have their attributes modified by this operation.
 * The returned ModifyResultIterator is used to retrieve the DNs of the
 * modified MOs together with the values of the modified attributes, and
 * the errors that may have occurred preventing modification of some
 * attributes.
 * For the special case when no managed objects are matched in
 * modify_managed_objects, the ModifyResultIterator will be returned.
 * Executing the next_basicCmInformations in the ModifyResultIterator
 * will return FALSE for completion.
 * @parm baseObject: the start MO in the containment tree.
 * @parm searchControl: the SearchControl to use; field "contents" has no
    meaning here and shall be ignored.
 * @parm modifications: the values for the attributes to modify and
     the way those values are to be applied to the attributes.
 @returns: a ModifyResultIterator (see above).
 * @raises ManagedGenericIRPSystem::OperationNotSupported: The operation
    is not supported
 * @raises ManagedGenericIRPSystem::InvalidParameter: An invalid
    parameter value has been provided
 ^{\star} @raises UndefinedMOException: The MO does not exist.
 * @raises IllegalDNFormatException: The DN syntax string is malformed.
 * @raises IllegalScopeTypeException: The ScopeType in scope contains
    an illegal value.
 * @raises IllegalScopeLevelException: The scope level is negative (<0).
 * @raises IllegalFilterFormatException: The filter string is malformed.
 * @raises FilterComplexityLimit: The filter syntax is correct,
    but the filter is too complex to be processed by the IRPAgent.
 * /
ModifyResultIterator modify managed objects (
    in BasicCMIRPConstDefs::DN baseObject,
    in BasicCMIRPConstDefs::SearchControl searchControl,
    in BasicCMIRPConstDefs::AttributeModificationSet modifications
raises (
   ModifyManagedObjects,
    ManagedGenericIRPSystem::OperationNotSupported,
   ManagedGenericIRPSystem::InvalidParameter,
   UndefinedMOException,
    IllegalDNFormatException,
   UndefinedScopeException,
    IllegalScopeTypeException,
    IllegalScopeLevelException,
    IllegalFilterFormatException,
    FilterComplexityLimit);
```

```
};
};
#endif // _BASICCMIRPSYSTEM_IDL_
```

# Annex B (informative): Change history

					Change history		
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
	S_12	SP-010283			Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0
Sep 2001	S_13	SP-010476	001		Correction of invokeldentifier usage	4.0.0	4.1.0
Mar 2002	S_15	SP-020019	002		Correction of erroneous CORBA module names and mapping tables	4.1.0	4.2.0
Mar 2002	S_15	SP-020019	003		Corrections to Basic CM IRP CORBA Solution Set IDLs	4.1.0	4.2.0
Mar 2002	_	SP-020038	004		Addition of missing CORBA exception "ManagedGenericIRPSystem::ValueNotSupported" onto CORBA method "find_managed_objects"	4.1.0	4.2.0
Jun 2002	S_16	SP-020294	005		Correcting IDL definitions of notification structured event Name Value pair names	4.2.0	4.3.0
Jul 2002					Updated the Version number (420->431) and the Date on the cover page	4.3.0	4.3.1
Sep 2002	S_17	SP-020483	006		Add Active Basic CM feature - CORBA Solution Set	4.3.1	5.0.0
Mar 2003		SP-030139	007		Add CORBA equivalents to IS operations "get{Operation Notification}Profile" - alignment with 32.602 & 32.312	5.0.0	5.1.0
Mar 2003	S_19	SP-030139	008		Correction of IDL errors	5.0.0	5.1.0
Mar 2003	S_19	SP-030144	009		Add description for notifications of each activeCM operation and one exception for createMO - alignment with 32.602, Information Service	5.0.0	5.1.0
Jun 2003	S_20	SP-030279	010		Alignment with Basic CM IRP information service (32.602) - add one exception for the operation createMO	5.1.0	5.2.0
Mar 2004	S_23	SP-040105			Automatic upgrade to Rel-6 (no CR)	5.2.0	6.0.0
Sep 2004	S_25	SP-040567	012		Removal of Rules for NRM extensions - Align with 32.622 (Generic NRM IS)	6.0.0	6.1.0
Sep 2004	S_25	SP-040566	014		Removal of unused/duplicate definition of types MOReference and MOReferenceSet	6.0.0	6.1.0
Dec 2004	S_26	SP-040806	015		Align the IDL style in the CORBA SS with the IDL Style Guide in 32.150	6.1.0	6.2.0
Mar 2005	S_27	SP-050044	016		IDL incompliant to the style guide	6.2.0	6.3.0
Mar 2005	S_27	SP-050044	017		Generic System Context, update of reference to IS specification	6.2.0	6.3.0
Apr 2005					Changed back TS Title from Bulk (v630) to Basic (620); erroneously changed with corrupted TS cover.	6.3.0	6.3.1

## History

Document history						
V6.2.0	December 2004	Publication				
V6.3.1	April 2005	Publication				