ETSI TS 128 656 V13.2.0 (2016-08)



Universal Mobile Telecommunications System (UMTS); LTE;

Telecommunication management;
GSM/EDGE Radio Access Network (GERAN)
Network Resource Model (NRM)
Integration Reference Point (IRP);
Solution Set (SS) definitions
(3GPP TS 28.656 version 13.2.0 Release 13)





Reference RTS/TSGS-0528656vd20 Keywords LTE.UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intell	lectual Property Rights	2
Forev	word	2
Moda	al verbs terminology	2
Forev	word	4
Intro	duction	4
1	Scope	5
2	References	
3 3.1	Definitions and abbreviations Definitions	6 6
3.2	Abbreviations	
4	Solution Set Definitions	7
Anne	ex A (normative): CORBA Solution Set	8
A.0	General	8
A.1 A.1.1 A.1.2	, <i>C</i>	8
A.2 A.2.1 A.2.2 A.2.2 A.2.2	Information Object Class (IOC) mapping	9 9 9
A.2.2	2.3 IOC GSMCell	10
A.2.2. A.2.2. A.2.2.	2.5 IOC ExternalGSMCell	10
A.3		
A.3.1 A.3.2		
	•	
	ex B (normative): XML Definitions	
B.0	General	
B.1 B.1.0	Architectural features	
в.1.0 В.1.1		
B.2	Mapping	
B.2.1 B.2.2		
B.3	Solution Set definitions	15
B.3.1	XML definition structure	15
B.3.2 B.3.3	1 1	
	<u> </u>	
	ex C (informative): Change history	
Histo	ory	22

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 28.654: GSM/EDGE Radio Access Network (GERAN) Network Resource Model (NRM) Integration Reference Point (IRP); Requirements.
- 28.655: GSM/EDGE Radio Access Network (GERAN) Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS).
- 28.656: GSM/EDGE Radio Access Network (GERAN) Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions.

1 Scope

The present document is part of an Integration Reference Point (IRP) named GERAN Network Resource Model (NRM) IRP, through which an IRPAgent can communicate configuration management information to one or several IRPManagers concerning GERAN resources. The GERAN NRM IRP comprises a set of specifications defining Requirements, a protocol neutral Information Service and one or more Solution Set definitions.

The present document specifies the Solution Set definitions for the GERAN NRM IRP.

This Solution Set specification is related to 3GPP TS 28.655 V13.0.X.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

	•
[1]	3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
[2]	3GPP TS 32.102: "Telecommunication management; Architecture".
[3]	3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
[4]	3GPP TS 28.655: "Telecommunication management; GERAN Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)".
[5]	3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
[6]	3GPP TS 28.623: 'Telecommunication management; Generic Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions'.
[7]	3GPP TS 32.616: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Solution Set (SS) definitions".
[8]	W3C REC-xml11-20060816: "Extensible Markup Language (XML) 1.1 (Second Edition)".
[9]	Void
[10]	W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures.
[11]	W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes.
[12]	W3C REC-xml-names-20060816: "Namespaces in XML 1.1 (Second Edition)".

3 Definitions and abbreviations

3.1 Definitions

For terms and definitions please refer to 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.600 [3] and 3GPP TS 28.655 [4].

XML file: See definition of [6].

XML document: See definition of [6].

XML declaration: See definition of [6].

XML element: See definition of [6].

empty XML See definition of [6].

XML content (of an XML element): See definition of [6].

XML start-tag: See definition of [6].

XML end-tag: See definition of [6].

XML empty-element tag: See definition of [6].

XML attribute specification: See definition of [6].

DTD: See definition of [6].

XML schema: See definition of [6].

XML namespace: See definition of [6].

XML complex type: See definition of [6].

XML element type: See definition of [6].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM Configuration Management

CORBA Common Object Request Broker Architecture

DN Distinguished Name
DTD Document Type Definition
EDGE Enhanced Data for GSM Evolution
GERAN GSM/EDGE Radio Access Network
GSM Global System for Mobile communication

IS Information Service

IDL Interface Definition Language (OMG)

IOC Information Object Class
IRP Integration Reference Point
IS Information Service
MO Managed Object

MO Managed Object
MOC Managed Object Class
NRM Network Resource Model
OMG Object Management Group

SS Solution Set

UMTS Universal Mobile Telecommunications System UTRAN Universal Terrestrial Radio Access Network

XML eXtensible Markup Language

4 Solution Set Definitions

This specification defines the following 3GPP GERAN NRM IRP Solution Set Definitions:

- 3GPP GERAN NRM IRP CORBA SS (Annex A)
- 3GPP GERAN NRM IRP XML Definitions (Annex B)

Annex A (normative): CORBA Solution Set

A.0 General

This annex contains the CORBA Solution Set for the IRP whose semantics is specified in GERAN NRM IRP: Information Service (TS 28.655 [4]).

A.1 Architectural features

The overall architectural feature of GERAN NRM IRP is specified in 3GPP TS 28.655 [4]. This clause specifies features that are specific to the CORBA SS.

A.1.1 Syntax for Distinguished Names

See clause A.1.1 of [5].

A.1.2 Rules for NRM extensions

See clause A.1.2 of [5].

A.2 Mapping

A.2.1 General mapping

See clause A.2.1 of [5].

A.2.2 Information Object Class (IOC) mapping

A.2.2.1 IOC BSSFunction

Mapping from NRM IOC BSSFunction attributes to SS equivalent MOC BssFunction attributes

IS Attributes	SS Attributes	SS Type
id	bssFunctionId	string
userLabel	userLabel	string

A.2.2.2 IOC BTSSiteMgr

Mapping from NRM IOC BTSSiteMgr attributes to SS equivalent MOC BtsSiteMgr attributes

IS Attributes	SS Attributes	SS Type
id	btsSiteMgrId	string
userLabel	userLabel	string
latitude	latitude	long
longitude	longitude	long
operationalState	operationalState	StateManagementIRPOptConstDefs::Ope rationalStateTypeOpt

A.2.2.3 IOC GSMCell

Mapping from NRM IOC GSMCell attributes to SS equivalent MOC GsmCell attributes

IS Attributes	SS Attributes	SS Type
id	gsmCellId	string
userLabel	userLabel	string
cellIdentity	cellIdentity	long
cellAllocation	cellAllocation	GenericNetworkResourcesIRPSystem::Attrib utesTypes::LongSet
ncc	ncc	long
bcc	bcc	long
lac	lac	long
mcc	mcc	long
mnc	mnc	long
rac	rac	long
racc	racc	long
tsc	tsc	long
rxLevAccessMin	rxLevAccessMin	long
msTxPwrMaxCCH	msTxPwrMaxCCH	long
rfHoppingEnabled	rfHoppingEnabled	boolean
hoppingSequenceList hoppingSequenceList		GeranNRMAttributeTypes::
		HoppingSequenceListType
plmnPermitted	plmnPermitted	long

A.2.2.4 IOC GSMRelation

Mapping from NRM IOC GSMRelation attributes to SS equivalent MOC GsmRelation attributes

IS Attributes	SS Attributes	SS Type
id	gsmRelationId	string
adjacentCell	adjacentCell	string
bcchFrequency	bcchFrequency	long
ncc	ncc	long
bcc	bcc	long
lac	lac	long
isHOAllowed	isHOAllowed	boolean
isRemoveAllowed	isRemoveAllowed	boolean
isESCoveredBy	isESCoveredBy	GeranNRMAttributeTypes::IsEsCoveredByE numType

A.2.2.5 IOC ExternalGSMCell

Mapping from NRM IOC ExternalGSMCell attributes to SS equivalent MOC ExternalGsmCell attributes

IS Attributes	SS Attributes	SS Type
id	externalGsmCellId	string
userLabel	userLabel	string
cellIdentity	cellIdentity	long
bcchFrequency	bcchFrequency	long
ncc	ncc	long
bcc	bcc	long
Lac	lac	long
mcc	mcc	long
mnc	mnc	long
rac	rac	long
racc	racc	long

A.2.2.6 IOC ExternalBSSFunction

Mapping from NRM IOC ExternalBSSFunction attributes to SS equivalent MOC ExternalBssFunction attributes

IS Attributes	SS Attributes	SS Type
id	externalBssFunctionId	string
userLabel	userLabel	string

A.3 Solution Set definitions

A.3.1 IDL definition structure

Clause A.3.2 defines the MO classes for the GERAN NRM IRP.

A.3.2 IDL specification "GeranNetworkResourcesNRMDefs.idl"

```
//File: GeranNetworkResourcesNRMDefs.idl
#ifndef GeranNetworkResourcesNRMDefs_idl
#define GeranNetworkResourcesNRMDefs idl
#include "GenericNetworkResourcesNRMDefs.idl"
#pragma prefix "3gppsa5.org"
/**
 * This module defines constants for each MO class name and
* the attribute names for each defined MO class.
module GeranNetworkResourcesNRMDefs
     /**
      * Definitions for MO class BssFunction
     interface BssFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
        const string CLASS = "BssFunction";
        // Attribute Names
        const string bssFunctionId = "bssFunctionId";
};
```

```
/**
      * Definitions for MO class BtsSiteMgr
      */
     interface\ Bts SiteMgr: Generic Network Resources NRMD efs:: Managed Function
      {
        const string CLASS = "BtsSiteMgr";
        // Attribute Names
        const string btsSiteMgrId = "btsSiteMgrId";
        const string latitude = "latitude";
        const string longitude = "longitude";
        const string operationalState = "operationalState";
};
     /**
      * Definitions for MO class GsmCell
      */
     interface\ GsmCell: GenericNetworkResourcesNRMDefs:: ManagedFunction
        const string CLASS = "GsmCell";
        // Attribute Names
        const string gsmCellId = "gsmCellId";
        const string cellIdentity = "cellIdentity";
        const string cellAllocation = "cellAllocation";
        const string ncc = "ncc";
        const string bcc = "bcc";
        const string lac = "lac";
        const string mcc = "mcc";
        const string mnc = "mnc";
        const string rac = "rac";
        const string racc = "racc";
        const string tsc = "tsc";
        const string rxLevAccessMin = "rxLevAccessMin";
        const string msTxPwrMaxCCH = "msTxPwrMaxCCH";
        const boolean rfHoppingEnabled = 'rfHoppingEnabled';
```

```
const string hoppingSequenceList = "hoppingSequenceList";
        const string plmnPermitted = "plmnPermitted";
};
     /**
      * Definitions for MO class GsmRelation
     interface GsmRelation :GenericNetworkResourcesNRMDefs::Top
        const string CLASS = "GsmRelation";
        // Attribute Names
        const string gsmRelationId = "gsmRelationId";
        const string adjacentCell = "adjacentCell";
        const string bcchFrequency = "bcchFrequency";
        const string ncc = "ncc";
        const string bcc = "bcc";
        const string lac = "lac";
        const string isHOAllowed = "isHOAllowed";
        const string isRemoveAllowed = "isRemoveAllowed";
        const string isESCoveredBy = "isESCoveredBy";
};
     /**
      * Definitions for MO class ExternalGsmCell
      */
     interface\ External GsmCell: Generic Network Resources NRMDefs:: Managed Function
        const string CLASS = "ExternalGsmCell";
        // Attribute Names
        //
        const string externalGsmCellId = "externalGsmCellId";
        const string cellIdentity = "cellIdentity";
        const string bcchFrequency = "bcchFrequency";
        const string ncc = "ncc";
        const string bcc = "bcc";
        const string lac = "lac";
        const string mcc = "mcc";
```

```
const string mnc = "mnc";
        const string rac = "rac";
        const string racc = "racc";
};
       * Definitions for MO class ExternalBssFunction
      interface\ External Bss Function: Generic Network Resources NRMD efs:: Managed Function
        const string CLASS = "ExternalBssFunction";
        // Attribute Names
        //
        const string externalBssFunctionId = "externalBssFunctionId";
};
};
module GeranNRMAttributeTypes
{
      enum\ is Es Covered By Enum Type
      no,
      partial,
      yes
      };
   typedef sequence<br/>
voolean> MAType;
   struct HoppingSequenceType
   {
      MAType ma;
       short hsn;
   };
   type def \ sequence < Hopping Sequence Type > Hopping Sequence List Type; \\
};
#endif
```

Annex B (normative): XML Definitions

B.0 General

This annex contains the XML Definitions for the GERAN NRM IRP as it applies to Itf-N, in accordance with GERAN NRM IRP IS definitions [4].

The XML file formats are based on XML [8], XML Schema [10] [11] and XML Namespace [12] standards.

B.1 Architectural features

B.1.0 General

The overall architectural feature of GERAN NRM IRP is specified in 3GPP TS 28.655 [4].

This clause specifies features that are specific to the Schema definitions.

B.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

B.2 Mapping

B.2.1 General mapping

An IOC maps to an XML element of the same name as the IOC's name in the IS. An IOC attribute maps to a subelement of the corresponding IOC's XML element, and the name of this sub-element is the same as the attribute's name in the IS.

B.2.2 Information Object Class (IOC) mapping

The mapping is nNot present in the current version of this specification.

B.3 Solution Set definitions

B.3.1 XML definition structure

The overall description of the file format of configuration data XML files is provided by 3GPP TS 32.616 [7].

Annex B.3.3 of the present document defines the NRM-specific XML schema geranNrm.xsd for the GERAN Network Resources IRP NRM defined in 3GPP TS 32.652 [4].

XML schema geranNrm.xsd explicitly declares NRM-specific XML element types for the related NRM.

The definition of those NRM-specific XML element types complies with the generic mapping rules defined in 3GPP TS 32.616 [7].

B.3.2 Graphical Representation

The graphical representation is not present in the current version of this specification.

B.3.3 XML schema "geranNrm.xsd"

```
<?xml version="1.1" encoding="UTF-8"?>
<!--
 3GPP TS 28.656 GERAN NRM IRP
 Bulk CM Configuration data file NRM-specific XML schema
 geranNrm.xsd
-->
<schema
 xmlns="http://www.w3.org/2001/XMLSchema"
 xmlns:xn="http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"
 xmlns:un="http://www.3gpp.org/ftp/specs/archive/28_series/28.653#utranNrm"
 xmlns:gn="http://www.3gpp.org/ftp/specs/archive/28_series/28.656#geranNrm"
 xmlns:sm="http://www.3gpp.org/ftp/specs/archive/28_series/28.626#stateManagementIRP"
 xmlns:en="http://www.3gpp.org/ftp/specs/archive/28_series/28.659#eutranNrm"
 xmlns:sp="http://www.3gpp.org/ftp/specs/archive/28_series/28.629#sonPolicyNrm"
 xmlns:gr="http://www.3gpp.org/ftp/specs/archive/28_series/28.663#genericRanNrm"
 targetNamespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.656#geranNrm"
 elementFormDefault="qualified"
<import
   namespace=
"http://www.3gpp.org/ftp/specs/archive/28 series/28.623#genericNrm"
 />
<import
   namespace=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.653#utranNrm"
 />
<import
   namespace=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.626#stateManagementIRP"
 />
<import
   namespace=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.659#eutranNrm"
<import
    namespace=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.629#sonPolicyNrm"
 />
```

<import

```
namespace=
"http://www.3gpp.org/ftp/specs/archive/28 series/28.663#genericRanNrm"
  <simpleType name="isESCoveredByEnumType">
    <restriction base="string">
      <enumeration value="no"/>
      <enumeration value="partial"/>
      <enumeration value="yes"/>
    </restriction>
  </simpleType>
  <complexType name="MA">
    <sequence>
      <element name="rfSelected" type="boolean" minOccurs="0"/>
    </sequence>
  </complexType>
  <complexType name="HoppingSequence">
    <sequence>
      <element name="ma" type="gn:MA" minOccurs="0"/>
      <element name="hsn" type="short" minOccurs="0"/>
    </sequence>
  </complexType>
  <complexType name="HoppingSequenceList">
      <element name="hoppingSequence" type="gn:HoppingSequence" minOccurs="0"/>
    </sequence>
  </complexType>
 <!-- GERAN Network Resources IRP NRM class associated XML elements -->
  <element
    name="BssFunction"
    substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass"
    <complexType>
      <complexContent>
        <extension base="xn:NrmClass">
           <sequence>
             <element name="attributes" minOccurs="0">
            <complexType>
                <all>
                   <element name="userLabel"/>
                </all>
               </complexType>
          </element>
             <choice minOccurs="0" maxOccurs="unbounded">
               <element ref="gn:BtsSiteMgr"/>
               <element ref="xn:VsDataContainer"/>
             </choice>
```

```
</sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element name="BtsSiteMgr">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
           <element name="attributes" minOccurs="0">
          <complexType>
              <all>
                <element name="userLabel"/>
                <element ref="gr:latitude" minOccurs="0"/>
                <element ref="gr:longitude" minOccurs="0"/>
                 <element
                    name="operationalState"
                    type="sm:operationalStateType"
                    minOccurs="0"
                 />
              </all>
             </complexType>
        </element>
           <choice minOccurs="0" maxOccurs="unbounded">
             <element ref="gn:GsmCell"/>
             <element ref="xn:VsDataContainer"/>
           <choice minOccurs="0" maxOccurs="1">
             <element ref="sp:InterRatEsPolicies"/>
           </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element name="GsmCell">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
         <sequence>
           <element name="attributes" minOccurs="0">
          <complexType>
              <all>
                <element name="userLabel"/>
                <element name="cellIdentity"/>
                <element name="cellAllocation"/>
                <element name="ncc"/>
                <element name="bcc"/>
                <element name="lac"/>
                <element name="mcc"/>
                <element name="mnc"/>
                <element name="rac" minOccurs="0"/>
                <element name="racc" minOccurs="0"/>
                <element name="tsc" minOccurs="0"/>
                <element name="rxLevAccessMin"/>
                <element name="msTxPwrMaxCCH"/>
```

```
<element name="rfHoppingEnabled"/>
                 <element name="hoppingSequenceList"/>
                 <element name="plmnPermitted"/>
              </all>
             </complexType>
        </element>
           <choice minOccurs="0" maxOccurs="unbounded">
             <element ref="gn:GsmRelation"/>
             <element ref="un:UtranRelation"/>
             <element ref="en:EUtranRelation"/>
             <element ref="xn:VsDataContainer"/>
             <element ref="gn:GsmCellOptionallyContainedNrmClass"/>
           </choice>
           <choice minOccurs="0" maxOccurs="1">
             <element ref="sp:InterRatEsPolicies"/>
           </choice>
         </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element name="GsmRelation">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
         <sequence>
           <element name="attributes" minOccurs="0">
          <complexType>
              <all>
                 <element name="adjacentCell"/>
                 <element name="bcchFrequency" minOccurs="0"/>
                 <element name="ncc" minOccurs="0"/>
                 <element name="bcc" minOccurs="0"/>
                 <element name="lac" minOccurs="0"/>
                 <element name="isRemoveAllowed" type="boolean" minOccurs="0"/>
                  <element name="isHOAllowed" type="boolean" minOccurs="0"/>
                  <element name="isESCoveredBy" type="gn:isESCoveredByEnumType" minOccurs="0"/>
              </all>
             </complexType>
        </element>
           <choice minOccurs="0" maxOccurs="unbounded">
             <element ref="xn:VsDataContainer"/>
           </choice>
         </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element
  name="ExternalGsmCell"
  substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass"
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
```

```
<sequence>
             <element name="attributes" minOccurs="0">
            <complexType>
                <all>
                   <element name="userLabel"/>
                   <element name="cellIdentity"/>
                   <element name="bcchFrequency"/>
                   <element name="ncc"/>
                   <element name="bcc"/>
                   <element name="lac"/>
                   <element name="mcc"/>
                   <element name="mnc"/>
                   <element name="rac" minOccurs="0"/>
                   <element name="racc" minOccurs="0"/>
                 </all>
               </complexType>
          </element>
             <choice minOccurs="0" maxOccurs="unbounded">
               <element ref="xn:VsDataContainer"/>
             </choice>
             <choice minOccurs="0" maxOccurs="1">
               <element ref="sp:InterRatEsPolicies"/>
             </choice>
           </sequence>
        </extension>
      </complexContent>
    </complexType>
  </element>
  <element
    name="ExternalBssFunction"
    substitutionGroup="xn:SubNetworkOptionallyContainedNrmClass"
    <complexType>
      <complexContent>
        <extension base="xn:NrmClass">
           <sequence>
             <element name="attributes" minOccurs="0">
            <complexType>
                <all>
                   <element name="userLabel"/>
                 </all>
               </complexType>
          </element>
             <choice minOccurs="0" maxOccurs="unbounded">
               <element ref="gn:ExternalGsmCell"/>
               <element ref="xn:VsDataContainer"/>
             </choice>
           </sequence>
         </extension>
      </complexContent>
    </complexType>
  </element>
<element name="GsmCellOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
</schema>
```

Annex C (informative): Change history

	Change history									
Date	TSG#	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New		
2014-06	SA#64	SP-140332	001	-	upgrade XSD	F	11.0.0	11.1.0		
		SP-140332	002	1	Use the latest version of 32.656 as base	F				
		SP-140359	003	-	remove the feature support statements	F				
2014-09	SA#65	SP-140560	005	-	Update the link from Solution Set to Information Service due to the end of Release 12	С	11.1.0	12.0.0		
2016-01	SA#70				ograde to Rel-13(MCC) 12.0.0 13			13.0.0		
2016-03	SA#71	SP-160031	800	-	ke the XML schema well formed A 13.0.0 13.1			13.1.0		

Change history									
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New		
							version		
2016-06	SA#72	SP-160408	0011	1	Α	Correct the definition of hoppingSequenceList - Align with 28.655	13.2.0		
2016-06	SA#72	SP-160407	0012	-	F	Update the link from IRP Solution Set to IRP Information Service	13.2.0		
2016-06	SA#72	SP-160408	0015	-	Α	Namespace reference for the XML attributes "latitude" and	13.2.0		
						"longitude" is missing			

History

	Document history							
V13.0.0	January 2016	Publication						
V13.1.0	April 2016	Publication						
V13.2.0	August 2016	Publication						