

| Genyu Tec | chnology(HK |)Limited | 确认此型号所有图纸;签字确认: | | | | | | | | | |
|---|-------------------|------------------|-----------------------|-------------|-----------------------|--------------|---------|----------------------|--|--|--|--|
| DESIGNED BY: | GY07924NM(CYP)-14 | VERSION: 1.0 | 1. DISPLAY TYPE: | VA/NEGATIVE | 6. POLARIZER TYPE: | TRANSMISSIVE | VERSION | REVISION RECORD | | | | |
| XXX | G10/3%4NM(01/)-14 | NO. 1 OF 1 | 2. OPERATING VOLTAGE: | 5.0V | 7. VIEWING DIRECTION: | 12:00 | 1.0 | 初版 | | | | |
| CHECKED BY: | | UNIT: mm | 3. DRIVE MODE: | 1/4D,1/3B | 8. CONNECTOR: | PIN | 2.0 | 11版玻璃总厚度改成2.0mm | | | | |
| XXX | | DATE: 2015-08-21 | 4. OPERATING TEMP: | -20°C∼70°C | 9. CUSTOMER NO: | | 3.0 | 12版修改图案、分段及逻辑走线、增加管脚 | | | | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: ±0.2 | | | 5. STORAGE TEMP: | -30°C~80°C | 10. LCM NO: | | 4.0 | 13版改分段及逻辑走线 | | | | |

| PIN | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 |
|------|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|-----|----|----|-----|-------|------|------|------|
| СОМ1 | S33 | S25 | S24 | S20 | S19 | 1F | 1A | 2F | 2A | 3F | 3A | S13 | S1 | S5 | S34 | СОМ 1 | | | |
| СОМ2 | S32 | S27 | S26 | S21 | S18 | 1 G | 1B | 2G | 2B | 3G | 3B | S14 | S2 | S6 | S35 | | СОМ2 | | |
| сомз | | S29 | S28 | S22 | S17 | 1E | 1 C | 2E | 2C | 3E | 3C | S15 | S3 | S7 | S36 | | | СОМЗ | |
| СОМ4 | | S31 | S30 | S23 | S16 | S10 | 1 D | S11 | 2D | S12 | 3D | S9 | S4 | S8 | | | | | СОМ4 |

