```
import os
import threading
from aiohttp import web
import telebot
from telebot import types

# 1. Bot tokeni va portni belgilash
BOT_TOKEN =
"8997335630:AAHynHX6WXRLLmtar_DLjVyqH4o3Nqk
M8w8"
PORT = int(os.environ.get("PORT", 10000))

bot = telebot.TeleBot(BOT_TOKEN)

# 2. 31 ta mavzu ro'yxati
topics = [
    "Cendlar",
    "AFU, SFU, FU, SELF FU, Inside FU",
    "Negationlar",
    "X2 va X3 Negation",
    "First, Third",
    "Likvidlik",
    "Major Minor Doji",
    "Doji",
    "LAL",
    "Imbalans",
    "Inside FU",
    "Self FU",
    "HCS modeli",
    "HCS X1, X2, X3",
```

```
    "HCS Negation",
    "HCS + Negation modeli",
    "True Stop Loss",
    "True Stop Loss bilan ishlash",
    "Time Frame Stretch",
    "TFS Established, Fresh, Closed",
    "Self Negation",
    "Entry modellari",
    "Special Candle",
    "0.1 Apart",
    "LAOL Negation",
    "X3 Negation",
    "X2 Manipulation",
    "X3 Manipulation",
    "X2 Negation",
    "True HCS",
    "Yo'nalish topish"
]

# 3. Bot buyruqlari
@bot.message_handler(commands=["start"])
def start(message):
    keyboard =
types.ReplyKeyboardMarkup(resize_keyboard=T
rue)
    keyboard.row("🎓 Discord Live", "ℹ️
Ma'lumot")
    keyboard.row("📚 Kurs haqida ma'lumot
olish", "👤 Admin bilan bog'lanish")

    text = (
        "Assalomu alaykum! 👋\n\n"
        "🎓 <b>To'liq Bank Sistema</b>
kursiga xush kelibsiz.\n\n"
```

```
        "Kerakli bo'limni tanlang."
    )
    bot.send_message(message.chat.id, text,
parse_mode="HTML", reply_markup=keyboard)

@bot.message_handler(func=lambda message:
message.text == "🎓 Discord Live")
def discord_live(message):
    text = "🎓 <b>DISCORD LIVE</b>\n\n"
    text += "📚 <b>TO'LIQ BANK
SISTEMA</b>\n\n"
    text += "Kursda quyidagi mavzular
mavjud:\n\n"

    for i, topic in enumerate(topics, 1):
        text += f"{i}. {topic}\n"

    text += "\n\n📌 Kurs haqida batafsil
ma'lumot olish uchun administrator bilan
bog'laning."
    bot.send_message(message.chat.id, text,
parse_mode="HTML")

@bot.message_handler(func=lambda message:
message.text == "ℹ️ Ma'lumot")
def information(message):
    text = (
        "ℹ️ <b>MA'LUMOT</b>\n\n"
        "🎓 To'liq Bank Sistema — trading
bo'yicha 31 ta mavzuni o'z ichiga olgan
kurs.\n\n"
        "Kursga ulanish va batafsil
ma'lumot uchun administrator bilan
bog'laning."
```

```
    )
    bot.send_message(message.chat.id, text,
parse_mode="HTML")

@bot.message_handler(func=lambda message:
message.text == "📚 Kurs haqida ma'lumot
olish")
def course_info(message):
    text = (
        "📚 <b>KURS HAQIDA</b>\n\n"
        "🎓 <b>To'liq Bank Sistema</b>\n\n"
        "📖 Kursda 31 ta mavzu mavjud.\n\n"
        "💵 <b>Narxi: $500</b>\n\n"
        "Kursga ulanish uchun administrator
bilan bog'laning:\n\n"
        "👤 @laa_admin"
    )
    bot.send_message(message.chat.id, text,
parse_mode="HTML")

@bot.message_handler(func=lambda message:
message.text == "👤 Admin bilan
bog'lanish")
def admin(message):
    keyboard = types.InlineKeyboardMarkup()

keyboard.add(types.InlineKeyboardButton("💬
@laa_admin", url="https://t.me/laa_admin"))

    text = (
        "👤 <b>ADMIN BILAN
BOG'LANISH</b>\n\n"
        "Kurs bo'yicha batafsil ma'lumot,
to'lov va ulanish masalalari uchun
```

```
administratorga yozing."
    )
    bot.send_message(message.chat.id, text,
parse_mode="HTML", reply_markup=keyboard)

# 4. UptimeRobot uchun aiohttp veb-
serverini sozlash
async def handle_ping(request):
    return web.Response(text="Bot is
running!")

def run_web_server():
    app = web.Application()
    app.router.add_get("/", handle_ping)
    # handle_signals=False: web.run_app
alohida oqimda signal handler o'rnata
olmaydi
    web.run_app(app, host="0.0.0.0",
port=PORT, handle_signals=False,
print=None)

# 5. Server va botni ishga tushirish
if __name__ == "__main__":
    # Veb-serverni alohida oqimda ishga
tushirish
    server_thread =
threading.Thread(target=run_web_server,
daemon=True)
    server_thread.start()

    print("✅ Veb-server va Bot
muvaffaqiyatli ishga tushdi...")
    bot.infinity_polling(skip_pending=True)
```