

PowerShell Command Aliases

A quick reference guide for common cmdlet shortcuts and built-in aliases

ALIAS	CMDLET NAME	DESCRIPTION
<code>%</code>	ForEach-Object	Performs an operation against each item in a collection of input objects.
<code>?</code>	Where-Object	Selects objects from a collection based on their property values.
<code>ac</code>	Add-Content	Appends content, such as words or data, to a file.
<code>asnp</code>	Add-PSSnapIn	Adds one or more Windows PowerShell snap-ins to the current session.
<code>cat</code>	Get-Content	Gets the contents of a file.
<code>cd</code>	Set-Location	Sets the current working location to a specified location.
<code>chdir</code>	Set-Location	Sets the current working location to a specified location.
<code>clc</code>	Clear-Content	Deletes the contents of an item, but does not delete the item.
<code>clear</code>	Clear-Host	Clears the display in the host program.
<code>clhy</code>	Clear-History	Deletes entries from the command history.
<code>cli</code>	Clear-Item	Deletes the contents of an item, but does not delete the item.
<code>clp</code>	Clear-ItemProperty	Deletes the value of a property but does not delete the property.
<code>cls</code>	Clear-Host	Clears the display in the host program.
<code>clv</code>	Clear-Variable	Deletes the value of a variable.
<code>cnsn</code>	Connect-PSSession	Reconnects to disconnected sessions.
<code>compare</code>	Compare-Object	Compares two sets of objects.
<code>copy</code>	Copy-Item	Copies an item from one location to another.
<code>cp</code>	Copy-Item	Copies an item from one location to another.
<code>cpì</code>	Copy-Item	Copies an item from one location to another.

ALIAS	CMDLET NAME	DESCRIPTION
cpp	Copy-ItemProperty	Copies a property and value from a specified location to another location.
curl	Invoke-WebRequest	Gets content from a webpage on the Internet.
cvpa	Convert-Path	Converts a path from a Windows PowerShell path to a Windows PowerShell provider path.
dbp	Disable-PSBreakpoint	Disables the breakpoints in the current console.
del	Remove-Item	Deletes files and folders.
diff	Compare-Object	Compares two sets of objects.
dir	Get-ChildItem	Gets the files and folders in a file system drive.
dnsn	Disconnect-PSSession	Disconnects from a session.
ebp	Enable-PSBreakpoint	Enables the breakpoints in the current console.
echo	Write-Output	Sends the specified objects to the next command in the pipeline. If the command is the last command in the pipeline, the objects are displayed in the console.
epal	Export-Alias	Exports information about currently defined aliases to a file.
epcsv	Export-Csv	Converts objects into a series of comma-separated (CSV) strings and saves the strings in a CSV file.
epsn	Export-PSSession	Imports commands from another session and saves them in a Windows PowerShell module.
erase	Remove-Item	Deletes files and folders.
etsn	Enter-PSSession	Starts an interactive session with a remote computer.
exsn	Exit-PSSession	Ends an interactive session with a remote computer.
fc	Format-Custom	Uses a customized view to format the output.
fl	Format-List	Formats the output as a list of properties in which each property appears on a new line.
foreach	ForEach-Object	Performs an operation against each item in a collection of input objects.

ALIAS	CMDLET NAME	DESCRIPTION
ft	Format-Table	Formats the output as a table.
fw	Format-Wide	Formats objects as a wide table that displays only one property of each object.
gal	Get-Alias	Gets the aliases for the current session.
gbp	Get-PSBreakpoint	Gets the breakpoints that are set in the current session.
gc	Get-Content	Gets the contents of a file.
gci	Get-ChildItem	Gets the files and folders in a file system drive.
gcm	Get-Command	Gets all commands.
gcs	Get-PSCallStack	Displays the current call stack.
gdr	Get-PSDrive	Gets drives in the current session.
ghy	Get-History	Gets a list of the commands entered during the current session.
gi	Get-Item	Gets files and folders.
gjb	Get-Job	Gets Windows PowerShell background jobs that are running in the current session.
gl	Get-Location	Gets information about the current working location or a location stack.
gm	Get-Member	Gets the properties and methods of objects.
gmo	Get-Module	Gets the modules that have been imported or that can be imported into the current session.
gp	Get-ItemProperty	Gets the properties of a specified item.
gps	Get-Process	Gets the processes that are running on the local computer or a remote computer.
group	Group-Object	Groups objects that contain the same value for specified properties.
gsn	Get-PSSession	Gets the Windows PowerShell sessions on local and remote computers.

ALIAS	CMDLET NAME	DESCRIPTION
<code>gsnp</code>	Get-PSSnapIn	Gets the Windows PowerShell snap-ins on the computer.
<code>gsv</code>	Get-Service	Gets the services on a local or remote computer.
<code>gu</code>	Get-Unique	Returns unique items from a sorted list.
<code>gv</code>	Get-Variable	Gets the variables in the current console.
<code>gwmi</code>	Get-WmiObject	Gets instances of Windows Management Instrumentation (WMI) classes or information about the available classes.
<code>h</code>	Get-History	Gets a list of the commands entered during the current session.
<code>history</code>	Get-History	Gets a list of the commands entered during the current session.
<code>icm</code>	Invoke-Command	Runs commands on local and remote computers.
<code>iex</code>	Invoke-Expression	Runs commands or expressions on the local computer.
<code>ihy</code>	Invoke-History	Runs commands from the session history.
<code>ii</code>	Invoke-Item	Performs the default action on the specified item.
<code>ipal</code>	Import-Alias	Imports an alias list from a file.
<code>ipcsv</code>	Import-Csv	Creates table-like custom objects from the items in a CSV file.
<code>ipmo</code>	Import-Module	Adds modules to the current session.
<code>ipsn</code>	Import-PSSession	Imports commands from another session into the current session.
<code>irm</code>	Invoke-RestMethod	Sends an HTTP or HTTPS request to a RESTful web service.
<code>ise</code>	powershell_ise.exe	Explains how to use the PowerShell_ISE.exe command-line tool.
<code>iwmi</code>	Invoke-WMIMethod	Calls Windows Management Instrumentation (WMI) methods.
<code>iwr</code>	Invoke-WebRequest	Gets content from a web page on the Internet.

ALIAS	CMDLET NAME	DESCRIPTION
kill	Stop-Process	Stops one or more running processes.
lp	Out-Printer	Sends output to a printer.
ls	Get-ChildItem	Gets the files and folders in a file system drive.
man	help	Displays information about Windows PowerShell commands and concepts.
md	mkdir	Creates a new item.
measure	Measure-Object	Calculates the numeric properties of objects, and the characters, words, and lines in string objects, such as files of text.
mi	Move-Item	Moves an item from one location to another.
mount	New-PSDrive	Creates temporary and persistent mapped network drives.
move	Move-Item	Moves an item from one location to another.
mp	Move-ItemProperty	Moves a property from one location to another.
mv	Move-Item	Moves an item from one location to another.
na1	New-Alias	Creates a new alias.
ndr	New-PSDrive	Creates temporary and persistent mapped network drives.
ni	New-Item	Creates a new item.
nmo	New-Module	Creates a new dynamic module that exists only in memory.
npssc	New-PSSessionConfigurationFile	Creates a file that defines a session configuration.
nsn	New-PSSession	Creates a persistent connection to a local or remote computer.
nv	New-Variable	Creates a new variable.
ogv	Out-GridView	Sends output to an interactive table in a separate window.

ALIAS	CMDLET NAME	DESCRIPTION
oh	Out-Host	Sends output to the command line.
popd	Pop-Location	Changes the current location to the location most recently pushed to the stack. You can pop the location from the default stack or from a stack that you create by using the Push-Location cmdlet.
ps	Get-Process	Gets the processes that are running on the local computer or a remote computer.
pushd	Push-Location	Adds the current location to the top of a location stack.
pwd	Get-Location	Gets information about the current working location or a location stack.
r	Invoke-History	Runs commands from the session history.
rbp	Remove-PSBreakpoint	Deletes breakpoints from the current console.
rcjb	Receive-Job	Gets the results of the Windows PowerShell background jobs in the current session.
rcsn	Receive-PSSession	Gets results of commands in disconnected sessions.
rd	Remove-Item	Deletes files and folders.
rdr	Remove-PSDrive	Deletes temporary Windows PowerShell drives and disconnects mapped network drives.
ren	Rename-Item	Renames an item in a Windows PowerShell provider namespace.
ri	Remove-Item	Deletes files and folders.
rjb	Remove-Job	Deletes a Windows PowerShell background job.
rm	Remove-Item	Deletes files and folders.
rmdir	Remove-Item	Deletes files and folders.
rmo	Remove-Module	Removes modules from the current session.
rni	Rename-Item	Renames an item in a Windows PowerShell provider namespace.
rnp	Rename-ItemProperty	Renames a property of an item.

ALIAS	CMDLET NAME	DESCRIPTION
rp	Remove-ItemProperty	Deletes the property and its value from an item.
rsn	Remove-PSSession	Closes one or more Windows PowerShell sessions (PSSessions).
rsnp	Remove-PSSnapin	Removes Windows PowerShell snap-ins from the current session.
rujb	Resume-Job	Restarts a suspended job.
rv	Remove-Variable	Deletes a variable and its value.
rvpa	Resolve-Path	Resolves the wildcard characters in a path, and displays the path contents.
rwmi	Remove-WMIObject	Deletes an instance of an existing Windows Management Instrumentation (WMI) class.
sajb	Start-Job	Starts a Windows PowerShell background job.
sal	Set-Alias	Creates or changes an alias (alternate name) for a cmdlet or other command element in the current Windows PowerShell session.
saps	Start-Process	Starts one or more processes on the local computer.
sasv	Start-Service	Starts one or more stopped services.
sbp	Set-PSBreakpoint	Sets a breakpoint on a line, command, or variable.
sc	Set-Content	Replaces the contents of a file with contents that you specify.
select	Select-Object	Selects objects or object properties.
set	Set-Variable	Sets the value of a variable. Creates the variable if one with the requested name does not exist.
shcm	Show-Command	Creates Windows PowerShell commands in a graphical command window.
si	Set-Item	Changes the value of an item to the value specified.