```
from flask import Flask, render_template, request

from cs50 import SQL

app = Flask(__name__)

db = SQL("sqlite:///froshims.db")

gapp.route("/")

def index():
    q = request.args.get("q")
    rows = db.execute("SELECT * FROM registrants WHERE name = :name", name=q)
    return render_template("index.html", rows=rows)
```

```
from cs50 import SQL

db = SQL("sqlite:///froshims.db")

rows = db.execute("SELECT * FROM registrants")

for row in rows:
    print(f"{row['name']} registered")
```

```
<!DOCTYPE html>
 2
     <html>
 4
          <head>
              <meta content="initial-scale=1, width=device-width" name="viewport"/>
<title>lecture</title>
 5
 6
7
          </head>
 8
          <body>
 9
              {% block body %}{% endblock %}
10
          </body>
     </html>
11
```

```
from flask import Flask, redirect, render_template, request, session
 2
     from flask_session import Session
 3
 4
     # Configure app
     app = Flask( name )
 6
 7
     # Configure sessions
 8
     app.config["SESSION_PERMANENT"] = False
9
     app.config["SESSION TYPE"] = "filesystem"
     Session(app)
10
11
12
     # Items for sale
13
     ITEMS = ["foo", "bar", "baz"]
14
15
    @app.route("/")
16
     def index():
17
         return render template("index.html")
18
19
20
    @app.route("/update", methods=["POST"])
21
     def update():
22
         for item in request.form:
23
             session[item] = int(request.form.get(item))
24
         return redirect("/cart")
25
26
27
    @app.route("/cart")
28
     def cart():
29
         return render template("cart.html", cart=session)
```

```
{% extends "layout.html" %}
 3
     {% block body %}
     <h1>Cart</h1>
     {% for item in cart %}
         {{ item }} : {{ cart[item] }} <br/><br/>
 6
 7
     {% endfor %}
 8
9
10
         <a href="/">Continue shopping</a>.
11
     {% endblock %}
12
```

```
{% extends "layout.html" %}
 2
 3
     {% block body %}
 4
     <h1>Store</h1>
 5
     <form action="/update" method="post">
         <input min="0" name="foo" type="number" value="0"/> Foo
 6
 7
         <br/>br/>
         <input min="0" name="bar" type="number" value="0"/> Bar
 8
 9
         <br/>
         <input min="0" name="baz" type="number" value="0"/> Baz
10
11
         <br/>br/>
12
         <input type="submit" value="Purchase"/>
13
     </form>
14
     >
15
        View your <a href="/cart">shopping cart</a>.
16
     {% endblock %}
17
```

```
<!DOCTYPE html>
 2
3
4
     <html>
          <head>
              <meta name="viewport" content="initial-scale=1, width=device-width"/>
<title>store</title>
 5
 6
7
          </head>
 8
          <body>
 9
               {% block body %}{% endblock %}
10
          </body>
     </html>
11
```