

Contents

1	Functions	2
1.1	arygcd – binary-like gcd algorithms	2
1.1.1	bit_num – the number of bits	2
1.1.2	binarygcd – gcd by the binary algorithm	2
1.1.3	arygcd_i – gcd over gauss-integer	2
1.1.4	arygcd_w – gcd over Eisenstein-integer	3

Chapter 1

Functions

1.1 arygcd – binary-like gcd algorithms

1.1.1 bit_num – the number of bits

`bit_num(a: integer) → integer`

a のビット数の値を返す。

1.1.2 binarygcd – gcd by the binary algorithm

`binarygcd(a: integer, b: integer) → integer`

binary gcd algorithm を使って a, b の最大公約数の値を返す。

1.1.3 arygcd_i – gcd over gauss-integer

`arygcd_i(a1: integer, a2: integer, b1: integer, b2: integer)
→ (integer, integer)`

二つの gauss 数体 a_1+a_2i , b_1+b_2i の最大公約数の値を返す。“ i ”は虚数。

If the output of `arygcd_i(a1, a2, b1, b2)` is (c_1, c_2) , then the gcd of a_1+a_2i and b_1+b_2i equals c_1+c_2i .

†This function uses $(1+i)$ -ary gcd algorithm, which is a generalization of the binary algorithm, proposed by A.Weilert[2].

1.1.4 arygcd_w – gcd over Eisenstein-integer

```
arygcd_w(a1: integer, a2: integer, b1: integer, b2: integer)
→ (integer, integer)
```

Eisenstein 数体 $a_1+a_2\omega$, $b_1+b_2\omega$ の最大公約数の値を返す。“ ω ” は 1 の虚立方根。

If the output of `arygcd_w(a1, a2, b1, b2)` is (c_1, c_2) , then the gcd of $a_1+a_2\omega$ and $b_1+b_2\omega$ equals $c_1+c_2\omega$.

†This functions uses $(1-\omega)$ -ary gcd algorithm, which is an generalization of the binary algorithm, proposed by I.B. Damgård and G.S. Frandsen [1].

Examples

```
>>> arygcd.binarygcd(32, 48)
16
>>> arygcd_i(1, 13, 13, 9)
(-3, 1)
>>> arygcd_w(2, 13, 33, 15)
(4, 5)
```

Bibliography

- [1] Ivan Bjerre Damgård and Gudmund Skovbjerg Frandsen. Efficient algorithms for the gcd and cubic residuosity in the ring of Eisenstein integers. *Journal of Symbolic Computation*, Vol. 39, No. 6, pp. 643–652, 2005.
- [2] André Weiler. $(1 + i)$ -ary gcd computation in $\mathbb{Z}[i]$ as an analogue to the binary gcd algorithm. *Journal of Symbolic Computation*, Vol. 30, No. 5, pp. 605–617, 2000.