

# Contents

<b>1</b>	<b>Classes</b>	<b>2</b>
1.1	imaginary – complex numbers and its functions . . . . .	2
1.1.1	ComplexField – field of complex numbers . . . . .	4
1.1.1.1	createElement – create Imaginary object . . . . .	5
1.1.1.2	getCharacteristic – get characteristic . . . . .	5
1.1.1.3	issubring – subring test . . . . .	5
1.1.1.4	issuperring – superring test . . . . .	5
1.1.2	Complex – a complex number . . . . .	6
1.1.2.1	getRing – get ring object . . . . .	7
1.1.2.2	arg – argument of complex . . . . .	7
1.1.2.3	conjugate – complex conjugate . . . . .	7
1.1.2.4	copy – copied number . . . . .	7
1.1.2.5	inverse – complex inverse . . . . .	7
1.1.3	ExponentialPowerSeries – exponential power series . . . . .	8
1.1.4	AbsoluteError – absolute error . . . . .	8
1.1.5	RelativeError – relative error . . . . .	8
1.1.6	exp(function) – exponential value . . . . .	8
1.1.7	expi(function) – imaginary exponential value . . . . .	8
1.1.8	log(function) – logarithm . . . . .	8
1.1.9	sin(function) – sine function . . . . .	8
1.1.10	cos(function) – cosine function . . . . .	8
1.1.11	tan(function) – tangent function . . . . .	8
1.1.12	sinh(function) – hyperbolic sine function . . . . .	8
1.1.13	cosh(function) – hyperbolic cosine function . . . . .	8
1.1.14	tanh(function) – hyperbolic tangent function . . . . .	8
1.1.15	atanh(function) – hyperbolic arc tangent function . . . . .	9
1.1.16	sqrt(function) – square root . . . . .	9

# Chapter 1

## Classes

### 1.1 `imaginary` – complex numbers and its functions

The module `imaginary` provides complex numbers. The functions provided are mainly corresponding to the `cmath` standard module.

- **Classes**
  - `ComplexField`
  - `Complex`
  - †`ExponentialPowerSeries`
  - †`AbsoluteError`
  - †`RelativeError`
- **Functions**
  - `exp`
  - `expi`
  - `log`
  - `sin`
  - `cos`
  - `tan`
  - `sinh`
  - `cosh`
  - `tanh`
  - `atanh`
  - `sqrt`

This module also provides following constants:

- e** :  
This constant is obsolete (Ver 1.1.0).
- pi** :  
This constant is obsolete (Ver 1.1.0).
- j** :  
j is the imaginary unit.
- theComplexField** :  
theComplexField is the instance of **ComplexField**.

### 1.1.1 ComplexField – field of complex numbers

The class is for the field of complex numbers. The class has the single instance **theComplexField**.

This class is a subclass of **Field**.

#### Initialize (Constructor)

**ComplexField()**  $\rightarrow$  *ComplexField*

Create an instance of ComplexField. You may not want to create an instance, since there is already **theComplexField**.

#### Attribute

**zero** :  
It expresses The additive unit 0. (read only)

**one** :  
It expresses The multiplicative unit 1. (read only)

#### Operations

operator	explanation
<b>in</b>	membership test; return whether an element is in or not.
<b>repr</b>	return representation string.
<b>str</b>	return string.

## Methods

### 1.1.1.1 createElement – create Imaginary object

`createElement(self, seed: integer) → Integer`

Return a Complex object with `seed`.

`seed` must be complex or numbers having embedding to complex.

### 1.1.1.2 getCharacteristic – get characteristic

`getCharacteristic(self) → integer`

Return the characteristic, zero.

### 1.1.1.3 issubring – subring test

`issubring(self, aRing: Ring) → bool`

Report whether another ring contains the complex field as subring.

### 1.1.1.4 issuperring – superring test

`issuperring(self, aRing: Ring) → bool`

Report whether the complex field contains another ring as subring.

### 1.1.2 Complex – a complex number

Complex is a class of complex number. Each instance has a coupled numbers; real and imaginary part of the number.

This class is a subclass of **FieldElement**.

All implemented operators in this class are delegated to complex type.

#### Initialize (Constructor)

**Complex(re: *number* im: *number*=0 ) → *Imaginary***

Create a complex number.

**re** can be either real or complex number. If **re** is real and **im** is not given, then its imaginary part is zero.

#### Attribute

**real :**

It expresses the real part of complex number.

**imag :**

It expresses the imaginary part of complex number.

## Methods

### 1.1.2.1 `getRing` – get ring object

`getRing(self)` → *ComplexField*

Return the complex field instance.

### 1.1.2.2 `arg` – argument of complex

`arg(self)` → *radian*

Return the angle between the x-axis and the number in the Gaussian plane.  
*radian* must be Float.

### 1.1.2.3 `conjugate` – complex conjugate

`conjugate(self)` → *Complex*

Return the complex conjugate of the number.

### 1.1.2.4 `copy` – copied number

`copy(self)` → *Complex*

Return the copy of the number itself.

### 1.1.2.5 `inverse` – complex inverse

`inverse(self)` → *Complex*

Return the inverse of the number.  
If the number is zero, `ZeroDivisionError` is raised.

### **1.1.3 ExponentialPowerSeries – exponential power series**

This class is obsolete (Ver 1.1.0).

### **1.1.4 AbsoluteError – absolute error**

This class is obsolete (Ver 1.1.0).

### **1.1.5 RelativeError – relative error**

This class is obsolete (Ver 1.1.0).

### **1.1.6 exp(function) – exponential value**

This function is obsolete (Ver 1.1.0).

### **1.1.7 expi(function) – imaginary exponential value**

This function is obsolete (Ver 1.1.0).

### **1.1.8 log(function) – logarithm**

This function is obsolete (Ver 1.1.0).

### **1.1.9 sin(function) – sine function**

This function is obsolete (Ver 1.1.0).

### **1.1.10 cos(function) – cosine function**

This function is obsolete (Ver 1.1.0).

### **1.1.11 tan(function) – tangent function**

This function is obsolete (Ver 1.1.0).

### **1.1.12 sinh(function) – hyperbolic sine function**

This function is obsolete (Ver 1.1.0).

### **1.1.13 cosh(function) – hyperbolic cosine function**

This function is obsolete (Ver 1.1.0).

### **1.1.14 tanh(function) – hyperbolic tangent function**

This function is obsolete (Ver 1.1.0).



**1.1.15    `atanh(function)` – hyperbolic arc tangent function**

This function is obsolete (Ver 1.1.0).

**1.1.16    `sqrt(function)` – square root**

This function is obsolete (Ver 1.1.0).