

Contents

1	Classes	2
1.1	poly.multivar – multivariate polynomial	2
1.1.1	PolynomialInterface – base class for all multivariate poly- nomials	3
1.1.2	BasicPolynomial – basic implementation of polynomial . .	3
1.1.3	TermIndeces – Indeces of terms of multivariate polynomials	3
1.1.3.1	pop	4
1.1.3.2	gcd	4
1.1.3.3	lcm	4

Chapter 1

Classes

1.1 poly.multivar – multivariate polynomial

- Classes
 - †**PolynomialInterface**
 - †**BasicPolynomial**
 - **TermIndeces**

1.1.1 PolynomialInterface – base class for all multivariate polynomials

Since the interface is an abstract class, do not instantiate.

1.1.2 BasicPolynomial – basic implementation of polynomial

Basic polynomial data type.

1.1.3 TermIndeces – Indeces of terms of multivariate polynomials

It is a tuple-like object.

Initialize (Constructor)

TermIndeces(indeces: *tuple*) → *TermIndeces*

The constructor does not check the validity of indeces, such as integerness, nonnegativity, etc.

Operations

operator	explanation
<code>t == u</code>	equality
<code>t != u</code>	inequality
<code>t + u</code>	(componentwise) addition
<code>t - u</code>	(componentwise) subtraction
<code>t * a</code>	(componentwise) multiplication by scalar <code>a</code>
<code>t <= u</code> , <code>t < u</code> , <code>t >= u</code> , <code>t > u</code>	ordering
<code>t[k]</code>	k-th index
<code>len(t)</code>	length
<code>iter(t)</code>	iterator
<code>hash(t)</code>	hash

Methods

1.1.3.1 pop

pop(self, pos: *integer*) → (*integer*, *TermIndeces*)

Return the index at pos and a new TermIndeces object as the omitting-the-pos indeces.

1.1.3.2 gcd

gcd(self, other: *TermIndeces*) → *TermIndeces*

Return the “gcd” of two indeces.

1.1.3.3 lcm

lcm(self, other: *TermIndeces*) → *TermIndeces*

Return the “lcm” of two indeces.

Bibliography