

Contents

1	Functions	2
1.1	combinatorial – combinatorial functions	2
1.1.1	binomial – binomial coefficient	2
1.1.2	combinationIndexGenerator – iterator for combinations	2
1.1.3	factorial – factorial	2
1.1.4	permutationGenerator – iterator for permutation	3
1.1.5	fallingfactorial – the falling factorial	3
1.1.6	risingfactorial – the rising factorial	3
1.1.7	multinomial – the multinomial coefficient	3
1.1.8	bernoulli – the Bernoulli number	3
1.1.9	catalan – the Catalan number	4
1.1.10	euler – the Euler number	4
1.1.11	bell – the Bell number	4
1.1.12	stirling1 – Stirling number of the first kind	4
1.1.13	stirling2 – Stirling number of the second kind	5
1.1.14	partition_number – the number of partitions	5
1.1.15	partitionGenerator – iterator for partition	5
1.1.16	partition_conjugate – the conjugate of partition	5

Chapter 1

Functions

1.1 combinatorial – combinatorial functions

1.1.1 binomial – binomial coefficient

binomial(*n*: integer, *m*: integer) → integer

n と *m* の二項係数の値を返す。すなはち、 $\frac{n!}{(n-m)!m!}$ 。

† 便宜上、binomial(*n*, *n*+*i*) は 0 整数 *i* に対して 0 を返し、binomial(0,0) は 1 を返す。

n は自然数。 *m* は整数。

1.1.2 combinationIndexGenerator – iterator for combinations

combinationIndexGenerator(*n*: integer, *m*: integer) → iterator

Return an iterator which generates indices of *m* element subsets of *n* element set.

combination_index_generator is an alias of combinationIndexGenerator.

1.1.3 factorial – factorial

factorial(*n*: integer) → integer

$n!$ の値を返す。 n は整数。

1.1.4 permutationGenerator – iterator for permutation

permutationGenerator(n : *integer*) \rightarrow *iterator*

Generate all permutations of n elements as list iterator.

The number of generated list is n 's **factorial**, so be careful to use big n .

permutation_generator is an alias of permutationGenerator.

1.1.5 fallingfactorial – the falling factorial

fallingfactorial(n : *integer*, m : *integer*) \rightarrow *integer*

下降階乗の値を返す。 ; n から m へ。 i.e. $n(n-1)\cdots(n-m+1)$.

1.1.6 risingfactorial – the rising factorial

risingfactorial(n : *integer*, m : *integer*) \rightarrow *integer*

上昇階乗の値を返す。 ; n から m へ。 i.e. $n(n+1)\cdots(n+m-1)$.

1.1.7 multinomial – the multinomial coefficient

multinomial(n : *integer*, $parts$: *list*) \rightarrow *integer*

多項係数の値を返す。

$parts$ は自然数数列。 $parts$ の要素をすべてあわせると n と等しくなる。

1.1.8 bernoulli – the Bernoulli number

bernoulli(n : *integer*) \rightarrow *Rational*

n 次 Bernoulli 数の値を返す。

1.1.9 catalan – the Catalan number

catalan(n: *integer*) → *integer*

n 次 Catalan 数の値を返す。

1.1.10 euler – the Euler number

euler(n: *integer*) → *integer*

n 次 Euler 数の値を返す。

1.1.11 bell – the Bell number

bell(n: *integer*) → *integer*

n 次ベル数の値を返す。

ベル数 b の定義:

$$b(n) = \sum_{i=0}^n S(n, i),$$

S は第 2 種スターリング数。(**stirling2**).

1.1.12 stirling1 – Stirling number of the first kind

stirling1(n: *integer*, m: *integer*) → *integer*

第 1 種スターリング数の値を返す。

s はスターリング数。 $(x)_n$ は下降階乗。

$$(x)_n = \sum_{i=0}^n s(n, i) x^i.$$

s satisfies the recurrence relation:

$$s(n, m) = s(n-1, m-1) - (n-1)s(n-1, m).$$

1.1.13 `stirling2` – Stirling number of the second kind

`stirling2(n: integer, m: integer) → integer`

Return Stirling number of the second kind.

S はスターリング数。 $(x)_i$ は下降階乗。 :

$$x^n = \sum_{i=0}^n S(n, i)(x)_i$$

S は以下の関係を満たす。

$$S(n, m) = S(n-1, m-1) + mS(n-1, m)$$

1.1.14 `partition_number` – the number of partitions

`partition_number(n: integer) → integer`

n の分割数の値を返す。

1.1.15 `partitionGenerator` – iterator for partition

`partitionGenerator(n: integer, maxi: integer=0) → iterator`

Return an iterator which generates partitions of n .

If `maxi` is given, then summands are limited not to exceed `maxi`.

The number of partitions (given by **`partition_number`**) grows exponentially, so be careful to use big n .

`partition_generator` is an alias of `partitionGenerator`.

1.1.16 `partition_conjugate` – the conjugate of partition

`partition_conjugate(partition: tuple) → tuple`

Return the conjugate of `partition`.

Examples

```
>>> combinatorial.binomial(5, 2)
10L
>>> combinatorial.factorial(3)
6L
>>> combinatorial.fallingfactorial(7, 3) == 7 * 6 * 5
True
>>> combinatorial.risingfactorial(7, 3) == 7 * 8 * 9
True
>>> combinatorial.multinomial(7, [2, 2, 3])
210L
>>> for idx in combinatorial.combinationIndexGenerator(5, 3):
...     print idx
...
[0, 1, 2]
[0, 1, 3]
[0, 1, 4]
[0, 2, 3]
[0, 2, 4]
[0, 3, 4]
[1, 2, 3]
[1, 2, 4]
[1, 3, 4]
[2, 3, 4]
>>> for part in combinatorial.partitionGenerator(5):
...     print part
...
(5,)
(4, 1)
(3, 2)
(3, 1, 1)
(2, 2, 1)
(2, 1, 1, 1)
(1, 1, 1, 1, 1)
>>> combinatorial.partition_number(5)
7
>>> def limited_summands(n, maxi):
...     "partition with limited number of summands"
...     for part in combinatorial.partitionGenerator(n, maxi):
...         yield combinatorial.partition_conjugate(part)
...
>>> for part in limited_summands(5, 3):
...     print part
...
(2, 2, 1)
```

(3, 1, 1)
(3, 2)
(4, 1)
(5,)

Bibliography