

Modeling the Effects of Nutrition with Mixed-Effect Bayesian Network

Jari Turkia

CGI, Next

University of Eastern Finland, School of Computing





Do eggs raise cholesterol levels?

Why my insulin levels are high?


Can I have more coffee?

**What if you could eat in
a way your body works?**


General guidelines won't answer to these!

| Recommendation: VRN-14/daily: Women 31-60 yrs | | | |
|---|-------------|-------------|------|
| Nutrient | Lower limit | Upper limit | Unit |
| alpha lipoic acid | 36,00 | 45,00 | g/d |
| fat | 59,00 | 106,00 | g/d |
| sucrose | | 10,00 | E% |
| safa | 23,00 | 53,00 | g/d |
| lignin | | | |
| mufa | 12,00 | 26,00 | g/d |
| pufa | 12,00 | 26,00 | g/d |
| linoleic acid | 0,71 | 1,53 | g/d |
| energy | 2110,00 | 2380,00 | kcal |
| carb.hydr. | 237,00 | 357,00 | g/d |
| protein | 53,00 | 119,00 | g/d |

?



Towards personal understanding




So, it's a graph! Which graph describes the reactions best?


From the graph to a graphical model

- Joint distribution factorizes into local distributions by Markov boundaries
- Finding an optimal graph directly is hard. It is easier to search for optimum.
- This search can be narrowed down with prior information

$$P(G|D) \propto P(D|G)P(G) = \prod P(X_i|pa(X_i), G_i)P(G_i)$$



Hierarchical local distributions - $P(D|G_i)$



The data: Sysdimet study



106 patients

4 repeated
measurements
during 12 weeks


17 nutrients, 5
blood tests and
personal info

originally RCT of
Nordic diet

food diaries and
blood tests


1 week response
time before test

Example effect: Protein's effect to blood insulin





- Linear model for single effects is considered adequate since we are more interested in the system as a whole
- Modeling can reveal if these personal differences are just random noise or possibility for personalization



Implementation: Estimation with R and Stan



- The graph search is implemented by R code that estimates local distributions for every non-root node with hierarchical Stan-model, and gathers summaries to an iGraph object.
- The notebook includes also a responsive JavaScript visualization for the graph. Connections that are not typically or personally relevant are removed.
- The model can be accessed from all these three layers...

JavaScript visualization





Let's query the graph – for typical effects

| From | To | Beta (normalized) |
|------------------------|-------------------|-------------------|
| cholesterol medication | LDL-cholesterol | -0.026897912 |
| cholesterol medication | blood cholesterol | -0.011823168 |
| carbon hydrate | HDL-cholesterol | -0.006123904 |

| From | To | Beta (normalized) |
|----------------------------|-----------------|-------------------|
| gender (female) | HDL-cholesterol | 0.017239135 |
| cholesterol medication | blood insulin | 0.008108980 |
| multisaturated fats (mufa) | blood insulin | 0.007027948 |

```
allnodes <- V(sysdimet_graph)
beta <- allnodes[allnodes$type=="beta"]
largest_typical_negative <- beta[order(beta$value),]
largest_typical_positive <- beta[order(-beta$value),]
```

... And for variances between persons

| From | To | b_{σ^2} |
|----------------|----------------------|-------------------|
| energy | blood insulin | 0.15997602 |
| energy | LDL-cholesterol | 0.10701078 |
| energy | HDL-cholesterol | 0.10680727 |
| protein | blood insulin | 0.10266477 |
| pufa | blood insulin | 0.10041444 |


```

allnodes <- V(sysdimet_graph)
b_sigma <- allnodes[allnodes$type=="b_sigma"]
largest_personal_variance <-
  b_sigma[order(-b_sigma$variance),]

```


Querying the local distribution from Stan model: CGI

Personal variance in protein's effect to insulin



```
library("bayesplot")
fsins_posterior <- as.array(mebn.get_localfit("fsins"))
id <- match("prot", datadesc$Name)
mcmc_intervals(fsins_posterior, pars =
  c(paste0("sigma_b[", id, "]"), prob_outer = 0.95)..)
```


Future work: Personal graphs and diets



- With this model we can predict personal graphs for new patients
- Personal diet can be inferred by turning arrows at the personal graph and fixing the blood tests to their desirable levels
- Model is improved by adding the multi-response cases and ARMA
- Studying new dataset with kidney disease patients and new variables



Thank you!

For more details or collaboration, contact me at
jari.turkia@cgi.com