

Analysis of 'When Malware is Packin' Heat; Limits of Machine Learning Classifiers Based on Static Analysis Features'

Thomas Turner
M14507785

Nathan Hafely
enter M number here

ABSTRACT

To maintain search functionalities without losing data privacy on untrusted remote servers, e.g., public clouds, many Searchable Encryption (SE) schemes have been proposed to search over encrypted data without decryption. Normally, a SE scheme leaks access pattern by default in order to provide correct search results to users. Unfortunately, by utilizing access pattern, some recent attacks, such as *range injection attacks*, can easily recover the plaintexts of encrypted data through a set of injected range queries.

ACM Reference Format:

Thomas Turner and Nathan Hafely. 2018. Analysis of 'When Malware is Packin' Heat; Limits of Machine Learning Classifiers Based on Static Analysis Features'. In *Proceedings of ACM XXXXX, XX, XX, XX, XX 2018 (ACM XXXXX'18)*, 1 pages.
https://doi.org/10.475/123_4

1 INTRODUCTION

Searchable Encryption (SE) [5, 13] aims to search encrypted data on an untrusted server without decrypting data. More specifically, with SE, a data owner, e.g., a company, can encrypt a dataset before storing data on an untrusted server, e.g., a public cloud. When this data owner or a user would like to search encrypted data on the server, it can submit a search token, i.e., the encrypted version of a query, to the server. With a search token, the server can return encrypted files/tuples matching to this query without accessing data or queries in plaintext. In addition to its implementation on public servers, SE could also act as the last line of defense minimizing data leakage on internal servers when security breaches, such as the recent leakage of Equifax's 143 million Social Security numbers, happen in practice.

Many SE schemes have been proposed to efficiently support different types of queries, including keyword queries [3–7, 10] and range queries [2, 8, 9, 12], over encrypted data. For example, while both data and queries are encrypted with a SE scheme, a user can retrieve encrypted files/emails containing a sensitive keyword, such as "Alzheimer", or it can retrieve encrypted records of patients' confidential information where attribute age is between (40, 50), from an untrusted server. Several secure data systems, such as CryptoDB [11] and Google Encrypted BigQuery [1], have been implemented in practice based on existing SE schemes.

2 RELATED WORKS

Related works

3 ANOTHER SECTION

This is another section.

4 ANOTHER SECTION

This is another section.

5 CONCLUSION

The natural leakage of a SE scheme, access pattern, could compromise encrypted data if range injection attacks are implemented. Instead of completely hiding access pattern, which would require extremely high and unbearable costs with existing generic countermeasures (e.g., Oblivious RAM), we propose two novel and lightweight mechanisms to alleviate access pattern leakage and mitigate the impact of range injection attacks with affordable tradeoffs.

REFERENCES

- [1] [n. d.]. ([n. d.]). <https://github.com/google/encrypted-bigquery-client>
- [2] Dan Boneh and Brent Waters. 2007. Conjunctive, Subset, and Range Queries on Encrypted Data. In *the Proceedings of Theory of Cryptography (TCC)*. Springer-Verlag, 535–554.
- [3] David Cash, Joseph Jaeger, Stanislaw Jarecki, Charanjit Jutla, Hugo Krawczyk, Marcel-Catalin Rosu, and Michael Steiner. 2014. Dynamic Searchable Encryption in Very-Large Databases: Data Structures and Implementation. In *Proc. of NDSS'14*.
- [4] David Cash, Stanislaw Jarecki, Charanjit Jutla, Hugo Krawczyk, Marcel-Catalin Rosu, and Michael Steiner. 2013. Highly-Scalable Searchable Symmetric Encryption with Support for Boolean Queries. In *Proc. of CRYPTO'13*.
- [5] Reza Curtmola, Juan A. Garay, Seny Kamara, and Rafail Ostrovsky. 2006. Searchable Symmetric Encryption: Improved Definitions and Efficient Constructions. In *Proc. of ACM CCS'06*.
- [6] Seny Kamara and Charalampos Papamanthou. 2013. Parallel and Dynamic Searchable Symmetric Encryption. In *Proc. of FC*.
- [7] Seny Kamara, Charalampos Papamanthou, and Tom Roeder. 2012. Dynamic Searchable Symmetric Encryption. In *Proc. of ACM CCS'12*. 965–976.
- [8] Florian Kerschbaum and Anselme Tueno. 2017. An Efficiently Searchable Encrypted Data Structure for Range Queries. (2017). <https://arxiv.org/abs/1709.09314>.
- [9] Yanbin Lu. 2012. Privacy-Preserving Logarithmic-time Search on Encrypted Data in Cloud. In *Proc. of NDSS'12*.
- [10] Vasilis Pappas, Fernando Krell, Binh Vo, Vladimir Kolesnikov, Tal Malkin, Seung Geol Choi, Wesley George, Angelos Keromytis, and Steven Bellovin. 2014. Blind Seer: A Searchable Private DBMS. In *Proc. of IEEE S&P'14*.
- [11] Raluca Ada Popa, Catherine M.S. Redfield, Nikolai Zeldovich, and Hari Balakrishnan. 2011. CryptDB: Protecting Confidentiality with Encrypted Query Processing. In *Proc. of ACM SOSP'11*.
- [12] Elaine Shi, John Bethencourt, T-H. Hubert Chan, Dawn Song, and Adrian Perrig. 2007. Multi-Dimensional Range Query over Encrypted Data. In *Proc. of IEEE S&P'07*. 350–364.
- [13] Dawn Song, David Wagner, and Adrian Perrig. 2000. Practical Techniques for Searches on Encrypted Data. In *Proc. of IEEE S&P'00*.

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

ACM XXXXX'18, XX 2018, XX, XX, XX

© 2018 Copyright held by the owner/author(s).

ACM ISBN 123-4567-24-567/08/06...\$15.00

https://doi.org/10.475/123_4