Vladimir M. Vishnevskiy Konstantin E. Samouylov Dmitry V. Kozyrev (Eds.)

Communications in Computer and Information Science

678

Distributed Computer and Communication Networks

19th International Conference, DCCN 2016 Moscow, Russia, November 21–25, 2016 Revised Selected Papers



Communications in Computer and Information Science

678

Commenced Publication in 2007 Founding and Former Series Editors: Alfredo Cuzzocrea, Dominik Ślęzak, and Xiaokang Yang

Editorial Board

Simone Diniz Junqueira Barbosa

Pontifical Catholic University of Rio de Janeiro (PUC-Rio), Rio de Janeiro. Brazil

Phoebe Chen

La Trobe University, Melbourne, Australia

Xiaoyong Du

Renmin University of China, Beijing, China

Joaquim Filipe

Polytechnic Institute of Setúbal, Setúbal, Portugal

Orhun Kara

TÜBİTAK BİLGEM and Middle East Technical University, Ankara, Turkey

Igor Kotenko

St. Petersburg Institute for Informatics and Automation of the Russian Academy of Sciences, St. Petersburg, Russia

Ting Liu

Harbin Institute of Technology (HIT), Harbin, China

Krishna M. Sivalingam

Indian Institute of Technology Madras, Chennai, India

Takashi Washio

Osaka University, Osaka, Japan

More information about this series at http://www.springer.com/series/7899

Vladimir M. Vishnevskiy · Konstantin E. Samouylov Dmitry V. Kozyrev (Eds.)

Distributed Computer and Communication Networks

19th International Conference, DCCN 2016 Moscow, Russia, November 21–25, 2016 Revised Selected Papers



Editors

Vladimir M. Vishnevskiy

V.A. Trapeznikov Institute of Control

Sciences

Russian Academy of Sciences

Moscow Russia

Konstantin E. Samouylov

RUDN University

Moscow Russia Dmitry V. Kozyrev

V.A. Trapeznikov Institute of Control

Sciences

Russian Academy of Sciences

Moscow Russia

and

RUDN University

Moscow Russia

ISSN 1865-0929 ISSN 1865-0937 (electronic) Communications in Computer and Information Science ISBN 978-3-319-51916-6 ISBN 978-3-319-51917-3 (eBook) DOI 10.1007/978-3-319-51917-3

Library of Congress Control Number: 2016963656

© Springer International Publishing AG 2016

This work is subject to copyright. All rights are reserved by the Publisher, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, reuse of illustrations, recitation, broadcasting, reproduction on microfilms or in any other physical way, and transmission or information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed.

The use of general descriptive names, registered names, trademarks, service marks, etc. in this publication does not imply, even in the absence of a specific statement, that such names are exempt from the relevant protective laws and regulations and therefore free for general use.

The publisher, the authors and the editors are safe to assume that the advice and information in this book are believed to be true and accurate at the date of publication. Neither the publisher nor the authors or the editors give a warranty, express or implied, with respect to the material contained herein or for any errors or omissions that may have been made. The publisher remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Printed on acid-free paper

This Springer imprint is published by Springer Nature
The registered company is Springer International Publishing AG
The registered company address is: Gewerbestrasse 11, 6330 Cham, Switzerland

Preface

This volume contains a collection of revised selected full-text papers presented at the 19th International Conference on Distributed Computer and Communication Networks (DCCN 2016), held in Moscow, Russia, November 21–25, 2016.

The conference is a continuation of traditional international conferences of the DCCN series, which took place in Bulgaria (Sofia, 1995, 2005, 2006, 2008, 2009, 2014), Israel (Tel Aviv, 1996, 1997, 1999, 2001), and Russia (Moscow, 1998, 2000, 2003, 2007, 2010, 2011, 2013, 2015) in the past 19 years. The main idea of the conference is to provide a platform and forum for researchers and developers from academia and industry from various countries working in the area of theory and applications of distributed computer and communication networks, mathematical modeling, methods of control and optimization of distributed systems, by offering them a unique opportunity to share their views, discuss prospective developments, and pursue collaborations in this area. The content of this volume is related to the following subjects:

- 1. Computer and communication networks architecture optimization
- 2. Control in computer and communication networks
- 3. Performance and QoS/QoE evaluation in wireless networks
- 4. Analytical modeling and simulation of next-generation communications systems
- 5. Queuing theory and reliability theory applications in computer networks
- 6. Wireless 4G/5G networks, cm- and mm-wave radio technologies
- 7. RFID technology and its application in intellectual transportation networks
- 8. Internet of Things, wearables, and applications of distributed information systems
- 9. Probabilistic and statistical models in information systems
- 10. Mathematical modeling of high-tech systems
- 11. Mathematical modeling and control problems
- 12. Distributed and cloud computing systems, big data analytics

The DCCN 2016 conference gathered 208 submissions from authors from 20 different countries. From these, 141 high-quality papers in English were accepted and presented during the conference, 56 of which were recommended by session chairs and selected by the Program Committee for the Springer proceedings.

All the papers selected for the proceedings are given in the form presented by the authors. These papers are of interest to everyone working in the field of computer and communication networks.

We thank all the authors for their interest in DCCN, the members of the Program Committee for their contributions, and the reviewers for their peer-reviewing efforts.

November 2016

Vladimir M. Vishnevskiy Konstantin E. Samouylov

Organization

DCCN 2016 was jointly organized by the Russian Academy of Sciences (RAS), the V. A. Trapeznikov Institute of Control Sciences of RAS (ICS RAS), the Peoples' Friendship University of Russia (RUDN), the National Research Tomsk State University, and the Institute of Information and Communication Technologies of Bulgarian Academy of Sciences (IICT BAS).

Steering Committee

General Chairs

S.N. Vasilyev ICS RAS, Russia

V.M. Filippov RUDN University, Russia

V.M. Vishnevskiy ICS RAS, Russia

K.E. Samouylov RUDN University, Russia

Program Committee

G. Adam Joint Institute for Nuclear Research, Romania
A.M. Andronov Transport and Telecommunication Institute, Latvia
E.A. Ayrjan Joint Institute for Nuclear Research, Armenia
L.I. Abrosimov Moscow Power Engineering Institute, Russia

Mo Adda University of Portsmouth, UK T.I. Aliev ITMO University, Russia

S.D. Andreev
Tampere University of Technology, Finland
G. Araniti
University Mediterranea of Reggio Calabria, Italy
Bijan Saha
Joint Institute for Nuclear Research, Bangladesh
J.Busa
Technical University of Košice (TUKE), Slovakia

H. Chaouchi Institut Télécom SudParis, France

T. Czachorski Institute of Informatics of the Polish Academy of Sciences,

Poland

B.N.Chetverushkin Keldysh Institute of Applied Mathematics of RAS, Russia

O. Chuluunbaatar National University of Mongolia, Mongolia

A.N. Dudin Belarusian State University, Belarus

D. Fiems Ghent University, Belgium

V.P. Gerdt Joint Institute for Nuclear Research, Russia A. Gelman IEEE Communications Society, USA

D. Grace York University, UK

A.A. Grusho Federal Research Center "Computer Science and Control"

of RAS. Russia

M. Hnatich Pavol Jozef Šafárik University in Košice (UPJŠ), Slovakia

J. HošekJ. KolodziejBrno University of Technology, Czech RepublicCracow University of Technology, Poland

V.Y. Korolev Lomonosov Moscow State University, Russia

B. Khoromskij Max Planck Institute for Mathematics in the Sciences,

Germany

C. Kim Sangji University, Korea

G. Kotsis Johannes Kepler University Linz, Austria

A. Krishnamoorthy
A.E. Kucheryavy

Cochin University of Science and Technology, India
Bonch-Bruevich St. Petersburg State University of

Telecommunications, Russia

E.A. Kucheryavy Tampere University of Technology, Finland

L. Lakatos
 Budapest University, Hungary
 R. Lazarov
 Texas A&M University, USA
 E. Levner
 Holon Institute of Technology, Israel

B.Y. Lemeshko Novosibirsk State Technical University, Russia

S.D. Margenov Institute of Information and Communication Technologies

of Bulgarian Academy of Sciences, Bulgaria

O. Martikainen Service Innovation Research Institute, Finland
L. Militano University Mediterranea of Reggio Calabria, Italy

E.V. Morozov Institute of Applied Mathematical Research of the Karelian

Research Centre RAS, Russia

G.K. Mishkoy Academy of Sciences of Moldova, Moldavia

A.A. Nazarov Tomsk State University, Russia

I. Novak Brno University of Technology, Czech Republic

D.A. Novikov ICS RAS, Russia

Y.N. Orlov Keldysh Institute of Applied Mathematics of RAS, Russia

M. Pagano Pisa University, Italy

I.V. Puzynin Joint Institute for Nuclear Research, Russia

Y.P. Rybakov RUDN University, Russia

V.V. Rykov Gubkin Russian State University of Oil and Gas, Russia Z. Saffer Budapest University of Technology and Economics,

Hungary

L.A. Sevastianov RUDN University, Russia

S.Ya. Shorgin Federal Research Center "Computer Science and Control"

of RAS, Russia

A.L. Skubachevskii RUDN University, Russia P. Stanchev Kettering University, USA

A.M. Turlikov St. Petersburg State University of Aerospace

Instrumentation, Russia

D. Udumyan University of Miami, USA

S.I. Vinitsky Joint Institute for Nuclear Research, Russia

J.P. Zaychenko Kyiv Polytechnic Institute, Ukraine

Executive Committee

D.V. Kozyrev (Chair) RUDN University and ICS RAS, Russia

S.P. Moiseeva Tomsk State University, Russia

T. Atanasova IICT BAS, Bulgaria

Y.V. Gaidamaka RUDN University, Russia D.S. Kulyabov RUDN University, Russia A.V. Demidova RUDN University, Russia

S.N. Kupriyakhina ICS RAS, Russia

Organizers and Partners

Organizers

Russian Academy of Sciences

RUDN University

V.A. Trapeznikov Institute of Control Sciences of RAS (ICS RAS)

National Research Tomsk State University (NR TSU)

Institute of Information and Communication Technologies of Bulgarian Academy of Sciences (IICT-BAS)

Research and Development Company "Information and Networking Technologies"

Support

Information support was provided by the Moscow department of the IEEE Communication Society. Financial support was provided by the Russian Foundation for Basic Research.

Contents

Computer and Con	mmunication	Networks
------------------	-------------	----------

Enhanced C-RAN Architecture Supporting SDN and NFV Functionalities for D2D Communications	3
On Internet of Things Programming Models	13
A Trial of Yoking-Proof Protocol in RFID-based Smart-Home Environment Anton Prudanov, Sergey Tkachev, Nikolay Golos, Pavel Masek, Jiri Hosek, Radek Fujdiak, Krystof Zeman, Aleksandr Ometov, Sergey Bezzateev, Natalia Voloshina, Sergey Andreev, and Jiri Misurec	25
Analysis and Simulation of UHF RFID Vehicle Identification System Vladimir Vishnevskiy, Andrey Larionov, and Roman Ivanov	35
Modeling and Performance Comparison of Caching Strategies for Popular Contents in Internet	47
Transient Change Detection in Mixed Count and Continuous Random Data and the Cyber-Physical Systems Security	57
Performance Modeling of Finite-Source Cognitive Radio Networks Using Simulation	64
Performance Measures and Optimization of Queueing System with Reserve Server	74
Reliability of a k-out-of-n System with a Repair Facility – Essential and Inessential Services	89
Tractable Distance Distribution Approximations for Hardcore Processes Pavel Abaev, Yulia Gaidamaka, Konstantin Samouylov, and Sergey Shorgin	98

The Total Capacity of Customers in the Infinite-Server Queue with MMPP Arrivals	110
On the Queue Length in the Discrete Cyclic-Waiting System of Geo/G/1 Type	121
Optimal Control of <i>M(t)/M/K</i> Queues with Homogeneous and Heterogeneous Servers	132
Algorithmic and Software Tools for Optimal Design of New Generation Computer Networks	145
One Problem of the Risk Control	162
Analysis of the Throughput in Selective Mode of Transport Protocol Vladimir Kokshenev, Pavel Mikheev, Sergey Suschenko, and Roman Tkachyov	168
A Cyclic Queueing System with Priority Customers and T-Strategy of Service	182
Comparative Analysis of Reliability Prediction Models for a Distributed Radio Direction Finding Telecommunication System	194
Low-Priority Queue and Server's Steady-State Existence in a Tandem Under Prolongable Cyclic Service	210
On Regenerative Envelopes for Cluster Model Simulation	222
Two Asymptotic Conditions in Queue with MMPP Arrivals and Feedback Agassi Melikov, Lubov Zadiranova, and Alexander Moiseev	231
Applications of Augmented Reality Traffic and Quality Requirements Study and Modeling	241
Rate of Convergence to Stationary Distribution for Unreliable Jackson-Type Queueing Network with Dynamic Routing	253

Contents	XII
On the Method of Group Polling upon the Independent Activity of Sensors in Unsynchronized Wireless Monitoring Networks	266
A Noising Method for the Identification of the Stochastic Structure of Information Flows	279
Efficiency of Redundant Multipath Transmission of Requests Through the Network to Destination Servers	290
The Fault-Tolerant Structure of Multilevel Secure Access to the Resources of the Public Network	302
Formation of the Instantaneous Information Security Audit Concept I.I. Livshitz, D.V. Yurkin, and A.A. Minyaev	314
Computer Simulation of Average Channel Access Delay in Cognitive Radio Network	325
Efficiency of Redundant Service with Destruction of Expired and Irrelevant Request Copies in Real-Time Clusters	337
Stationary Waiting Time Distribution in $G M n r$ with Random Renovation Policy	349
Analysis of the Packet Path Lengths in the Swarms for Flying Ubiquitous Sensor Networks	361
Properties of Fluid Limit for Closed Queueing Network with Two Multi-servers	369
On Strong Bounds of Rate of Convergence for Regenerative Processes Galina Zverkina	381
Convergence Evaluation of Adaptation to Losses: The Case of Subscription Notification Delivery to Mobile Users in Smart Spaces	394
Sojourn Time Analysis for Processor Sharing Loss Queuing System with Service Interruptions and MAP Arrivals	406

The Estimation of Probability Characteristics of Cloud Computing Systems with Splitting of Requests	41
Anastasia Gorbunova, Ivan Zaryadov, Sergey Matyushenko, and Eduard Sopin	
Simulation of Medical Sensor Nanonetwork Applications Traffic	43
Long-Range Data Transmission on Flying Ubiquitous Sensor Networks (FUSN) by Using LPWAN Protocols	44
Hardware-Software Simulation Complex for FPGA-Prototyping of Fault-Tolerant Computing Systems	45
Mathematical Modeling and Computation	
Numerical and Analytical Modeling of Guided Modes of a Planar Gradient Waveguide	47
Diagram Representation for the Stochastization of Single-Step Processes <i>Ekaterina G. Eferina, Michal Hnatich, Anna V. Korolkova,</i> <i>Dmitry S. Kulyabov, Leonid A. Sevastianov, and Tatiana R. Velieva</i>	48
Construction and Analysis of Nondeterministic Models of Population Dynamics	49
Model of Diatomic Homonuclear Molecule Scattering by Atom or Barriers A.A. Gusev, O. Chuluunbaatar, S.I. Vinitsky, L.L. Hai, V.L. Derbov, and P.M. Krassovitskiy	51
The Coupled-Channel Method for Modelling Quantum Transmission of Composite Systems	52
The Stochastic Processes Generation in OpenModelica	53

	Contents	XV
Metric Analysis as a Tool for Interpolating Multivariate Functin the Case of an Information Lack		553
Systems of Differential Equations of Infinite Order with Small and Countable Markov Chains		565
Applying OpenCL Technology for Modelling Seismic Process Using Grid-Characteristic Methods		577
Linear Approach for Mathematical Modelling as a Tool for Enterportfolio Selection		589
Mathematical Modeling of Smoothly-Irregular Integrated-Optic Waveguide and Mathematical Synthesis of Waveguide Lunebu Edik Ayrjan, Genin Dashitsyrenov, Konstantin Lovetskiy, Nikolai Nikolaev, Anton Sevastianov, Leonid Sevastianov, and Eugeny Laneev		601
Damping Problem for Multidimensional Control System with A.S. Adkhamova and A.L. Skubachevskii	Delays	612
Nonclassical Hamilton's Actions and the Numerical Performance of Variational Methods for Some Dissipative Problems		624
Modeling of Spinning Sphere Motion in Shear Flow of Viscon Yuri P. Rybakov	us Fluid	635
Fast Two-Dimensional Smoothing with Discrete Cosine Trans Pavel Lyubin and Eugeny Shchetinin	form	646
Cluster Method of Description of Information System Data M on Multidimensional Approach		657
Author Index		669

Diagram Representation for the Stochastization of Single-Step Processes

Ekaterina G. Eferina¹, Michal Hnatich^{3,4,5}, Anna V. Korolkova¹, Dmitry S. Kulyabov^{1,2(\boxtimes)}, Leonid A. Sevastianov^{1,3}, and Tatiana R. Velieva¹

Department of Applied Probability and Informatics, RUDN University (Peoples' Friendship University of Russia), 6 Miklukho-Maklaya Street, Moscow 117198, Russia eg.eferina@gmail.com, {akorolkova,dharma,sevast}@sci.pfu.edu.ru, trvelieva@gmail.com

- Laboratory of Information Technologies, Joint Institute for Nuclear Research,
 6 Joliot-Curie, Dubna, Moscow Region 141980, Russia
 Bogoliubov Laboratory of Theoretical Physics,
 Joint Institute for Nuclear Research,
 6 Joliot-Curie, Dubna, Moscow Region 141980, Russia
 hnatic@saske.sk
- ⁴ Department of Theoretical Physics, SAS, Institute of Experimental Physics, Watsonova 47, 040 01 Košice, Slovakia
 - Faculty of Science, Pavol Jozef Šafárik University in Košice (UPJŠ), Šrobárova 2, 041 80 Košice, Slovakia

Abstract. Background. By the means of the method of stochastization of one-step processes we get the simplified mathematical model of the original stochastic system. We can explore these models by standard methods, as opposed to the original system. The process of stochastization depends on the type of the system under study. Purpose. We want to get a unified abstract formalism for stochastization of one-step processes. This formalism should be equivalent to the previously introduced. Methods. To unify the methods of construction of the master equation, we propose to use the diagram technique. Results. We get a diagram technique, which allows to unify getting master equation for the system under study. We demonstrate the equivalence of the occupation number representation and the state vectors representation by using a Verhulst model. Conclusions. We have suggested a convenient diagram formalism for unified construction of stochastic systems.

Keywords: Occupation numbers representation \cdot Fock space \cdot Dirac notation \cdot One-step processes \cdot Master equation \cdot Diagram technique

1 Introduction

When modeling various physical and technical systems, we often can model them in the form of a one-step processes (see [1,3,4,24]). Then there is the problem

© Springer International Publishing AG 2016 V.M. Vishnevskiy et al. (Eds.): DCCN 2016, CCIS 678, pp. 483–497, 2016. DOI: 10.1007/978-3-319-51917-3_42 of adequate representation and study of the resulting model. For the statistical systems in addition to representation of the state vectors (combinatorial approach) [3,4] the representation of the occupation numbers (operator approach) (see [12,13,17,19,20,23]) is also used. This representation is especially well suited for the system with a variable number of elements description.

However, technique for obtaining models for the combinatorial approach is quite different from the technique for the operator approach. In this paper, we want to propose a unified methodology for both approaches on the basis of the diagram technique.

The structure of the article is as follows. In the Sect. 2 basic notations and conventions are introduced. The ideology of the method of stochastization of one-step process and its components are described in the Sect. 3. Then the interaction schemes and master equation overview are presented in the next Sects. 5 and 4. The combinatorial method of modelling is discussed in the following Sect. 6. The operator model approach is presented in the Sect. 7. In fact diagram technique introduced in Sect. 8. Application of of this technique is described in Sect. 9 on the example of Verhulst model.

2 Notations and Conventions

- 1. The abstract indices notation (see [22]) is used in this work. Under this notation a tensor as a whole object is denoted just as an index (e.g., x^i), components are denoted by underlined index (e.g., $x^{\underline{i}}$).
- 2. We will adhere to the following agreements. Latin indices from the middle of the alphabet (i, j, k) will be applied to the space of the system state vectors. Latin indices from the beginning of the alphabet (a) will be related to the Wiener process space. Greek indices (α) will set a number of different interactions in kinetic equations.

3 General Review of the Methodology

Our methodology is completely formalized in such a way that it is sufficient when the original problem is formulated accordingly. It should be noted that the most of the models under our study can be formalized as a one-step process (see [10,18]). In fact, for this type of models we developed this methodology, but it may be expanded for other processes.

First we transform our model to the one-step process (see Fig. 1). Next, we need to formalize this process in the form of interaction schemes (see [3,4,13]).

Each scheme has its own interaction semantics. Semantics leads directly to the master equation (see [10,18]). However, the master equation has usually rather complex structure that makes it difficult for direct study and solution. Our technique involves two possibilities (see Fig. 2):

¹ The analogs of the interaction schemes are the equations of chemical kinetics, reaction particles and etc.

- computational approach—the solution of the master equation with help of perturbation theory;
- modeling approach—the approximate models are obtained in the form of Fokker-Planck and Langevin equations.




Fig. 1. One-step process




Fig. 2. The general structure of the methodology




Fig. 3. Combinatorial modeling approach

The computational approach allows to obtain a concrete solution for the studied model. In our methodology, this approach is associated with perturbation theory (see [14-16]).




Fig. 4. Operator modeling approach

The model approach provides a model that is convenient to study numerically and qualitatively. In addition, this approach assumes the iterative process of research: the obtained approximate model can be specified and changed, which leads to the correction of initial interaction schemes.

There are two ways of building the master equation²

- combinatorial approach (see Fig. 3);
- operator approach (see Fig. 4).

In the combinatorial approach, all operations are performed in the space of states of the system, so we deal with a particular system throughout manipulations with the model.

For the operator approach we can abstract from the specific implementation of the system under study. We are working with abstract operators. We return to the state space only at the end of the calculations. In addition, we choose a particular operator algebra on the basis of symmetry of the problem.

4 Interaction Schemes

The system state is defined by the vector $\varphi^i \in \mathfrak{R}^n$, where n is system dimension³. The operator $I_j^i \in \mathfrak{N}_0^n \times \mathfrak{N}_0^n$ describes the state of the system before the interaction, the operator $F_j^i \in \mathfrak{N}_0^n \times \mathfrak{N}_0^n$ describes the state of the system after the interaction⁴. The result of interaction is the system transition from one state to another one.

There are s types of interaction in our system, so instead of I_j^i and F_j^i operators we will use operators $I_j^{i\alpha} \in \mathfrak{N}_0^n \times \mathfrak{N}_0^n \times \mathfrak{N}_+^s$ and $F_j^{i\alpha} \in \mathfrak{N}_0^n \times \mathfrak{N}_0^n \times \mathfrak{N}_+^s$.

² In quantum field theory the path integrals approach can be considered as an analogue of the combinatorial approach and the method of second quantization as analog of the operator approach.

³ We denote the module over the field \mathbb{R} as \mathfrak{R} . Accordingly, \mathfrak{N} , \mathfrak{N}_0 , \mathfrak{N}_+ are modules over rings \mathbb{N} , \mathbb{N}_0 (cardinal numbers with 0), \mathbb{N}_+ (cardinal numbers without 0).

⁴ The component dimension indices take on values $\underline{i}, j = \overline{1, n}$.

⁵ The component indices of number of interactions take on values $\underline{\alpha} = \overline{1, s}$.

The interaction of the system elements will be described by interaction schemes, which are similar to schemes of chemical kinetics [11,26]:

$$I_{j}^{i\underline{\alpha}}\varphi^{j} \stackrel{+_{k_{\underline{\alpha}}}}{\longleftarrow_{k_{\alpha}}} F_{j}^{i\underline{\alpha}}\varphi^{j}, \qquad \underline{\alpha} = \overline{1, s}, \tag{1}$$

the Greek indices specify the number of interactions and Latin are the system order. The coefficients ${}^+k_{\underline{\alpha}}$ and ${}^-k_{\underline{\alpha}}$ have meaning intensity (speed) of interaction.

We can also write (1) not in the form of vector equations but in the form of sums:

$$I_{j}^{i\underline{\alpha}}\varphi^{j}\delta_{i} \stackrel{+_{k_{\underline{\alpha}}}}{\longleftarrow} F_{j}^{i\underline{\alpha}}\varphi^{j}\delta_{i}, \tag{2}$$

where $\delta_i = (1, ..., 1)$.

Also the following notation will be used:

$$I^{i\underline{\alpha}}:=I^{i\underline{\alpha}}_j\delta^j,\quad F^{i\underline{\alpha}}:=F^{i\underline{\alpha}}_j\delta^j,\quad r^{i\underline{\alpha}}:=r^{i\underline{\alpha}}_j\delta^j.$$

The state transition is given by the operator:

$$r_j^{i\underline{\alpha}} = F_j^{i\underline{\alpha}} - I_j^{i\underline{\alpha}}.$$
 (3)

5 The Master Equation

For the system description we will use the master equation, 6 which describes the transition probabilities for Markov process (see [10,18]):

$$\frac{\partial p(\varphi_2, t_2|\varphi_1, t_1)}{\partial t} = \int \left[w(\varphi_2|\psi, t_2) p(\psi, t_2|\varphi_1, t_1) - w(\psi|\varphi_2, t_2) p(\varphi_2, t_2|\varphi_1, t_1) \right] d\psi,$$

where $w(\varphi|\psi,t)$ is the probability of transition from the state ψ to the state φ for unit time.

By fixing the initial values of φ_1, t_1 , we can write the equation for subensemble:

$$\frac{\partial p(\varphi, t)}{\partial t} = \int [w(\varphi|\psi, t)p(\psi, t) - w(\psi|\varphi, t)p(\varphi, t)]d\psi. \tag{4}$$

For the discrete domain of φ , the (4) can be written as follows (the states are numbered by n and m):

$$\frac{\partial p_n(t)}{\partial t} = \sum_m \left[w_{nm} p_m(t) - w_{mn} p_n(t) \right],\tag{5}$$

where the p_n is the probability of the system to be in a state n at time t, w_{nm} is the probability of transition from the state m into the state n per unit time.

⁶ Master equation can be considered as an implementation of the Kolmogorov equation. However, the master equation is more convenient and has an immediate physical interpretation (see [18]).

6 Combinatorial Approach

There are two types of system transition from one state to another (based on one-step processes) as a result of system elements interaction: in the forward direction $(\varphi^i + r^{i\underline{\alpha}})$ with the probability ${}^+s_{\underline{\alpha}}(\varphi^k)$ and in the opposite direction $(\varphi^i - r^{i\underline{\alpha}})$ with the probability ${}^-s_{\underline{\alpha}}(\varphi^k)$ (Fig. 1). The matrix of transition probabilities has the form:

$$w_{\underline{\alpha}}(\varphi^i|\psi^i,t) = {}^+s_{\alpha}\delta_{\varphi^i,\psi^i+1} + {}^-s_{\alpha}\delta_{\varphi^i,\psi^i-1}, \qquad \underline{\alpha} = \overline{1,s},$$

where $\delta_{i,j}$ is Kronecker delta.

Thus, the general form of the master equation for the state vector φ^i , changing by steps with length $r^{i\underline{\alpha}}$, is:

$$\begin{split} \frac{\partial p(\varphi^i,t)}{\partial t} &= \sum_{\underline{\alpha}=1}^s \left\{ -s_{\underline{\alpha}}(\varphi^i + r^{i\underline{\alpha}},t) p(\varphi^i + r^{i\underline{\alpha}},t) \right. \\ &+ \left. +s_{\underline{\alpha}}(\varphi^i - r^{i\underline{\alpha}},t) p(\varphi^i - r^{i\underline{\alpha}},t) - \left[+s_{\underline{\alpha}}(\varphi^i) + -s_{\underline{\alpha}}(\varphi^i) \right] p(\varphi^i,t) \right\}. \end{split} \tag{6}$$

7 Operator Approach

7.1 Occupation Numbers Representation

Occupation number representation is the main language in the description of many-body physics. The main elements of the language are the wave functions of the system with information about how many particles are in each single-particle state. The creation and annihilation operators are used for system states change.

The method of application of the formalism of second quantization for the non-quantum systems (statistical, deterministic systems) was studied in a series of articles (see [6,7,12,21]).

The Dirac notation is commonly used for occupation numbers representation recording.

7.2 Dirac Notation

This notation is proposed by Dirac⁷ (see [5]). Under this notation, state of the system is described by an element of the projective Hilbert space \mathcal{H} . The vector $\varphi^i \in \mathcal{H}$ is defined as $|i\rangle$, and covariant vector (covector) $\varphi_i \in \mathcal{H}^* := \mathcal{H}_{\bullet}$ is defined as $\langle i|$. Conjunction operation is used for raising and lowering of indices⁸:

$$\varphi_i^* := \varphi_i = (\varphi^i)^\dagger \equiv \langle i| = |i\rangle^\dagger.$$

⁷ The notation is based on the notation, proposed by G. Grassmann in 1862 (see [2, p. 134]).

⁸ In this case, we use Hermitian conjugation •[†]. The sign of the complex conjugate •* in this case is superfluous.

The scalar product is as follows:

$$\varphi_i \varphi^i \equiv \langle i | i \rangle.$$

The tensor product is:

$$\varphi_j \varphi^i \equiv |i\rangle\langle j|.$$

7.3 Creation and Annihilation Operators

The transition to the space of occupation numbers is not a unitary transformation. However, the algorithm of transition (specific to each task) can be constructed.

Let's write the master equation (5) in the occupation number representation. We will consider a system that does not depend on the spatial variables. For simplicity, we consider the one-dimensional version.

Let's denote in (5) the probability that there are n particles in our system as φ_n :

$$\varphi_n := p_n(\varphi, t).$$

The vector space \mathcal{H} consists of states of φ .

Depending on the structure of the model, we can introduce the probability-based or the moment-based inner products [12]. We introduce a scalar product, exclusive $(\langle | \rangle_{ex})$ and inclusive $(\langle | \rangle_{in})$. Let $|n\rangle$ are basis vectors.

$$\langle \varphi | \psi \rangle_{\text{ex}} = \sum_{n} n! p_{n}^{*}(\varphi) p^{n}(\psi);$$

$$\langle \varphi | \psi \rangle_{\text{in}} = \sum_{n} \frac{1}{k!} n_{k}^{*}(\varphi) n^{k}(\psi).$$

$$(7)$$

There n_k are factorial moments:

$$n_k(\varphi) = \langle n(n-1)\cdots(n-k+1)\rangle = \frac{\partial k}{\partial z^k}G(z,\varphi)|_{z=1},$$

G is generating function:

$$G(z,\varphi) = \sum_{n} z^{n} p_{n}(\varphi).$$

Let's use creation and annihilation operators:

$$\pi |n\rangle = |n+1\rangle,$$

$$a|n\rangle = n|n-1\rangle$$

and commutation rule⁹:

$$[a,\pi] = 1. \tag{8}$$

If the form of scalar product is (7) then from (8) follows that our system is described by Bose–Einstein statistics.

 $[\]overline{\ }^{9} \text{ In fact, } a\pi |n\rangle - \pi a|n\rangle = (n+1)|n\rangle - n|n\rangle = |n\rangle.$

7.4 The Liouville Operator

In the occupation numbers formalism the master equation becomes the Liouville equation:

$$\frac{\partial}{\partial t}|\varphi(t)\rangle = L|\varphi(t)\rangle.$$

The Liouville operator L satisfies the relation:

$$\langle 0|L=0. \tag{9}$$

8 Diagram Representation

We describe our proposed diagram technique for the stochastization of one-step processes.



Fig. 5. Forward interaction

Fig. 6. Backward interaction

We will write the scheme of interaction in the form of diagrams. Each scheme (1) or (2) corresponds to a pair of diagrams (see Figs. 5 and 6) for forward and backward interaction respectively. The diagram consists of the following elements.

- Incoming lines (in the Fig. 5 are denoted by the solid line). These lines are directed to the line of interaction. These lines are marked with the number and type of interacting entities. You can write a single entity per a line or group them.
- Outgoing lines (in the Fig. 5 are denoted by the solid line). These lines are directed from the line of interaction. These lines are marked with the number and type of interacting entities. You can write a single entity per a line or group them.
- Line of interaction (in the Fig. 5 is denoted by the dotted line). The direction
 of time is denoted by the arrow. This line is marked by the coefficient of
 intensity of the interaction.

Each line is attributed to a certain factor (depending on the the approach chosen). The resulting expression is obtained by multiplying these factors.

¹⁰ In order not to clutter the diagram, we have only one type of interacting entities left in these schemes.

8.1 Operator Approach

We obtain the Liouville operator when using interaction diagrams in the operator approach. Let us assign the corresponding factor for each line. The resulting term is obtained as the normal ordered product of factors.¹¹

Fig. 7. Forward interaction (operator approach)

Fig. 8. Backward interaction (operator approach)

We use the following factors for each type of line (Fig. 7).

- Incoming line. This line corresponds to the disappearance of one entity from the system. Therefore, it corresponds to the annihilation operator a. It is clear that the line with combined capacity I corresponds to the operator a^{I} .
- Outgoing line. This line corresponds to the emergence of one entity in the system. Therefore, it corresponds to the creation operator π . It is clear that the line with combined capacity F corresponds to the operator π^F .
- Line of interaction. This line corresponds to the ratio of the interaction intensity.

$$I\varphi \xrightarrow{a^I} \xrightarrow{-\stackrel{+}{k}} \xrightarrow{\frac{+}{k}} \frac{F\varphi}{1}$$

Fig. 9. Forward interaction (operator approach), extended notation

$$I\varphi \xrightarrow{\frac{\pi^I}{1}} - \underbrace{-\frac{k}{k}}_{-\frac{k}{k}} - \underbrace{\frac{a^F}{\pi^F a^F}}_{F\varphi}$$

Fig. 10. Backward interaction (operator approach), extended notation

That is, for the Fig. 7 we obtain a factor ${}^{+}k\pi^{F}a^{I}$. However, this violates the Eq. (9). Redressing this, we have to subtract the number of entities that have entered into interaction, multiplied by the intensity of the interaction. Then we get a following term of the Liouville operator:

$$+k\pi^{F}a^{I} - k\pi^{I}a^{I} = k(\pi^{F} - \pi^{I})a^{I}.$$
 (10)

To backward interactions (Fig. 8), we use the same rules.

¹¹ In normal ordering product all creation operators are moved so as to be always to the left of all the annihilation operators.

To account for the additional factor of (10) we will use the extended diagrams (Figs. 9 and 10). Here, from the the normal ordered product of the numerators the normal product of the denominators is subtracted.

Thus, the following Liouville operator corresponds to the scheme (1):

$$L = \sum_{\underline{\alpha},\underline{i}} \left[{}^{+}k_{\underline{\alpha}} \left((\pi_{\underline{i}})^{F^{\underline{i}\underline{\alpha}}} - (\pi_{\underline{i}})^{I^{\underline{i}\underline{\alpha}}} \right) (a_{\underline{i}})^{I^{\underline{i}\underline{\alpha}}} + {}^{-}k_{\underline{\alpha}} \left((\pi_{\underline{i}})^{I^{\underline{i}\underline{\alpha}}} - (\pi_{\underline{i}})^{F^{\underline{i}\underline{\alpha}}} \right) (a_{\underline{i}})^{F^{\underline{i}\underline{\alpha}}} \right]. \tag{11}$$

8.2 Combinatorial Approach

For the combinatorial approach we get the master equation in the representation of the state vectors. In this approach, with the help of diagrams, we obtain the transition probability ${}^+s_{\underline{\alpha}}$ and ${}^-s_{\underline{\alpha}}$. They are, as in the case of operator approach, obtained by multiplying the diagrams factors.

However, the structure of the right-hand side of the Eq. (6) more complicated than Liouville operator. In the representation the state vectors the additive terms are presented in the functions arguments (dependency of the arguments from the operator r, see (3).). Therefore, we can not use only the factors multiplication.

$$I\varphi \xrightarrow{\varphi!} - +k - - \frac{1}{1} F\varphi$$




Fig. 11. Forward interaction (combinatorial approach)

Fig. 12. Backward interaction (combinatorial approach)

We use the following factors for each type of line (Fig. 11).

– Incoming line. If all lines correspond to different state vectors, the factor of each line is the corresponding state vector. If there are several lines corresponding to the same state vector, the first line corresponds to the actual state vector (φ) , the second line corresponds to the value of $\varphi - 1$ (as the first line has reduced the number of entities of this type in the system by one), and so further. That is, for a combined line factor can be written as follows:

$$\frac{\varphi!}{(\varphi-I)!}$$
.

– Outgoing line do not give multiplicative contribution. It serves to obtain the step coefficient r:

$$r = F - I$$
.

 Line of interaction. This line corresponds to the ratio of the interaction intensity. In addition, we need the transition probabilities for the previous and the next steps:

$$\varphi^i + r^{i\underline{\alpha}},$$
$$\varphi^i - r^{i\underline{\alpha}}.$$

Thus, for the Fig. 11 transition probability will be as follows:

$$^{+}s(\varphi) = {}^{+}k \frac{\varphi!}{(\varphi - I)!},$$

$$^{-}s(\varphi) = {}^{-}k \frac{\varphi!}{(\varphi - F)!}.$$

For the general case:

$$\begin{split} ^+s_{\underline{\alpha}}(\varphi^i) &= {}^+k_{\underline{\alpha}} \prod_{\underline{i}=1}^n \frac{\varphi^{\underline{i}}!}{(\varphi^{\underline{i}} - I^{\underline{i}\underline{\alpha}})!}, \\ ^-s_{\underline{\alpha}}(\varphi^i) &= {}^-k_{\underline{\alpha}} \prod_{\underline{i}=1}^n \frac{\varphi^{\underline{i}}!}{(\varphi^{\underline{i}} - F^{\underline{i}\underline{\alpha}})!}. \end{split}$$

To backward interactions (Fig. 12), we use the same rules.

The general form of the master equation for the state vector φ^i we obtain on the basis of formula (6).

9 Verhulst Model

As a demonstration of the method, we consider the Verhulst model [8,9,25], which describes the limited growth¹². Initially, this model was written down as the differential equation:

$$\frac{\mathrm{d}\varphi}{\mathrm{d}t} = \lambda\varphi - \beta\varphi - \gamma\varphi^2,$$

where λ denotes the breeding intensity factor, β —the extinction intensity factor, γ —the factor of population reduction rate (usually the rivalry of individuals is considered)¹³.

The interaction scheme for the stochastic version of the model is:

$$\varphi \stackrel{\lambda}{\rightleftharpoons} 2\varphi,$$

$$\varphi \stackrel{\beta}{\Longrightarrow} 0.$$
(12)

The interaction schemes (12) match Figs. 13, 14, and 15.

The first relation means that an individual who eats one unit of meal is immediately reproduced, and in the opposite direction is the rivalry between individuals. The second relation describes the death of an individual.

 $[\]overline{}^{12}$ The attractiveness of this model is that it is one-dimensional and non-linear.

¹³ The same notation as in the original model [25] is used.




Fig. 13. First forward interaction

Fig. 14. First backward interaction

Fig. 15. Second forward interaction

9.1 Combinatorial Approach

The interaction schemes (12) in combinatorial approach match Figs. 16, 17, and 18.




Fig. 16. First forward interaction (combinatorial approach)

Fig. 17. First backward interaction (combinatorial approach)

Fig. 18. Second forward interaction (combinatorial approach)

Let's define transition rates within the Verhults model as follows:

$$\begin{array}{lll} ^+s_1(\varphi)=\lambda\varphi, & ^+s_1(\varphi-1)=\lambda(\varphi-1), & ^+s_1(\varphi+1)=\lambda(\varphi+1), \\ ^-s_1(\varphi)=\gamma\varphi(\varphi-1), & ^-s_1(\varphi-1)=\gamma(\varphi-1)(\varphi-2), & ^-s_1(\varphi+1)=\gamma(\varphi+1)\varphi, \\ ^+s_2(\varphi)=\beta\varphi. & ^+s_2(\varphi-1)=\beta(\varphi-1). & ^+s_2(\varphi+1)=\beta(\varphi+1). \end{array}$$

Then, based on (6), the form of the master equation is:

$$\begin{split} \frac{\partial p(\varphi,t)}{\partial t} &= -\left[\lambda \varphi + \beta \varphi + \gamma \varphi(\varphi-1)\right] p(\varphi,t) \\ &+ \left[\beta (\varphi+1) + \gamma (\varphi+1) \varphi\right] p(\varphi+1,t) + \lambda (\varphi-1) p(\varphi-1,t). \end{split}$$


For particular values of φ (as in (5)):

$$\frac{\partial p_n(t)}{\partial t} := \frac{\partial p(\varphi, t)}{\partial t} \bigg|_{\varphi=n} = -\left[\lambda n + \beta n + \gamma n(n-1)\right] p_n(t)
+ \left[\beta(n+1) + \gamma(n+1)n\right] p_{n+1}(t) + \lambda(n-1)p_{n-1}(t). (13)$$

9.2 Operator Approach

The interaction schemes (12) in operator approach match Figs. 19, 20, and 21. From (12) and (11) the Liouville operator is:

$$\begin{split} L &= \lambda (\pi^2 - \pi) a + \gamma (\pi - \pi^2) a^2 + \beta (1 - \pi) a \\ &= \lambda \left((a^\dagger)^2 - a^\dagger \right) a + \gamma \left(a^\dagger - (a^\dagger)^2 \right) a^2 + \beta \left(1 - a^\dagger \right) a \\ &= \lambda \left(a^\dagger - 1 \right) a^\dagger a + \beta \left(1 - a^\dagger \right) a + \gamma \left(1 - a^\dagger \right) a^\dagger a^2. \end{split}$$



 $\varphi \xrightarrow{\frac{\pi}{1}} \qquad \varphi \xrightarrow{\frac{\pi}{1}} \xrightarrow{\frac{\gamma}{\gamma}} \underbrace{\frac{a}{\pi a}} \qquad \varphi \xrightarrow{\frac{a}{\pi a}} \xrightarrow{\frac{\beta}{2}} - \otimes$




Fig. 19. First forward interaction (operator approach)

Fig. 20. First backward interaction (operator approach)

Fig. 21. Second forward interaction (operator approach)

The master equation by Liouville operator:

$$\begin{split} \frac{\partial p_n(t)}{\partial t} &= \frac{1}{n!} \langle n|L|\varphi\rangle \\ &= \frac{1}{n!} \langle n| - \left[\lambda a^{\dagger} a + \beta a^{\dagger} a + \gamma a^{\dagger} a^{\dagger} a a\right] + \left[\beta a + \gamma a^{\dagger} a a\right] + \lambda a^{\dagger} a^{\dagger} a|\varphi\rangle \\ &= -\left[\lambda n + \beta n + \gamma n(n-1)\right] \langle n|\varphi\rangle \\ &+ \left[\beta (n+1) + \gamma (n+1)n\right] \langle n + 1|\varphi\rangle + \lambda (n-1)\langle n - 1|\varphi\rangle \\ &= -\left[\lambda n + \beta n + \gamma n(n-1)\right] p_n(t) + \\ &+ \left[\beta (n+1) + \gamma (n+1)n\right] p_{n+1}(t) + \lambda (n-1)p_{n-1}(t). \end{split}$$
(14)

The result (14) coincides with the formula (13), which was obtained by combinatorial method.

Conclusions 10

The authors proposed a diagram technique for the stochastization of one-step processes. At the moment, this technique allows to get main master equation. Also, this technique makes it possible to unify different approaches to the stochastization of one-step processes.

Acknowledgments. The work is partially supported by RFBR grants No's. 14-01-00628, 15-07-08795, and 16-07-00556. Also the publication was supported by the Ministry of Education and Science of the Russian Federation (the Agreement No. 02.a03.21.0008).

References

- Basharin, G.P., Samouylov, K.E., Yarkina, N.V., Gudkova, I.A.: A new stage in mathematical teletraffic theory. Autom. Remote Control 70(12), 1954–1964 (2009)
- 2. Cajori, F.: A History of Mathematical Notations, vol. 2 (1929)
- Demidova, A.V., Korolkova, A.V., Kulyabov, D.S., Sevastianov, L.A.: The method
 of stochastization of one-step processes. In: Mathematical Modeling and Computational Physics, p. 67, JINR, Dubna (2013)
- Demidova, A.V., Korolkova, A.V., Kulyabov, D.S., Sevastyanov, L.A.: The method
 of constructing models of peer to peer protocols. In: 6th International Congress on
 Ultra Modern Telecommunications and Control Systems and Workshops (ICUMT),
 pp. 557–562. IEEE Computer Society (2015)
- 5. Dirac, P.A.M.: A new notation for quantum mechanics. In: Mathematical Proceedings of the Cambridge Philosophical Society, vol. 35, no. 03, p. 416 (1939)
- 6. Doi, M.: Second quantization representation for classical many-particle system. J. Phys. A: Math. Gen. 9(9), 1465–1477 (1976)
- 7. Doi, M.: Stochastic theory of diffusion-controlled reaction. J. Phys. A: Math. Gen. **9**(9), 1479–1495 (1976)
- Feller, W.: Die Grundlagen der Volterraschen Theorie des Kampfes ums Dasein in wahrscheinlichkeitstheoretischer Behandlung. Acta Biotheor. 5(1), 11–40 (1939)
- 9. Feller, W.: On the theory of stochastic processes, with particular reference to applications. In: Proceedings of the [First] Berkeley Symposium on Mathematical Statistics and Probability, pp. 403–432 (1949)
- Gardiner, C.W.: Handbook of Stochastic Methods: for Physics, Chemistry and the Natural Sciences. Springer Series in Synergetics, Springer, Heidelberg (1985)
- Gorban, A.N., Yablonsky, G.S.: Three waves of chemical dynamics. Math. Model. Nat. Phenom. 10(5), 1–5 (2015)
- 12. Grassberger, P., Scheunert, M.: Fock-space methods for identical classical objects. Fortschr. Phys. **28**(10), 547–578 (1980)
- Hnatič, M., Eferina, E.G., Korolkova, A.V., Kulyabov, D.S., Sevastyanov, L.A.: Operator approach to the master equation for the one-step process. In: EPJ Web of Conferences, vol. 108, p. 02027 (2016)
- Hnatič, M., Honkonen, J., Lučivjanský, T.: Field-theoretic technique for irreversible reaction processes. Phys. Part. Nuclei 44(2), 316–348 (2013)
- 15. Hnatich, M., Honkonen, J.: Velocity-fluctuation-induced anomalous kinetics of the $A+A \rightarrow$ reaction. Phys. Rev. E, 3904–3911 (2000). Statistical physics, plasmas, fluids, and related interdisciplinary topics 61(4 Pt A)
- Hnatich, M., Honkonen, J., Lučivjanský, T.: Field theory approach in kinetic reaction: role of random sources and sinks. Theoret. Math. Phys. 169(1), 1489–1498 (2011)
- Janssen, H.K., Täuber, U.C.: The field theory approach to percolation processes. Ann. Phys. 315(1), 147–192 (2005)
- van Kampen, N.G.: Stochastic Processes in Physics and Chemistry. Elsevier Science, North-Holland Personal Library, Amsterdam (2011)
- Korolkova, A.V., Eferina, E.G., Laneev, E.B., Gudkova, I.A., Sevastianov, L.A., Kulyabov, D.S.: Stochastization of one-step processes in the occupations number representation. In: Proceedings - 30th European Conference on Modelling and Simulation, ECMS 2016, pp. 698-704 (2016)
- Mobilia, M., Georgiev, I.T., Täuber, U.C.: Fluctuations and correlations in lattice models for predator-prey interaction. Phys. Rev. E 73(4), 040903 (2006)

- 21. Peliti, L.: Path integral approach to birth-death processes on a lattice. J. de Phys. **46**(9), 1469–1483 (1985)
- 22. Penrose, R., Rindler, W.: Spinors and Space-Time: Volume 1, Two-Spinor Calculus and Relativistic Fields, vol. 1. Cambridge University Press, Cambridge (1987)
- 23. Täuber, U.C.: Field-theory approaches to nonequilibrium dynamics. In: Ageing and the Glass Transition, vol. 716, pp. 295–348. Springer, Heidelberg (2005)
- Velieva, T.R., Korolkova, A.V., Kulyabov, D.S.: Designing installations for verification of the model of active queue management discipline RED in the GNS3.
 In: 6th International Congress on Ultra Modern Telecommunications and Control Systems and Workshops (ICUMT), pp. 570–577. IEEE Computer Society (2015)
- Verhulst, P.F.: Notice sur la loi que la population suit dans son accroissement, vol. 10 (1838)
- Waage, P., Gulberg, C.M.: Studies concerning affinity. J. Chem. Educ. 63(12), 1044 (1986)