Basic Info.

Model NO.	CY-1020
Test Types	Powder
Brand	Cyeeyo
Detection Method	Ventilation
Minimum Measuring Range	0.001m²/g
Automatic Grade	Fully Automatic
Repeatability	≤ ±1.5 %
Detection Principle	Static Volumetric Method
Type	Multi-point
Application Area	Investigation Area
Pipeline System	Integrated
Test Principle	Low-Temperature Nitrogen Physical Adsorption (Stat
Specific Surface Area	0.01 M 2 Without Upper Limit

Analysis of Range for Pore Size	3.5-5000 Angstrom
Adsorbed Gas	Nitrogen
P/Po Test Range	B
Transport Package	Carton
Specification	75cm*65cm*70cm
Trademark	CYEEYO
Origin	Shan Dong
HS Code	9027500090
Production Capacity	100

Packaging & Delivery

Package Size	69.00cm * 98.00cm * 187.00cm
Package Gross Weight	89.000kg
Lead Time	15 days (1 - 1 Pieces) To be negotiated (> 1 Pieces)

Product Description

Bet Surface Area Porosimetry Analyzer Measurement Analysis

Product Description

CY-1010	CY-1020	CY
1tested sample and 3 pretreated samples in the meantime	2tested sample and 3 pretreated samples in the meantime	3t m

Brief Introduction to the Instrument

CY-1020 Surface Area And Porosimetry Analyzer accords with the international standards ISO9277, ISO 15901 and National standard Gb-119587. It tests desorption process in the principle of static capacity measurement tested through static gas balance and pressure tested. They are tested in the temperature of liquid nitrogen. The gas of known quantity is filled into the sample tube and the pressure is to fall, then the Moore's quality of adsorbed gas is calculated. With calculated balance adsorption quantity and theoretical model, the instrument evaluates the parameters such as single-point, multipoint BET specific surface area, Langmuir specific surface area of the samples; BJH mesoporous, macroporous area,area distribution; t-plot microporous and surface areas, Dubinin Astakhov microporous distribution, Hovath-Kawazoe microporous distribution; DFT and MC aperture distribution model.

Guarantee for Trustworthy Tested Data

Reasonable connection of pipes, capability of s vacuum pumping, precision and sensitivity of sensors, automation of the instrument and numbers of the digital models for the different samples.

Modular Gas pipes Design

Rise-1020 Surface Area And Porosimetry Analyzer accords with the most developed design ideas, designed with special modular stainless steel vacuum pipes . It is leak proof and pollution-free. It is high vacuum and avoids leakage due to excessive pipe connections. It is specially-designed research instrument for the micropores study, with diffusion pump to keep the system high vacuum.

Constant temperature

Dewar flasks is self-developed with special internal structure, store the liquid nitrogen for more than 10 days. The liquid nitrogen is almost free of losses during the test so that the temperature of the tested samples is constant and that the Dewar flasks are protected as they are fragile and unfavorable for movement.

High-precision sensors

Several high-precision sensors and 22-bit AD converters ensure the precision of the specific surface area and aperture.

Developed theoretical model

With DFT and MC aperture distribution models, it is developed in the world, and is the Number One of the specific surface area and Pore size distribution Analyzers in

China

Automatic operation

Adsorption and desorption processes are automatically controlled by computers and free of manual operation.

Technical characteristics

1, single-point, multipoint BET specific surface area

2, BJH specific surface area, area distribution, total area

3,t-plot micropores volume and surface areas, Dubinin Astakhov micropores size distribution, Hovath-Kawazoe micropores size distribution

4, DFT and MC aperture distribution model

Technical parameters and instrument configuration

1, Test principle: low-temperature nitrogen physical adsorption (static capacity)

2, specific surface area : 0.01 m^2 without upper limit

3, Analysis of range for pore size : 3.5-5000 angstrom

4, adsorbed gas: nitrogen

5, P/PO test range: 1 X 10^{-6} - 0.998

6, pressure and temperature measurement:

4 imported absolute pressure sensors 0-133 Kpa(precision 0.12%)

1 temperature sensor PT-100(Precision 0.1)

7, Dewar flask: 2.0L, duration of 80 hours

8, vacuum pump: mechanical pump

9, Ultimate vacuum: 1.0 X 10^{-4} Torr

10, Measurement software: adsorption /desorption isotherm curve

11, physical parameter: 535 X 435 X 720 mm 40kg (exclusive of vacuum pump)

12, 2tested sample and 3 pretreated samples in the meantime

Output Report

Directly printed and Excel output the parameters such as adsorption /desorption isotherm, BET specific surface area, Langmuir specific surface area , t-plot micropores areas, BJH specific surface area ,Dubinin Astakhov micropores distribution, Hovath-Kawazoe micropores distribution.

Applied range

It is applied in study and test of all kinds of materials such as zeolite, carbon material, molecular sieve, silicic acid anhydride, aluminum oxide,soil, clay, catalytic agent, organic metal compound cageconstruction.