## Products Characteristics

Advanced optical path design: NKT2020-L adopts focused Fourier transform test technology to ensure the maximum range in the shortest focal length and effectively improve the resolution of the instrument; the unique arrangement of small probes enables 2020 to have super small particle test ability. The superior automatic alignment system and computer operating system show NKT2020-L humanized design.

High stability optical path optimization: the unique design makes NKT2020-L have the most advanced high stability optical path, it uses high stability and high power fiber output laser, and the excellent configuration makes NKT2020-L have super stability; the main optical path adopts the full closed design, which ensures the long-term test of the instrument in complex environment.

96 channels of simultaneous acquisition main board: NKT2020-L took the lead in using 96 channels of simultaneous acquisition main board. All channels collect signals at the same time, which makes the data more real and reliable. Other manufacturers claim that how many times of acquisition per second is a single acquisition for all channels, and the data is not true.

Special feeding system for pharmaceutical industry: NKT2020-L specially developed a special feeding system for pharmaceutical factories. Many medicinal materials with small density, light weight and traditional vibration feeding are difficult to be evenly cut. The newly developed feeding system is changed from passive feeding to active feeding by instruments. Even feeding can ensure the normal test of very light samples.

Unique dry method dispersion system: NKT2020-L dispersion system is optimized based on the French theoretical data, which makes NKT2020-L disperse the dry powder more evenly, super negative pressure ensures the continuity and uniformity of the feed, and effectively avoids the adhesion of the dry powder in the test process.

Software: in line with GMP regulations of Pharmacopoeia, with electronic signature, permission setting, data tracking, data can not be changed and other functions

## Product Parameters

| Model: | NKT2020-L |
|---|---|
| Execution standard: | ISO 13320-1:1999;GB/T19077.1-2008 |
| Measurement range: | 0.1μm -800μm/0.1μm -2000μm |
| Channels number: | 76 |
| Accuracy error: | <1% |
| Repeatably error: | <1% |
| Automatic testing: | It is the first in China to realize one key automatic test, and all operation instruments are automatically completed without the assistance of customers. It is the first real automatic dry test instrument. |

| | | |
|---|---|---|
| Oil free silent air compressor | | With dust filtering function to ensure the accuracy of test |
| Cold dryer | | Freeze dryer can filter the moisture in the air to ensure the dispersion effect |
| Misoperation protection | | The instrument has self-protection function for misoperation, and it does not respond to misoperation. |
| Laser parameters | | Imported fiber output high power laser λ = 650nm, > P > 15MW (constant power, automatic adjustable) |
| Dispersing method | | High pressure air dispersion |
| Operation mode | | Software automatic control operation |
| Optical alignment | | Automatic proofreading of optical path |
| 96 channel simultaneous acquisition main board | | At present, 96 channels of simultaneous acquisition motherboard are used exclusively in China, which makes the data more accurate and more stable. |
| Latest active feeding system | | The traditional vibration feeding system is not suitable for the feeding of some new drugs. The newly improved active feeding system can perfectly test all powder samples, and the feeding is even. |
| software function | Analysis mode | It includes free distribution, R-R distribution, lognormal distribution, and statistical model by category, etc. to meet the different requirements of different industries for the statistical methods of particle size of the tested samples. |
| | Statistical method | Volume distribution and quantity distribution to meet different statistical methods for particle size distribution in different industries |
| | Statistical comparison | It can be used for statistical comparison and analysis of multiple test results, and can obviously compare the differences of test results of different batches of samples, samples before and after processing and at different times, which is of great practical significance for quality control of industrial raw materials. |
| | Self DIY display template | Users can customize the data to be displayed, calculate the percentage according to the particle size, calculate the particle size according to the percentage or calculate the percentage according to the particle size interval, so as to meet the representation mode of particle size test in different industries. Radial distance, consistency, interval accumulation, etc. |
| | Test report | The test report can be exported to word, Excel, BMP, text and other forms of documents, which can be used to view the test report and scientific research articles in any situation. |
| | Multilingual support | Chinese and English language interface support, and other language interfaces can be embedded according to user requirements. |

| | | |
|---|---|---|
| | Intelligent operation mode | Truly automatic and unmanned intervention operation, unmanned interference, you just need to add the sample to be tested according to the prompts, and the repeatability of the test results is better. |
| Testing speed | | < 1min / time (excluding sample dispersion time) |
| volume | | 980mm*410mm*450mm |