Basic Info.

Model NO.	UV2800
Appliance	Laboratory Apparatus
Ray Type	Dual Split-Beam
Gaspath System	Double
Advantage	High Sensitive
Wavelength Range	190-1100nm
Wavelength Accuracy	±0.3nm
Dispersive Element	Grating Spectrometer
Baseline Linearity	±0.001A
Baseline Drift	0.0005A/H(500nm)
Transport Package	Export Standard Wooden Package
Specification	540× 445× 230mm
Trademark	Pharmao

Origin

China

Production Capacity

10000

Product Description

UV2800 is double beam UV-VIS spectrophotometer with a big screen and scanning function. New optical system and circuit system make the instrument have high-resolution, low stray light, lasting stability, high-SNR. This instrument can meet the multi-level analysis application requirements. The computer application system of UV-VIS Spectrophotometer can achieve more powerful function for your instrument.

Function

1. Photometric measurement
2. Spectrum scan
3. Quantitative determination
4. Multi-wavelength test
5. Dynamics measurement (time scanning)
6. DNA/Protein concentration measurement

Feature

1. Long lasting Stability
2. Ultra-low stray light
3. User friendly interface
4. Can be easily replaced light source
5. Easily upgraded

	UV2800	UV2800S
Optical System	Double beam	Double beam
Spectral Bandwidth	1.8nm	0.5,1,1.8,4nm
Wavelength Range	190~1100nm	190~1100nm
Wavelength Accuracy	±0.3nm	±0.3nm
Wavelength Repeatability	0.2nm	0.2nm

Photometric Range	T: 0~200.00%T A: -0.301~3.0000Abs C: 0~9999	T: 0~200.00%T A: -0.301~3.0000Abs C: 0~9999
Photometric Accuracy	±0.3%T	±0.3%T
Photometric Repeatability	0.1%T	0.1%T
Stray Light	≤0.05%T(220nm, 340nm)	≤0.05%T(220nm, 340nm)
Baseline linearity	±0.001A	±0.001A
Baseline drift	0.0005A/h(500nm)	0.0005A/h(500nm)
Noise	100%(T)line noise≤0.1%(T) 0%(T)line noise≤0.05%(T)	100%(T)line noise≤0.1%(T) 0%(T)line noise≤0.05%(T)
Monitor	320×240 large screen LCD(6 inch)	320×240 large screen LCD(6 inch)
Software (Optional)	UV-Solution 3.0	UV-Solution 3.0
Dimensions	540×445×230mm	540×445×230mm