Basic Info.

Model NO.	UV-5660
Detection Method	Spectrophotometer
Advantage	High Sensitive
Principle	Classic Spectrometer
Wavelengths	UV Spectrometer
Dispersive Element	Grating Spectrometer
Light Number	Monochromator
Certification	ISO9001, CE
Customized	Customized
Light Source	Deuterium &Tungsten Lamp
Bandwidth	2nm
Wavelength Range	190-1100nm
Display	10" Color Touchscreen
Wavelength Accuracy	±0.5nm
Wavelength Repeatability	≤0.2nm
Wavelength Setting	Automatically
Stray Light	≤0.10%T
Output	USB Port & Parallel Port
Power Requirements	AC 85-250V
Stability	≤0.001A/H
Transport Package	Carton
Specification	620×400×280mm
Trademark	UNICO
Origin	China Shanghai
HS Code	9027300090
Production Capacity	

1000/Year

Product Description

Product Description

UNICO UV-5660 Touchscreen Scanning Single-Beam UV-Vis Spectrophotometer

Product Descirption:

UNICO UV-5660 is a high-performance touchscreen scanning UV-Vis spectrophotometer. With advanced optical system and quality materials, it offers stable and accurate detection. Covering 190-1100nm, it integrates multiple functions to meet various lab needs. The 10-inch touchscreen and multiple data transmission methods ensure convenient operation. Featuring automatic calibration, long-life light sources and dual-mode operation, it is suitable for qualitative and quantitative analysis in chemistry, biology and other fields.

Features:

1. Equipped with 1200line/mm holographic blazed grating and long-life light sources, 190-1100nm wavelength range.
2. Diverse functions: fixed-wavelength measurement, spectral scanning, DNA/protein analysis, etc.
3. 10-inch touchscreen, supports U-disk storage, Bluetooth sharing, and computer connection.
4. Automatic startup calibration and system self-upgrade, ensuring high stability.
5. Dual-mode operation (host/computer) and complete standard configuration for easy use.

Specifications:

Optical System	Single-Beam, Grating 1200 lines/mm
Wavelength Range	190 nm - 1100nm
Spectral Bandwidth	2nm
Wavelength Accuracy	±0.5nm
Wavelength Repeatability	≤0.2nm
Photometric Accuracy	±0.3%T(0~100%T)
Photometric Repeatability	0.1%T(0~100%T)
Photometric Range	-0.6020-5.000A

Stray light	0.1%T
Stability	±0.001
Baseline Flatness	±0.001A
Noise	0.001 A
Scanning Speed	Fast, Mid, Slow
Light Source	Deuterium &Tungsten lamp
Display	10" color Touchscreen
Photometric Mode	T,A,C,E
Detector	Imported Silicon Photodiode
Output	USB port & Parallel port (Printer)
Power	AC 220V/50Hz or AC 110V/60Hz
Dimension	620 x 400 x 280mm
Net Weight	19kg
Shipping Size	755*555*390mm
Gross Weight	21kg