For manufacturing bar-shaped rubber composites using steam vulcanization, the equipment you need is an **industrial steam vulcanizing autoclave** (also called a rubber curing oven or vulcanizer). Here are the details on pricing and available product imagery.

□ Machine Prices

The price varies significantly based on size, automation level, pressure rating, and certification. Here is a summary of available price data:

Specification / Model	Price (USD)	Source
Small basic autoclave	**$2,000 – $10,000**	Alibaba listing
Continuous curing oven / autoclave	**~$15,000**	Made-in-China (Shandong Mosen)
Customized OEM steam autoclave (for rubber pulley)	**~$11,000**	Made-in-China (Shandong Mosen)
Rubber curing chamber (1000×15000mm, CE)	**$28,000**	Made-in-China (Changzhou Sinomac)
Vulcanization tank (for truck tyres)	**$30,000**	Made-in-China (Qingdao Evertech)
Rubber curing chamber (cable sheath, 1700mm dia.)	**¥55,000 (~$7,600)**	机电之家 (Shandong)

The global average market price for vulcanizing autoclaves was approximately **US$3,496 per unit** in 2025, though this reflects a broad mix of sizes and types . Industrial-grade machines for large-scale production typically fall in the **$10,000–$50,000** range, with larger and more automated systems costing significantly more.

□ Real Photos and Product Images

Several of the B2B listings include links to product image galleries where you can view real photos:

* **Changzhou Sinomac Machinery**: Their Made-in-China product pages for the "2800X4500mm ASME Approved Steam Heating Industrial Rubber Vulcanizer" and the "1000X15000mm CE Approved Rubber Curing Chamber" include "Enlarged Product Images" and "On-Site Scanning" galleries .

* **Shandong Mosen Machinery**: Their listings for the "Continuous Industrial Rubber Curing Oven" and "Customized OEM Industrial Steam Rubber Autoclave" on Made-in-China.com typically display product images .

* **Alibaba**: The "Rubber Vulcanizing tank / Vulcanizing Autoclave" listing includes standard product photo galleries .

* **LinkedIn**: A recent post from TSB Energy shows photos of a rubber curing autoclave successfully commissioned at Polem Polimer, including images of the installed equipment .

□ Key Technical Specifications for Bar-Shaped Rubber

For producing bar-shaped composites (which often have a solid, dense cross-section), **direct steam heating** is generally recommended for its excellent temperature uniformity, which is crucial for even curing through thick sections .

Typical specifications for a steam-heated industrial autoclave suitable for this purpose include:

| Parameter | Typical Value |

|:---|:---|

| **Heating Method** | Direct Steam / Indirect Steam |

| **Working Pressure** | 0.8 – 1.0 MPa (8 – 10 Bar) |

| **Max. Temperature** | 180°C – 190°C |

| **Control System** | PLC + PC with Thermal Processing Control (TPC) |

| **Pressure Vessel Standard** | ASME Sec VIII, PED/CE, or GB150 |

Note on Steam vs. Other Heating: For bar-shaped rubber, direct steam provides both heat and pressure simultaneously, which is effective for solid cross-sections. However, if your product requires a specific surface finish or has a complex geometry, an indirect steam system with a fan (hot air circulation) might offer better control .

To get accurate pricing for your specific production requirements (vessel diameter, length, and batch capacity), I recommend contacting suppliers directly with your bar dimensions and desired output rate.