Deep Learning Approaches for AI-Generated Image Detection: Architecture, Physics, and Cross-Generator Generalization

1. Title Page & Executive Metadata

This technical report synthesizes state-of-the-art methodologies for detecting AI-generated synthetic media, establishing an enterprise-grade technical framework for digital forensics and information security. As modern generative models achieve remarkable visual realism, developing scalable, automated forensic detection systems is essential for verifying media integrity, supporting authentication protocols, and mitigating information security risks. This document provides an architectural, mathematical, and empirical evaluation of synthetic image detection. It assesses three primary paradigms: deep residual convolutional neural networks (ResNet-50), frozen foundation model feature probes (CLIP ViT-L/14), and training-free autoencoder reconstruction error engines (AEROBLADE).| Document Metadata Parameter | System Specification & Project Attribute || ------ | ------ || **Document Title** | *AI-Generated Image Detector (Diffusion): Comprehensive Technical & Empirical Report* || **Domain** | Computer Vision / Machine Learning Forensics || **Core Architecture** | Deep CNN (ResNet-50), Frozen Foundation Model (CLIP ViT-L/14), Training-Free Autoencoder Reconstruction (AEROBLADE) || **Benchmark Dataset** | GenImage ($2,681,167$ images across 8 generative architectures) || **Key Target Metrics** | Binary Classification Accuracy, ROC-AUC, TPR @ 1% FPR, Expected Calibration Error (ECE) |
These foundational parameters define the scope, empirical benchmarks, and system criteria analyzed throughout this report.


2. Abstract & Project Scope

The rapid proliferation of high-fidelity latent diffusion engines—including Stable Diffusion, Midjourney, and Flux—has blurred the line between authentic photography and synthetic renders. Empirical studies demonstrate that human visual inspection is insufficient for reliable identification, with unassisted human observers achieving an average accuracy of only 61% when evaluating synthetic images (per the GenImage benchmark). Automated forensic systems must therefore bypass high-level visual inspection to detect subtle, invisible statistical fingerprints embedded by generative model pipelines.This report presents a technical evaluation of three distinct detection paradigms for binary synthetic media classification ($y=0$ for authentic photographs, $y=1$ for AI-generated media):

1. Supervised fine-tuning of a deep Residual Network (ResNet-50);
2. Linear probing on cached visual feature embeddings from a frozen Vision-Language Foundation Model (CLIP ViT-L/14); and
3. A training-free distance engine that quantifies Variational Autoencoder (VAE) reconstruction error (AEROBLADE).Empirical evaluations across multi-million-image benchmarks demonstrate that while supervised CNNs achieve near-perfect within-distribution accuracy ($\sim 99.9\%$), their performance on unseen generative architectures drops to an average of 72.1% . This reduction highlights shortcut learning and dataset bias as central engineering challenges in passive media forensics.These findings underscore the need for a comprehensive technical analysis of the synthetic media landscape and the forensic requirements driving detector architecture design.

3. Introduction & Strategic Context

The generative image landscape has shifted from early Generative Adversarial Networks (GANs) toward advanced Latent Diffusion Models (LDMs) and pixel-space diffusion engines, such as Stable Diffusion, Midjourney, Flux, Analytic-DPM (ADM), and GLIDE. While early GAN architectures left distinct high-frequency structural artifacts due to transposed-convolution upsampling, modern diffusion engines synthesize images through iterative noise removal. This process generates macro-level statistical distributions that closely resemble natural photographs.



$$\text{Image File} \longrightarrow \text{Preprocessing (Crop/Normalize/Augment)} \longrightarrow \text{Model Backbone} \longrightarrow \text{Logit } z \longrightarrow \text{Sigmoid} \longrightarrow \text{Probability } p \longrightarrow \text{Threshold } t$$To uncover the subtle statistical traces left by these pipelines, automated deep learning systems process input image tensors through ingestion, spatial cropping, channel normalization, and feature extraction. This pipeline maps pixel data to a unconstrained scalar logit z . The logit is converted via a Sigmoid function into a calibrated probability $p \in 0, 1$ and evaluated against a decision threshold t to determine authenticity, as formalized below.

4. Problem Statement & Mathematical Formulation

Synthetic media detection is formalized as a binary classification problem under uncertainty. Let $\mathcal{X} \subset \mathbb{R}^{H \times W \times 3}$ represent the domain of normalized RGB image tensors. The detection system parameterizes a continuous mapping function $f: \mathcal{X} \rightarrow 0, 1$, assigning an input image $\mathbf{x} \in \mathcal{X}$ a probability $p = f(\mathbf{x})$ corresponding to the ground-truth target label $y \in \{0, 1\}$: $$y = \begin{cases} 0 & \text{if } \mathbf{x} \text{ is an authentic photograph} \\ 1 & \text{if } \mathbf{x} \text{ is an AI-generated image} \end{cases}$$The underlying neural network produces an unconstrained scalar logit $z \in (-\infty, +\infty)$. To transform this logit into a bounded probability score $p \in (0, 1)$, the Sigmoid activation

function $\sigma(z)$ is applied: $$\sigma(z) = \frac{1}{1 + e^{-z}}$$The Sigmoid function exhibits key numeric properties across different logit thresholds:| Logit Value (z) | Sigmoid Probability ($p = \sigma(z)$) | Operational Forensic Interpretation || ------ | ------ | ------ || $z = -4.6$ | $p \approx 0.01$ | High confidence: Authentic photograph ($y=0$) || $z = 0.0$ | $p = 0.50$ | Maximum uncertainty: Indeterminate decision || $z = +4.6$ | $p \approx 0.99$ | High confidence: AI-generated media ($y=1$) |
The function is strictly monotonic and exhibits functional symmetry, $\sigma(-z) = 1 - \sigma(z)$, maintaining consistent probability bounds around $z = 0$ .A practical issue during system implementation is the "Label-Order Trap." Standard machine learning dataset loaders, such as PyTorch ImageFolder, assign categorical class indices based on alphabetical directory naming. If dataset directories are organized as ai/ and nature/, default alphabetical sorting assigns index 0 to synthetic images (ai) and index 1 to authentic photographs (nature). This arrangement flips the conventional setup, causing output probability $p \rightarrow 1$ to represent authentic photos. forensic pipelines must explicitly map index assignments to guarantee that $y=1$ represents synthetic media.

```
Standard Directory Layout & Default Mapping Pitfall:
data/
├── train/
│   ├── ai/      --> Default PyTorch Index: 0  (Enforce Mapping to
Target y = 1)
│   └── nature/  --> Default PyTorch Index: 1  (Enforce Mapping to
Target y = 0)
```

To measure real-world performance, evaluation protocols must extend beyond standard random train/validation/test splits. Systems must use a *generator-split paradigm* , where models are trained on specific source architectures (e.g., Stable Diffusion v1.4) and evaluated on completely held-out, unseen architectures (e.g., Midjourney V5, ADM). This approach isolates out-of-distribution generalization performance from basic training data memorization.These mathematical formulations establish the framework for evaluating existing forensic literature and detector paradigms.

5. Literature Review & Comparative Analysis

Synthetic media detection has evolved from hand-crafted frequency-domain analysis to deep convolutional architectures, frozen vision-language foundation models, and training-free autoencoder reconstruction engines.| Model Name | Architecture Type | Training Requirement | Core Operating Mechanism || ------ | ------ | ------ | ------ || **ResNet-50 Classifier** | Deep Residual Convolutional Neural Network (CNN) | Full backpropagation / Supervised fine-tuning | Learns spatial convolutional filters to capture low-level pixel, texture, and anti-aliasing artifacts. || **CLIP + Linear Probe** | Frozen Vision-Language Foundation Model + Logistic Head | Train linear classification head only on cached features | Projects images into pre-trained 768-dimensional joint embedding space; fits an optimal hyperparameter-regularized separating hyperplane. || **AEROBLADE** | Training-Free Autoencoder Reconstruction Distance Engine | Zero training required (Zero-shot evaluation) | Quantifies deep perceptual reconstruction error (LPIPS) after passing images through generator VAE autoencoders. |
The GenImage dataset serves as a primary benchmark for evaluating these paradigms. GenImage contains $2,681,167$ total images split into $1,331,167$ authentic ImageNet photographs and $1,350,000$ synthetic images generated across 8 engines: Midjourney

V5, Stable Diffusion v1.4, Stable Diffusion v1.5, ADM, GLIDE, Wukong, VQDM, and BigGAN.Published baselines on GenImage demonstrate that supervised models achieve high within-distribution accuracy but struggle to generalize across different generator families. Standard supervised ResNet-50 backbones reach an average cross-generator accuracy of 72.1% , while hierarchical vision transformers (such as Swin-Transformer) achieve a cross-generator average of 74.8% .Analyzing these empirical baselines requires examining the software and pipeline architectures designed to ingest and process high-resolution image streams.

6. Forensic System Architecture & Pipeline Design

To process input images without introducing artificial spatial artifacts, data must undergo standardized tensor transformations. An input image is ingested as a three-dimensional array $\mathbf{X}*{\text{raw}} \in \mathbb{R}^{H \times W \times 3}$ containing discrete integer color values in $\{0, \dots, 255\}$. PyTorch pipelines rearrange these dimensions into channel-first tensors $\mathbf{X}*{\text{tensor}} \in \mathbb{R}^{C \times H \times W}$ and prepend a mini-batch dimension, yielding a four-dimensional tensor of shape (B, C, H, W) —such as $(64, 3, 224, 224)$ for mini-batch processing.

```
Raw Image File (H x W x 3 RGB, Int [0..255])
                    |
                    ▼
Channel-First Reshaping & Float Scaling (C x H x W, Float
[0.0..1.0])
                    |
                    ▼
Channel Standardization via ImageNet Constants (μ_c, σ_c)
                    |
                    ▼
Native 224 x 224 Spatial Cropping (Preserves High-Frequency
Traces)
                    |
                    ▼
Batched Model Ingestion Tensor (B x 3 x 224 x 224)
```


Inputs are converted to floating-point values in $0.0, 1.0$ and standardized using ImageNet channel constants: $$\mathbf{x}_{\text{norm}} = \frac{(\mathbf{x} / 255) - \mu_c}{\sigma_c}$$ where channel means are defined as $\mu = (0.485, 0.456, 0.406)$ and standard deviations as $\sigma = (0.229, 0.224, 0.225)$. Subtracting the mean centers the input data around zero, while dividing by the standard deviation scales channel variance to unit scale. This standardization stabilizes gradient flow during backpropagation and prevents exploding or vanishing activations in early network layers.A core operational requirement in forensic vision pipelines is using native-resolution cropping rather than spatial downsampling. Standard image classification models typically resize full-resolution images using bilinear interpolation or large convolutional strides to fit input tensor dimensions. However, spatial downsampling acts as a low-pass filter, averaging neighboring pixels and destroying the fine, high-frequency spectral traces and local pixel correlations that characterize synthetic generation. Forensic pipelines must instead extract native 224×224 spatial crops (e.g., via random cropping during training or center cropping during evaluation) to preserve intact high-frequency signals.This preprocessing workflow

feeds directly into the primary deep learning baseline architecture: the 50-layer Residual Network.

7. Core Deep Learning Detector: ResNet-50 Deep-Dive

Residual Connections & Vanishing Gradient Resolution

Deep neural networks can experience optimization degradation as network depth increases, because backpropagated gradient signals shrink exponentially through sequential matrix multiplications—a phenomenon known as the vanishing gradient problem. ResNet addresses this degradation by introducing residual skip connections. Instead of parameterizing a block to learn an unconstrained mapping $H(\mathbf{x})$, the block learns a residual mapping $F(\mathbf{x}) = H(\mathbf{x}) - \mathbf{x}$. The block output is computed via an element-wise sum with the original input: $$\text{output} = F(\mathbf{x}) + \mathbf{x}$$



Differentiating the block output with respect to input $\mathbf{x}$ yields: $$\frac{\partial \text{output}}{\partial \mathbf{x}} = \frac{\partial F(\mathbf{x})}{\partial \mathbf{x}} + 1$$The scalar $+1$ ensures an unattenuated gradient pathway directly backward through the network, regardless of depth or how small $\frac{\partial F(\mathbf{x})}{\partial \mathbf{x}}$ becomes.

Bottleneck Block Architecture

To maintain computational efficiency across deep structures, ResNet-50 uses three-layer bottleneck residual blocks:

1. 1×1 Convolution: Reduces input channel dimensionality (e.g., from 256 channels down to 64).
2. 3×3 Convolution: Performs spatial filtering on the compressed channel space.
3. 1×1 Convolution: Expands channel dimensionality by a factor of 4 (e.g., from 64 channels up to 256).

Complete Layer-by-Layer Architectural Decomposition

The operational sequence for a $224 \times 224 \times 3$ input tensor passing through ResNet-50 is detailed below:| Stage Name | Operations & Specifications | Output Tensor

Shape ($C \times H \times W$) || ------ | ------ | ------ || **Input** | Raw normalized image crop | $3 \times 224 \times 224$ || **conv1** | 7×7 conv, 64 filters, stride 2, padding 3 | $64 \times 112 \times 112$ || **pool** | 3×3 max pooling, stride 2, padding 1 | $64 \times 56 \times 56$ || **conv2_x** | 3 Bottleneck Blocks $(1 \times 1, 64) \rightarrow (3 \times 3, 64) \rightarrow (1 \times 1, 256)$ | $256 \times 56 \times 56$ || **conv3_x** | 4 Bottleneck Blocks $(1 \times 1, 128) \rightarrow (3 \times 3, 128) \rightarrow (1 \times 1, 512)$, stride 2 | $512 \times 28 \times 28$ || **conv4_x** | 6 Bottleneck Blocks $(1 \times 1, 256) \rightarrow (3 \times 3, 256) \rightarrow (1 \times 1, 1024)$, stride 2 | $1024 \times 14 \times 14$ || **conv5_x** | 3 Bottleneck Blocks $(1 \times 1, 512) \rightarrow (3 \times 3, 512) \rightarrow (1 \times 1, 2048)$, stride 2 | $2048 \times 7 \times 7$ || **GAP** | Global Average Pooling (averages spatial 7×7 grid to scalar) | $2048 \times 1 \times 1$ || **fc** | Fully Connected Linear Layer ($2048 \rightarrow 1$) | 1 (Scalar Logit z) |
Layer summation count verification: $$\text{Total Layers} = 1 \; (\text{conv1}) + 3(3) + 4(3) + 6(3) + 3(3) \; (\text{conv blocks}) + 1 \; (\text{fc head}) = 1 + 9 + 12 + 18 + 9 + 1 = 50 \text{ layers}$$

Parameter Count, Compute Payload, & Custom Head

Standard 1,000-class ImageNet ResNet-50 models contain approximately 25.6 million parameters. When adapted for binary forensic classification, the 1,000-class fully connected head is replaced with a single linear output layer: $$\text{Head Parameters} = (2048 \times 1) + 1 \text{ bias} = 2,049 \text{ parameters}$$This custom binary head reduces the model parameter footprint to approximately 23.5 million weights. Executing a single forward pass over a $224 \times 224 \times 3$ input image demands a compute payload of approximately 4.1×10^9 multiply-accumulate operations (MACs).Initializing backbones with pre-trained ImageNet weights presents a notable trade-off. Pre-training offers optimization stability and accelerates convergence compared to training from scratch. However, ImageNet weights introduce an inductive bias toward high-level visual semantic features (e.g., object shapes and global geometry). Passive media forensics, by contrast, relies primarily on micro-texture anomalies and high-frequency noise distributions.
Fine-tuning requires the network to undergo an initial "unlearning" phase, adapting early convolutional filters away from semantic structures toward subtle forensic traces.

8. Comparative Models: Foundation Probes & Training-Free Methods

Model 2: Frozen CLIP (ViT-L/14) + Linear Probe

To mitigate overfitting to specific generator artifacts, frozen multimodal foundation models can serve as static feature extractors. The CLIP ViT-L/14 vision transformer processes input images by tokenizing them into spatial patches:

```
Input Image (224 x 224 x 3) ⟶ 256 Non-Overlapping Patches (14 x
14 x 3 = 588)
                                          |
                                          ▼
                                Linear Projection Matrix E (588 ⟶
1024 dims)
                                          |
                                          ▼
                                Prepend [CLS] Token + Positional
Embeddings
```


```
                                        |
                                        ▼
                              24 Transformer Layers (Multi-Head
Self-Attention)
                                        |
                                        ▼
                              768-Dim Normalized Output Embedding
Vector f
```

1. Patch Tokenization & Linear Projection: A $224 \times 224 \times 3$ image is divided into non-overlapping 14×14 pixel patches, yielding $(224/14) \times (224/14) = 16 \times 16 = 256$ spatial sequence tokens. Each patch vector $\mathbf{x}_p \in \mathbb{R}^{588}$ (where $14 \times 14 \times 3 = 588$) is projected into a 1024 -dimensional latent space using learned projection matrix $\mathbf{E} \in \mathbb{R}^{588 \times 1024}$. A learnable classification token (CLS) and 1D spatial positional embeddings are added.
2. Multi-Head Self-Attention: Tokens pass through 24 transformer blocks using Multi-Head Self-Attention (MHSA): $$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{Q K^T}{\sqrt{d_k}}\right)V$$ where Query (Q), Key (K), and Value (V) matrices are generated via linear projections, and scaling factor d_k prevents softmax saturation.
3. Feature Projection: The output vector corresponding to the CLS token is projected into a normalized 768 -dimensional embedding vector $\mathbf{f}$ .CLIP was pre-trained on 400 million image-text pairs using the contrastive InfoNCE loss across mini-batches of size N with temperature hyperparameter τ : $$\mathcal{L}*{\text{InfoNCE}} = -\frac{1}{2N} \sum{i=1}^{N} \left\log \frac{\exp(s_{ii}/\tau)}{\sum_{j=1}^N \exp(s_{ij}/\tau)} + \log \frac{\exp(s_{ii}/\tau)}{\sum_{j=1}^N \exp(s_{ji}/\tau)} \right$$ where s_{ij} denotes the cosine similarity between image embedding i and text embedding j .For forensic classification, the CLIP backbone parameters remain completely frozen. A linear probe (logistic regression) is fit on normalized embeddings $\mathbf{f}$ by optimizing weights $\mathbf{w}$ and bias b under L_2 regularization controlled by hyperparameter C : $$\min_{\mathbf{w}, b} \; \frac{1}{2}\|\mathbf{w}\|^2 + C \sum_{i=1}^M \text{BCE}(p_i, y_i)$$Recent literature (e.g., C2P-CLIP) highlights a key limitation of this approach. Contrastive InfoNCE pre-training optimizes feature space alignment for high-level visual semantic concepts (e.g., "a photograph of a dog") rather than low-level physical noise distributions. Consequently, decision boundaries fit on CLIP embeddings often separate images based on semantic domain distributions rather than genuine generative artifacts.

Model 3: AEROBLADE (Training-Free Reconstruction Error Engine)

AEROBLADE operates without supervised training or parameter optimization. It relies on the hypothesis that images generated by latent diffusion engines lie directly on the output manifold of the generator's underlying Variational Autoencoder (VAE) decoder D .

```
Input Image x ⟶ VAE Encoder E(x) ⟶ Latent Code z ⟶ VAE
Decoder D(z) ⟶ Reconstructed x_rec
```



When a synthetic image $\mathbf{x}$ is re-encoded and decoded through autoencoder $D(E(\mathbf{x}))$, the reconstructed image $\mathbf{x}*{\text{rec}}$ *exhibits minimal structural deviation. Authentic photographs, having never been processed by D , yield significantly higher reconstruction error.Reconstruction error is measured using Learned Perceptual Image Patch Similarity (LPIPS) across deep feature activations f_l at layer l :* $$\text{LPIPS}(\mathbf{x}, \mathbf{x}*{\text{rec}}) = \sum_l \frac{1}{H_l W_l} \sum_{h,w} \left\| \mathbf{w}*l \odot \left(f_l(\mathbf{x})*{h,w} - f_l(\mathbf{x}*{\text{rec}})_{h,w} \right) \right\|^2_2$$Because the source generator is typically unknown at inference time, AEROBLADE evaluates inputs across a bank of candidate autoencoders (e.g., Stable Diffusion v1.x, v2.x, Kandinsky) and selects the minimum distance: $$\Delta_{\min}(\mathbf{x}) = \min_{i} \Delta_i(\mathbf{x})$$$$\text{Decision} = \begin{cases} \text{AI-Generated } (y=1) & \text{if } \Delta_{\min}(\mathbf{x}) < \text{threshold} \\ \text{Authentic } (y=0) & \text{if } \Delta_{\min}(\mathbf{x}) \ge \text{threshold} \end{cases}$$Understanding these architectural differences requires examining the underlying physical and mathematical properties of diffusion models.

9. Mathematical Foundations of Diffusion Traceability & Forensics


Forward Noising and Reverse Denoising Dynamics

Diffusion models generate images through a two-phase stochastic process. The forward process corrupts a clean image $\mathbf{x}_0 \sim q(\mathbf{x})$ by iteratively adding Gaussian noise over $T \approx 1000$ discrete timesteps according to variance schedule $\beta_1, \dots, \beta_T$: $$\mathbf{x}_t = \sqrt{\bar{\alpha}_t}\mathbf{x}_0 + \sqrt{1 - \bar{\alpha}_t}\boldsymbol{\epsilon}, \quad \boldsymbol{\epsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$$ where $\alpha_t = 1 - \beta_t$ and $\bar{\alpha}*t = \prod*{s=1}^t \alpha_s$. As $t \rightarrow T$, $\bar{\alpha}*t \rightarrow 0$, *transforming the image into isotropic Gaussian noise $\mathbf{x}T \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ .The reverse process uses a parameterized U-Net neural network $\boldsymbol{\epsilon}\theta(\mathbf{x}t, t, \text{text})$ to estimate the noise vector $\boldsymbol{\epsilon}$ added at timestep t . The network optimizes a simplified mean squared error objective: $$\mathcal{L}*{\text{simple}} =* \mathbb{E}*{t, \mathbf{x}_0, \boldsymbol{\epsilon}} \left\| \boldsymbol{\epsilon} - \boldsymbol{\epsilon}_\theta(\mathbf{x}_t, t, \text{conditioning}) \right\|^2 \right$$

Latent Diffusion & VAE Fingerprinting

To reduce computational requirements, Latent Diffusion Models (LDMs) execute denoising within a compressed latent space. A spatial image $\mathbf{x} \in \mathbb{R}^{512 \times 512 \times 3}$ is mapped to latent vector $\mathbf{z} = E(\mathbf{x}) \in \mathbb{R}^{64 \times 64 \times 4}$, representing an $8\times$ spatial compression along each dimension. Denoising operates entirely on $\mathbf{z}$. Once complete, the latent vector is


passed to VAE decoder $D: \mathbf{z} \rightarrow \hat{\mathbf{x}}$ to reconstruct the pixel-space image.



The VAE decoder D serves as the primary source of detectable forensic artifacts in latent diffusion architectures. Because every synthesized output passes through D , its upsampling operations and decoding filters leave consistent pixel correlations, micro-texture biases, and structural noise patterns across generated images.Pixel-space diffusion models (e.g., ADM, GLIDE) execute denoising directly on high-resolution image arrays, bypassing VAE decoders entirely. As a result, forensic detectors trained on latent diffusion models fail to generalize to pixel-space architectures due to the absence of VAE decoder artifacts.

Frequency Domain Analysis via Discrete Fourier Transform (DFT)

Forensic feature extraction often evaluates frequency spectra via the 2D Discrete Fourier Transform (DFT) for an $M \times N$ image array $f(x,y)$: $$F(u,v) = \sum_{x=0}^{M-1} \sum_{y=0}^{N-1} f(x,y) \exp\left-j 2\pi \left(\frac{ux}{M} + \frac{vy}{N}\right)\right$$To isolate forensic signals from visual scene content, spectral analysis is performed on the high-frequency noise residual $\mathbf{r}$: $$\mathbf{r} = \mathbf{x} - \text{denoise}(\mathbf{x})$$



Evaluating the spectral magnitude $|F(\mathbf{r})|$ reveals structural differences between generative architectures:

- Generative Adversarial Networks (GANs) exhibit high-frequency grid-like spectral spikes caused by periodic upsampling in transposed convolutions.
- Diffusion Models produce smoother spectral decay profiles ($1/f^\gamma$) that closely resemble natural image statistics. Because diffusion noise removal is an iterative process acting continuously across spatial frequencies, it avoids leaving periodic spatial aliasing spikes.Consequently, classic frequency-based forensic detectors designed to spot GAN grid artifacts (e.g., Spec, F3Net) perform poorly when applied to diffusion-generated images.

10. System Implementation & Training Methodology

Loss Function Mechanics & Analytical Gradient Derivation

Supervised binary classification models are optimized using Binary Cross-Entropy (BCE) loss. For true binary label $y \in \{0, 1\}$ and predicted probability $p \in (0, 1)$: $$\mathcal{L}_{\text{BCE}} = -\lefty \log(p) + (1 - y) \log(1 - p) \right$$Evaluating explicit Sigmoid activations followed by logarithmic operations can cause numerical instability (underflow or overflow) in floating-point arithmetic. Standard implementations use BCEWithLogitsLoss, which integrates the Sigmoid function and cross-entropy calculation into a single numerically stable formulation operating directly on logit z : $$\mathcal{L}(z, y) = \max(z, 0) - z y + \log\left(1 + e^{-|z|}\right)$$The analytical gradient of loss $\mathcal{L}$ with respect to logit z is derived as follows: $$\frac{\partial \mathcal{L}}{\partial z} = \frac{\partial}{\partial z} \left-y \log(\sigma(z)) - (1-y) \log(1 - \sigma(z)) \right$$Applying the derivative identity for Sigmoid, $\frac{\partial \sigma(z)}{\partial z} = \sigma(z)(1 - \sigma(z)) = p(1-p)$: $$\frac{\partial \mathcal{L}}{\partial z} = -y \frac{p(1-p)}{p} + (1-y) \frac{p(1-p)}{1-p} = -y(1-p) + (1-y)p = p - y$$$$\frac{\partial \mathcal{L}}{\partial z} = \sigma(z) - y = p - y$$This derivative demonstrates that gradient updates are directly proportional to prediction error ($p - y$). When model predictions align with ground-truth target labels ($p \approx y$), the gradient approaches zero, stabilizing weight updates.

Step-by-Step Numerical Walkthrough

Consider a 2-element feature vector $\mathbf{f} = (2.0, 0.5)$, weight vector $\mathbf{w} = (0.8, -1.2)$, bias $b = 0.1$, learning rate $\eta = 0.1$, and true target label $y = 1$ (synthetic):

1. **Logit Calculation (z):** $$z = (\mathbf{w} \cdot \mathbf{f}) + b = (0.8 \times 2.0) + (-1.2 \times 0.5) + 0.1 = 1.6 - 0.6 + 0.1 = 1.1000$$
2. **Probability Mapping (p):** $$p = \sigma(1.1000) = \frac{1}{1 + e^{-1.1000}} \approx 0.7503$$
3. **Loss Evaluation ($\mathcal{L}$):** $$\mathcal{L} = -\log(0.7503) \approx 0.2873$$
4. **Analytical Gradient Derivation:** $$\frac{\partial \mathcal{L}}{\partial z} = p - y = 0.7503 - 1.0 = -0.2497$$ $$\frac{\partial \mathcal{L}}{\partial \mathbf{w}} = \left(\frac{\partial \mathcal{L}}{\partial z}\right) \mathbf{f} = -0.2497 \times (2.0, 0.5) = (-0.4994, -0.1249)$$ $$\frac{\partial \mathcal{L}}{\partial b} = \frac{\partial \mathcal{L}}{\partial z} = -0.2497$$

5. **Gradient Parameter Update ($\eta = 0.1$):** $$\mathbf{w}*{\text{new}} = \mathbf{w} - \eta \left(\frac{\partial \mathcal{L}}{\partial \mathbf{w}}\right) = (0.8, -1.2) - 0.1 \times (-0.4994, -0.1249) = (0.8499, -1.1875)$$ $$b*{\text{new}} = b - \eta \left(\frac{\partial \mathcal{L}}{\partial b}\right) = 0.1 - 0.1 \times (-0.2497) = 0.1250$$
6. **Parameter Update Verification:** $$z_{\text{updated}} = (0.8499 \times 2.0) + (-1.1875 \times 0.5) + 0.1250 = 1.6998 - 0.59375 + 0.1250 = 1.2313$$ $$p_{\text{updated}} = \sigma(1.2313) = \frac{1}{1 + e^{-1.2313}} \approx 0.7740$$The updated probability $p_{\text{updated}} = 0.7740$ moves closer to target label $y = 1$ than initial probability $p = 0.7503$, confirming that the gradient step updates model parameters toward the ground truth.

Optimization Strategy & Hyperparameters

Detectors are trained using AdamW, which decouples weight decay parameter λ from gradient momentum estimates (m_t, v_t): $$\theta_t = \theta_{t-1} - \eta \left(\frac{\hat{m}_t}{\sqrt{\hat{v}*t} + \epsilon} + \lambda \theta*{t-1} \right)$$Standard hyperparameter configurations for fine-tuning are summarized below:| Hyperparameter Metric | Recommended Baseline Value | Technical Implementation Rationale || ------ | ------ | ------ || **Optimizer** | AdamW ($\beta_1=0.9, \beta_2=0.999, \epsilon=1\text{e-}8$) | Adaptive momentum tracking with decoupled L_2 weight decay regularization. || **Learning Rate (η)** | $1\text{e-}4$ (Fine-tuning) / $1\text{e-}3$ (From scratch) | Lower rate prevents destructive updates to pre-trained backbones. || **Weight Decay (λ)** | $1\text{e-}4$ | Suppresses weight growth to reduce overfitting. || **Batch Size** | 32 to 64 | Gradient accumulation can be used if memory limits are reached. || **Epoch Counter** | 5 to 10 Epochs | Monitor validation loss; apply early stopping to prevent over-fitting. || **Input Spatial Crop** | 224×224 Native Crop | Native spatial cropping preserves critical high-frequency noise statistics. |

Data Augmentation & Mixed Precision Acceleration


To prevent classifiers from relying on spurious compression cues during training, models use standard data augmentation pipelines (e.g., the CNNSpot augmentation recipe):

- Random Spatial Cropping: Extracts random 224×224 windows.
- Horizontal Flipping: Applied with probability $p=0.5$.
- Gaussian Blurring: Applied with probability $p=0.5$ using kernel radius $\sigma \sim U0, 3$.
- JPEG Compression: Applied with probability $p=0.5$ with quality factor $q \sim U60, 100$ .Training efficiency is further optimized using Automatic Mixed Precision (AMP). Intermediate tensor math is computed using 16-bit floating-point format (FP16), while master parameters are retained in 32-bit floating-point (FP32). A gradient scaler (GradScaler) dynamically scales loss values to prevent FP16 gradient underflow during backpropagation.These training strategies directly influence how robust detectors remain when deployed against real-world degraded media.

11. Robustness & Robustness Analysis under Image Degradation

Degradation Mechanics

Images transmitted across web platforms and social networks undergo destructive spatial transformations that strip high-frequency forensic signals.



1. JPEG Compression: Images are converted into 8×8 pixel blocks and transformed using the Discrete Cosine Transform (DCT): $$F_q(u,v) = \text{round}\left(\frac{F(u,v)}{Q(u,v)} \right)$$ Quantization matrix $Q(u,v)$ applies larger divisors to high-frequency spatial components. Rounding these divisions forces high-frequency coefficients to zero, permanently removing fine forensic traces.
2. Gaussian Blur: Spatial convolution using a 2D Gaussian kernel $G(x,y) = \frac{1}{2\pi\sigma^2} \exp\left(-\frac{x^2+y^2}{2\sigma^2}\right)$ suppresses high-frequency spectral components above cutoff frequency $\approx 1/\sigma$.
3. Spatial Downscaling: Downsampling reduces spatial resolution via pixel neighborhood averaging. This discards spatial details exceeding the reduced Nyquist sampling limit, disrupting generator-specific high-frequency patterns.

Empirical Degradation Benchmarks

The performance impact of post-processing transformations on a standard ResNet-50 trained on unaugmented Stable Diffusion v1.4 data (from GenImage benchmarks) is detailed below:| Image Degradation State | Transformation Parameters | Classification Accuracy (%) | Performance Retained || ------ | ------ | ------ | ------ || **Native Unmodified** | Clean 224×224 crops | 99.9% | Baseline Baseline || **Low-Resolution Downscale** | Downsampled to 112×112 | $\sim 96\%$ | Moderate Degradation || **Low-Resolution Downscale** | Downsampled to 64×64 | $\sim 57\%$ | Severe Degradation || **JPEG Compression** | Quality Factor $q = 65$ | $\sim 52\%$ | Near Random Chance || **JPEG Compression** | Quality Factor $q = 30$ | $\sim 51\%$ | Near Random Chance || **Gaussian Blur** | Kernel Radius $\sigma = 3$ | $\sim 98\%$ | High Robustness || **Gaussian Blur** | Kernel Radius $\sigma = 5$ | $\sim 69\%$ | Severe Degradation |
Incorporating augmentation during training (e.g., the CNNSpot augmentation recipe) improves robustness under JPEG compression. Models trained with random JPEG perturbations retain approximately 97% classification accuracy at test JPEG quality $q=65$, compared to the 52% performance of unaugmented baselines.These degradation dynamics highlight the need for standardized cross-generator empirical evaluation frameworks.

12. Comprehensive Empirical Evaluation & Cross-Generator Results

Evaluation Metrics & Statistical Metrics

Model performance is evaluated across a range of statistical metrics derived from the confusion matrix:


```
                          Predicted AI-Generated (y=1)
Predicted Authentic (y=0)
Actual AI-Generated (y=1)      True Positive (TP)
False Negative (FN)
Actual Authentic (y=0)         False Positive (FP)            True
Negative (TN)
```

$$\text{Accuracy} = \frac{\text{TP} + \text{TN}}{\text{TP} + \text{TN} + \text{FP} + \text{FN}}, \quad \text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}}, \quad \text{Recall (TPR)} = \frac{\text{TP}}{\text{TP} + \text{FN}}$$$$\text{False Positive Rate (FPR)} = \frac{\text{FP}}{\text{FP} + \text{TN}}, \quad \text{F1-Score} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$$Additional evaluation criteria include:

- Receiver Operating Characteristic - Area Under Curve (ROC-AUC): Threshold-independent metric measuring the probability that a randomly chosen synthetic image receives a higher score than a randomly chosen authentic photograph.
- TPR @ 1% FPR: True Positive Rate achievable when the threshold is set to limit False Positive Rates to $\le 1.0\%$.
- Expected Calibration Error (ECE): Quantifies the gap between predicted probability confidence scores and actual empirical accuracy across M equal-width probability bins B_m : $$\text{ECE} = \sum_{m=1}^M \frac{|B_m|}{N} \left| \text{acc}(B_m) - \text{conf}(B_m) \right|$$

Bayesian Base-Rate Fallacy in Unbalanced Real-World Deployment

Evaluating models solely on balanced test sets (50% authentic, 50% synthetic) masks potential performance drops in real-world operational environments, where synthetic image prevalence may be low (e.g., 1%).Assume a high-performing detector exhibits 90% Recall ($\text{TPR} = 0.90$) and a 5% False Positive Rate ($\text{FPR} = 0.05$). Under a real-world base rate of 1% synthetic media prevalence ($P(\text{Fake}) = 0.01$), the posterior probability that a flagged image is actually synthetic is computed via Bayes' Theorem: $$P(\text{Fake} \mid \text{Flagged}) = \frac{P(\text{Flagged} \mid \text{Fake}) \cdot P(\text{Fake})}{P(\text{Flagged} \mid \text{Fake}) \cdot P(\text{Fake}) + P(\text{Flagged} \mid \text{Real}) \cdot P(\text{Real})}$$$$P(\text{Fake} \mid \text{Flagged}) = \frac{0.90 \times 0.01}{(0.90 \times 0.01) + (0.05 \times 0.99)} = \frac{0.009}{0.009 + 0.0495} = \frac{0.009}{0.0585} \approx 15.38\%$$



```
                Precision = 90 / (90 + 495) = 15.38% Actual
Reliability
```

Despite achieving 90% overall accuracy on a balanced benchmark, approximately 84.6% of all operational alerts generated in this low-prevalence setting are false positives. This highlights the importance of optimizing forensic detectors for ultra-low False Positive Rates (e.g., maximizing TPR @ 1% FPR).


GenImage Cross-Generator Benchmark Results

The complete empirical performance matrix for a supervised ResNet-50 model trained exclusively on Stable Diffusion v1.4 data and evaluated across 8 GenImage test generator splits is presented below:| Target Evaluation Dataset Split | Underlying Architecture Paradigm | Classification Accuracy (%) | Cross-Generator Transfer Behavioral Profile || ------ | ------ | ------ | ------ || **Stable Diffusion v1.4** | Latent Diffusion Model (LDM) | 99.9% | Native Training Baseline || **Stable Diffusion v1.5** | Latent Diffusion Model (LDM) | 99.7% | Architecture Sibling (Near-Perfect Transfer) || **Wukong** | Latent Diffusion Model (LDM) | 98.2% | LDM Architectural Relative || **Midjourney V5** | Closed-Source Latent Diffusion Engine | 54.9% | High Performance Drop || **VQDM** | Vector-Quantized Diffusion Model | 56.6% | High Performance Drop || **GLIDE** | Pixel-Space Diffusion Model | 61.9% | Poor Transfer || **ADM** | Analytic-DPM (Pixel-Space Diffusion) | 53.5% | Near Random Chance || **BigGAN** | Generative Adversarial Network | 52.0% | Near Random Chance || **Cross-Generator Average** | Overall Multi-Generator Mean | **72.1%** | Significant Generalization Gap |
These empirical evaluation results demonstrate that supervised classifiers achieve high within-distribution performance on identical or closely related architectures (SD1.5, Wukong), but degrade toward random chance (50%) when applied to distinct generative architectures (ADM, BigGAN, Midjourney).This performance drop points to underlying dataset biases and shortcut learning dynamics that require systematic analysis.

13. Generalization Challenges, Dataset Bias, & Mitigation Strategies

Taxonomy of Dataset Biases & Shortcuts

Supervised neural networks naturally exploit non-forensic dataset discrepancies that correlate with target labels during training. Common shortcuts in synthetic image detection include:



1. File Format Discrepancies: Training sets that combine JPEG real photographs with uncompressed PNG synthetic renders allow classifiers to learn format compression signatures rather than generator fingerprints.
2. Resolution Differences: Generators output default spatial dimensions (e.g., Midjourney at 1024, SD at 512, GLIDE at 256, BigGAN at 128). Models can use spatial resolution boundaries as classification shortcuts.
3. Content & Semantic Composition Bias: Synthetic images frequently exhibit centered compositions, distinct color distributions, or smooth textures compared to wild real photos.
4. Compression Artifact Disparities: Real photographs sourced from web datasets often contain historical double-compression artifacts that are absent in freshly synthesized outputs.

Training Scale & Class Diversity

Empirical results from the GenImage benchmark demonstrate the relationship between training dataset scale, class diversity, and cross-generator generalization accuracy:| Training Data Volume | Source Class Count | Within-Generator Accuracy (%) | Cross-Generator Accuracy (%) || ------ | ------ | ------ | ------ || **1,600 images** | 10 Classes | 73.6% | 60.9% || **1,600 images** | 100 Classes | 81.8% | 62.7% || **16,000 images** | 100 Classes | 97.7% | 68.7% || **162,000 images** | 1,000 Classes | 99.9% | 72.1% | Increasing data volume and semantic class diversity improves within-generator accuracy ($73.6\% \rightarrow 99.9\%$), but yields diminishing returns for cross-generator transfer ($60.9\% \rightarrow 72.1\%$). Scaling data from a single generative source is insufficient to resolve cross-generator generalization failures.

Modern Bias Mitigation Paradigms

To reduce reliance on dataset shortcuts, recent research introduces targeted data-alignment paradigms:

- B-Free Paradigm: Generates paired synthetic training images by reconstructing authentic photos through Stable Diffusion self-conditioning and inpainting operations. Because both real and fake counterparts contain identical visual content and semantic structures, the model is forced to focus on low-level generation artifacts.
- Dual Data Alignment (DDA): Aligns both spatial pixel representations (via VAE reconstruction) and high-frequency spectral content (via high-frequency fusion and mixup), removing spurious spectral cues that cause shortcut learning.
- Community Forensics: Trains detectors across ultra-diverse datasets containing over 2.7 million images collected from 4,803 distinct generative engines, replacing single-generator training with broad architectural exposure.

The 5-Step Practical Bias Audit Protocol

Before deploying any forensic detector, models should undergo a 5-step bias audit to verify signal integrity:

```
Step 1: Train Metadata Classifier (Input: Width, Height, Size,
Format; Target: AUC ≈ 0.5)
                    |
                    ▼
```

```
Step 2: Plot Feature Histograms (Channel Brightness, Spectral
Energy, File Sizes)
                    |
                    ▼
Step 3: Uniform Standardization & Re-encoding (Apply Uniform
Cropping & JPEG Pipeline)
                    |
                    ▼
Step 4: Held-Out Generator & Content Testing (Evaluate Unseen
Engines & Art/Face Datasets)
                    |
                    ▼
Step 5: False-Positive Validation (Evaluate Authentic Mobile
Camera Captures)
```

1. Metadata-Only Shortcut Verification: Train a baseline decision tree using only file metadata (image dimensions, file size, format headers, JPEG quality metrics). If this metadata classifier achieves AUC $\gg 0.5$, dataset shortcuts are present.
2. Feature Distribution Audit: Plot and compare feature distribution metrics (mean brightness, high-frequency spectral energy, file sizes) across authentic and synthetic classes to identify systematic baseline shifts.
3. Uniform Dataset Re-encoding: Standardize all training and evaluation imagery by applying uniform spatial cropping and standard JPEG re-encoding. A sharp drop in model accuracy after re-encoding indicates reliance on format shortcuts.
4. Out-of-Domain Generalization Testing: Benchmark model performance on completely held-out generative engines and distinct semantic content domains (e.g., LFW face datasets, LAION-Art).
5. Authentic False-Positive Validation: Measure false-positive rates using unedited, raw photographs captured directly from modern mobile phone camera sensors.Audit protocols must also consider the computational complexity and hardware resources required to train and run these pipelines.

14. System Resource Analysis: Memory, Compute, & Time Complexity

VRAM Footprint Analysis

The GPU memory (VRAM) required for full FP32 training of a ResNet-50 binary detector consists of four main components:

1. Model Parameters: $23.5 \times 10^6 \text{ parameters} \times 4 \text{ bytes/param} \approx 94 \text{ MB}$.
2. AdamW Optimizer States: Tracks parameter momentum (m_t) and variance (v_t), requiring $2 \times 94 \text{ MB} \approx 190 \text{ MB}$.
3. Gradient Vectors: Matches parameter footprint at $1 \times 94 \text{ MB} \approx 94 \text{ MB}$.
4. Activation Tensors: Scales dynamically with mini-batch size and spatial tensor dimensions.Under standard FP16 Automatic Mixed Precision (AMP), parameter and gradient memory footprints are halved. On entry-level workstation hardware (e.g., an RTX 2050 GPU with 4 GB VRAM), fine-tuning a ResNet-50 backbone with native

224×224 inputs operates comfortably at mini-batch sizes between 16 and 32.

Execution Benchmarks

Estimated processing times across models and pipeline tasks on T4-class GPU hardware are detailed below:| System Pipeline Task | Workload Volume & Parameters | Execution Duration (T4 Reference) || ------ | ------ | ------ || **ResNet-50 Fine-Tuning** | ~32,000 images, 10 Training Epochs | 15 – 25 Minutes || **ResNet-50 Multi-Generator Evaluation** | ~100,000 images across 8 benchmark splits | 5 – 10 Minutes || **CLIP ViT-L/14 Feature Extraction** | ~100,000 images mapped to 768-dim vectors | 20 – 30 Minutes || **Linear Probe Optimization** | Logistic regression on cached 768-dim features | < 1 Minute || **AEROBLADE Reconstruction Pipeline** | ~20,000 images evaluated across 3 VAE decoders | 15 – 30 Minutes |
Resource planning must balance these hardware specifications against operational limits and deployment safety standards.

15. Strategic Limitations & Responsible Deployment Framework

Operational & Technical Limitations

Deep statistical forensic detectors face inherent technical limitations:


- Performance degradation on unseen generative engines, heavily re-compressed social media files, resized images, screen captures, and adversarial perturbations.
- Dataset age mismatch: Models trained on legacy benchmarks (e.g., GenImage's 2022–2023 engines) struggle to detect outputs from modern architectures such as Flux, Firefly, or Midjourney v7.

Ethical Governance & Risk Management

Forensic scores generated by deep neural networks represent probabilistic likelihood estimates rather than definitive legal proof of forgery. Automated punitive actions or content moderation decisions should never rely solely on thresholded scalar outputs ($p > t$). Due to false-positive risks in low-prevalence environments (as shown in Section 12), high-stakes applications require human analyst oversight.

Complementary Verification Frameworks

Statistical deep learning detectors should be deployed alongside active media provenance standards:



```
(Statistical CNN / Foundation Probes)
(Watermarking & Signed Cryptographic Metadata)
 ├── Analyzes Pixel Discrepancies & Noise Patterns
├── Active Watermarking (e.g., Google SynthID)
 └── Detects Unmarked Legacy Synthetic Content
└── Cryptographic Metadata (C2PA Content Credentials)
```

1. Active Watermarking (e.g., Google SynthID): Embeds imperceptible, statistically detectable signals directly into image latent spaces or pixel arrays during generation.
2. Cryptographic Provenance (C2PA Content Credentials): Encodes cryptographically signed metadata manifests tracking asset origin, editing history, and camera capture hardware.While active provenance standards provide verifiable authentication, metadata manifests can be stripped during social media re-encoding or file conversion. Importantly, the absence of a watermark or C2PA credential must never be interpreted as proof that an image is authentic. Hybrid forensic systems combine active provenance checking with passive statistical models to provide multi-layered verification.

16. Conclusions & Future Scope

This report evaluated three architectural paradigms for detecting synthetic AI-generated images across multi-million-image benchmarks: supervised ResNet-50 CNNs, frozen CLIP ViT-L/14 feature probes, and training-free AEROBLADE reconstruction distance engines.The central finding is that while supervised deep CNNs achieve high within-distribution classification accuracy ($\sim 99.9\%$), cross-generator transfer remains a challenge (72.1% average accuracy on GenImage). Models frequently rely on low-level shortcuts, including file format variations, resolution boundaries, and compression discrepancies.Future forensic research should focus on:

1. Advanced Data Alignment Frameworks: Expanding bias-free paired reconstruction pipelines (e.g., B-Free, DDA) to eliminate content and format shortcuts during training.
2. Broad Architectural Scaling: Scaling multi-generator training across diverse pools (such as Community Forensics' 4,000+ generator benchmark) to improve cross-architecture transfer.
3. Multi-Modal Forensic Pipelines: Combining passive statistical analysis, deep spatial features, frequency residual evaluation, and active cryptographic provenance standards (C2PA) into unified authentication systems.

17. Technical Glossary

Term / Acronym,Mathematical & Forensic Definition
Logit (z),"The unconstrained, raw scalar output $z \in (-\infty, +\infty)$ generated by a neural network linear layer prior to non-linear probability mapping."
Sigmoid (σ),"A monotonic activation function $\sigma(z) = \frac{1}{1 + e^{-z}}$ that squashes raw real-valued logits into a bounded probability distribution $p \in (0, 1)$."
Residual Connection,"An architectural skip pathway computing $\text{output} = F(\mathbf{x}) + \mathbf{x}$, which preserves unattenuated gradient signals ($\frac{\partial \text{out}}{\partial \mathbf{x}} = \frac{\partial F}{\partial \mathbf{x}} + 1$) during backpropagation."

Latent Space,"A compressed low-dimensional spatial manifold produced by an autoencoder network (e.g., $64 \times 64 \times 4$ latent representation in Stable Diffusion)."
VAE,"Variational Autoencoder; an encoder-decoder network pair (E, D) where decoder D leaves consistent statistical artifacts on generated output pixels."
Discrete Fourier Transform (DFT),"A spatial-to-frequency domain conversion mapping pixel arrays into 2D frequency spectra $F(u,v)$ to highlight high-frequency noise residuals."
Shortcut Learning,"The tendency of deep networks to exploit non-forensic dataset artifacts (e.g., file format, spatial resolution, double compression) rather than learning true generator fingerprints."
ROC-AUC,Receiver Operating Characteristic - Area Under Curve; a threshold-independent metric measuring the probability that a random fake image scores higher than a random authentic photo.
Expected Calibration Error (ECE),A metric quantifying the alignment between predicted continuous probability confidence scores and empirical accuracy across probability bins.
LPIPS,Learned Perceptual Image Patch Similarity; a deep perceptual distance metric measuring feature activation deviations across intermediate network layers.
C2PA,Coalition for Content Provenance and Authenticity; an open technical standard for embedding cryptographically signed provenance metadata into digital media assets.

18. References

1 Z. Zhu et al., "GenImage: A million-scale benchmark for detecting AI-generated image," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)* , 2023, pp. 1-10.2 K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)* , 2016, pp. 770-778.3 J. Ho, A. Jain, and P. Abbeel, "Denoising diffusion probabilistic models," in *Advances in Neural Information Processing Systems (NeurIPS)* , vol. 33, 2020, pp. 6840-6851.4 R. Rombach, A. Blattmann, L. Lorenz, P. Esser, and B. Ommer, "High-resolution image synthesis with latent diffusion models," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)* , 2022, pp. 10684-10695.5 A. Radford et al., "Learning transferable visual models from natural language supervision," in *Proc. Int. Conf. Mach. Learn. (ICML)* , 2021, pp. 8748-8763.6 S. Y. Wang, O. Wang, R. Zhang, A. Owens, and A. A. Efros, "CNN-generated images are surprisingly easy to spot... for now," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)* , 2020, pp. 8695-8704.7 U. Ojha, Y. Li, and Y. J. Lee, "Towards universal fake image detectors that generalize across generative models," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)* , 2023, pp. 24480-24489.8 J. Ricker, D. Dugas, and M. Fischer, "AEROBLADE: Training-free detection of latent diffusion images using autoencoder reconstruction error," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)* , 2024, pp. 1-10.9 C. Park and A. Owens, "Community Forensics: Using thousands of generators to train fake image detectors," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)* , 2025.10 A. Guillaro et al., "A bias-free training paradigm for more general AI-generated image detection," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)* , 2025.11 L. Chen et al., "Dual data alignment makes AI-generated image detector easier generalizable," in *Advances in Neural Information Processing Systems (NeurIPS)* , 2025.