

Project 1: Deploy a Sample Application using AWS CodePipeline and CodeDeploy

- **Region Used: ap-south-1 (Mumbai)**
- **Architecture:**
- **S3 → CodePipeline → CodeDeploy → EC2 (Amazon Linux)**

1: Create S3 Bucket

- Bucket Name: codepipeline-demo-ap-south-1-12345
- Region: ap-south-1

2: Download & Upload Sample App

- Download SampleApp_Linux.zip from AWS Docs
- Upload zip file to S3 bucket

3: Create IAM Role for EC2

- Role Name: CodeDeployEC2Role
- Policy: AmazonEC2RoleforAWSCodeDeploy

4: Launch EC2 Instance

- Name: CodeDeploy-EC2
- AMI: Amazon Linux 2
- Instance Type: t3.micro
- Allow HTTP & SSH
- Attach IAM Role

5: Install CodeDeploy Agent Commands:

- `sudo yum update -y`
- `sudo yum install ruby wget -y`
- `wget https://aws-codedeploy-ap-south-1.s3.ap-south-1.amazonaws.com/latest/install`
- `chmod +x install`
- `sudo ./install auto`

6: Create CodeDeploy Application

- Application Name: SampleApp
- Deployment Group: SampleApp-DG
- Service Role: CodeDeployServiceRole

7: Create CodePipeline

- Pipeline Name: SamplePipeline
- Source: Amazon S3
- Deploy: AWS CodeDeploy

8: Run Pipeline

- Release Change
- Verify Success

9: Verify Output

- Access EC2 Public IP in browser
- index.html page displayed

10: Cleanup Resources

- Delete Pipeline, Application, EC2, S3, IAM Roles





