ADVIKA VALVES

Authorised Dealer of Flowsid Valves

Precision Industrial Flow Control & Valve Solutions

COMPLETE PRODUCT CATALOG (TECHNICAL SPECIFICATIONS EDITION)

Featuring 78 Authentically Documented Industrial Valve Products

Stainless Steel | Cast Iron | Cast Steel | Forged Steel | Polypropylene | Brass

ADVIKA VALVES — Authorized Business Details

Legal Owner: Alka Jain
Managers: Dinesh Jain (+91 9811049614) | Sidharth Jain (+91 8447952332)
Email: advikavalves@gmail.com
Address: 831, Kucha Pati Ram, Sita Ram Bazaar, Chawri Bazar, Delhi – 110006, India.



Item #1: Stainless Steel Screwed Ball Valve (Medium Imported)
Category: Stainless Steel Ball Valves | **Make:** FLOWSID (Imported)
Design: Investment Casting, Two-Piece Screwed End (S/E), Full Bore
Pressure Rating: Body: 225 Psig (16 kg/cm²), Seat: 165 Psig (11.5 kg/cm²)
Available Sizes: 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Screwed BSP, Screwed BSPT
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Medium pattern investment cast stainless steel ball valve with screwed ends for industrial liquid and gas flow control.



Item #2: Stainless Steel Screwed Ball Valve (Standard Heavy Duty)
Category: Stainless Steel Ball Valves | **Make:** FLOWSID
Design: Investment Casting, Heavy Duty Screwed End (S/E), Full Bore
Pressure Rating: Body: 225 Psig (16 kg/cm²), Seat: 165 Psig (11.5 kg/cm²)
Available Sizes: 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Screwed BSP, Screwed BSPT
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy-duty investment cast stainless steel ball valve with screwed BSP/BSPT connections in SS 304 and SS 316.



Item #3: Stainless Steel 3-Piece Screwed Ball Valve
Category: Stainless Steel Ball Valves | **Make:** FLOWSID (Imported)
Design: Three-Piece Design (3 Pcs), Investment Casting, Screwed End (S/E)
Pressure Rating: Body: 225 Psig (16 kg/cm²), Seat: 165 Psig (11.5 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2"
Connections: Screwed BSP, Screwed BSPT
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Three-piece investment casting stainless steel ball valve with screwed ends for easy in-line maintenance.



Item #4: Stainless Steel 3-Piece Flanged Ball Valve Class 150 (Full Bore)
Category: Stainless Steel Ball Valves | **Make:** FLOWSID
Design: Three Piece Design (3 Pcs), Full Bore (F/B), Flanged End (F/E)
Pressure Rating: Body: 425 Psig (30 kg/cm²), Seat: 300 Psig (21 kg/cm²), Class 150#
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10"
Connections: Flanged To ANSI B 16.5 RF (150#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Class 150 full bore flanged 3-piece investment cast stainless steel ball valve conforming to ANSI B 16.5 RF.



Item #5: Stainless Steel 2-Piece Flanged Ball Valve Class 150
Category: Stainless Steel Ball Valves | **Make:** FLOWSID
Design: Two Piece Design (2 Pcs), Flanged End
Pressure Rating: Body: 425 Psig (30 kg/cm²), Seat: 300 Psig (21 kg/cm²), Class 150#
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Flanged To ANSI B (150#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Two-piece flanged stainless steel ball valve with ANSI B 150# connections for compact high-integrity pipeline installations.



Item #6: Stainless Steel 3-Piece Flanged Ball Valve Class 300 (300#)
Category: Stainless Steel Ball Valves | **Make:** FLOWSID
Design: Three Piece Design, Full Bore, Class 300 Flanged
Pressure Rating: Class 300# (Body: 425 Psig / 30 kg, Seat: 300 Psig / 21 kg)
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2", 3", 4"
Connections: Flanged To ANSI B 16.5 RF (300#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: High-pressure Class 300 flanged 3-piece full bore stainless steel ball valve for demanding industrial lines.

7



Item #7: Stainless Steel Three-Way Ball Valve (T-Port)
Category: Stainless Steel Ball Valves | **Make:** FLOWSID
Design: Three-Way T-Port, Investment Cast Body, Flow Diverter
Pressure Rating: Body: 425 Psig (30 kg/cm²), Seat: 225 Psig (21 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Screwed BSP/BSPT/NPT, Flanged To ANSI B 16.5 RF (150#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Three-way T-Port stainless steel ball valve available in screwed and flanged ANSI 150# configurations for mixing and diverting.



Item #8: SS 304 Threaded Ball Valve 2-Piece Design (Imported)
Category: Stainless Steel Ball Valves | **Make:** FLOWSID (Imported)
Design: Two Piece Design (2 Pcs), Threaded End
Pressure Rating: Standard process utility rating (16 bar)
Available Sizes: 1/4", 3/8", 1/2", 3/4", 1"
Connections: Threaded / Screwed BSP
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Compact two-piece threaded SS 304 ball valve for precision instrumentation and small-bore process connections.



Item #9: SS 304 Reduced Bore Ball Valve 1-Piece Design (Imported)
Category: Stainless Steel Ball Valves | **Make:** FLOWSID (Imported)
Design: One Piece Body (1 Pcs. Design), Threaded End
Pressure Rating: Standard utility pressure rating
Available Sizes: 1/4", 3/8", 1/2"
Connections: Threaded / Screwed BSP
Documented Applications: Water, Steam, Gas, Oil, Air
Description: One-piece uni-body stainless steel 304 ball valve offering minimal leak paths for compact utility applications.



Item #10: Stainless Steel Butterfly Valve with Silicon Kit (Imported)
Category: Stainless Steel Butterfly Valves | **Make:** FLOWSID
Design: Wafer Pattern, Silicon Seated, Lever / Gear Operated
Pressure Rating: PN-16 (16 Bar)
Available Sizes: 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10"
Connections: Wafer Type to fit PN-16 / ANSI 150# flanges
Documented Applications: Water, Steam, Gas, Oil, Air
Description: SS 304 wafer butterfly valve fitted with high-purity silicon kit and stainless steel handle for sanitary and process applications.



Item #11: Stainless Steel Investment Casting Butterfly Valve (API 609)
Category: Stainless Steel Butterfly Valves | **Make:** FLOWSID
Design: Wafer Type Butterfly Valve, Centric Disc, Flow Control Lever
Pressure Rating: Body: 300 Psig (21 kg/cm²), Seat: 160 Psig (11 kg/cm²)
Available Sizes: 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"
Connections: Wafer Type To Suit ANSI B16.5 (150#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: API 609 compliant investment cast SS 304 butterfly valve with EDPE seat and ANSI B16.5 wafer mounting.



Item #12: Stainless Steel Wafer Type Non-Return Check Valve
Category: Stainless Steel Check Valves | **Make:** FLOWSID
Design: Wafer Type Non-Return Check Valve, Compact Face-to-Face
Pressure Rating: Body: 165 Psig, Seat: 225 Psig
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14", 16", 18", 20"
Connections: Wafer Type Suitable Flanges To Class 150# / BS 10 Table D / E / F
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Slim wafer pattern stainless steel non-return check valve fitting between Class 150 and BS 10 flanges from 25mm to 500mm.



Item #13: Stainless Steel Disc Check Valve (DCV)
Category: Stainless Steel Check Valves | **Make:** FLOWSID
Design: Spring-Assisted Disc Check Valve, Wafer Mounting
Pressure Rating: Body: 425 Psig (30 kg/cm²), Seat: 300 Psig (21 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"
Connections: Wafer Type For 15 mm To 100 mm Flanges
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Spring-loaded stainless steel disc check valve for ultra-rapid closure, water hammer prevention, and multi-orientation mounting.



Item #14: Stainless Steel Flanged Sight View Glass (Class 150)
Category: Stainless Steel Sight Glasses & Strainers | **Make:** FLOWSID
Design: Flanged Double Window Sight Flow Indicator, Length: 6"
Pressure Rating: Body: 165 Psig, Seat: 225 Psig
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Flanges To ANSI B 16.5 RF (150#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Flanged ANSI 150# investment cast stainless steel sight glass fitted with toughened glass for clear pipeline flow monitoring.



Item #15: Stainless Steel Screwed Y-Type Strainer (Imported)
Category: Stainless Steel Sight Glasses & Strainers | **Make:** FLOWSID (Imported)
Design: Y-Pattern Strainer, Screwed / Socketweld Ends
Pressure Rating: Body: 425 Psig (30 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3"
Connections: Screwed BSP / BSPT / NPT, Socketweld Ends to ANSI B-16.11
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Compact investment cast CF8 stainless steel Y-type pipeline strainer with fine SS 304 mesh screen for particulate filtration.



Item #16: Stainless Steel Flanged Y-Type Strainer
Category: Stainless Steel Sight Glasses & Strainers | **Make:** FLOWSID
Design: Flanged Y-Type Strainer with Inspection Port
Pressure Rating: Body: 165 Psig, Seat: 225 Psig
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"
Connections: Flanged Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Flanged investment cast stainless steel Y-strainer available in SS 304 and SS 316 for high-capacity industrial pipeline filtration.



Item #17: Stainless Steel Tri-Clamp (TC) Sanitary Ball Valve
Category: Stainless Steel Dairy & Sanitary Valves | **Make:** FLOWSID
Design: Sanitary Tri-Clamp Quick-Release Ball Valve
Pressure Rating: Sanitary working pressure up to 10 bar
Available Sizes: 3/4", 1", 1-1/2", 2", 2-1/2", 3"
Connections: Tri-Clamp (TC) Ferrule Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Sanitary stainless steel ball valve with Tri-Clamp (TC) end connections for hygienic food, beverage, and dairy applications.



Item #18: Stainless Steel 304 Union-Type Dairy Butterfly Valve
Category: Stainless Steel Dairy & Sanitary Valves | **Make:** FLOWSID
Design: Sanitary Union Type, Multi-Position Pull Handle
Pressure Rating: Sanitary working pressure rating (10 bar)
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Sanitary Union Threaded Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Sanitary SS 304 union-type butterfly valve with pull-handle for hygienic piping disassembly and cleaning.



Item #19: Stainless Steel 304L Tri-Clamp (TC) Dairy Butterfly Valve
Category: Stainless Steel Dairy & Sanitary Valves | **Make:** FLOWSID
Design: Sanitary Tri-Clamp Butterfly Valve, 304L Low Carbon
Pressure Rating: Sanitary working pressure up to 10 bar
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Tri-Clamp (TC) Sanitary Clamp Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Low-carbon SS 304L Tri-Clamp sanitary butterfly valve for high-hygiene food, beverage, and dairy processing lines.



Item #20: Stainless Steel 304L Weld-End Dairy Butterfly Valve
Category: Stainless Steel Dairy & Sanitary Valves | **Make:** FLOWSID
Design: Weldable Butt-Weld Sanitary Butterfly Valve, 304L
Pressure Rating: Sanitary rated (10 bar)
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Butt-Weld (Welded) Tube Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Butt-weld end sanitary SS 304L butterfly valve for permanent, leak-proof integration in hygienic process piping.



Item #21: Stainless Steel Screwed Gate Valve (High Pressure)
Category: Stainless Steel Gate & Globe Valves | **Make:** FLOWSID
Design: Investment Casting, Inside Screw Rising Stem, Solid Wedge
Pressure Rating: Body: 1100 Psig (77 kg/cm²), Seat: 800 Psig (56 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3"
Connections: Screwed To BSP, Socketweld End To ANSI B 16.11
Documented Applications: Water, Steam, Gas, Oil, Air
Description: High-pressure investment cast SS 304 gate valve with screwed BSP and socketweld connections rated for 1100 Psig body test.



Item #22: Stainless Steel Flanged Gate Valve (API 600)
Category: Stainless Steel Gate & Globe Valves | **Make:** FLOWSID
Design: OS&Y; Rising Stem, Bolted Bonnet, Flanged ANSI 150#
Pressure Rating: Body: 1100 Psig (77 kg/cm²), Seat: 800 Psig (56 kg/cm²), Class 150#
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 6", 8"
Connections: Flanges To ANSI B 16.5 RF (150#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: API 600 flanged Class 150 stainless steel gate valve with flexible/solid wedge in SS 304 and SS 316.



Item #23: Stainless Steel Screwed Globe Valve (Imported)
Category: Stainless Steel Gate & Globe Valves | **Make:** FLOWSID (Imported)
Design: Investment Casting, Globe Pattern, Regulating Plug
Pressure Rating: Body: 1100 Psig (77 kg/cm²), Seat: 800 Psig (56 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2"
Connections: Screwed To BSP, Socketweld end To ANSI B 16.11
Documented Applications: Water, Steam, Gas, Oil, Air
Description: High-pressure investment cast SS 304 globe valve for precise fluid throttling and isolation with screwed and socketweld ends.



Item #24: Stainless Steel Flanged Globe Valve (API 600)
Category: Stainless Steel Gate & Globe Valves | **Make:** FLOWSID
Design: OS&Y; Bolted Bonnet Globe Valve, Flanged Class 150#
Pressure Rating: Body: 1100 Psig (77 kg/cm²), Seat: 800 Psig (56 kg/cm²), Class 150#
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"
Connections: Flanges To ANSI B 16.5 RF (150#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: API 600 flanged Class 150 stainless steel globe valve for heavy throttling and positive shut-off in SS 304 and SS 316.



Item #25: Stainless Steel Vertical Lift Check Valve (Imported)
Category: Stainless Steel Check Valves | **Make:** FLOWSID (Imported)
Design: Vertical Lift Type Non-Return Valve, High Pressure
Pressure Rating: Body: 1100 Psig (77 kg/cm²), Seat: 800 Psig (56 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3"
Connections: Screwed To BSP, Socketweld end To ANSI B 16.11
Documented Applications: Water, Steam, Gas, Oil, Air
Description: High-pressure vertical line stainless steel lift non-return check valve for upward flow prevention and backflow protection.




Item #26: Stainless Steel Horizontal Lift Check Valve (Imported)
Category: Stainless Steel Check Valves | **Make:** FLOWSID (Imported)
Design: Horizontal Lift Check Valve, Bolted Cap
Pressure Rating: Body: 1100 Psig (77 kg/cm²), Seat: 800 Psig (56 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3"
Connections: Screwed To BSP, Socketweld end To ANSI B 16.11
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Horizontal flow stainless steel lift check valve for high-pressure process pipelines with threaded and socketweld ends.



Item #27: Stainless Steel Swing Check Valve (BS 5352)
Category: Stainless Steel Check Valves | **Make:** FLOWSID
Design: Investment Casting Swing Type NRV, Horizontal & Vertical Orientation
Pressure Rating: Body: 425 Psig (30 kg/cm²), Seat: 300 Psig (21 kg/cm²)
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"
Connections: Flanged To BSP / BSPT / NPT
Documented Applications: Water, Steam, Gas, Oil, Air
Description: BS 5352 compliant investment cast SS 304/316 swing non-return valve suitable for horizontal and vertical lines.




Item #28: Stainless Steel High Pressure Needle Valve (1500 / 3000 PSI)
Category: Stainless Steel Needle & Float Valves | **Make:** FLOWSID
Design: Round Body (1500 PSI) / Square Body (3000 PSI), Fine Tapered Needle Stem
Pressure Rating: Round Body: 1500 PSI; Square Body: 3000 PSI
Available Sizes: 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2"
Connections: Screwed To BSP, Screwed To BSPT
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Precision metering stainless steel needle valve in Round Body (1500 PSI) and Square Body (3000 PSI) designs.



Item #29: Stainless Steel 304 Threaded Float Valve
Category: Stainless Steel Needle & Float Valves | **Make:** FLOWSID
Design: Lever-Operated Mechanical Float Level Control Valve
Pressure Rating: Tank operating pressure rating (up to 10 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2"
Connections: Screwed / Threaded BSP
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Automatic liquid level control SS 304 float valve with threaded connections and stainless steel lever assembly.



Item #30: Stainless Steel 304 Threaded Gauge Glass (GG) Set
Category: Stainless Steel Needle & Float Valves | **Make:** FLOWSID
Design: Upper and Lower Level Gauge Valve Set with Drain
Pressure Rating: Boiler & tank rated working pressure
Available Sizes: 1/2", 3/4", 1"
Connections: Threaded / Screwed BSP
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Direct-reading SS 304 boiler and tank liquid level gauge glass set with top and bottom isolation valves.



Item #31: Stainless Steel 304 Pressure Gauge Syphon (Pigtail Coil)
Category: Stainless Steel Needle & Float Valves | **Make:** FLOWSID
Design: Circular Pigtail Coil Syphon
Pressure Rating: High pressure steam line rating
Available Sizes: 3/8", 1/2"
Connections: Threaded Male / Female BSP
Documented Applications: Water, Steam, Gas, Oil, Air
Description: SS 304 coil pigtail syphon for protecting pressure gauges and transmitters from hot steam and thermal shock.



Item #32: Stainless Steel 304 Pressure Gauge Syphon (U-Type)
Category: Stainless Steel Needle & Float Valves | **Make:** FLOWSID
Design: U-Type Loop Syphon
Pressure Rating: High pressure steam line rating
Available Sizes: 3/8", 1/2"
Connections: Threaded Male / Female BSP
Documented Applications: Water, Steam, Gas, Oil, Air
Description: U-type SS 304 syphon designed for vertical pipeline gauge installations to isolate instruments from hot steam.



Item #33: Cast Iron Butterfly Valve PN 16 (Integral Moulded EDPE)
Category: Cast Iron Butterfly Valves | **Make:** FLOWSID
Design: Wafer Pattern Centric Disc Butterfly Valve, PN 16
Pressure Rating: 16 kg Bar Pressure (PN 16)
Available Sizes: 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14", 16", 18", 20"
Connections: Wafer Type to fit PN-16 / ANSI 150#
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy-duty PN 16 cast iron butterfly valve with integrally moulded EDPE liner for water, steam, gas, oil, and air services.



Item #34: Cast Iron Butterfly Valve with SS 304 Disc (Export Model PN 16)
Category: Cast Iron Butterfly Valves | **Make:** FLOWSID (Export Model)
Design: Wafer Pattern, Epoxy Coated, Stainless Steel Disc
Pressure Rating: 16 kg Bar Pressure (PN 16)
Available Sizes: 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14", 16", 18", 20"
Connections: Wafer Type to fit PN-16 / ANSI 150#
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Export-spec PN 16 cast iron butterfly valve with epoxy powder coated body and investment cast SS 304 (CF8) disc.



Item #35: Cast Iron Heavy Duty Butterfly Valve (Standard Model PN 16)
Category: Cast Iron Butterfly Valves | **Make:** FLOWSID
Design: Wafer Type Heavy Duty, Lever / Gear Operated
Pressure Rating: 16 kg Bar Pressure (PN 16)
Available Sizes: 2", 2-1/2", 3", 4", 5", 6"
Connections: Wafer Type to fit PN-16 / ANSI 150#
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy-duty PN 16 cast iron butterfly valve with epoxy coated seat, EPDM liner, and choice of CI or SS disc.



Item #36: Cast Iron Metal-to-Metal (M to M) Damper Butterfly Valve PN 10
Category: Cast Iron Butterfly Valves | **Make:** FLOWSID
Design: Metal to Metal Seated Damper Butterfly Valve, PN 10
Pressure Rating: PN 10 (10 Bar)
Available Sizes: 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"
Connections: Wafer Type to fit PN-10 / PN-16
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Metal-to-metal seated cast iron damper butterfly valve for hot air, flue gas, and duct regulation at PN 10 rating.



Item #37: Pneumatic Double-Acting Actuator Cast Iron Butterfly Valve (SS Disc)
Category: Cast Iron Butterfly Valves | **Make:** FLOWSID
Design: Pneumatically Actuated Double-Acting Butterfly Valve Package
Pressure Rating: PN-10 (10 Bar)
Available Sizes: 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"
Connections: Wafer Type to fit PN-10 / ANSI 150#
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Automated pneumatic double-acting actuator butterfly valve with SS disc for plant automation and remote throttling.



Item #38: Double Flange Butterfly Valve Class 150# (EDPE Seat)
Category: Cast Iron Butterfly Valves | **Make:** FLOWSID
Design: Double Flanged Body, Lever Operated, Class 150#
Pressure Rating: Class 150# / 16 Bar
Available Sizes: 2", 2-1/2", 3", 4", 5", 6"
Connections: Double Flange To Class 150#
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Double flanged Class 150# butterfly valve with EDPE rubber seat for rigid dead-end service and pipeline bolting.



Item #39: Mild Steel Wafer Type Non-Return Check Valve (Heavy Duty)
Category: Cast Iron Check Valves | **Make:** FLOWSID
Design: Wafer Single Flap Check Valve, Heavy Duty
Pressure Rating: MS Flap: BPT 10 kg/cm², WP 11 kg/cm²; SS Disc: BPT 16 kg/cm², WP 11 kg/cm², PN-16
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14", 16", 18"
Connections: Wafer Flange Clamping (Class 150# / Table E)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy-duty mild steel wafer swing check valve available with MS or SS disc configurations from 25mm to 450mm.



Item #40: Cast Iron Dual Plate Non-Return Valve (PN 16)
Category: Cast Iron Check Valves | **Make:** FLOWSID
Design: Dual Plate Wafer Check Valve, Spring Assisted
Pressure Rating: PN-16 (16 Bar)
Available Sizes: 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14"
Connections: Wafer Universal Flange Fitment (PN-16 / 150#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Dual plate wafer check valve with spring-assisted twin doors for rapid slam-free backflow shut-off in sizes up to 350mm.



Item #41: Mild Steel Dual Plate Check Valve PN 16 (Krishana Make)
Category: Cast Iron Check Valves | **Make:** KRISHANA
Design: Wafer Dual Plate Non-Return Valve, M.S. Fabricated Body
Pressure Rating: PN-16 (16 Bar)
Available Sizes: 1-1/2", 2", 2-1/2", 3", 4", 5"
Connections: Wafer Flange Fitment PN-16
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Krishana make mild steel dual plate check valve with SG iron flap and AISI 304 pins for PN 16 pipelines.

42



Item #42: Cast Iron Heavy Duty Foot Valve (Royal Make)
Category: Cast Iron Foot Valves & Sight Glasses | **Make:** ROYAL MAKE (HEAVY)
Design: Suction Foot Valve with Integral Strainer, Heavy Quality
Pressure Rating: Body Test: 21 kg/cm² (300 psig hyd.)
Available Sizes: 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"
Connections: Flange End P.N-16 (BS Table Drilled/Undrilled), Screwed BSP
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Royal Make heavy-duty cast iron foot valve with strainer for pump suction lines in flanged and screwed ends.



Item #43: Cast Iron Foot Valve PN 16 Heavy Duty (Flowsid Make)
Category: Cast Iron Foot Valves & Sight Glasses | **Make:** FLOWSID
Design: Flanged Suction Foot Valve, Heavy Duty PN-16
Pressure Rating: PN-16 (Body Test: 21 kg/cm² / 300 psig hyd.)
Available Sizes: 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14"
Connections: Flange End P.N -16 as per BS Table Drilled/Undrilled
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Flowsid make PN 16 flanged cast iron heavy-duty foot valve with high-intake strainer for large industrial pumping stations.



Item #44: Gun Metal Screwed Sight Glass (Toughened Glass CAF Sealed)
Category: Cast Iron Foot Valves & Sight Glasses | **Make:** FLOWSID
Design: In-Line Cylindrical Viewing Sight Glass, Screwed Female
Pressure Rating: Body Test Pressure: 300 Psig hyd.
Available Sizes: 1"
Connections: Screwed Female End BSP
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Gun metal screwed sight glass with toughened glass windows and CAF dual-sided sealing for 300 psig hydraulic test lines.



Item #45: Cast Iron Two-Piece Screwed Ball Valve (Full Bore)
Category: Cast Iron Ball Valves | **Make:** FLOWSID
Design: Two Piece Design, Straight Pattern, Full Bore
Pressure Rating: Body Test Pressure: 32 Barg (500 Psig Hyd.)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Screwed Female BSP Parallel Threads BS: 21
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Two-piece straight pattern cast iron full bore ball valve with renewable Teflon seat and AISI 304 ball.



Item #46: Cast Iron Three-Piece Flanged Ball Valve (Full Bore 150#)
Category: Cast Iron Ball Valves | **Make:** FLOWSID
Design: Three Piece Design, Straight Pattern, Full Bore Flanged
Pressure Rating: Body Test Pressure: 32 Barg (500 Psig Hyd.), Flanges 150#
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10"
Connections: Flanges As Per 150#
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Three-piece straight pattern cast iron flanged ball valve with renewable Teflon seat and AISI 304 ball for Class 150 pipelines.



Item #47: Cast Iron Three-Way Ball Valve (T-Port)
Category: Cast Iron Ball Valves | **Make:** FLOWSID
Design: Three Way T-Port Diverter Ball Valve
Pressure Rating: Body: 225 Psig (16 kg/cm²), Seat: 165 Psig (11.5 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Screwed To BSP / BSPT / NPT, Flanged Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Three-way T-port cast iron ball valve manufactured to BS 5159 with screwed and flanged connections for stream routing.



Item #48: Cast Iron Screwed Y-Type Strainer (MVI / Flowsid)
Category: Cast Iron Strainers | **Make:** M V I / FLOWSID
Design: Y-Pattern Strainer, Screwed Female Ends
Pressure Rating: Body Test Pressure: 21 kg/sq. cm. G 300 Psig Hyd.
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"
Connections: Screwed BSP / NPT
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy-duty cast iron Y-strainer with screwed ends and stainless steel filtration mesh proof tested to 21 kg/cm².



Item #49: Cast Iron / Mild Steel Flanged Y-Type Strainer (Table-E)
Category: Cast Iron Strainers | **Make:** FLOWSID
Design: Flanged Y-Type Strainer, Table-E Drilling
Pressure Rating: Body Test Pressure: 21 kg/sq. cm. G 300 Psig Hyd.
Available Sizes: 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14", 16", 18"
Connections: Flange End Table-E
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy-duty flanged Table-E Y-strainer with SS mesh, available in CI casting (25-100mm) and MS casting (125-450mm).



Item #50: Mild Steel Flanged T-Type Strainer (Flowsid / Drona)
Category: Cast Iron Strainers | **Make:** FLOWSID / Drona
Design: T-Type / Pot Pattern Fabricated Strainer, Flanged End
Pressure Rating: Body Test Pressure: 21 kg/sq. cm. G 300 Psig Hyd.
Available Sizes: 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14", 16"
Connections: Flanges As Per Table-E
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy-duty T-pattern flanged mild steel strainer with SS mesh and Table-E drilling for large pipeline protection up to 400mm.



Item #51: Cast Iron Swing Check Valve (Sona Make BS 1868)
Category: Cast Iron Swing NRV & Sluice Valves | **Make:** SONA
Design: Flanged Swing Check Valve, Bolted Cover
Pressure Rating: Body: 425 Psig (30 kg/cm²), Seat: 300 Psig (21.5 kg/cm²)
Available Sizes: 2", 2-1/2", 3", 4", 5", 6", 8"
Connections: Flanged Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: BS 1868 flanged cast iron swing check valve with 13% Cr. stainless steel trims, manufactured by Sona.



Item #52: Cast Iron Heavy Duty Reflex Non-Return Valve (Kalbana Make)
Category: Cast Iron Swing NRV & Sluice Valves | **Make:** KALBANA
Design: Flanged Heavy Duty Reflex Non-Return Valve
Pressure Rating: Industrial waterworks working pressure
Available Sizes: 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14"
Connections: Flange End
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy-duty cast iron reflex check valve for municipal waterworks and industrial pumping lines from 50mm to 350mm.



Item #53: Cast Iron Heavy Duty Sluice Gate Valve (Kalbana / Goldway / King)
Category: Cast Iron Swing NRV & Sluice Valves | **Make:** KALBANA / GOLDWAY / KING
Design: Heavy Pattern Sluice Valve, Handwheel Operated
Pressure Rating: Body Test Pressure: 21 kg/sq. cm. G 300 Psig Hyd.
Available Sizes: 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14"
Connections: Flange End (Flanges as per BS Table Drilled / IS Drilling)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy pattern flanged cast iron sluice valve with BS / IS flange drilling proof tested to 21 kg/cm² (300 psig).



Item #54: Cast Iron Diaphragm Valve (Sun Make BS 5156 Ebonite Lined)
Category: Cast Iron Diaphragm & Sluice Valves | **Make:** SUN
Design: Weir Pattern Diaphragm Valve, Ebonite Lined
Pressure Rating: Body: 213 Psig (15 kg/cm²), Seat: 142 Psig (10 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"
Connections: Flanged To BS 10 Table "D", Screwed BSP
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Weir type cast iron diaphragm valve with ebonite rubber lining and BS 5156 compliance, manufactured by Sun.




Item #55: Cast Iron Flanged Globe Valve (Heavy Duty Aarko Make)
Category: Cast Iron Diaphragm & Sluice Valves | **Make:** AARKO
Design: Flanged Globe Pattern Regulating Valve, Heavy Duty
Pressure Rating: Body Test Pressure: 21 kg/sq. cm. G 300 Psig Hyd.
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 3"
Connections: Flange End as per BS Table Drilled / Undrilled
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Heavy-duty flanged cast iron globe valve with BS table drilling and 21 kg/cm² (300 psig) proof rating, made by Aarko.



Item #56: Cast Iron Flanged Gate Valve Class 150# (SS 304 Parts Aarko Make)
Category: Cast Iron Diaphragm & Sluice Valves | **Make:** AARKO
Design: Flanged Class 150# Gate Valve, SS 304 Internals
Pressure Rating: Flanged 150#
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2"
Connections: Flanged 150#
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Class 150 flanged cast iron gate valve with internal SS 304 working parts, manufactured by Aarko.



Item #57: Forged Brass Screwed Ball Valve (Aviko Make)
Category: Brass & Balancing Valves | **Make:** AVIKO
Design: Two-Piece Forged Brass Construction, Screwed Female
Pressure Rating: PN 16 / High utility pressure rating
Available Sizes: 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1.5", 2", 2.5", 3", 4"
Connections: Screwed BSP Female Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: High-density forged brass ball valve with brass ball, brass stem, and PTFE O-ring sealing, made by Aviko.



Item #58: Forged Brass Hydronic Balancing Valve PN 16
Category: Brass & Balancing Valves | **Make:** FLOWSID
Design: Variable Orifice Hydronic Balancing Valve with P/T Nozzles
Pressure Rating: PN - 16 (16 Bar)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2"
Connections: Screwed BSP Female Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Precision hydronic balancing valve in forged brass with digital PVC indicator, test nozzles, and Teflon seat (PN 16).



Item #59: Cast Iron Flanged Hydronic Balancing Valve PN 16
Category: Brass & Balancing Valves | **Make:** FLOWSID
Design: Flanged Y-Pattern Hydronic Balancing Valve, PN 16
Pressure Rating: RATING : PN-16 (16 Bar)
Available Sizes: 5"
Connections: Flanged Ends PN-16
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Large-bore flanged cast iron balancing valve with micrometer handwheel and test ports for heavy HVAC mains.



St
G
O

Item #60: Cast Steel Flanged Globe Valve ND 40 / Class 150# (Connect CE)
Category: Cast Steel Valves | **Make:** Connect (CE)
Design: OS&Y; Bolted Bonnet Globe Valve, DIN 2545 Flanged
Pressure Rating: Body: 854 Psig (60 kg/cm²), Seat: 569 Psig (40 kg/cm²), ND 40 / 150#
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"
Connections: Flanged To DIN 2545 (ND 40 / 150#)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Cast steel WCB globe valve conforming generally to BS 1873 with DIN 2545 flanged ends, made by Connect (CE).



Item #61: Cast Steel Flanged Gate Valve Class 150# (Connect CE API 600)
Category: Cast Steel Valves | **Make:** Connect (CE)
Design: OS&Y; Rising Spindle, Flexible Wedge, Flanged Class 150#
Pressure Rating: Body: 425 Psig (30 kg/cm²), Seat: 300 Psig (21 kg/cm²), ASA 150#
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12", 14", 16"
Connections: Flanged To ANSI B 16.5 RF - 150 #
Documented Applications: Water, Steam, Gas, Oil, Air
Description: API 600 compliant cast steel WCB gate valve with ANSI B 16.5 RF Class 150 flanges, made by Connect (CE).



Item #62: Cast Steel Three-Piece Flanged Ball Valve (Class 150# Flowsid)
Category: Cast Steel Valves | **Make:** FLOWSID
Design: Three Piece Design, Straight Pattern, Class 150# Flanged
Pressure Rating: Body Test Pressure: 32 Barg 500 Psig Hyd., Flanges 150#
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"
Connections: Flanges As Per IS 3516-1966 150 # / 300 #
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Three-piece straight pattern cast steel ball valve with AISI 304 ball, Teflon seat, and Class 150# flanges.



Item #63: Forged Carbon Steel Screwed Ball Valve Class 800# (Connect CE)
Category: Cast Steel Valves | **Make:** Connect (CE)
Design: Forged Steel Compact Ball Valve, Class 800# Pattern
Pressure Rating: Class 800# (Hyd. Test Body: 213 Psig / 15 kg; Seat: 142 Psig / 10 kg)
Available Sizes: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2"
Connections: Screwed BSP, Flanged to BS 10 Table "D"
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Class 800# forged steel ball valve with AISI 304 ball and GFT (Glass Filled Teflon) seating, made by Connect (CE).



Item #64: Cast Steel Swing Check Valve Class 150# (Connect / Flowsid)
Category: Cast Steel Valves | **Make:** CONNECT / FLOWSID
Design: Bolted Cover Swing Check Valve, Full Flow Passage
Pressure Rating: Body: 425 Psig (30 kg/cm²), Seat: 300 Psig (21 kg/cm²), ASA 150#
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"
Connections: Flanged To ANSI B 16.5 RF 150 #
Documented Applications: Water, Steam, Gas, Oil, Air
Description: BS 1868 / API 6D cast steel swing non-return valve with ANSI B 16.5 RF Class 150 flanges and 13% Cr trims.



Item #65: Cast Steel Flanged Y-Type Strainer Class 150# (Flowsid ASME B 16.34)
Category: Cast Steel Valves | **Make:** FLOWSID
Design: Flanged Y-Type Strainer, ASME B 16.34 Standard
Pressure Rating: Hyd. Test Pressure: 425 Psig (30 kg/cm²), ASA -150 #
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8"
Connections: Flanged To ANSI B 16.5 RF 150 #
Documented Applications: Water, Steam, Gas, Oil, Air
Description: ASME B 16.34 flanged Class 150 cast steel Y-strainer with SS 304 screen for high-pressure pipeline protection.



Item #66: Thermodynamic Steam Trap Td3 (CA-15 / 410 Stainless Steel)
Category: Steam Traps | **Make:** CONNECT
Design: Thermodynamic Disc Type Steam Trap Td3
Pressure Rating: Hyd. Test Body: 450 Psig (32 kg/cm²)
Available Sizes: 1/2", 3/4", 1"
Connections: Screwed BSP (Female)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: High-pressure thermodynamic steam trap Td3 in investment cast 410 (CA-15) steel rated up to 425°C.



Item #67: Inverted Bucket Steam Trap (Horizontal Line Connect Make)
Category: Steam Traps | **Make:** CONNECT
Design: Inverted Bucket Steam Trap for Horizontal Mounting
Pressure Rating: Hyd. Test Body: 150 Psig (10.54 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1.5", 2"
Connections: Screwed BSP (Female)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Inverted bucket steam trap for horizontal pipelines with Gun Metal & SS trims, rated for 220°C.



Item #68: Ball Float Steam Trap (Horizontal Line Connect Make)
Category: Steam Traps | **Make:** CONNECT
Design: Ball Float Steam Trap for Horizontal Line Installation
Pressure Rating: Hyd. Test Body: 150 Psig (10.54 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1.5", 2"
Connections: Screwed BSP (Female)
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Continuous-discharge ball float steam trap for horizontal installation with thermostatic air venting (220°C).



Item #69: Forged Carbon Steel Globe Valve Class 800# (ASTM A 105 Connect)
Category: Forged Steel 800# Valves | **Make:** CONNECT
Design: OS&Y; Bolted Bonnet Forged Globe Valve, Class 800#
Pressure Rating: A-105 ASA-800# (Body: 3000 Psig / 211 kg; Seat: 2000 Psig / 140 kg)
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2"
Connections: Screwed To BSP/BSPT/NPT (Female), Socketweld To ANSI B 16.11
Documented Applications: Water, Steam, Gas, Oil, Air
Description: High-pressure Class 800# ASTM A 105 forged steel globe valve built to API 602 / BS 5352 standards.



Item #70: Forged Carbon Steel Gate Valve Class 800# (ASTM A 105 Connect)
Category: Forged Steel 800# Valves | **Make:** CONNECT
Design: OS&Y; Rising Stem Bolted Bonnet Gate Valve, Class 800#
Pressure Rating: A-105 ASA-800# (Body: 3000 Psig / 211 kg; Seat: 2000 Psig / 140 kg)
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2"
Connections: Screwed To BSP/BSPT/NPT (Female), Socketweld To ANSI B 16.11
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Class 800# forged carbon steel gate valve with solid wedge and 13% Cr trims, manufactured to API 602.



Item #71: Forged Carbon Steel Lift Check Valve Class 800# (Connect API 602)
Category: Forged Steel 800# Valves | **Make:** CONNECT
Design: Bolted Cap Piston Lift Check Valve, Class 800#
Pressure Rating: A-105 ASA-800# (Body: 3000 Psig / 211 kg; Seat: 2000 Psig / 140 kg)
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2"
Connections: Screwed To BSP/BSPT/NPT (Female), Socketweld To ANSI B 16.11
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Class 800# forged carbon steel non-return lift check valve with bolted cover and 13% Cr trims to API 602.



Item #72: Polypropylene (PP) 3-Piece Ball Valve (Shree Ram / CPI)
Category: Polypropylene (PP) Valves | **Make:** Shree Ram, CPI
Design: Three Piece Bolted Body Polypropylene Ball Valve
Pressure Rating: Chemical piping rated (10 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8", 10", 12"
Connections: Screwed End BSP, Flanged End
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Chemical-resistant virgin polypropylene 3-piece ball valve with 13% Cr trims in screwed and flanged ends.



Item #73: Polypropylene (PP) Foot Valve (CPI Make)
Category: Polypropylene (PP) Valves | **Make:** CPI
Design: Polypropylene Suction Foot Valve with Integrated Strainer
Pressure Rating: Chemical suction working pressure
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 6", 8", 10", 12"
Connections: Screwed End, Flanged End
Documented Applications: Water, Steam, Gas, Oil, Air
Description: All-plastic polypropylene foot valve with integrated strainer for corrosive acid/alkali suction lines up to 300mm.



Item #74: Polypropylene (PP) Non-Return Check Valve (CPI Make)
Category: Polypropylene (PP) Valves | **Make:** CPI
Design: Polypropylene In-Line Non-Return Check Valve
Pressure Rating: Chemical process line pressure rating
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 6", 8", 10", 12"
Connections: Screwed End, Flanged End
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Corrosion-proof polypropylene non-return check valve in screwed and flanged connections for acid/alkali pipelines.



Item #75: Polypropylene (PP) Diaphragm Valve (CPI Make)
Category: Polypropylene (PP) Valves | **Make:** CPI
Design: Weir Pattern Polypropylene Diaphragm Valve
Pressure Rating: Chemical process line pressure (up to 10 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2", 2-1/2", 3", 4", 6"
Connections: Screwed End, Flanged End
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Polypropylene weir-type diaphragm valve for highly aggressive chemical acids and slurries, made by CPI.



Item #76: Polypropylene (PP) Y-Type Strainer (CPI Make)
Category: Polypropylene (PP) Valves | **Make:** CPI
Design: Y-Pattern Chemical Strainer, Bolted / Threaded Cover
Pressure Rating: Chemical piping rating (up to 10 kg/cm²)
Available Sizes: 1/2", 3/4", 1", 1-1/2", 2", 2-1/2", 3", 4", 6"
Connections: Screwed End, Flanged End
Documented Applications: Water, Steam, Gas, Oil, Air
Description: All-polypropylene Y-strainer with removable PP filter basket for chemical particulate removal, made by CPI.



Item #77: Polypropylene (PP) Wafer Butterfly Valve (CPI Make)
Category: Polypropylene (PP) Valves | **Make:** CPI
Design: Wafer Type Polypropylene Butterfly Valve, Lever / Gear Operated
Pressure Rating: Chemical process line pressure rating
Available Sizes: 2", 2-1/2", 3", 4", 6", 8", 10", 12", 16"
Connections: Wafer Flange Fitment
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Lightweight polypropylene wafer butterfly valve with lever or gear operator for chemical flow regulation up to 400mm.



Item #78: Polypropylene (PP) In-Line Sight Glass (CPI / Shree Ram)
Category: Polypropylene (PP) Valves | **Make:** CPI / Shree Ram
Design: Full-View Tubular In-Line Sight Flow Indicator
Pressure Rating: Chemical piping pressure rating
Available Sizes: 1", 1-1/2", 2", 2-1/2", 3", 4", 6", 8", 10", 12"
Connections: Flanged Ends
Documented Applications: Water, Steam, Gas, Oil, Air
Description: Chemical-resistant polypropylene tubular sight glass with transparent viewing cylinder for corrosive fluid lines.