

Indian Institute of Technology, Kharagpur

# Optimal Control of Seeded Batch Crystallizer

by

Author Name

A thesis submitted in partial fulfillment for the  
degree of Doctor of Philosophy

in the

Faculty Name

Department of Chemical Engineering

April 2018

# Declaration of Authorship

I, AUTHOR NAME, declare that this thesis titled, 'THESIS TITLE' and the work presented in it are my own. I confirm that:

- This work was done wholly or mainly while in candidature for a research degree at this University.
- Where any part of this thesis has previously been submitted for a degree or any other qualification at this University or any other institution, this has been clearly stated.
- Where I have consulted the published work of others, this is always clearly attributed.
- Where I have quoted from the work of others, the source is always given. With the exception of such quotations, this thesis is entirely my own work.
- I have acknowledged all main sources of help.
- Where the thesis is based on work done by myself jointly with others, I have made clear exactly what was done by others and what I have contributed myself.

Signed:

---

Date:

---

*“Write a funny quote here.”*

If the quote is taken from someone, their name goes here

Indian Institute of Technology,Kharagpur *Abstract*

Faculty Name

Department of Chemical Engineering

Doctor of Philosophy

by Author Name

The Thesis Abstract is written here (and usually kept to just this page). The page is kept centered vertically so can expand into the blank space above the title too...

# *Acknowledgements*

The acknowledgements and the people to thank go here, don't forget to include your project advisor...

# Contents

<b>Declaration of Authorship</b>	<b>i</b>
<b>Abstract</b>	<b>iii</b>
<b>Acknowledgements</b>	<b>iv</b>
<b>List of Figures</b>	<b>vii</b>
<b>List of Tables</b>	<b>viii</b>
<b>Abbreviations</b>	<b>ix</b>
<b>Physical Constants</b>	<b>x</b>
<b>Symbols</b>	<b>xi</b>
<b>1 Introduction</b>	<b>1</b>
Deterministic Optimal Control . . . . .	1
Stochastic Optimal Control . . . . .	2
1.1 Previous Work . . . . .	2
<b>2 Theory</b>	<b>3</b>
. . . . .	3
2.1 Nucleation . . . . .	4
2.2 Crystal Growth . . . . .	4
<b>3 Modelling a Seeded Batch Crystallizer</b>	<b>6</b>
3.1 Population Balance Equation . . . . .	6
3.2 Model Equations . . . . .	7
3.3 Solution Methodology . . . . .	8
<b>4 Optimal Control Problems</b>	<b>9</b>
<b>A An Appendix</b>	<b>10</b>

**Bibliography**

**12**

# List of Figures



# List of Tables

# Abbreviations

**LAH** List Abbreviations **Here**

# Physical Constants

Speed of Light  $c = 2.997\,924\,58 \times 10^8 \text{ ms}^{-\text{s}}$  (exact)

# Symbols

$a$	distance	m
$P$	power	W ( $\text{Js}^{-1}$ )
$\omega$	angular frequency	$\text{rads}^{-1}$

*For/Dedicated to/To my...*

# Chapter 1

## Introduction

Batch crystallization is widely used in chemical, pharmaceutical, photographic, and other manufacturing processes for the preparation of crystalline products with several desirable attributes.

The batch system helps to obtain a narrower Particle size distribution (PSD) with high crystal purity. The crystallization process has an influence on the downstream processing and, hence, reproducible PSD in each operation is of prime importance. Thus, it is essential to find the variables affecting the process and control them within an acceptable range, so as to satisfy the final product quality requirements. Considering the operation of crystallizers, a batch process is preferable as a larger mean crystal size and narrower Crystal size distribution (CSD) can be achieved. In general, the CSD which is typically characterized by the mean and variance of crystal size is a key property to control this process because it directly affects final product qualities. Therefore, finding effective control strategy to obtain the crystals with a desired CSD is significant in order for improving the performance of batch crystallization processes and at the same time reducing difficulties in downstream processing. In the following work we formulate the problem using the population balance equations and obtain the solution for the optimal Temperature profile using Deterministic and Probabilistic methods

**Deterministic Optimal Control** Quisque tristique urna in lorem laoreet at laoreet quam congue. Donec dolor turpis, blandit non imperdiet aliquet, blandit et felis. In lorem nisi, pretium sit amet vestibulum sed, tempus et sem. Proin non ante turpis. Nulla imperdiet fringilla convallis. Vivamus vel bibendum nisl. Pellentesque justo lectus, molestie vel luctus sed, lobortis in libero. Nulla facilisi. Aliquam erat volutpat. Suspendisse vitae nunc nunc. Sed aliquet est suscipit sapien rhoncus non adipiscing nibh consequat. Aliquam metus urna, faucibus eu vulputate non, luctus eu justo.

**Stochastic Optimal Control** Donec urna leo, vulputate vitae porta eu, vehicula blandit libero. Phasellus eget massa et leo condimentum mollis. Nullam molestie, justo at pellentesque vulputate, sapien velit ornare diam, nec gravida lacus augue non diam. Integer mattis lacus id libero ultrices sit amet mollis neque molestie. Integer ut leo eget mi volutpat congue. Vivamus sodales, turpis id venenatis placerat, tellus purus adipiscing magna, eu aliquam nibh dolor id nibh. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Sed cursus convallis quam nec vehicula. Sed vulputate neque eget odio fringilla ac sodales urna feugiat. **Ito Process and Polynomial Chaos Expansions**

## 1.1 Previous Work

The concept of programmed cooling in batch crystallizers was first discussed by Mullin and Nyvlt [1] in 1971. They studied the laboratory-scale crystallization of potassium sulfate and ammonium sulfate using a temperature controller and observed improvement in the crystal size and quality under programmed cooling.

Later, in 1974, A. G. Jones [2] presented a mathematical theory based on moment transformations of population balance equations. He used the continuous maximum principle to predict optimal cooling curves. Rawlings et al. [3] discussed issues in crystal size measurement using laser light scattering experiments and optimal control problem formulation. In 1994, Miller and Rawlings [4] discussed the uncertain bounds on model parameter estimates for a batch crystallization system.

Most importantly optimal temperature prediction for batch crystallization has also been done by Hu et al.[5], Shi et al.[6], Paengjuntuek et al.[7], and Corriou and Rohani.[?] ], the data and knowledge from which have been used in further work in this project . Grosso et al.[?] ] presented a stochastic approach for modeling PSD and comparative assessments of different models. Ma et al.[?] ] presented a worse-case performance analysis of optimal control trajectories by considering features such as the computational effort, parametric uncertainty and control implementation inaccuracies.

The focus of the current work is to be able to handle parametric uncertainties in mathematical formulations of batch crystallization process.

## Chapter 2

# Theory

Crystallization is the (natural or artificial) process where a solid forms where the atoms or molecules are highly organized in a structure known as a crystal. Some of the ways which crystals form are through precipitating from a solution, melt or more rarely deposited directly from a gas.

Crystal shapes can include cubic, tetragonal, orthorhombic, hexagonal, monoclinic, triclinic, and trigonal. In order for crystallization to take place a solution must be "supersaturated". Supersaturation refers to a state in which the liquid (solvent) contains more dissolved solids (solute) than can ordinarily be accommodated at that temperature.

Supersaturation, can be mathematically defined as :

$$\text{Supersaturation} = \Delta C = C - C_s$$

$$\text{Relative Supersaturation} = \Delta C / C_s$$

$C_s$  : Concentration of solute in saturated solution

$C$  : Concentration of solute in the solution

$S$  : Supersaturation ratio

The crystallization process consists of two major type of kinetics, *nucleation* and *crystal growth* which are driven by thermodynamic properties as well as chemical properties.

- **Nucleation** is the step where the solute molecules or atoms dispersed in the solvent start to gather into clusters, on the microscopic scale (elevating solute concentration in a small region). These stable clusters constitute the nuclei.



nucleation.png

- **Crystal growth** is the subsequent size increase of the nuclei that succeed in achieving the critical cluster size. it is a dynamic process occurring in equilibrium where solute molecules or atoms precipitate out of solution, and dissolve back into solution.

Supersaturation is one of the driving forces of crystallization, as the solubility of a species is an equilibrium process quantified by  $K_{sp}$ . Depending upon the conditions, either nucleation or growth may be predominant over the other, dictating crystal size.

Two other phenomena which are rare and are often neglected in the crystallization modelling process are **Agglomeration** and **Breakage**.

Agglomeration occurs when two particles collide and stick together to form a larger particle. Breakage occurs in stirred vessels; the larger particle breaks into smaller fragments, because of attrition .

## 2.1 Nucleation

The initial process that occurs in the formation of a crystal from a solution, a liquid, or a vapour, in which a small number of ions, atoms, or molecules become arranged in a pattern characteristic of a crystalline solid, forming a site upon which additional particles are deposited as the crystal grows.

Nucleation requires supersaturation, which is obtained usually by a change in temperature (cooling in case of a positive gradient of the solubility curve and heating in case of a negative gradient), by removing the solvent, or by adding a drowning out agent or reaction partners. If the solution contains neither solid foreign particles or crystals of its own type, nuclei are formed only through homogeneous nucleation. If foreign particles are present then nuclei are formed through heterogeneous nucleation.

Both homogeneous nucleation and heterogeneous nucleation are classified as primary nucleation.

## 2.2 Crystal Growth

Crystal growth occurs as soon as nuclei with radius larger than the critical radius have been formed. There are many proposed mechanisms for crystal growth.

Diffusion theories assume that matter is deposited continuously on the crystal face at a rate proportional to the difference in concentration between the point of deposition and

the bulk of the solution.

When dealing with crystal growth in an ionizing solute, the following steps can be distinguished :

- Bulk diffusion of solvated ions through the diffusion boundary layer
- Bulk diffusion of solvated ions through adsorption layer
- Surface diffusion of solvated or unsolvated ions
- Partial or total desolvation of ions
- Integration of ions into the lattice
- Counterdiffusion through adsorption layer of water released
- Counterdiffusion of water through the boundary layer

*The slowest of these steps are rate determining.*

A crystal surface grow in such a way that units in a supersaturated solution are first transported by diffusion and convection and then built into the surface of the crystal by integration or an integration reaction , with the supersaturation,  $\Delta C$ , being the driving force.

Thus, determination of the optimal temperature or supersaturation trajectory for a seeded batch crystallizer is the most well-studied problem in chemical engineering, apart from batch reactors and batch distillation as the evolution of supersaturation in time affects almost all the kinetic phenomena occurring in the crystallization process. For example, growth can be size-independent or size-dependent; it can have a constant value or it may be a function of a thermodynamic parameter such as solubility and thus selection of appropriate kinetics is essential for accurate modelling .

## Chapter 3

# Modelling a Seeded Batch Crystallizer

### 3.1 Population Balance Equation

Analysis of a particulate system seeks to synthesize the behavior of the population of particles and its environment from the behavior of single particles in their local environments. The population is described by the density of a suitable extensive variable, usually the **number of particles**, but sometimes by other variables such as the mass or volume of particles. The usual transport equations expressing conservation laws for material systems apply to the behavior of single particles. Particulate processes are characterized by properties such as particle shape, size, surface area, mass, and product purity.

A population balance formulation describes the process of crystal size distribution with time most effectively. Thus, modeling of a batch crystallizer involves the use of population balances to model the crystal size prediction and the mass balance on the system can be modeled as a simple differential equation having concentration as the state variable. The population balance can be expressed as eq :

$$\frac{\partial n(r, t)}{\partial t} + \frac{\partial G(r, t)n(r, t)}{\partial r} = B$$

(3.1)

where  $\mathbf{n}$  is the number density distribution,  $\mathbf{t}$  is the time,  $\mathbf{r}$  represents the characteristic dimension for size measurements,  $\mathbf{G}$  is the crystal growth rate, and  $\mathbf{B}$  is the nucleation rate. Both growth and nucleation processes describe crystallization kinetics, and their expression may vary, depending on the system under consideration.

### 3.2 Model Equations

In this work, the system under consideration is potassium sulfate, which has been studied earlier by Hu et al. [5], Shi et al. [6], and Paengjuntuek et al.[7].

Nucleation kinetics<sup>(5-7)</sup> are defined by :

$$B(t) = k_b \exp(-E_b/RT) \left( \frac{C - C_s(T)}{C_s(T)} \right)^b \mu_3 \quad (3.2)$$

Growth Kinetics<sup>(5-7)</sup> are given by:

$$G(t) = k_g \exp(-E_g/RT) \left( \frac{C - C_s(T)}{C_s(T)} \right)^g \quad (3.3)$$

where  $k_b$  and  $k_g$  are constants of the system,  $E_b$  and  $E_g$  are activation energies, and  $b$  and  $g$  are exponents of nucleation and growth, respectively.  $C_s(T)$  is the saturation concentration at a given temperature. The following equations are used to evaluate the saturation and metastable concentrations corresponding to the solution temperature  $T$  (expressed in units of °C)[6].

$$C_s(T) = 6.29 \times 10^{-2} + 2.46 \times 10^{-3}T - 7.14 \times 10^{-6}T^2 \quad (3.4)$$

$$C_m(T) = 7.76 \times 10^{-2} + 2.46 \times 10^{-3}T - 8.1 \times 10^{-6}T^2 \quad (3.5)$$

The mass balance, in terms of concentration of the solute in the solution, is expressed as :

$$\frac{dC}{dt} = -3\rho k_v G(t) \mu_2(t) \quad (3.6)$$

where  $\rho$  is the density of the crystals,  $k_v$  the volumetric shape factor, and  $\mu_2$  is the second moment of particle size distribution (PSD).

Since  $n(r, t)$  represents the population density of the crystals[? ], the  $i$ th moment of the particle size distribution(PSD) is given by :

$$\mu_i = \int_0^\infty r^i n(r, t) dr \quad (3.7)$$

The above equations along with the Population Balance Equation represent a complete model of a seeded batch crystallizer . Since population balance equations are multidimensional, their implementation in control functions is tedious; hence, much research has been focused on the model order reduction methods.

For simplifying the solution method, we reduce the population balance equations into moment balance equations. It is also advantageous, since it is difficult and time-consuming to formulate an optimization problem involving PBEs. Thus, the moment model leads to a reduced-order model involving the process dynamics in batch crystallization.

### 3.3 Solution Methodology

Separate moment equations are used for the seed and nuclei classes of crystals, and they are defined as :

$$\mu_i^n = \int_0^{r_g} r^i n(r, t) dr \quad (3.8)$$

$$\mu_i^s = \int_{r_g}^\infty r^i n(r, t) dr \quad (3.9)$$

n : nucleation , s: seed ,  $r_g$  : critical radius separating the two

Since, we ignore the agglomeration and breakage phenomena, the number of seeds added to the process ( $\mu_0^s$ ) remain constant.

The differential equations for nucleated and seeded crystals are as follows :

1. Nucleated crystals<sup>5,7</sup>

$$\frac{du_0^n}{dt} = B(t) \quad (3.10)$$

$$\frac{du_i^n}{dt} = iG(t)u_{i-1}^n(t) \quad i = 1, 2, 3 \quad (3.11)$$

2. Seeded crystals<sup>5,7</sup>

$$\frac{du_i^s}{dt} = iG(t)u_{i-1}^n(t) \quad i = 1, 2, 3 \quad (3.12)$$

The total moment is obtained as the summation  $\mu_i^t = \mu_i^n + \mu_i^s$

## Chapter 4

# Optimal Control Problems

### 4.1 Deterministic Optimal Control

**Aim** To find an optimal temperature trajectory, which minimizes the total volume of fine crystals, represented by the third moment of nucleated crystals ( $3n$ ) and maximizes the size of seeded crystals represented by the third moment of seeded crystals ( $3s$ ) in order to satisfy the product quality requirements..

## Appendix A

# An Appendix

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Vivamus at pulvinar nisi. Phasellus hendrerit, diam placerat interdum iaculis, mauris justo cursus risus, in viverra purus eros at ligula. Ut metus justo, consequat a tristique posuere, laoreet nec nibh. Etiam et scelerisque mauris. Phasellus vel massa magna. Ut non neque id tortor pharetra bibendum vitae sit amet nisi. Duis nec quam quam, sed euismod justo. Pellentesque eu tellus vitae ante tempus malesuada. Nunc accumsan, quam in congue consequat, lectus lectus dapibus erat, id aliquet urna neque at massa. Nulla facilisi. Morbi ullamcorper eleifend posuere. Donec libero leo, faucibus nec bibendum at, mattis et urna. Proin consectetur, nunc ut imperdiet lobortis, magna neque tincidunt lectus, id iaculis nisi justo id nibh. Pellentesque vel sem in erat vulputate faucibus molestie ut lorem.

Quisque tristique urna in lorem laoreet at laoreet quam congue. Donec dolor turpis, blandit non imperdiet aliquet, blandit et felis. In lorem nisi, pretium sit amet vestibulum sed, tempus et sem. Proin non ante turpis. Nulla imperdiet fringilla convallis. Vivamus vel bibendum nisl. Pellentesque justo lectus, molestie vel luctus sed, lobortis in libero. Nulla facilisi. Aliquam erat volutpat. Suspendisse vitae nunc nunc. Sed aliquet est suscipit sapien rhoncus non adipiscing nibh consequat. Aliquam metus urna, faucibus eu vulputate non, luctus eu justo.

Donec urna leo, vulputate vitae porta eu, vehicula blandit libero. Phasellus eget massa et leo condimentum mollis. Nullam molestie, justo at pellentesque vulputate, sapien velit ornare diam, nec gravida lacus augue non diam. Integer mattis lacus id libero ultrices sit amet mollis neque molestie. Integer ut leo eget mi volutpat congue. Vivamus sodales, turpis id venenatis placerat, tellus purus adipiscing magna, eu aliquam nibh dolor id nibh. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Sed cursus convallis quam nec vehicula. Sed vulputate neque eget odio fringilla ac sodales urna feugiat.

Phasellus nisi quam, volutpat non ullamcorper eget, congue fringilla leo. Cras et erat et nibh placerat commodo id ornare est. Nulla facilisi. Aenean pulvinar scelerisque eros eget interdum. Nunc pulvinar magna ut felis varius in hendrerit dolor accumsan. Nunc pellentesque magna quis magna bibendum non laoreet erat tincidunt. Nulla facilisi.

Duis eget massa sem, gravida interdum ipsum. Nulla nunc nisl, hendrerit sit amet commodo vel, varius id tellus. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nunc ac dolor est. Suspendisse ultrices tincidunt metus eget accumsan. Nullam facilisis, justo vitae convallis sollicitudin, eros augue malesuada metus, nec sagittis diam nibh ut sapien. Duis blandit lectus vitae lorem aliquam nec euismod nisi volutpat. Vestibulum ornare dictum tortor, at faucibus justo tempor non. Nulla facilisi. Cras non massa nunc, eget euismod purus. Nunc metus ipsum, euismod a consectetur vel, hendrerit nec nunc.



# Bibliography

- [1] Mulin, J. W.; Nyvlt, J. Programmed cooling of batch crystallizers. *Chem. Eng. Sci.* **1971**, *26*, 369377.
  - [2] Jones, A. G. Optimal operation of a batch cooling crystallizer. *Chem. Eng. Sci.* **1974**, *29*, 10751087.
  - [3] Rawlings, J. B.; Witkowski, W. R.; Eaton, J. W. Modeling and control of crystallizers. *Powder Technol.* **1992**, *69*, 39.
  - [4] Miller, S. M.; Rawlings, J. B. Model identification and control strategies for batch cooling crystallizers. *AIChE J.* **1994**, *40*, 1312 1327.
  - [5] Hu, Q.; Rohani, S.; Jutan, A. Modelling and optimization of seeded batch crystallizers. *Comput. Chem. Eng.* **2005**, *29*, 911918.
  - [6] Shi, D.; El-Farra, N.; Li, M.; Mhaskar, P.; Christofides, P. D. Predictive control of particle size distribution in particulate processes. *Chem. Eng. Sci.* **2006**, *61*, 26828.
  - [7] Paengjuntuek, W.; Arpornwichanop, A.; Kittisupakorn, P. Product quality improvement of batch crystallizers by a batch to batch optimization and non-linear control approach. *Chem. Eng. J.* **2008**, *139*, 344350.
-