

Set up a Logic App to send email notifications after the **pipeline** completes, with success or failure status based on **pipeline** execution. This includes connecting ADF to Logic Apps and configuring alerts.

This screenshot shows the Microsoft Azure portal interface for configuring a Logic App named 'notificationpipeline'. The left sidebar displays the 'Factory Resources' tree with 'Pipelines' expanded, showing 'notificationpipeline' with 1 instance. The main canvas shows the Logic App workflow with two 'Web' activities: 'Success email' and 'Failed email'. The 'Settings' tab is active, showing the following configuration:

- URL:** `https://prod-05.centralindia.logic.azure.c...` (Warning: Information will be sent to the URL specified. Please ensure you trust the URL entered.)
- Method:** POST
- Body:** `@json(concat('f, ', 'pipelineName:', '....'))`
- Authentication:** None
- Headers:** A table with columns 'Name' and 'Value'. The 'Content-Type' header is set to 'application/json'.

The 'Properties' panel on the right shows the 'General' tab with the Name 'notificationpipeline' and a Description field.

This screenshot is identical to the one above, showing the Microsoft Azure portal interface for configuring a Logic App named 'notificationpipeline'. The left sidebar displays the 'Factory Resources' tree with 'Pipelines' expanded, showing 'notificationpipeline' with 1 instance. The main canvas shows the Logic App workflow with two 'Web' activities: 'Success email' and 'Failed email'. The 'Settings' tab is active, showing the following configuration:

- URL:** `https://prod-05.centralindia.logic.azure.c...` (Warning: Information will be sent to the URL specified. Please ensure you trust the URL entered.)
- Method:** POST
- Body:** `@json(concat('f, ', 'pipelineName:', '....'))`
- Authentication:** None
- Headers:** A table with columns 'Name' and 'Value'. The 'Content-Type' header is set to 'application/json'.

The 'Properties' panel on the right shows the 'General' tab with the Name 'notificationpipeline' and a Description field.

Microsoft Azure

Search resources, services, and docs (G+/)

Copilot

kolteushar@outlook.com
DEFAULT DIRECTORY (OLULIUS)

Home > Microsoft.Web-LogicAppConsumption-Portal-79865153-b980 | Overview > sendnoti

sendnoti | Logic app designer

Search

Overview
Activity log
Access control (IAM)
Tags
Diagnose and solve problems
Resource visualizer
Development Tools
Logic app designer
Logic app code view
Logic app templates
Run history
Chat (Preview)
Versions
API connections
Quick start guides
Settings
Monitoring
Automation
Help

When an HTTP request is received

Send email (V2)

Add or remove favorites by pressing Ctrl+Shift+F

Microsoft Azure

Search resources, services, and docs (G+/)

Copilot

kolteushar@outlook.com
DEFAULT DIRECTORY (OLULIUS)

Home > Microsoft.Web-LogicAppConsumption-Portal-79865153-b980 | Overview > sendnoti

sendnoti | Logic app designer

Search

Overview
Activity log
Access control (IAM)
Tags
Diagnose and solve problems
Resource visualizer
Development Tools
Logic app designer
Logic app code view
Logic app templates
Run history
Chat (Preview)
Versions
API connections
Quick start guides
Settings
Monitoring
Automation
Help

When an HTTP request is received

Send email (V2)

When an HTTP request is received

Changing the trigger name updates the callback URL when you save the workflow.

Add a description

Parameters Settings Code view About

HTTP URL

https://prod-05.centralindia.logic.azure.com/443/workflows/3fa1682b3ce741f0b9a45be3ae7c19a3/tri...

Method

Default (Allow All Methods)

Request Body JSON Schema

```
{
  "pipelineName": "TestPipeline",
  "status": "Succeeded",
  "runId": "123"
}
```

Use sample payload to generate schema

Advanced parameters

Showing 0 of 1

Show all Clear all

The screenshot displays the Microsoft Azure Logic App Designer. The central workspace shows a workflow diagram with two steps: 'When an HTTP request is received' and 'Send email (V2)'. The right-hand pane is focused on the 'Send email (V2)' action. Under the 'Parameters' tab, the 'To' field is populated with 'koltetush@gmail.com'. The 'Subject' field is set to 'ADF Pipeline triggerBody()'. The 'Body' field is expanded, revealing a JSON structure where 'Pipeline Name', 'Run ID', 'Status', and 'Time' are all mapped to 'triggerBody()' expressions. The 'Time' field specifically uses 'utcNow()'.

Expression:

```
@json(concat(
'{' ,
'"pipelineName":', pipeline().Pipeline, '",',
'"status":"Failed",',
'"runId":', pipeline().RunId, '",',
'}'
))
```

11:44

LTE 62



ADF Pipeline
notificationpipeline -
Succeeded Inbox



contact 11:38 AM
to me ^

Unsubscribe



From contact@tusharkolte.com

To koltetush@gmail.com

Date 22 Apr 2026 at 11:38 AM



Standard encryption (TLS)

[Learn more](#)

Pipeline Name: notificationpipeline
Run ID: 7411c898-e9f5-4eb0-b4bb-5b8cdc1a9946
Status: Succeeded
Time: 2026-04-22T06:08:32.4347302Z

↩ Reply

➦ Forward

