

Outline

- Data Models and Their Categories
- History of Data Models
- Schemas, Instances, and States
- Three-Schema Architecture
- Data Independence
- DBMS Languages and Interfaces
- Database System Utilities and Tools
- Centralized and Client-Server Architectures
- Classification of DBMSs

Data Models

- **Data Model:**

- A set of concepts to describe the *structure* of a database, the *operations* for manipulating these structures, and certain *constraints* that the database should obey.

- **Data Model Structure and Constraints:**

- Constructs are used to define the database structure
- Constructs typically include *elements* (and their *data types*) as well as groups of elements (e.g. *entity*, *record*, *table*), and *relationships* among such groups
- Constraints specify some restrictions on valid data; these constraints must be enforced at all times

Data Models (continued)

● Data Model Operations:

- These operations are used for specifying database *retrievals* and *updates* by referring to the constructs of the data model.
- Operations on the data model may include ***basic model operations*** (e.g. generic insert, delete, update) and ***user-defined operations*** (e.g. compute_student_gpa, update_inventory)

Categories of Data Models

- **Conceptual (high-level, semantic) data models:**
 - Provide concepts that are close to the way many users perceive data.
 - (Also called *entity-based* or *object-based* data models.)
- **Physical (low-level, internal) data models:**
 - Provide concepts that describe details of how data is stored in the computer. These are usually specified in an ad-hoc manner through DBMS design and administration manuals
- **Implementation (representational) data models:**
 - Provide concepts that fall between the above two, used by many commercial DBMS implementations (e.g. relational data models used in many commercial systems).

Schemas versus Instances

- Database Schema:
 - The *description* of a database.
 - Includes descriptions of the database structure, data types, and the constraints on the database.
- Schema Diagram:
 - An *illustrative* display of (most aspects of) a database schema.
- Schema Construct:
 - A *component* of the schema or an object within the schema, e.g., STUDENT, COURSE.

Schemas versus Instances

- Database State:

- The actual data stored in a database at a *particular moment in time*. This includes the collection of all the data in the database.
- Also called database instance (or occurrence or snapshot).
 - The term *instance* is also applied to individual database components, e.g. *record instance*, *table instance*, *entity instance*

Database Schema vs. Database State

- Database State:
 - Refers to the *content* of a database at a moment in time.
- Initial Database State:
 - Refers to the database state when it is initially loaded into the system.
- Valid State:
 - A state that satisfies the structure and constraints of the database.

Database Schema vs. Database State (continued)

- Distinction
 - The *database schema* changes very infrequently.
 - The *database state* changes every time the database is updated.
- **Schema** is also called **intension**.
- **State** is also called **extension**.

Example of a Database Schema

Example of a database state

Three-Schema Architecture

- Proposed to support DBMS characteristics of:
 - **Program-data independence.**
 - Support of **multiple views** of the data.
- Not explicitly used in commercial DBMS products, but has been useful in explaining database system organization

Three-Schema Architecture

- Defines DBMS schemas at *three* levels:
 - **Internal schema** at the internal level to describe physical storage structures and access paths (e.g indexes).
 - Typically uses a **physical** data model.
 - **Conceptual schema** at the conceptual level to describe the structure and constraints for the whole database for a community of users.
 - Uses a **conceptual** or an **implementation** data model.
 - **External schemas** at the external level to describe the various user views.
 - Usually uses the same data model as the conceptual schema.



The three-schema architecture

Three-Schema Architecture

- Mappings among schema levels are needed to transform requests and data.
 - Programs refer to an external schema, and are mapped by the DBMS to the internal schema for execution.
 - Data extracted from the internal DBMS level is reformatted to match the user's external view (e.g. formatting the results of an SQL query for display in a Web page)

Data Independence

- **Logical Data Independence:**

- The capacity to change the conceptual schema without having to change the external schemas and their associated application programs.

- **Physical Data Independence:**

- The capacity to change the internal schema without having to change the conceptual schema.
- For example, the internal schema may be changed when certain file structures are reorganized or new indexes are created to improve database performance

Data Independence (continued)

- When a schema at a lower level is changed, only the **mappings** between this schema and higher-level schemas need to be changed in a DBMS that fully supports data independence.
- The higher-level schemas themselves are **unchanged**.
 - Hence, the application programs need not be changed since they refer to the external schemas.

DBMS Languages

- Data Definition Language (DDL)
- Data Manipulation Language (DML)
 - High-Level or Non-procedural Languages: These include the relational language SQL
 - May be used in a standalone way or may be embedded in a programming language
 - Low Level or Procedural Languages:
 - These must be embedded in a programming language

DBMS Languages

- **Data Definition Language (DDL):**

- Used by the DBA and database designers to specify the conceptual schema of a database.
- In many DBMSs, the DDL is also used to define internal and external schemas (views).
- In some DBMSs, separate **storage definition language (SDL)** and **view definition language (VDL)** are used to define internal and external schemas.
 - SDL is typically realized via DBMS commands provided to the DBA and database designers

DBMS Languages

- **Data Manipulation Language (DML):**

- Used to specify database retrievals and updates
- DML commands (data sublanguage) can be *embedded* in a general-purpose programming language (host language), such as COBOL, C, C++, or Java.
 - A library of functions can also be provided to access the DBMS from a programming language
- Alternatively, stand-alone DML commands can be applied directly (called a *query language*).

Types of DML

- **High Level or Non-procedural Language:**

- For example, the SQL relational language
- Are “set”-oriented and specify what data to retrieve rather than how to retrieve it.
- Also called **declarative** languages.

- **Low Level or Procedural Language:**

- Retrieve data one record-at-a-time;
- Constructs such as looping are needed to retrieve multiple records, along with positioning pointers.

DBMS Interfaces

- Stand-alone query language interfaces
 - Example: Entering SQL queries at the DBMS interactive SQL interface (e.g. SQL*Plus in ORACLE)
- Programmer interfaces for embedding DML in programming languages
- User-friendly interfaces
 - Menu-based, forms-based, graphics-based, etc.

DBMS Programming Language Interfaces

- Programmer interfaces for embedding DML in a programming languages:
 - **Embedded Approach:** e.g. embedded SQL (for C, C++, etc.), SQLJ (for Java)
 - **Procedure Call Approach:** e.g. JDBC for Java, ODBC for other programming languages
 - **Database Programming Language Approach:** e.g. ORACLE has PL/SQL, a programming language based on SQL; language incorporates SQL and its data types as integral components

User-Friendly DBMS Interfaces

- Menu-based, popular for browsing on the web
- Forms-based, designed for naïve users
- Graphics-based
 - (Point and Click, Drag and Drop, etc.)
- Natural language: requests in written English
- Combinations of the above:
 - For example, both menus and forms used extensively in Web database interfaces

Other DBMS Interfaces

- Speech as Input and Output
- Web Browser as an interface
- Parametric interfaces, e.g., bank tellers using function keys.
- Interfaces for the DBA:
 - Creating user accounts, granting authorizations
 - Setting system parameters
 - Changing schemas or access paths

Database System Utilities

- To perform certain functions such as:
 - Loading data stored in files into a database. Includes data conversion tools.
 - Backing up the database periodically on tape.
 - Reorganizing database file structures.
 - Report generation utilities.
 - Performance monitoring utilities.
 - Other functions, such as sorting, user monitoring, data compression, etc.

Other Tools

- Data dictionary / repository:
 - Used to store schema descriptions and other information such as design decisions, application program descriptions, user information, usage standards, etc.
 - **Active data dictionary** is accessed by DBMS software and users/DBA.
 - **Passive data dictionary** is accessed by users/DBA only.

Other Tools

- Application Development Environments and CASE (computer-aided software engineering) tools:
- Examples:
 - PowerBuilder (Sybase)
 - JBuilder (Borland)
 - JDeveloper 10G (Oracle)

Typical DBMS Component Modules

Centralized and Client-Server DBMS Architectures

- Centralized DBMS:
 - Combines everything into single system including- DBMS software, hardware, application programs, and user interface processing software.
 - User can still connect through a remote terminal – however, all processing is done at centralized site.

A Physical Centralized Architecture

Basic 2-tier Client-Server Architectures

- Specialized Servers with Specialized functions
 - Print server
 - File server
 - DBMS server
 - Web server
 - Email server
- Clients can access the specialized servers as needed



Logical two-tier client server architecture

Clients

- Provide appropriate interfaces through a client software module to access and utilize the various server resources.
- Clients may be diskless machines or PCs or Workstations with disks with only the client software installed.
- Connected to the servers via some form of a network.
 - (LAN: local area network, wireless network, etc.)

DBMS Server

- Provides database query and transaction services to the clients
- Relational DBMS servers are often called SQL servers, query servers, or transaction servers
- Applications running on clients utilize an Application Program Interface (**API**) to access server databases via standard interface such as:
 - ODBC: Open Database Connectivity standard
 - JDBC: for Java programming access
- Client and server must install appropriate client module and server module software for ODBC or JDBC
- See Chapter 9

Two Tier Client-Server Architecture

- A client program may connect to several DBMSs, sometimes called the data sources.
- In general, data sources can be files or other non-DBMS software that manages data.
- Other variations of clients are possible: e.g., in some object DBMSs, more functionality is transferred to clients including data dictionary functions, optimization and recovery across multiple servers, etc.

Three Tier Client-Server Architecture

- Common for Web applications
- Intermediate Layer called Application Server or Web Server:
 - Stores the web connectivity software and the business logic part of the application used to access the corresponding data from the database server
 - Acts like a conduit for sending partially processed data between the database server and the client.
- Three-tier Architecture Can Enhance Security:
 - Database server only accessible via middle tier
 - Clients cannot directly access database server

Three-tier client-server architecture

Classification of DBMSs

- Based on the data model used
 - Traditional: Relational, Network, Hierarchical.
 - Emerging: Object-oriented, Object-relational.
- Other classifications
 - Single-user (typically used with personal computers) vs. multi-user (most DBMSs).
 - Centralized (uses a single computer with one database) vs. distributed (uses multiple computers, multiple databases)

Variations of Distributed DBMSs (DDBMSs)

- Homogeneous DDBMS
- Heterogeneous DDBMS
- Federated or Multidatabase Systems
- Distributed Database Systems have now come to be known as client-server based database systems because:
 - They do not support a totally distributed environment, but rather a set of database servers supporting a set of clients.

Cost considerations for DBMSs

- Cost Range: from free open-source systems to configurations costing millions of dollars
- Examples of free relational DBMSs: MySQL, PostgreSQL, others
- Commercial DBMS offer additional specialized modules, e.g. time-series module, spatial data module, document module, XML module
 - These offer additional specialized functionality when purchased separately
 - Sometimes called cartridges (e.g., in Oracle) or blades
- Different licensing options: site license, maximum number of concurrent users (seat license), single user, etc.

History of Data Models

- Network Model
- Hierarchical Model
- Relational Model
- Object-oriented Data Models
- Object-Relational Models

History of Data Models

● **Network Model:**

- The first network DBMS was implemented by Honeywell in 1964-65 (IDS System).
- Adopted heavily due to the support by CODASYL (Conference on Data Systems Languages) (CODASYL - DBTG report of 1971).
- Later implemented in a large variety of systems - IDMS (Cullinet - now Computer Associates), DMS 1100 (Unisys), IMAGE (H.P. (Hewlett-Packard)), VAX -DBMS (Digital Equipment Corp., next COMPAQ, now H.P.).

Example of Network Model Schema

Network Model

- Advantages:

- Network Model is able to model complex relationships and represents semantics of add/delete on the relationships.
- Can handle most situations for modeling using record types and relationship types.
- Language is navigational; uses constructs like FIND, FIND member, FIND owner, FIND NEXT within set, GET, etc.
 - Programmers can do optimal navigation through the database.

Network Model

- Disadvantages:
 - Navigational and procedural nature of processing
 - Database contains a complex array of pointers that thread through a set of records.
 - Little scope for automated “query optimization”

History of Data Models

● **Hierarchical Data Model:**

- Initially implemented in a joint effort by IBM and North American Rockwell around 1965. Resulted in the IMS family of systems.
- IBM's IMS product had (and still has) a very large customer base worldwide
- Hierarchical model was formalized based on the IMS system
- Other systems based on this model: System 2k (SAS inc.)

Hierarchical Model

- Advantages:

- Simple to construct and operate
- Corresponds to a number of natural hierarchically organized domains, e.g., organization (“org”) chart
- Language is simple:
 - Uses constructs like GET, GET UNIQUE, GET NEXT, GET NEXT WITHIN PARENT, etc.

- Disadvantages:

- Navigational and procedural nature of processing
- Database is visualized as a linear arrangement of records
- Little scope for "query optimization"

History of Data Models

● **Relational Model:**

- Proposed in 1970 by E.F. Codd (IBM), first commercial system in 1981-82.
- Now in several commercial products (e.g. DB2, ORACLE, MS SQL Server, SYBASE, INFORMIX).
- Several free open source implementations, e.g. MySQL, PostgreSQL
- Currently most dominant for developing database applications.
- SQL relational standards: SQL-89 (SQL1), SQL-92 (SQL2), SQL-99, SQL3, ...
- Chapters 5 through 11 describe this model in detail

History of Data Models

● **Object-oriented Data Models:**

- Several models have been proposed for implementing in a database system.
- One set comprises models of persistent O-O Programming Languages such as C++ (e.g., in OBJECTSTORE or VERSANT), and Smalltalk (e.g., in GEMSTONE).
- Additionally, systems like O2, ORION (at MCC - then ITASCA), IRIS (at H.P.- used in Open OODB).
- Object Database Standard: ODMG-93, ODMG-version 2.0, ODMG-version 3.0.
- Chapters 20 and 21 describe this model.

History of Data Models

● **Object-Relational Models:**

- Most Recent Trend. Started with Informix Universal Server.
- Relational systems incorporate concepts from object databases leading to object-relational.
- Exemplified in the latest versions of Oracle-10i, DB2, and SQL Server and other DBMSs.
- Standards included in SQL-99 and expected to be enhanced in future SQL standards.
- Chapter 22 describes this model.

Summary

- Data Models and Their Categories
- History of Data Models
- Schemas, Instances, and States
- Three-Schema Architecture
- Data Independence
- DBMS Languages and Interfaces
- Database System Utilities and Tools
- Centralized and Client-Server Architectures
- Classification of DBMSs