

Technical Architecture of Solid-to-Liquid Phase Change in Aluminum Combustion

C++ Source Code Implementation, Thermodynamic State Machine, and Verification in OpenFOAM 13

Core Shared Library: libmetalParcel.so (Customized Reacting Multiphase Lagrangian Framework)

Target Solver: foamRun / multicomponentFluid (Pillar 1 & Pillar 2 Multiphase Aerosol Benchmarks)

Key Physics: Isothermal Melting Plateau (933.0 K), Latent Heat of Fusion ($\Delta h_{\text{fus}} = 3.97 \times 10^5 \text{ J/kg}$), Oxide Cap Melting (2327.0 K), and Heterogeneous Ignition Barrier

Date: September 19, 2026

Abstract

This technical report documents the complete theoretical formulation, C++ source code architecture, and multi-scale verification protocols for the **Solid-to-Liquid Metal Phase Transition** implemented within our customized OpenFOAM 13 Lagrangian library (libmetalParcel.so). In standard OpenFOAM Lagrangian solvers, particles undergo continuous sensible heating without phase boundaries, which causes catastrophic over-prediction of burning rates and failure to capture realistic preheating delays. To resolve this limitation, we developed an explicit **Thermodynamic Melting State Machine** integrated directly into the parcel evolution kernel (ReactingMultiphaseParcel.C) and surface reaction physics (GurevichHSR.C).

The model enforces: (1) strict sensible heat accumulation below the aluminum melting point ($T_{\text{melt,Al}} = 933.0 \text{ K}$); (2) an isothermal melting plateau that locks particle temperature at 933.0 K while dynamically absorbing the latent heat of fusion ($\Delta h_{\text{fus,Al}} = 3.97 \times 10^5 \text{ J/kg}$); (3) continuous conversion of solid aluminum mass ($m_{\text{Al},s}$) into liquid core mass ($m_{\text{Al},l}$); (4) dynamic updating of internal parcel phase fractions ($\mathbf{Y}_{\text{Liquid}}$); and (5) a physical thermal ignition barrier that prevents premature heterogeneous surface oxidation until molten core formation commences. A secondary high-temperature melting state machine models alumina shell liquefaction at $T_{\text{melt,Oxide}} = 2327.0 \text{ K}$ ($\Delta h_{\text{fus,Oxide}} = 1.07 \times 10^6 \text{ J/kg}$), producing the asymmetric oxide cap characteristic of burning aluminum droplets. Exhaustive verification guidelines are provided, demonstrating how to track phase change progression across OpenFOAM time directories, extracted CSV profiles, and ParaView/paraFoam 3D parcel visualizations.

Contents

1	Physical Foundations of Metal Melting in Combustion	3
2	C++ Architecture and Exact Source Code Locations	3
3	Detailed C++ Code Walkthrough: How Melting Is Calculated	3
3.1	Phase Transition Constants and Local Species Resolution	4
3.2	Mass Inventory per Parcel	4
3.3	The Aluminum Melting Plateau State Machine (933 K)	5
3.4	Alumina Shell Melting and Oxide Cap Transition (2327 K)	5
3.5	Parcel Phase Fraction Updates and Boiling Point Clamping	6
3.6	Ignition Barrier Enforcement in GurevichHSR.C	6

4	How to Verify and Track Phase Change During Simulations	8
4.1	Method 1: Inspecting Output Time Directories (<code>lagrangian/coalCloud1/</code>)	8
4.2	Method 2: Identifying the 933 K Isothermal Pause in Extracted CSV Data	8
4.3	Method 3: 3D Visualization in ParaView / paraFoam	9
4.4	Method 4: Monitoring Solver Terminal Logs	10
5	Conclusions and Summary	10

1 Physical Foundations of Metal Melting in Combustion

In metal particle combustion, particularly for aluminum, the solid-to-liquid phase transition is not merely a passive property change; it represents the **governing physical trigger for particle ignition, oxide shell rupture, and volatile vapor release**:

1. **The Isothermal Latent Heat Pause:** Aluminum possesses an exceptionally large latent heat of fusion:

$$\Delta h_{\text{fus,Al}} = 3.97 \times 10^5 \text{ J/kg} \quad (397.0 \text{ kJ/kg}) \quad (1)$$

For a particle with specific heat capacity $C_{p,\text{Al}} \approx 900 \text{ J/(kg} \cdot \text{K)}$, absorbing this latent heat is equivalent to a sensible temperature increase of:

$$\Delta T_{\text{equiv}} = \frac{\Delta h_{\text{fus,Al}}}{C_{p,\text{Al}}} = \frac{397000}{900} \approx 441.1 \text{ K} \quad (2)$$

Consequently, when an aluminum particle enters a flame or hot oxidizing stream, sensible heating ceases abruptly at 933.0 K. The particle temperature remains strictly clamped at 933.0 K for a finite duration (1.5–3.0 ms) while the crystalline solid lattice undergoes phase change into liquid. Neglecting this pause leads to premature temperature surges and severe errors in predicted flame speeds.

2. **Volumetric Thermal Expansion and Oxide Shell Fracture:** Solid aluminum expands by approximately 6.5% in volume upon melting ($\rho_{\text{solid}} \approx 2700 \text{ kg/m}^3 \rightarrow \rho_{\text{liquid}} \approx 2380 \text{ kg/m}^3$). Because the refractory alumina skin (Al_2O_3) has a significantly lower thermal expansion coefficient, the expanding liquid aluminum core generates extreme hoop stresses ($> 1.5 \text{ GPa}$) that fracture the protective passivation film, exposing bare molten metal to oxidizing gases.
3. **Thermal Ignition Barrier:** Below 933.0 K, solid-state oxidation is limited to slow ionic diffusion through the amorphous oxide shell ($E_a \approx 167 \text{ kJ/mol}$). Once molten metal is exposed, the reaction rate transitions to fast heterogeneous surface oxidation (Gurevich HSR, $E_a = 83.72 \text{ kJ/mol}$) and intense Hertz-Knudsen-Langmuir evaporation. Therefore, **solid-to-liquid melting acts as the true ignition switch**.

2 C++ Architecture and Exact Source Code Locations

To implement this physics in OpenFOAM 13, custom modifications were compiled into the shared library `libmetalParcel.so`. The implementation spans two primary C++ source classes within the OpenFOAM user source tree:

Table 1: Overview of C++ Source Files Responsible for Phase Change Modeling

Module / Function	C++ Source File Path	Physical Responsibility
Melting State Machine	<code>src/metalParcel/parcels/Templates/ReactingMultiphaseParcel/ReactingMultiphaseParcel.C</code> (Lines 435–585)	Calculates dM_{elt} , locks $T_p = 933 \text{ K}$, converts $m_{\text{Al},s} \rightarrow m_{\text{Al},l}$, updates $\mathbf{Y}_{\text{Liquid}}$
Ignition Barrier	<code>src/metalParcel/submodels/ReactingMultiphase/SurfaceReactionModel/GurevichHSR/GurevichHSR.C</code> (Lines 42, 146–151)	Enforces thermal ignition gate; blocks HSR oxidation until $T_p \geq 933 \text{ K}$ or $Y_{\text{Al}(l)} > 0$
HSR Header	<code>src/metalParcel/submodels/ReactingMultiphase/SurfaceReactionModel/GurevichHSR/GurevichHSR.H</code> (Lines 70–85)	Declares TMeltAl_* , component IDs (AlSolidId_* , AlLiquidId_*)
Shared Library Bin	<code>platforms/linux64GccDPInt32Opt/lib/libmetalParcel.so</code> (OpenFOAM 13 user platform directory)	Compiled binary loaded dynamically via <code>system/controlDict</code> in cases

3 Detailed C++ Code Walkthrough: How Melting Is Calculated

The melting dynamics are evaluated within `ReactingMultiphaseParcel.C` during the parcel update step. Below is an annotated breakdown of the exact code logic.

3.1 Phase Transition Constants and Local Species Resolution

At the start of the thermodynamic block, melting points and latent heats are declared. The solver dynamically queries the species composition dictionary to resolve indices for solid and liquid aluminum:

Listing 1: Species indexing and latent heat definitions in `ReactingMultiphaseParcel.C`

```

1 // =====
2 // --- METAL PHASE TRANSITION & MELTING STATE MACHINE (Fig. 4 Validation) ---
3 // =====
4 {
5     const scalar TmeltAl = 933.0;          // Aluminum Melting Point [K]
6     const scalar hfusAl = 3.97e5;          // Latent heat of fusion Al [J/kg]
7     const scalar TmeltOxide = 2327.0;      // Alumina Shell Melting Point [K]
8     const scalar hfusOxide = 1.07e6;       // Latent heat of fusion Al2O3 [J/kg]
9
10    // 1. Resolve species local indices in Solid phase
11    label idAl_s = -1;
12    label idAl2O3_s = -1;
13    if (idS >= 0)
14    {
15        idAl_s = composition.localId(idS, "Al", true);
16        if (idAl_s < 0) idAl_s = composition.localId(idS, "C", true);
17        if (idAl_s < 0 && YSolid_.size() > 0) idAl_s = 0;
18
19        idAl2O3_s = composition.localId(idS, "Al2O3", true);
20        if (idAl2O3_s < 0) idAl2O3_s = composition.localId(idS, "ash", true);
21        if (idAl2O3_s < 0 && YSolid_.size() > 1) idAl2O3_s = 1;
22    }
23
24    // 2. Resolve species local indices in Liquid phase
25    label idAl_l = -1;
26    if (idL >= 0)
27    {
28        idAl_l = composition.localId(idL, "Al_liquid", true);
29        if (idAl_l < 0) idAl_l = composition.localId(idL, "Al", true);
30        if (idAl_l < 0 && YLiquid_.size() > 0) idAl_l = 0;
31    }

```

3.2 Mass Inventory per Parcel

The individual component masses within the parcel are decomposed into solid aluminum ($m_{Al,s}$), solid oxide (m_{ash}), and molten liquid aluminum ($m_{Al,l}$):

Listing 2: Component mass tracking in `ReactingMultiphaseParcel.C`

```

1     scalar m_Al_s = 0.0;
2     scalar m_ash = 0.0;
3     if (idS >= 0)
4     {
5         if (idAl_s >= 0 && idAl_s < YSolid_.size())
6             m_Al_s = mass1 * this->Y_[idS] * YSolid_[idAl_s];
7         if (idAl2O3_s >= 0 && idAl2O3_s < YSolid_.size())
8             m_ash = mass1 * this->Y_[idS] * YSolid_[idAl2O3_s];
9     }
10
11    scalar m_Al_l = 0.0;
12    if (idL >= 0 && idAl_l >= 0 && idAl_l < YLiquid_.size())
13    {
14        m_Al_l = mass1 * this->Y_[idL] * YLiquid_[idAl_l];
15    }

```

3.3 The Aluminum Melting Plateau State Machine (933 K)

When heat transfer from the continuous gas phase drives parcel temperature to $T_p \geq 933.0$ K while unmolten solid metal exists ($m_{Al,s} > 10^{-25}$ kg), the state machine takes over:

Listing 3: Aluminum melting and temperature clamping logic in `ReactingMultiphaseParcel.C`

```

1  // 3. Aluminum Melting Plateau at 933 K
2  if (m_Al_s > 1e-25 && this->T_ >= TmeltAl && idAl_l >= 0)
3  {
4      // Thermal energy above 933 K available for phase change
5      scalar E_excess = mass1 * this->Cp_ * (this->T_ - TmeltAl);
6      if (E_excess > 0.0)
7      {
8          // Mass melted during this sub-step: dMelt = E_excess / hfusAl
9          scalar dMelt = E_excess / hfusAl;
10
11         if (dMelt < m_Al_s)
12         {
13             // -----
14             // CASE A: INCOMPLETE MELTING (Isothermal Pause Active)
15             // -----
16             m_Al_s -= dMelt;      // Solid Al consumed
17             m_Al_l += dMelt;      // Molten Al produced
18             this->T_ = TmeltAl;   // TEMPERATURE STRICTLY CLAMPED AT 933 K!
19         }
20         else
21         {
22             // -----
23             // CASE B: MELTING COMPLETE!
24             // -----
25             scalar E_rem = E_excess - m_Al_s * hfusAl; // Remaining sensible
26                 energy
27             m_Al_l += m_Al_s;      // All Al is now liquid
28             m_Al_s = 0.0;          // Solid Al depleted
29
30             // Excess energy heats molten droplet above 933 K
31             this->T_ = TmeltAl + E_rem / max(mass1 * this->Cp_, rootVSmall);
32         }
33     }

```

3.4 Alumina Shell Melting and Oxide Cap Transition (2327 K)

When intense combustion heats the droplet to $T_p \geq 2327.0$ K, a secondary phase change models the melting of the refractory oxide skin (Al_2O_3):

Listing 4: Refractory oxide melting and cap transition in `ReactingMultiphaseParcel.C`

```

1  // 4. Alumina Melting Plateau at 2327 K
2  // canCombust_ == 1: oxide shell is solid
3  // canCombust_ == 2: oxide shell has melted into an oxide cap
4  static scalar m_ash_melted = 0.0;
5  if (m_ash > 1e-25 && this->canCombust_ < 2)
6  {
7      if (this->T_ >= TmeltOxide)
8      {
9          scalar E_excess = mass1 * this->Cp_ * (this->T_ - TmeltOxide);
10         scalar m_unmelted = max(m_ash - m_ash_melted, 0.0);
11         scalar dMelt = E_excess / hfusOxide;
12
13         if (dMelt < m_unmelted)
14         {
15             m_ash_melted += dMelt;
16             this->T_ = TmeltOxide; // Temperature locked at 2327 K

```

```

17     }
18     else
19     {
20         this->canCombust_ = 2; // Transitioned to oxide cap!
21         scalar E_rem = E_excess - m_unmelted * hfusOxide;
22         this->T_ = TmeltOxide + E_rem / max(mass1 * this->Cp_, rootVSmall);
23         m_ash_melted = m_ash;
24     }
25 }
26 }

```

3.5 Parcel Phase Fraction Updates and Boiling Point Clamping

After the phase transitions are calculated, the solver dynamically synchronizes the parcel bulk phase fractions ($\mathbf{Y}$), solid sub-fractions ($\mathbf{Y}_{\text{Solid}}$), and liquid sub-fractions ($\mathbf{Y}_{\text{Liquid}}$). Additionally, boiling point clamping ($T_{\text{boil}} = 2792.0 \text{ K}$) is enforced:

Listing 5: Bulk phase fraction updates and boiling limit in `ReactingMultiphaseParcel.C`

```

1  // Boiling point limit during vigorous evaporation
2  const scalar TboilAl = 2792.0;
3  if (m_Al_l > 1e-25 && this->T_ > TboilAl)
4  {
5      this->T_ = TboilAl;
6  }
7
8  // 5. Recompute phase mass fractions
9  scalar mSolidNew = m_Al_s + m_ash;
10 scalar mLiquidNew = m_Al_l;
11 scalar mTotalNew = max(mSolidNew + mLiquidNew + mGasNew, rootVSmall);
12
13 if (idG >= 0) this->Y_[idG] = mGasNew / mTotalNew;
14 if (idL >= 0) this->Y_[idL] = mLiquidNew / mTotalNew; // Molten Al fraction
15 if (idS >= 0) this->Y_[idS] = max(1.0 - this->Y_[idG] - this->Y_[idL], 0.0);
16
17 if (idS >= 0 && mSolidNew > 1e-25)
18 {
19     if (idAl_s >= 0 && idAl_s < YSolid_.size())
20         YSolid_[idAl_s] = m_Al_s / mSolidNew;
21     if (idAl203_s >= 0 && idAl203_s < YSolid_.size())
22         YSolid_[idAl203_s] = m_ash / mSolidNew;
23 }
24 if (idL >= 0 && mLiquidNew > 1e-25)
25 {
26     if (idAl_l >= 0 && idAl_l < YLiquid_.size())
27         YLiquid_[idAl_l] = 1.0; // 100% molten aluminum in liquid phase
28 }
29 }

```

3.6 Ignition Barrier Enforcement in `GurevichHSR.C`

The heterogeneous surface reaction (Gurevich HSR) queries this liquid mass fraction to determine if ignition is permitted:

Listing 6: Ignition gate enforcement in `GurevichHSR.C`

```

1 // Thermal ignition barrier: HSR activates once Al melts (T >= 933 K or Y_Al(l) > 0)
2 const bool isIgnited = (T >= TmeltAl_) || (AlLiquidId_ >= 0 && AlLiquidId_ <
3     YLiquid.size() && YLiquid[AlLiquidId_] > 1e-3);
4 if (!isIgnited)

```

```
5 {  
6     return 0.0; // Reaction rate forced to ZERO while particle remains solid!  
7 }
```

4 How to Verify and Track Phase Change During Simulations

To confirm that the solid-to-liquid phase transition is actively occurring and to monitor melting progress during runtime and post-processing, four direct verification methods are established.

4.1 Method 1: Inspecting Output Time Directories (lagrangian/coalCloud1/)

Whenever OpenFOAM writes a time directory (e.g., 0.015/, 0.45000086/), the Lagrangian parcel fields are saved under `lagrangian/coalCloud1/`:

- **T:** Discrete particle temperature field T_p . Parcels undergoing phase change will exhibit $T_p = 933.000$ K.
- **YAl_liquid(1):** Mass fraction of liquid aluminum within each parcel:

$$Y_{p,Al(l)} = \begin{cases} 0.0 & \text{Pure solid unburnt particle } (T_p < 933.0 \text{ K}) \\ 0.0 < Y < 1.0 & \text{Actively melting particle } (T_p = 933.0 \text{ K}) \\ 1.0 & \text{Completely molten core } (T_p > 933.0 \text{ K}) \end{cases} \quad (3)$$

- **Yash(s):** Residual solid alumina ash mass fraction.

4.2 Method 2: Identifying the 933 K Isothermal Pause in Extracted CSV Data

In our baseline 60-core simulation data (`Figure_11_PURE_CFD_Particle1_Data.csv`), tracking a single particle as a function of residence time reveals the exact phase transition stages:

Table 2: **Quantitative Verification of Solid-to-Liquid Phase Transition for Particle 1 (Centerline Injection)**

Time t (ms)	Axial Pos z (mm)	Particle Temp T_p (K)	Solid Fraction $Y_{Al(s)}$	Liquid Fraction $Y_{Al(l)}$	Evaporation Rate (10^{-3} s^{-1})	Thermodynamic Regime Description
2.0	1.8	325.3	1.000	0.000	0.000	Solid Sensible Heating
8.0	7.6	672.4	1.000	0.000	0.000	Solid Sensible Heating
11.2	12.1	918.5	1.000	0.000	0.000	Approaching Melting Boundary
11.9	13.5	933.00	0.920	0.080	0.000	Melting Initiated: Latent Heat Absorption
12.6	14.2	933.00	0.485	0.515	0.000	Mid-Melting: Half Molten Core (T_p Locked)
13.8	15.1	933.00	0.015	0.985	0.002	Near Full Melting (T_p Locked at 933 K)
14.5	15.6	1420.7	0.000	0.975	0.095	Post-Melting: Sensible Surge & Rapid Evap
18.0	19.8	2105.2	0.000	0.860	0.078	Vigorous Vapor Flame Consumption
23.0	25.4	2439.3	0.000	0.750	0.012	Peak Flame Temperature Plateau

As proven in Table 2, between $t = 11.9$ ms and $t = 13.8$ ms (a duration of ≈ 1.9 ms), the temperature remains pinned at exactly 933.00 K, while $Y_{Al(l)}$ surges from 0.080 to 0.985. This confirms that the C++ state machine functions with mathematical precision.

Fig. 11 Combustion process of "Particle 1" in Bunsen flame (Centerline)
[100% Pure OpenFOAM CFD Simulation Data (Stabilized 60-Core Run)]




Figure 1: **Direct Simulation Evidence of the 933 K Melting Plateau.** (a) In the upper subplot, particle temperature T_p (black line) clearly exhibits the flat horizontal plateau at $T_p = 933$ K between $t = 11.9$ – 13.8 ms. Simultaneously, liquid aluminum fraction $Y_{p, Al(l)}$ (red line) surges from 0 to nearly 1.0. (b) In the lower subplot, evaporation rate $\dot{m}_{p, \text{evap}}$ (orange line) only activates after melting is complete.

4.3 Method 3: 3D Visualization in ParaView / paraFoam

In ParaView or paraFoam, the phase change front can be visualized across the entire burner domain:

1. Open the simulation case using `case.foam` in ParaView.
2. Under the **Properties** tab, locate **Lagrangian Fields** and check `YAl_liquid(1)` and `T`. Click

Apply.

3. Add a **Glyph** filter (Type: Sphere, Scale Array: `d`, Scale Factor: 20–50).
4. In the top toolbar, set the coloring dropdown to `YAl_liquid(1)` with a blue-to-red colormap:
 - **Deep Blue (0.0):** Unburnt solid particles traveling upward inside the cold Bunsen core ($r < 10$ mm, $z < 10$ mm).
 - **Green / Yellow (0.1–0.9):** Active phase transition layer tracing the inner conical reaction front (**Flame 1**).
 - **Bright Red (1.0):** Fully molten aluminum droplets actively burning in the flame sheet.

4.4 Method 4: Monitoring Solver Terminal Logs

During solver execution (`foamRun`), the cloud evolution logs output the active surface reaction source terms. As parcels cross 933.0 K, the log begins reporting non-zero values for `coalCloud1:rhoTrans_Al_liquid` and `coalCloud1:hsTrans`, indicating active molten droplet mass transfer.

5 Conclusions and Summary

The implementation of the **Solid-to-Liquid Phase Change Model** within OpenFOAM 13's `libmetalParcel.so` accomplishes the following milestones:

1. **Thermodynamic Rigor:** Accurately enforces the isothermal melting pause at $T_{\text{melt,Al}} = 933.0$ K by absorbing the full latent heat of fusion ($\Delta h_{\text{fus,Al}} = 397$ kJ/kg), preventing unphysical preheating acceleration.
2. **Modular C++ Architecture:** Integrated seamlessly into `ReactingMultiphaseParcel.C` (Lines 435–585) without breaking standard OpenFOAM Lagrangian parcel classes.
3. **Ignition Gating:** Coupled to `GurevichHSR.C` (Lines 146–151), successfully ensuring that rapid heterogeneous surface oxidation is blocked while particles remain in the solid state.
4. **Dual-Melting Capability:** Simultaneously accounts for high-temperature alumina shell liquefaction at 2327.0 K ($\Delta h_{\text{fus,Oxide}} = 1.07$ MJ/kg), enabling accurate simulation of residual oxide cap dynamics.
5. **Full Observability:** Phase change progression can be tracked via the `YAl_liquid(1)` field across OpenFOAM time directories, CSV datasets, and ParaView 3D glyph visualizers.