
# RDF Schema, RDFa

Pedro Szekely
University of Southern California/ISI



### Semantic Web Layer Cake





#### Components from Last Lecture

#### Unicode

Standard for encoding international characters

#### URI

- String of standardized form to uniquely identify resources
  - URL: <a href="http://www.example.org">http://www.example.org</a>
  - URN: urn:isbn:0-123-45678-9
- IRI: international variant of URI (with unicode)

#### XML

So that we have a common syntax for Semantic Web

#### XML schema


 Define types, e.g., USAddress, for a particular set of XML documents, e.g., Invoices

#### and ...


- Namespace
  - So that we can have different markup vocabularies in one document
- RDF (resource description framework)
  - Was used to represent metadata of Web resources
    - E.g., title, author, modification date
  - Generally, a graph representation of any resources
    - Triple: resource-property-value or subject-predicateobject
  - Anyone can define vocabulary of terms

#### RDF Recap

- FOAF (friend of a friend)
  - Terms for describing people and Social Web
  - Classes, e.g., Person, OnlineAccount
  - Properties, e.g., name, homepage, accountname
- Using FOAF



 RDF predefine some classes (e.g., rdf:Property) and properties (e.g., rdf:type)




### RDF Serialization: RDF/XML

```
Ex:DavidSmith foaf:givenName David
```

#### RDF Serialization: Turtle

- Terse RDF triple language
  - RDF in compact text format



@prefix Ex: <http://www.example.org/person#>

Ex:DavidSmith foaf:givenName "David".

### Limited Vocabulary in RDF

- RDF vocabulary
  - Classes: rdf:Property, rdf:XMLLiteral, rdf:HTML, rdf:langString (language-tagged string values)
  - Properties, e.g., rdf:type
    - allow you to state "instance-of" relationship
- Use rdf:type to explicitly define new properties
  - Ex:title rdf:type rdf:Property


```
or simply:
```

Ex:title a rdf:Property

('a' is a syntactic shortcut for rdf:type)

#### RDF Schema or RDFS

- Add new vocabulary for describing
  - Classes
    - e.g., rdfs:Class
  - Taxonomy of classes
    - e.g., rdfs:subClassOf
  - Taxonomy of properties
    - e.g., rdfs:subPropertyOf
  - Domain and range of properties
    - rdfs:domain, rdfs:range



@prefix : <http://www.example.org/sample.rdfs#> .

@prefix rdf: <a href="http://www.w3.org/1999/02/22-rdf-syntax-ns#">http://www.w3.org/1999/02/22-rdf-syntax-ns#</a> .

@prefix rdfs: <a href="http://www.w3.org/2000/01/rdf-schema">http://www.w3.org/2000/01/rdf-schema">http://www.w3.org/2000/01/rdf-schema</a>

:Dog rdfs:subClassOf :Animal.

:Person rdfs:subClassOf :Animal.

:hasChild rdfs:range :Animal;

rdfs:domain:Animal.

:hasSon rdfs:subPropertyOf


:hasChild.

:Max a :Dog.

:Abel a :Person.

:Adam a :Person;

:hasSon :Abel.



#### **RDFS: New Predefined Classes**

- Major ones:
  - rdfs:Resource a top-level class
  - rdfs:Class a class of all classes
  - rdfs:Literal a class of literals, e.g., strings and integers
    - A literal may have 3 components: "David"^^xsd:string@en
      - Lexical form: "David"
      - Data type IRI: ^^xsd:string
      - Language tag (for string only): @en
    - RDFS reuses XML schema built-in data types
      - xsd:string, xsd:boolean, xsd:decimal, xsd:integer, etc
    - Note rdf:XMLLiteral is a subclass of rdfs:Literal
      - XMLLIteral: XML fragment as a literal

#### More ...

- rdfs:DataType a class of all data types, including
  - Built-in data types in XSD
  - rdf:HTML
  - rdf:XMLLiteral

#### Notes:


- Every instance of rdfs:DataType (e.g., rdf:XMLLiteral) is a subclass of rdf:Literal
- rdfs:DataType is a subclass of rdfs:Class, since it contains a set of classes (data types)

## Summary of Classes in RDF(S)


Class	Represent	SubClassOf	InstanceOf
rdfs:Resource	All resources	rdfs:Resource	rdfs:Class
rdfs:Class	All classes	rdfs:Resource	rdfs:Class
rdfs:Literal	Literal values	rdfs:Resource	rdfs:Class
rdfs:DataType	Data types	rdfs:Class	rdfs:Class
rdf:XMLLiteral/ rdf:langString/ rds:HTML	XML/ language-tagged/ HTML literal values	rdfs:Literal	rdfs:DataType
rdf:Property	All properties	rdfs:Resource	rdfs:Class

Note: Properties are resources too

### Summary in an RDF Graph




# Adding rdf:XMLLiteral (1)






# Adding rdf:XMLLiteral (2)






# Adding rdfs:Property (1)





# Adding rdfs:Property (2)





## Summary of Properties in RDF(S)


- Defined in RDF
  - rdf:type, rdf:value

- Defined in RDFS
  - rdfs:domain, rdfs:range
  - rdfs:subClassOf, rdfs:subPropertyOf
  - rdfs:label (human-readable name of resource),
     rdfs:comment, rdfs:seeAlso, rdfs:definedBy

All theses are instances of rdf:Property


## Summary of Properties in RDF(S)

Property	Relates	Domain (rdfs:domain)	Range (rdfs:range)
rdfs:domain	Restricts subjects	?	?
rdfs:range	Restricts objects	?	?
rdfs:subPropertyOf	Subproperty	?	?
rdfs:subClassOf	Subclass of	?	?
rdf:type	Instance of	?	?



# Summary of Properties in RDF(S)

Property	Relates	Domain (rdfs:domain)	Range (rdfs:range)
rdfs:domain	Restricts subjects	rdfs:Property	rdfs:Class
rdfs:range	Restricts objects	rdfs:Property	rdfs:Class
rdfs:subPropertyOf	Subproperty	rdfs:Property	rdfs:Property
rdfs:subClassOf	Subclass of	rdfs:Class	rdfs:Class
rdf:type	Instance of	rdfs:Resource	rdfs:Class



RDF in Attributes



#### RDFa:

#### Resource Description Framework – in – attributes

#### Plain XHTML

```
In his latest book
    <cite>Wikinomics</cite>,
    <span>Don Tapscott</span>
    explains deep changes in technology,
    demographics and business.
    The book is due to be published in
    <span>October 2006</span>.
```

## Browser shows



### RDFa: Namespaces

#### namespace declaration

```
    In his latest book
    <cite>Wikinomics</cite>,
    <span>Don Tapscott</span>
    explains deep changes in technology,
    demographics and business.
    The book is due to be published in
    <span>October 2006</span>.
```

## Browser shows



#### RDFa: Resources

#### Resource declaration

```
   In his latest book
   <cite>Wikinomics</cite>,
   <span>Don Tapscott</span>
   explains deep changes in technology,
   demographics and business.
   The book is due to be published in
   <span>October 2006</span>.
```

## Browser shows



#### RDFa: Property

#### property declaration

```
   In his latest book
        <cite property="dc:title">Wikinomics</cite>,
        <span>Don Tapscott</span>
        explains deep changes in technology,
        demographics and business.
        The book is due to be published in
        <span>October 2006</span>.
```

## Browser shows



### RDFa: Property

```
   In his latest book
   <cite property="dc:title">Wikinomics</cite>,
        <span>Don Tapscott</span>
        explains deep changes in technology,
        demographics and business.
   The book is due to be published in
        <span>October 2006</span>.
```

#### RDF-enabled computer sees:



http://www.example.com/books/wikinomics

dc:title

"Wikinomics"

#### What's the Difference?

```
   In his latest book
   <cite property="dc:title">Wikinomics</cite>,
   <span>Don Tapscott</span>
...
```

```
   In his latest book
   <cite property="title">Wikinomics</cite>,
        <span>Don Tapscott</span>
   ...
```

#### What's the Difference?

```
about="http://www.example.com/books/wikinomics">
 In his latest book
 <cite property="dc:title">Wikinomics</cite>,
 <span>Don Tapscott/span>
```


```
about="http://www.example.com/books/wikinomics">
 In his latest book
 <cite property="title">Wikinomics</cite>,
 <span>Don Tapscott
                          what does title mean?
```

### I Can Look Up the Meaning on the Web

```
   In his latest book
   <cite property="dc:title">Wikinomics</cite>,
        <span>Don Tapscott</span>
...
```




## I Can Look Up the Meaning on the Web



#### **Index of Terms**

Properties in the /terms/ namespace abstract, accessRights, accrualMethod, accrualPeriodicity, accrualPolicy, alternative, audience, available, bibliographicCitation, conformsTo, contributor, coverage, created, creator, date, dateAccepted, dateCopyrighted, dateSubmitted, description, educationLevel, extent, format, hasFormat, hasPart, hasVersion, identifier, instructionalMethod, isFormatOf, isPartOf, isReferencedBy, isReplacedBy, isRequiredBy, issued, isVersionOf, language, license, mediator, medium, modified, provenance, publisher, references, relation, replaces, requires, rights, rightsHolder, source, spatial, subject, tableOfContents, temporal, title, type, valid

## I Can Look Up the Meaning on the Web




Humans can look up what it means

### Computers Can Look It Up Too

```
<rdf:RDF>
- <rdf:Description rdf:about="http://purl.org/dc/elements/1.1/">
    <dcterms:title xml:lang="en-US">Dublin Core Metadata Element Set, Version 1.1</dcterms:titl</p>
    <dcterms:publisher rdf:resource="http://purl.org/dc/aboutdcmi#DCMI"/>
    <dcterms:modified>2010-10-11</dcterms:modified>
  </rdf:Description>
- <rdf:Property rdf:about="http://purl.org/dc/elements/1.1/title">
    <rdfs:label xml:lang="en-US">Title</rdfs:label>
    <rdfs:comment xml:lang="en-US">A name given to the resource.</rdfs:comment>
    <rdfs:isDefinedBy rdf:resource="http://purl.org/dc/elements/1.1/"/>
    <dcterms:issued>1999-07-02</dcterms:issued>
    <dcterms:modified>2008-01-14</dcterms:modified>
    <rdf:type rdf:resource="http://www.w3.org/1999/02/22-rdf-syntax-ns#Property"/>
    <dcterms:hasVersion rdf:resource="http://dublincore.org/usage/terms/history/#title-006"/>
  - <skos:note xml:lang="en-US">
      A second property with the same name as this property has been declared in the dcterms: names
      "DCMI Metadata Terms" (http://dublincore.org/documents/dcmi-terms/) for an explanation.
    </skos:note>
  </rdf:Property>
- <rdf:Property rdf:about="http://purl.org/dc/elements/1.1/creator">
    <rdfs:label xml:lang="en-US">Creator</rdfs:label>
```

## What's the Big Deal?



Claudia, Pedro & the computers can all agree on the meaning of dc:title



#### Where Were We?

#### RDFa: Property

```
   In his latest book
   <cite property="dc:title">Wikinomics</cite>,
        <span>Don Tapscott</span>
   explains deep changes in technology,
   demographics and business.
   The book is due to be published in
   <span>October 2006</span>.
```

#### RDF-enabled computer sees:

http://www.example.com/books/wikinomics

dc:title

"Wikinomics"



## What's Wrong Here?

```
   In his latest book
   <cite property="dc:title">Wikinomics</cite>,
        <span property="dc:creator">Don Tapscott</span>
        explains deep changes in technology,
        demographics and business.
   The book is due to be published in
        <span property="dc:date">October 2006</span>.
```

Not a computer understandable date e.g., an xsd:date



### RDFa: Content Attribute

```
about="http://www.example.com/books/wikinomics">
 In his latest book
 <cite property="dc:title">Wikinomics</cite>,
 <span property="dc:creator">Don Tapscott
 explains deep changes in technology,
 demographics and business.
 The book is due to be published in
 <span property="dc:date"</pre>
       content="2006-10-01"
       datatype="xsd:date">October 2006</span>.
```

### RDFa:

### Resource Description Framework – in – attributes

```
XHTML
```

+

RDFa

```
   In his latest book
   <cite property="dc:title">Wikinomics</cite>,
        <span property="dc:creator">Don Tapscott</span>
   explains deep changes in technology,
   demographics and business.
   The book is due to be published in
   <span property="dc:date"
        content="2006-10-01"
        datatype="xsd:date">October 2006</span>.
```

### Extracted RDF

```
@prefix dc: http://purl.org/dc/elements/1.1/ .

<http://www.example.com/books/wikinomics>
    dc:title "Wikinomics"@en ;
    dc:creator "Don Tapscott"@en ;
    dc:date "2006-10-01"^^xsd:date .
```


# Browser

In his latest book *Wikinomics*, Don Tapscott explains deep changes in technology, demographics and business. The book is due to be published in October 2006.



## More RDFa

# RDFa: vocab and typeof



Define default vocabulary for an HTML element

Nested elements don't need vocabulary URI

# RDFa: property and href

When href is present, it supplies the value for the property



# RDFa: Using Extra Span Tags

```
<div vocab="http://xmlns.com/foaf/0.1/">
<a property="homepage" href="http://example.com/bob/">
      <span property="name">Bob</span></a>
  <a property="homepage" href="http://example.com/eve/">
      <span property="name">Eve</span></a>
```

Need a span tag to contain the property="name" tag of my friends



# Putting It All Together

```
<div vocab="http://xmlns.com/foaf/0.1/" typeof="Person">
  >
    <span property="name">Alice Birpemswick</span>,
      Email: <a property="mbox"
               href="mailto:alice@example.com">alice@example.com</a>,
      Phone: <a property="phone"
               href="tel:+1-617-555-7332">+1 617.555.7332</a>
  <a property="homepage" href="http://example.com/bob/">
        <span property="name">Bob</span></a>
  <a property="homepage" href="http://example.com/eve/">
        <span property="name">Eve</span></a>
    </div>
                                                  RDF properties: e.g., phone
```

RDF objects: e.g., Eve

# Resulting RDF

```
<div vocab="http://xmlns.com/foaf/0.1/" typeof="Person">
  >
    <span property="name">Alice Birpemswick</span>,
       Email: <a property="mbox"
         href="mailto:alice@example.com">alice@example.com</a>,
       Phone: <a property="phone"
         href="tel:+1-617-555-7332">+1 617.5
                                           a foaf:Person;
  foaf:name
                                                     "Alice";
  <l
                                           foaf:mbox
                                                      <mailto:alice@example.com>;
    foaf:phone <tel:+1-617-555-7332>;
       <a property="homepage href="http://ex
                                           foaf:knows
         <span property="name">Bob</span>
                                                  foaf:Person:
  <a href="http://example.com/bob/"> ;</a>
                                             foaf:homepage
    foaf:name
                                                             "Bob"
       <a property="homepage" href="http://e
                                           1:
         <span property="name">Eve</span>
                                           foaf:knows
    foaf:Person;
  foaf:homepage
                                                             <a href="http://example.com/eve/"> ;
</div>
                                             foaf:name
                                                             "Fve"
                                           ];
```

# Facebook OpenGraph



RDF used by the "Like" button

```
<html>
<head prefix="og: http://ogp.me/ns#" >
 <meta property="og:title" content="The Trouble with Bob" />
 <meta property="og:type" content="text" />
 <meta property="og:image" content="http://example.com/alice/ugly.jpg" />
</head>
<body>
</body>
</html>
```



## RDFa: rel Attribute

</div>

## Benefits of RDFa

Navigation bar (from RDFa?)

Reviews from RDFa



Sony VAIO Laptop / Intel® Core™ i3 Processor / 15.5" Divplay / 4GB ...

www.bestbuy.com > ... > Laptop & Netbook Computers > PC Laptops

★★★★ 29 reviews

SONY VAIO E Series Laptop / Intel Core i3 Processor / 15.5. ... Best Buy Logo .... Intel® Core™ i3 Processor / 15.5" Display / 4GB Memory / 640GB Hard Drive

•••



Shop All New Laptops - Best Buy

www.bestbuy.com/site/Laptop...Laptops/pcmcat138500050001.c?id...

Best Buy has a vast selection of new laptops in assorted prices, color and ... Intel® Core™ i3 Processor / 15.6" Display / 4GB Memory / 500GB Hard Drive - Black ....
Toshiba - Intel® Core™ i5 Processor / 14" Display / 6GB Memory / 640GB Hard


Drive - ... Sony - VAIO Laptop / Intel® Core™ i3 Processor / 15.5" Display / 4GB

Google understands the page content



```
http://www.data-vocabulary.org/Review-aggregate/
<div class="rating"
  typeof="v:Review-aggregate"
  about="#review 3505047">
                                  4.0 of 5 (30 reviews)
  <span
    property="v:itemreviewed"
    content=""></span>
  <span rel="v:rating">
    <span typeof="v:Rating">
    <img src="http://images.bestbuy.com/BestBuy US/images.../>
    <span
        property="v:rating"
        datatype="xsd:string">4.0</span> of
    <span property="v:best">5</span>
    <span
      property="v:count"
      datatype="xsd:string"
      content="30">
    </span>
    (<a class="customer-review"</pre>
      href="#tabbed-customerreviews">30 reviews</a>)
    </span>
  </span>
</div>
```

http://searchnewscentral.com/20110207129/Technical/rdfa-the-inside-story-from-best-buy.html



### RDFa: The Inside Story from Best Buy

Written by Doc Sheldon Monday, 07 February 2011 14:08

### An Interview with Jay Myers

Late last year, I approached Jay Myers, Lead Development Engineer for Best Buy, and asked him if he'd be willing to be interviewed about his project of implementing RDFa on Best Buy's web site. He accepted, and we began exchanging information, a process that culminated in a voice interview last Monday.

### Who Uses RDFa?

RDFa is the fastest growing data markup format on the Web, and is used on more than 430 million web pages.

It accounts for roughly 3.6% of the all of the Web pages on the Internet.

How much did RDFa grow last year? 510% (2010)

... will show even stronger growth as people start to realize the search engine advantage that RDFa gives web content publishers.

http://rdfa.info/2011/01/26/rdfa-grows/



"You use the schema.org vocabulary, along with the microdata format, to add information to your HTML content."



non-RDFa microdata even though RDF vocabulary was defined

```
<div
  itemscope
  itemtype="http://schema.org/Movie">
  <h1 itemprop="name">Avatar</h1>
  <span>Director:
    <span itemprop="director">James Cameron</span>
      (born August 16, 1954)
  </span>
  <span itemprop="genre">Science fiction</span>
  <a href="../movies/avatar-theatrical-trailer.html"</pre>
    itemprop="trailer">Trailer</a>
</div>
```

Backup slides

## **RDF Schema**

# RDFS Vocabulary

xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"

### Classes

rdfs:Resource

rdfs:Class

rdfs:Literal

rdfs:Datatype

rdf:XMLLiteral

rdf:Property

### Properties

rdfs:range

rdfs:domain

rdf:type

rdfs:subClassOf

rdfs:subPropertyOf

rdfs:label

rdfs:comment

### **Utility Properties**


rdfs:seeAlso

rdfs:isDefinedBy


rdf:value



## **Notation and Conventions**




# Meaning of Subclass




A

В

# Meaning of Subclass





if B is a subclass of A, the instances of B are a subset of the instances of A




### rdfs:Resource

All things described by RDF are called *resources*, and are instances of the class rdfs:Resource

This is similar to Object class in Java class hierarchy


#### **Implications**

- Every class/property is a resource too
- Properties can themselves have properties





## rdfs:Class



rdfs:Class is an instance of rdfs:Class

In fact, every class, including rdfs:Resource, is an instance of rdfs:Class



# rdfs:Literal, rdfs:Datatype

class rdfs:Literal is the class of literal values such as strings and integers

typed literals

class rdfs:Datatype is the class of typed literals


plain literals

there is no class for plain literals?




# The Story So Far

# Every class is subclass of Resource



# rdfs:Property

# the class of resources that are RDF properties



# RDF Schema Vocabulary

#### Classes

rdfs:Resource

rdfs:Class

rdfs:Literal

rdfs:Datatype

rdf:XMLLitera/

rdf:Property/

### Properties

rdfs:range

rdfs:domain

rdf:type

rdfs:subClassOf

rdfs:subPropertyOf

rdfs:label

rdfs:comment

### **Utility Properties**


rdfs:seeAlso

rdfs:isDefinedBy

rdf:value




# rdfs:domain, rdfs:range



rdfs:domain and rdfs:range are instances of rdf:property





# Semantics of rdfs:range



# Semantics of rdfs:range

P rdfs:range C.






хРу.



# Semantics of rdfs:range



# rdfs:range Example

```
foaf:based_near rdf:type rdf:Property; rdfs:domain foaf:Person; rdfs:range wgs84:SpatialThing .
```


ex:pedro foaf:based\_near dbpedia:Los\_Angeles .



dbpedia:Los\_Angeles rdf:type wgs84:SpatialThing .



### Semantics of rdfs:domain



# Multiple rdfs:domain, rdfs:range

Prdfs:domain C1.

Prdfs:domain C2.

xPy.



x rdf:type C1.

x rdf:type C2.

P rdfs:range C1.

P rdfs:range C2.

xPy.




? rdf:type C1.

? rdf:type C2.



## rdfs:subClassOf



rdf:Property

rdfs:subClassOf

C1 rdfs:subClassOf C2.


C1 rdfs:subClassOf C2.

C2 rdfs:subClassOf C3.

**Transitive** 





## rdfs:subClassOf



# rdfs:subPropertyOf

P1 rdfs:subPropertyOf P2.










# Multiple Assertions

P1 rdfs:subPropertyOf P2.



## rdfs:label, rdfs:comment

rdfs:label is an instance of rdf:Property

used to provide a human-readable version of a resource's name

every resource should have a label in multiple languages

because browsers show the label when they show a resource



## rdfs:label, rdfs:comment

rdfs:label is an instance of rdf:Property

used to provide a human-readable version of a resource's name

every resource should have a label in multiple languages

because browsers show the label when they show a resource

rdfs:comment is an instance of rdf:Property

used to provide a human-readable description of a resource



### rdfs:seeAlso

rdfs:seeAlso is an instance of rdf:Property

used to indicate a resource that might provide additional information about the subject resource



## rdfs:seeAlso

```
<a href="http://schema.rdfs.org/all">http://schema.rdfs.org/all</a> a owl:Ontology;
   dct:title
                                   "The schema.org terms in RDFS+OWL"@en;
                                    "This is a conversion of the terms defined at schema.org to RDFS and
   dct:description
OWL."@en;
   foaf:page
                                   <http://schema.rdfs.org/>;
   rdfs:seeAlso
                                   <http://schema.org/>;
                                   <a href="http://github.com/mhausenblas/schema-org-rdf">http://github.com/mhausenblas/schema-org-rdf</a>;
   rdfs:seeAlso
   dct:hasFormat
                                   <a href="http://schema.rdfs.org/all.ttl">http://schema.rdfs.org/all.ttl</a>;
                                   <a href="http://schema.rdfs.org/all.rdf">http://schema.rdfs.org/all.rdf</a>;
   dct:hasFormat
   dct:hasFormat
                                   <a href="http://schema.rdfs.org/all.nt">http://schema.rdfs.org/all.nt</a>;
   dct:hasFormat
                                    <a href="http://schema.rdfs.org/all.json">http://schema.rdfs.org/all.json</a>;
   dct:hasFormat
                                     dct:hasPart <http://schema.rdfs.org/all-classes.csv>;
                                     dct:hasPart <http://schema.rdfs.org/all-properties.csv>;
   dct:source <http://schema.org/>;
   dct:license <a href="http://schema.org/docs/terms.html">dct:license <a href="http://schema.org/docs/terms.html">http://schema.org/docs/terms.html</a>;
   dct:valid "2012-06-16"^^xsd:date;
```

slide by Pedro Szekely

# rdfs:isDefinedBy

rdfs:isDefinedBy is an instance of rdf:Property a subproperty of rdf:seeAlso

used to indicate a resource defining the subject resource

this property may be used to indicate an RDF vocabulary in which a resource is described



# Example

#### ... from the schema.org vocabulary definition

```
schema:ContactPage a rdfs:Class;
rdfs:label "Contact Page"@en;
rdfs:comment "Web page type: Contact page."@en;
rdfs:subClassOf schema:WebPage;
rdfs:isDefinedBy <http://schema.org/ContactPage>;
.
```

# RDF/XML for an XML Literal

```
<?xml version="1.0"?>
<rdf:RDF xmlns:rdf="http://www.w3.org/1999/02/22-rdf-
syntax-ns#" xmlns:dc="http://purl.org/dc/elements/1.1/"
xml:base="http://www.example.com/books">
<rdf:Description rdf:ID="book12345">
      <dc:title rdf:parseType="Literal">
             <span xml:lang="en"> The <em>&lt;br
/></em> Element Considered Harmful. </span>
      </dc:title>
</rdf:Description>
</rdf:RDF>
```