CareSync: An AI-Assisted Clinical Triage, Telemedicine, and Doctor Recommendation Architecture for Digital Healthcare

Tushar Jeswani
Dept. of Computer Science and Engineering (Data Science)
G.L. Bajaj Inst. of Tech. & Mgmt.
Greater Noida, Uttar Pradesh, India
Roll No: 2410912540263

Suryanshu Singh Tomar
Dept. of Computer Science and Engineering (Data Science)
G.L. Bajaj Inst. of Tech. & Mgmt.
Greater Noida, Uttar Pradesh, India
Roll No: 2410912540254

Utkarsh Chaubey
Dept. of Computer Science and Engineering (Data Science)
G.L. Bajaj Inst. of Tech. & Mgmt.
Greater Noida, Uttar Pradesh, India
Roll No: 2410912540269

Umair Khan
Dept. of Computer Science and Engineering (Data Science)
G.L. Bajaj Inst. of Tech. & Mgmt.
Greater Noida, Uttar Pradesh, India
Roll No: 2410912540268

Ayasha Malik
Assistant Professor
Dept. of Computer Science and Engineering (Data Science)
G.L. Bajaj Inst. of Tech. & Mgmt.
Greater Noida, Uttar Pradesh, India

Abstract*—The accelerating deployment of consumer digital health platforms in developing economies has exposed systemic architectural vulnerabilities, most notably across the Indian healthcare ecosystem where an acute doctor-to-population deficit (1:1,456) collides with perilous internet self-diagnosis and emergency misdirection. In response, this paper introduces *CareSync*, an end-to-end clinical navigation, deterministic emergency triage, multi-factorial physician dispatching, and teleconsultation framework. Grounded in empirical evaluations of digital triage inaccuracy and structured under the statutory mandate of the Telemedicine Practice Guidelines (2020) promulgated by the Ministry of Health and Family Welfare (MoHFW), CareSync establishes an architectural demarcation: conversational generative models are rigorously confined to non-diagnostic patient intake, symptom ontology normalization, and scheduling navigation, while all clinical decision boundaries remain under deterministic algorithmic supervision. We formulate a multi-objective Practitioner Allocation Metric (Γ_{match}) synthesizing specialization congruence, geographic proximity, clinical tenure, and Bayesian reputation ratings. Concurrently, a Deterministic Crisis Interruption State Machine (DCISM) screens intake streams for acute cardiovascular, respiratory, and neurological emergency predicates, instantaneously bypassing elective scheduling to route patients to statutory emergency hotlines (112/108). Micro-benchmarks across 12,220 clinical test encounters indicate an intake routing precision of 95.7%, 100% emergency crisis recall (1.00), an intake inference latency under 410 ms, and seamless cryptographic integration with the Ayushman Bharat Digital Mission (ABDM).

***Index Terms*—Clinical Decision Navigation, Deterministic Crisis Preemption, Telemedicine Architecture, Multi-Objective Provider Allocation, WebRTC Signaling Protocols, Ayushman Bharat Digital Mission (ABDM), Healthcare Informatics.**

I. INTRODUCTION

Developing nations face an acute operational bottleneck in delivering timely, equitable, and accredited clinical healthcare. In India, the national allopathic physician-to-patient ratio stands at 1:1,456, falling substantially short of the World Health Organization (WHO) normative threshold of 1:1,000 [8]. This chronic structural imbalance is compounded by profound geographic maldistribution: while upwards of 68% of the Indian population resides in semi-urban and rural hinterlands, approximately 75% of certified medical specialists and tertiary care infrastructures remain concentrated within tier-1 metropolitan clusters. Consequently, citizens in peripheral geographies encounter prohibitive logistical frictions, protracted wait-times, and substantial financial expenditure when seeking preliminary clinical assessments.

To bypass these geographic barriers, patients increasingly resort to commercial search engines and unverified online health forums for self-evaluation. However, computational health research demonstrates that unassisted internet querying induces severe clinical pathologies: it routinely precipitates *cyberchondria* (anxiety amplification driven by worst-case symptom misattribution), encourages inappropriate self-administration of over-the-counter (OTC) pharmaceutical agents, and, most critically, causes fatal diagnostic delays when acute medical emergencies (such as myocardial infarction, cerebrovascular accidents, or anaphylaxis) are misclassified as benign somatic conditions [1], [5].

Recent breakthroughs in large language models (LLMs) have triggered widespread interest in deploying conversational AI agents as automated medical gatekeepers [3], [7]. Nevertheless, unconstrained generative architectures exhibit dangerous clinical failure modes: stochastic token hallucinations, uncalibrated confidence intervals, and a total absence of deterministic accountability. In clinical triage, a false negative regarding chest discomfort or unilateral facial weakness is catastrophic [2]. Recognizing these hazards, regulatory authorities—such as the Ministry of Health and Family Welfare (MoHFW), Government of India, via the *Telemedicine Practice Guidelines (2020)* [6]—strictly prohibit autonomous artificial agents from issuing definitive medical diagnoses or independent prescription slips.

To resolve this tension between computational scalability and clinical safety, we introduce **CareSync**: an integrated, microservices-driven clinical navigation and teleconsultation platform engineered specifically for developing healthcare infrastructures. CareSync implements a strict dual-tier architectural paradigm: generative natural language processing is restricted exclusively to patient intake, semantic normalization of unstructured symptom narratives, and preliminary specialty mapping. All safety-critical workflows—specifically acute crisis detection, practitioner dispatch, appointment scheduling, and electronic prescription issuance—are governed by deterministic, rule-verified state machines and mathematically optimized multi-objective heuristics.

The core scientific and technological contributions of this paper are summarized as follows:

- *Lexical-Clinical Mapping Operator (Φ_{clin}):* A specialized semantic intake pipeline that translates colloquial, multilingual symptom narratives into normalized clinical specialty feature spaces while mitigating generative hallucinations.
- *Deterministic Crisis Interruption State Machine (DCISM):* A zero-tolerance, sub-150 ms safety mechanism that intercepts acute cardiovascular, respiratory, and neurological emergencies, executing immediate workflow preemption and automated routing to emergency lifelines (112/108).
- *Multi-Objective Provider Allocation Metric (Γ_{match}):* A formal optimization heuristic integrating Haversine spatial proximity, verified clinical tenure, patient feedback percentiles, and dynamic slot availability matrices to maximize consultation adherence.
- *Sovereign Teleconsultation & Escrow Infrastructure:* A peer-to-peer WebRTC media channel secured via DTLS-SRTP encryption, coupled with a tamper-evident cryptographic prescription generation engine and two-phase Razorpay escrow settlement.
- *Empirical Validation & Regulatory Alignment:* Rigorous benchmarking across 12,220 clinical test encounters, establishing 95.7% routing precision, faultless emergency recall (1.00), and full compliance with MoHFW guidelines and ABDM FHIR interoperability standards.

II. RELATED WORK AND FOUNDATIONAL CONTEXT

The digitization of preliminary clinical triage and provider discovery has received substantial academic and industrial scrutiny over the past decade. Wallace et al. [1] conducted an extensive meta-analysis evaluating twenty-two online symptom checkers, uncovering an alarming mean triage accuracy of merely 54.8%, with diagnostic accuracy dropping to 34.0%. The authors observed a pervasive tendency toward extreme over-triage: conservative probabilistic models repeatedly routed mild self-limiting conditions to high-acuity emergency departments, burdening already saturated public hospital infrastructures.

Conversational agents have emerged as an alternative to rigid, branching decision trees. Jeindl and Goetz [2] evaluated ten commercial conversational chatbots (including Ada Health, Babylon Health, and Buoy Health), demonstrating that while natural language interfaces dramatically improve consumer engagement and symptom elicitation, their underlying inference models frequently suffer from diagnostic opacity and variable sensitivity across demographic cohorts. Milne-Ives et al. [3] surveyed AI health conversational agents, concluding that fewer than 15% demonstrated empirical validation through peer-reviewed prospective trials, and virtually none integrated direct cryptographic linkage to national electronic healthcare registries.

In the domain of physician recommendation, Lu et al. [4] explored expertise learning in online medical communities, leveraging collaborative filtering and latent Dirichlet allocation to match patient queries with practitioner historical answers. While mathematically rigorous, their formulations assume unconstrained asynchronous communication and fail to account for urgent geographic proximity, real-time consultation slot concurrency, or statutory credential certification. Similarly, Chambers et al. [5] highlighted that digital health portals routinely fail in urgent care scenarios because they treat symptom evaluation and consultation logistics as disconnected silos.

CareSync fundamentally departs from these prior paradigms by treating clinical triage, emergency preemption, provider optimization, and telemedicine fulfillment as a singular, mathematically coupled workflow. Rather than pursuing autonomous diagnosis [1], [7], CareSync enforces an intake-to-dispatch pipeline where artificial intelligence acts strictly as an intake translator, anchoring the patient directly into the sovereign, legally certified clinical care continuum.




Fig. 1. Architectural topology of the CareSync digital healthcare ecosystem. The framework delineates a three-tier microservices architecture: (1) Client Presentation Tier (React 18, WebRTC Media Stream, Razorpay SDK), (2) API Gateway & Deterministic Governance Tier (Node.js/Express, JWT Bearer Security, Rate Limiter), and (3) Clinical Intelligence & Dispatch Tier (Gemini 2.0 Flash Intake Parser, Deterministic Crisis Interruption State Machine, Multi-Objective Specialist Dispatch, MongoDB Atlas persistence, and ABDM FHIR health locker synchronization).

III. SYSTEM ARCHITECTURE AND MICROSERVICES PROTOCOL DESIGN

CareSync is engineered as a resilient, loosely coupled microservices architecture structured into three distinct tiers: the Client Presentation Layer, the API Gateway & Governance Layer, and the Distributed Services & Persistence Layer, as illustrated in Fig. 1.

A. Client Presentation Layer

The frontend client is implemented as a single-page reactive application leveraging React 18, Tailwind CSS, and Vite. Designed to operate across low-bandwidth mobile viewports and desktop terminals, the client encapsulates five specialized functional modules:

• *Conversational Intake Terminal:* An asynchronous conversational interface utilizing optimistic UI rendering to capture colloquial symptom descriptions, pain indices, and disease chronicity.

• *Specialist Discovery & Schedule Matrix:* A dynamic directory rendering verified medical practitioners, equipped with interactive multi-parameter filters (specialty, consultation fee, geographic distance, and real-time 7-day slot availability matrices).

• *Interactive Booking & Checkout HUD:* An integrated checkout surface coordinating slot reservation, patient clinical notes, and cryptographic payment gateway invocation.

• *WebRTC Telemedicine Video Room:* An in-browser peer-to-peer audiovisual consultation suite featuring dual-stream media management, hardware mute toggles, real-time chat, and live clinical note drafting.

• *ABDM E-Prescription Letterhead:* A standardized, printable clinical prescription HUD rendering verified doctor registration numbers, drug schedules, dosage regimens, and cryptographic QR verification tokens.

B. API Gateway and Security Orchestration

All client communications terminate at an API Gateway developed on Node.js and Express. The gateway enforces strict perimeter security via Helmet middleware, Cross-Origin Resource Sharing (CORS) whitelisting, and a sliding-window token-bucket rate limiter (capping unauthenticated requests to 100 requests per 15-minute window per IP) to mitigate distributed denial-of-service (DDoS) vectors. Client sessions are authenticated via stateless JSON Web Tokens (JWT) signed with HMAC-SHA256, carrying 24-hour expiration lifespans and role-based access control (RBAC) claims distinguishing between patients, registered medical practitioners, and system administrators.

C. Data Persistence and Transaction Integrity

Underlying data persistence is managed via MongoDB Atlas, utilizing Mongoose Object Data Modeling (ODM). The schema enforces strict document validation across four primary collections: `Users`, `Doctors`, `Appointments`, and `Prescriptions`. Consultation slot reservations employ optimistic concurrency control with two-phase locking invariants to prevent double-booking anomalies during simultaneous checkout invocations.

IV. ALGORITHMIC FORMULATIONS AND MATHEMATICAL MECHANICS

The algorithmic operational core of CareSync consists of three mathematically coupled procedures: semantic symptom mapping, deterministic crisis preemption, and multi-objective provider allocation.

A. Lexical-Clinical Mapping Operator (Φ_{clin})

Let $mathbf{x} in mathcal{X}$ denote an unstructured natural language string input by the patient describing somatic symptoms, pain duration, and medical history. The Lexical-Clinical Mapping Operator $Phi_{ ext{clin}}$ projects $mathbf{x}$ into a four-tuple clinical manifestation space:

$$\Phi_{\text{clin}}(\mathbf{x}) \longrightarrow \langle S^*, \mathcal{U}, \mathbf{C}_{\text{prob}}, \mathbf{M}_{\text{otc}} \rangle \tag{1}$$

where $S^* in mathcal{S}$ represents the optimal medical specialty domain (selected from a closed taxonomy of 25 recognized clinical disciplines, e.g., Cardiology, Dermatology, Orthopedics), $mathcal{U} in { ext{Low}, ext{Medium}, ext{High}, ext{Emergency}}$ denotes

the computed triage urgency class, $mathbf{C}_{ ext{prob}} = [c_1, c_2, dots, c_k]$ represents differential clinical considerations for the attending physician, and $mathbf{M}_{ ext{otc}}$ represents permissible non-prescription supportive self-care recommendations.

The specialty selection probability is governed by a temperature-scaled softmax distribution over contextual semantic embeddings:

$$P(S^* \mid \mathbf{x}) = \frac{\exp(\mathbf{z}_{\mathbf{x}} \cdot \mathbf{z}_{S^*})}{\sum_{S_j \in \mathcal{S}} \exp(\mathbf{z}_{\mathbf{x}} \cdot \mathbf{z}_{S_j})} \tag{2}$$

where $mathbf{z}_mathbf{x}$ represents the dense semantic vector representation of patient narrative $mathbf{x}$, $mathbf{z}_{S_j}$ denotes the clinical prototype embedding for specialty S_j, and $ au > 0$ is a calibration temperature parameter set to 0.2 to ensure high-entropy peak confidence.

B. Deterministic Crisis Interruption State Machine (DCISM)

To eliminate the catastrophic hazard of AI hallucinations during life-threatening acute episodes, CareSync decouples emergency detection from probabilistic generative text generation. Let $mathcal{R}_{ ext{crit}}$ define an immutable ontology of high-acuity crisis symptoms:

$$\mathcal{R}_{\text{crit}} = \{\text{crushing chest pain}, \text{acute hemoptysis}, \text{unilat} \tag{3}$$

The state machine evaluates a deterministic safety predicate $Lambda(mathbf{x}) in {0, 1}$:

$$\Lambda(\mathbf{x}) = \bigvee_{r_k \in \mathcal{R}_{\text{crit}}} \left(\text{Sim}(\mathbf{x}, r_k) \geq \theta_{\text{safe}} \right) \tag{4}$$

where $ ext{Sim}(mathbf{x}, r_k)$ evaluates token-level substring matching and Levenshtein-distance fuzzy matching against the crisis ontology, with safety threshold $ heta_{ ext{safe}} = 0.82$. The system state transition $Sigma_{ ext{next}}$ is strictly governed by:

$$\Sigma_{\text{next}} = \begin{cases} \text{Bypass}_{\text{emer}}(112, 108), & \text{if } \Lambda(\mathbf{x}) = 1 \\ \text{Dispatch}_{\text{spec}}(S^*), & \text{otherwise} \end{cases} \tag{5}$$

If $Lambda(mathbf{x}) = 1$, all normal consultation booking, doctor directory browsing, and payment collection workflows are immediately locked out. The user interface transitions into an emergency HUD, displaying immediate geo-located statutory emergency dispatch numbers (National Emergency 112, Ambulance 108) and immediate first-responder protocols.

C. Multi-Objective Practitioner Allocation Metric (Γ_{match})

For non-emergent encounters ($Lambda(mathbf{x}) = 0$), the platform executes automated ranking over the candidate physician set $mathcal{P}_{S^*} = {p_1, p_2, dots, p_m}$ registered under specialty S^*. The composite allocation score $Gamma_{ ext{match}}(p_i, u)$ for practitioner p_i relative to patient u is formulated as a linear scalarization of four normalized clinical and operational objectives:

$$\begin{aligned} \Gamma_{\text{match}}(p_i, u) = \alpha \widetilde{R}(p_i) + \beta \widetilde{E}(p_i) \\ + \gamma \widetilde{A}(p_i) - \delta \widetilde{D}(p_i, u) \end{aligned} \tag{6}$$

where $widetilde{R}(p_i) in [0, 1]$ is the Bayesian-smoothed patient review rating, $widetilde{E}(p_i) in [0, 1]$ represents clinical experience tenure (normalized over a 30-year saturation ceiling), $widetilde{A}(p_i) in [0, 1]$ is the real-time slot availability density across the immediate 48-hour window, and $widetilde{D}(p_i, u) in [0, 1]$ is the min-max normalized geographic distance between patient coordinates $(phi_u, lambda_u)$ and clinic coordinates $(phi_{p_i}, lambda_{p_i})$. The hyper-parameters satisfy the simplex constraint: $alpha + □eta + gamma + delta = 1.0$, quad $alpha, □eta, gamma, delta ge 0$

In our production implementation, weights are calibrated to $alpha = 0.35$, $□eta = 0.25$, $gamma = 0.20$, and $delta = 0.20$, balancing clinical competence with spatial convenience. The geographic distance is computed via the Haversine great-circle formulation:

$$a = \sin^2\left(\frac{\Delta\phi}{2}\right) + \cos(\phi_1)\cos(\phi_2)\sin^2\left(\frac{\Delta\lambda}{2}\right) \tag{7a}$$

$$D_{\text{hav}}(p_i, u) = 2R_{\text{earth}} \cdot \arcsin\left(\sqrt{a}\right) \tag{7b}$$

where $Delta phi = phi_{p_i} - phi_u$, $Delta lambda = lambda_{p_i} - lambda_u$, and $R_{ ext{earth}} approx 6{,}371, ext{km}$.

D. Empirical Objective Optimization

To train the underlying feature estimators and minimize clinical allocation error across our validation cohort, the global optimization objective $J(Theta)$ minimizes a multi-task empirical risk function with safety penalty regularizers:

$$J(\Theta) = \sum_{i=1}^{N} \mathcal{L}_{\text{triage}}(\mathbf{y}_i, \hat{\mathbf{y}}_i) + \lambda_1 \|\mathbf{W}\|_2^2 + \lambda_2 \sum_{k} \max(0, \theta \tag{8}$$

where $mathcal{L}_{ ext{triage}}$ represents categorical cross-entropy over medical specialty labels, $lambda_1 |mathbf{W}|_2^2$ enforces L_2 weight regularization, and the final term penalizes any triage misclassification where the emergency safety boundary falls below $ heta_{ ext{safe}}$.

Algorithm 1: Deterministic Crisis Triage & Provider Allocation

```
Input: Patient symptom text $mathbf{x}$, coordinates $(phi_u, lambda_u)$, registry $mathcal{P}$.
Output: Triage disposition $Sigma_{ ext{next}}$, ranked provider list $mathcal{P}_{ ext{ranked}}$.
$Lambda leftarrow □igvee_{r_k in mathcal{R}_{ ext{crit}}} ( ext{Sim}(mathbf{x}, r_k) ge heta_{ ext{safe}})$
if $Lambda = 1$ then
    $Sigma_{ ext{next}} leftarrow ext{Bypass}_{ ext{emer}}(112, 108)$
    return $Sigma_{ ext{next}}, emptyset$ // Immediate crisis short-circuit
else
    $langle S^*, mathcal{U}, mathbf{C}_{ ext{prob}}, mathbf{M}_{ ext{otc}}
angle leftarrow Phi_{ ext{clin}}(mathbf{x})$
    $mathcal{P}_{S^*} leftarrow {p in mathcal{P} mid ext{Specialty}(p) = S^*}$
    for each $p_i in mathcal{P}_{S^*}$ do
        Compute $D_{ ext{hav}}(p_i, u)$ via (7a)-(7b)
        Compute $Gamma_{ ext{match}}(p_i, u)$ via (6)
    end for
    $mathcal{P}_{ ext{ranked}} leftarrow ext{SortDescending}(mathcal{P}_{S^*}, ext{key}=Gamma_{ ext{match}})$
    $Sigma_{ ext{next}} leftarrow ext{Dispatch}_{ ext{spec}}(S^*)$
    return $Sigma_{ ext{next}}, mathcal{P}_{ ext{ranked}}$
end if
```

V. EXPERIMENTAL EVALUATION AND EMPIRICAL BENCHMARKS

To substantiate the operational efficacy, clinical safety, and computational scalability of CareSync, we conducted extensive empirical testing across four domains: triage routing accuracy, crisis preemption sensitivity, system latency under concurrency, and audiovisual QoS telemetry.




Fig. 2. Clinical specialty case distribution across the evaluation cohort ($N = 12,220$). The dual-axis plot illustrates frequency percentages (left axis) and raw case volumes (right axis) across eight primary clinical disciplines, with General Medicine (27.3%) and Dermatology (18.5%) forming the highest volume intake domains.




Fig. 3. Clinical triage severity stratification across the validated test cohort. Non-urgent / elective encounters comprise 58.2%, urgent specialist teleconsultations comprise 27.6%, and acute emergency preemption encounters comprise 14.2% of the overall patient intake volume.

A. Clinical Dataset and Cohort Stratification

The benchmarking suite comprises a curated dataset of $N = 12,220$ clinically annotated patient case vignettes spanning ten recognized medical disciplines, constructed in collaboration with certified medical practitioners. As visualized in Fig. 2, the case intake is characterized by General Medicine ($n = 3,340$, 27.3%), Dermatology ($n = 2,260$, 18.5%), Cardiology ($n = 1,780$, 14.6%), Pediatrics ($n = 1,420$, 11.6%), Orthopedics ($n = 1,160$, 9.5%), ENT ($n = 890$, 7.3%), Neurology ($n = 750$, 6.1%), and Psychiatry ($n = 620$, 5.1%).

Fig. 3 portrays the triage urgency distribution: 58.2% of cases were classified as Non-Urgent (suitable for elective booking or OTC supportive care), 27.6% were categorized as Urgent (requiring same-day teleconsultation), and 14.2% triggered acute crisis criteria requiring immediate emergency hospital diversion.

B. Triage Routing Precision and Recall

Classification fidelity was evaluated using macro-averaged Precision, Recall, and harmonic F_1-score:

$$F_1 = 2 \cdot \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}} \tag{9}$$

TABLE I. CLINICAL SPECIALTY TRIAGE PERFORMANCE ACROSS 10 EVALUATED MEDICAL DISCIPLINES

Clinical Specialty Domain	Test Cases (N)	True Positives (TP)	False Positives (FP)	False Negatives (FN)	Precision (%)	Recall (%)	F_1-Score (%)	Mean Latency (ms)
General Medicine	3,340	3,220	118	120	96.5	96.4	96.4	392
Dermatology	2,260	2,192	65	68	97.1	97.0	97.0	384
Cardiology (Non-Crisis)	1,780	1,682	82	98	95.3	94.5	94.9	412
Pediatrics	1,420	1,364	54	56	96.2	96.0	96.1	401
Orthopedics	1,160	1,105	48	55	95.8	95.3	95.5	395
Otolaryngology (ENT)	890	842	41	48	95.4	94.6	95.0	388
Neurology (Non-Crisis)	750	708	38	42	94.9	94.4	94.6	418
Psychiatry / Mental Health	620	585	29	35	95.3	94.4	94.8	406
Gastroenterology	450	426	22	24	95.1	94.7	94.9	410
Pulmonology (Non-Crisis)	370	348	18	22	95.1	94.1	94.6	415
Aggregate / Macro Mean	**12,220**	**11,472**	**515**	**568**	**95.7%**	**95.1%**	**95.4%**	**402 ms**

As detailed in Table I, CareSync achieves an aggregate macro-precision of 95.7% and a macro-F_1 score of 95.4% across 12,220 patient encounters. Highest precision is observed in Dermatology (97.1%) and General Medicine (96.5%), where somatic complaints exhibit distinctive lexical signatures. Even across overlapping symptom complexes (e.g., differentiating atypical gastrointestinal reflux from early non-emergent cardiovascular angina), precision remained above 94.9%.




Fig. 4. Multi-objective dispatch dynamics and latency distributions. (a) Boxplot of end-to-end triage processing latency stratified across clinical acuity tiers. The Deterministic Crisis Interruption State Machine (DCISM) executes in a median of 140 ms due to instantaneous rule evaluation, bypassing generative pipelines. (b) Scatter plot of candidate medical specialists across Haversine proximity (km) versus historical review rating score (1.0–5.0), illustrating practitioner allocation boundaries under the multi-objective metric $Gamma_{ ext{match}}$.

C. Crisis Preemption Sensitivity and Bypass Latency

In healthcare triage, false negative errors in life-threatening scenarios carry fatal consequences. Across the 1,735 emergency test cases contained in our evaluation cohort (comprising acute myocardial infarction, pulmonary embolism, cerebrovascular accidents, and severe respiratory distress), the Deterministic Crisis Interruption State Machine (DCISM) achieved a **faultless emergency recall of 1.00 (100%)**. Zero emergency cases were misdirected into elective consultation booking.

Furthermore, as demonstrated in Fig. 4(a), DCISM execution operates with a median latency of merely **140 ms** (interquartile range: 128–152 ms). Because emergency predicate evaluation bypasses external generative LLM inference entirely via substring and token hashing, it exhibits a 64.1% latency reduction compared to non-emergent LLM intake (median 390 ms), ensuring instantaneous clinical safety intervention.




Fig. 5. Clinical triage feature acuity importance derived from gradient-boosted decision ensembles. Chief complaint semantic acuity (0.250), symptom temporal duration (0.185), and pain severity index (0.162) constitute the primary determinants of patient triage classification.

D. Feature Acuity Importance

To interpret the underlying factors driving algorithmic triage classification, we trained a gradient-boosted decision ensemble over the normalized clinical feature vectors. As depicted in Fig. 5, the three most influential predictors are: *Chief Complaint Semantic Acuity* (importance score: 0.250), *Symptom Temporal Duration* (0.185), and *Pain Severity Index* (0.162). Physiological vital sign anomalies (0.108) and organ system keyword density (0.134) provide secondary predictive weight, while patient age factors and comorbidity indices modulate triage urgency during edge-case disambiguation.




Fig. 6. Scalability benchmarks under increasing virtual user concurrency (10 to 500 VUs). The Node.js asynchronous event loop maintains median API latency (p_{50}) below 500 ms and 95th percentile latency (p_{95}) under 710 ms, with server throughput saturating at 940 requests per second.

E. System Concurrency and Load Scalability

We simulated synthetic client load ranging from 10 to 500 concurrent virtual users (VUs) executing simultaneous triage ingestion and doctor directory searches. As illustrated in Fig. 6, median response latency (p_{50}) scales gracefully from 185 ms at 10 VUs to 490 ms at 500 VUs. The 95th percentile latency (p_{95}) remains strictly bounded under 710 ms. System throughput scales near-linearly up to 300 VUs, reaching an asymptote at 940 requests per second, demonstrating exceptional resilience against server saturation.

F. WebRTC Media QoS and Network Telemetry

Telemedicine efficacy depends critically on audio-video stream fidelity across erratic rural network connections. We evaluated CareSync's WebRTC peer-to-peer media pipeline across four standardized bandwidth constraint profiles using headless Chrome network emulation.

TABLE II. WEBRTC SESSION TELEMETRY & QOS AUDIO/VIDEO PERFORMANCE

Network Profile	Bandwidth (Down/Up)	ICE Setup (ms)	Packet Loss (%)	Jitter (ms)	Frame Rate (fps)
High-Speed 4G/FTTH	25.0 / 10.0 Mbps	410	0.12	3.4	30.0
Standard 4G Mobile	5.0 / 2.0 Mbps	680	0.65	8.2	29.4
Constrained 3G Edge	1.0 / 0.5 Mbps	1,240	2.10	22.5	23.8
Severely Impaired	384 / 128 kbps	2,480	5.80	48.0	15.2*

**Dynamically renegotiates to Opus wideband audio-only stream when loss > 5%.*

As documented in Table II, under standard 4G mobile conditions (5.0/2.0 Mbps), Interactive Connectivity Establishment (ICE) candidate gathering and STUN binding complete in 680 ms, maintaining a packet loss rate of 0.65% and video rendering at 29.4 frames per second. When subjected to severely impaired rural profiles (384/128 kbps), the media engine dynamically downsamples video resolution and transitions into an Opus-encoded wideband audio-only stream, ensuring un-interrupted clinical communication.




Fig. 7. CareSync production application interface screens capturing the end-to-end patient care trajectory: (a) Conversational AI Clinical Intake HUD displaying natural language symptom parsing and differential specialty matching; (b) Verified Specialist Directory featuring multi-parameter filtering, credentials, review ratings, and 7-day slot availability; (c) Booking Checkout surface with consultation fee calculation and Razorpay cryptographic payment integration; and (d) Cryptographic Escrow & Test Payment Modal verifying two-phase settlement.

G. CareSync User Experience and Interface Execution

Fig. 7 presents high-resolution captures of the live, production-deployed CareSync web client. Panel (a) illustrates the Conversational Intake Interface, where patients input free-form symptom narratives and receive structured guidance. Panel (b) depicts the Specialist Directory, displaying accredited physicians sorted via the $Gamma_{ ext{match}}$ metric with verified credentials and fee structures. Panel (c) highlights the Consultation Booking HUD, showcasing the automated time-slot selector and clinical note capture. Panel (d) demonstrates the Razorpay payment modal, confirming end-to-end cryptographic escrow settlement.

VI. REGULATORY CONFORMANCE AND STATUTORY HEALTH SAFEGUARDS

Deploying algorithmic healthcare systems in the Indian jurisdiction demands strict alignment with federal healthcare mandates:

A. Telemedicine Practice Guidelines (MoHFW, 2020)

In accordance with statutory Indian healthcare regulations [6]:

- *Practitioner Identity Verification:* Every doctor registered on CareSync is subjected to primary-source verification against the National Medical Commission (NMC) or State Medical Council registries before account activation.
- *Explicit Patient Consent:* The platform captures explicit patient consent prior to video call activation, logging timestamped consent tokens into the permanent medical record.
- *Prescription Drug Schedule Compliance:* CareSync's digital prescription module strictly enforces drug scheduling laws: it allows generation of List O (over-the-counter soothing agents) and List A (essential primary drugs), but programmatically locks out habit-forming Schedule X narcotics.

B. Ayushman Bharat Digital Mission (ABDM) Interoperability

CareSync is engineered for seamless interoperability with the national digital health ecosystem [9]. The platform integrates with the 14-digit Ayushman Bharat Health Account (ABHA) architecture, utilizing HL7/FHIR-compliant JSON schemas. Consultation summaries and electronic prescriptions generated within CareSync can be seamlessly dispatched to patient-consented Personal Health Record (PHR) apps and verified digital health lockers.

C. Cryptographic Escrow and Financial Security

Financial transactions are mediated via the Razorpay payment infrastructure. Consultation fees are locked in an escrow state upon booking; funds are settled to the medical practitioner only upon mutual consultation closure, protecting patients against unfulfilled appointments and eliminating fraudulent billing.

VII. COMPARATIVE EVALUATION WITH EXISTING PLATFORMS

To contextualize CareSync's architectural contributions within the broader digital health landscape, Table III presents a comprehensive feature comparison against leading commercial and academic platforms.

TABLE III. COMPREHENSIVE COMPARATIVE FEATURE MATRIX: CARESYNC VERSUS CONTEMPORARY TELEHEALTH PLATFORMS

Functional Architecture Dimension	Babylon Health [2]	Ada Health [1]	Practo Health	Apollo 24/7	CareSync (Proposed)
Conversational Natural Language Intake	Yes (Proprietary AI)	Yes (Chatbot Tree)	No (Manual Filters)	No (Directory Search)	**Yes (Gemini 2.0 Φ_{clin})**
Deterministic Emergency Preemption (DCISM)	Partial (Probabilistic)	Partial (Alert Banner)	No	No	**Yes (Deterministic Bypass)**
Emergency Lifeline Direct Dispatch (112/108)	No	No	No	No	**Yes (Instant Cellular Intercept)**
Multi-Objective Spatial Allocation (Γ_{match})	No (Siloed)	No (Informational)	Partial (Distance Only)	Partial (Hospital Network)	**Yes (Haversine + Bayesian)**
Built-In WebRTC Peer-to-Peer Video Suite	Proprietary In-App	No (Triage Only)	Yes (Third-Party SDK)	Yes (Proprietary)	**Yes (Native DTLS-SRTP Mesh)**
Tamper-Evident E-Prescription with QR Hash	Yes	No	Yes (Standard PDF)	Yes (Standard PDF)	**Yes (Cryptographic QR & ABDM)**
ABDM / ABHA 14-Digit Health ID Integration	No	No	In-Progress	Partial	**Yes (Native FHIR Schema)**
Cryptographic Payment Escrow Protection	No (Direct Charge)	N/A (Free App)	Direct Payment	Direct Payment	**Yes (Two-Phase Razorpay)**
Strict Separation of AI from Autonomous Rx	No (Attempted Rx)	Yes (Informational)	Yes (Doctor Only)	Yes (Doctor Only)	**Yes (Architectural Firewall)**

VIII. TECHNICAL DELIBERATIONS AND ARCHITECTURAL LIMITATIONS

While empirical evaluations confirm the efficacy of CareSync, several operational constraints warrant technical discussion. First, conversational symptom parsing relies inherently on subjective patient articulation. Pediatric patients, elderly individuals with cognitive impairments, or users expressing symptoms in regional idiomatic dialects may articulate complaints with ambiguous or contradictory clinical terminology.

Second, although CareSync supports photographic dermatological upload, autonomous computer-vision diagnostic inference is intentionally withheld. Consistent with our regulatory framework [6], image artifacts are transmitted directly to the human dermatologist's HUD without automated classification, preventing uncertified AI diagnosis.

Third, peer-to-peer WebRTC mesh architectures, while highly cost-effective and privacy-preserving for one-on-one teleconsultations, become bandwidth-constrained in multi-party clinical conferences (e.g.,

joint patient-specialist-caregiver sessions), which will require transition to Selective Forwarding Units (SFU) in subsequent releases.

IX. CONCLUSION AND FUTURE RESEARCH DIRECTIONS

This paper presented the engineering design, algorithmic formulation, and empirical validation of **CareSync**, an AI-assisted clinical triage, provider recommendation, and teleconsultation platform tailored for developing healthcare infrastructures. By establishing an architectural firewall that confines generative artificial intelligence strictly to conversational symptom ingestion and semantic normalization, CareSync eliminates the severe hazards of medical hallucinations while achieving a 95.7% specialty triage precision and a faultless 100% emergency recall via its Deterministic Crisis Interruption State Machine.

Future work will advance in three strategic directions: (1) integrating quantized multi-dialect voice models supporting Indian regional languages (Hindi, Bengali, Tamil, Telugu) for direct voice-driven intake; (2) incorporating real-time wearable Bluetooth biometric telemetry (photoplethysmography, pulse oximetry, and blood pressure streams) directly into the WebRTC data channel; and (3) deploying federated learning protocols across participating hospitals to continuously refine the $Gamma_{ ext{match}}$ allocation weights without compromising centralized patient privacy.

ACKNOWLEDGMENT

The authors express their profound gratitude to **Ms. Ayasha Malik**, Assistant Professor, Department of Computer Science and Engineering (Data Science), G.L. Bajaj Institute of Technology and Management, Greater Noida, for her invaluable technical supervision, rigorous architectural critiques, and steadfast academic mentorship throughout the inception and development of the CareSync framework.

REFERENCES

[1] W. Wallace, C. Chan, S. Chidambaram, et al., "The diagnostic and triage accuracy of digital and online symptom checker tools: a systematic review," *npj Digital Medicine*, vol. 5, no. 1, p. 118, Aug. 2022.

[2] R. Jeindl and G. Goetz, "Chatbot-based symptom-checkers: A systematic review," *International Journal of Technology Assessment in Health Care*, vol. 38, no. S1, p. S32, Dec. 2022.

[3] M. Milne-Ives, C. de Cock, E. Lim, et al., "The effectiveness of artificial intelligence conversational agents in health care: Systematic review," *Journal of Medical Internet Research*, vol. 22, no. 10, p. e20346, Oct. 2020.

[4] X. Lu, Y. Zhang, J. Li, and S. Zong, "Doctor recommendation in online health forums via expertise learning," in *Proc. IEEE/ACM Int. Conf. Advances in Social Networks Analysis and Mining (ASONAM)*, Nov. 2022, pp. 245–252.

[5] D. Chambers, A. J. Cantrell, M. Johnson, L. Preston, S. K. Baxter, A. Booth, and J. Turner, "Digital and online symptom checkers and health assessment/triage services for urgent health problems: systematic review," *BMJ Open*, vol. 9, no. 8, p. e027743, Aug. 2019.

[6] Ministry of Health and Family Welfare (MoHFW), Government of India, "Telemedicine Practice Guidelines: Enabling Registered Medical Practitioners to Provide Healthcare Using Telemedicine," *The Gazette of India*, New Delhi, India, Mar. 2020.

[7] P. Lewis, E. Perez, A. Piktus, et al., "Retrieval-augmented generation for knowledge-intensive NLP tasks," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 33, Dec. 2020, pp. 9459–9474.

[8] World Health Organization, "Global strategy on digital health 2020–2025," World Health Organization, Geneva, Switzerland, Tech. Rep., 2021.

[9] National Health Authority, Government of India, "Ayushman Bharat Digital Mission (ABDM): Architecture and Strategy Document," New Delhi, India, White Paper, 2022.

[10] C. Holmberg, H. Alvestrand, and C. Jennings, "WebRTC: Real-Time Communication in Browsers," *IEEE Internet Computing*, vol. 25, no. 4, pp. 6–14, Jul.–Aug. 2021.

[11] K. Singhal, S. Azizi, T. Tu, et al., "Large language models encode clinical knowledge," *Nature*, vol. 620, no. 7972, pp. 172–180, Aug. 2023.

[12] H. N. D. Le, A. Tran, and T. Le, "Deep learning-based multi-criteria doctor recommendation system using electronic medical records," in *Proc. IEEE Int. Conf. Bioinformatics and Biomedicine (BIBM)*, Dec. 2021, pp. 1924–1929.

[13] HL7 International, "Fast Healthcare Interoperability Resources (FHIR) Release 4B," Health Level Seven International, Ann Arbor, MI, Standard, 2022.

[14] E. Rescorla, "Datagram Transport Layer Security Version 1.2," RFC 6347, Internet Engineering Task Force (IETF), Jan. 2012.

Manuscript submitted for IEEE Conference Review. Conducted at the Department of Computer Science and Engineering (Data Science), G.L. Bajaj Institute of Technology and Management, Greater Noida, India. *All authors contributed equally to this work. Corresponding email: tushar.jeswani@glbitm.ac.in.