

Assignment Project Exam Help

5QQMN534: Algorithmic Finance

WeChat: cstutorcs

Week4: Data Visualisation

Appendix B: Option Example

Class Definition

- The following presents a class definition for a European call option in the Black-Scholes-Merton (1973) model. The class-based implementation is an alternative to the one based on functions as presented in “Python Script”:

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
#
# Valuation of European call options in Black-Scholes-Merton model
# incl. vega function and implied volatility estimation
# -- class-based implementation
#
# Python for Finance, 2nd ed.
# (c) Dr. Yves J. Hilpisch
#
from math import log, sqrt, exp
from scipy import stats
```

```
class bsm_call_option(object):
    ''' Class for European call options in BSM model.
```

Attributes

=====

```
S0: float
    initial stock/index level
K: float
    strike price
T: float
    maturity (in year fractions)
r: float
    constant risk-free short rate
sigma: float
    volatility factor in diffusion term
```

Methods

=====

```
value: float
    returns the present value of call option
vega: float
    returns the vega of call option
imp_vol: float
    returns the implied volatility given option quote
'''
```

```
def __init__(self, S0, K, T, r, sigma):
    self.S0 = float(S0)
    self.K = K
    self.T = T
    self.r = r
    self.sigma = sigma
```

```
def value(self):
    ''' Returns option value.
    '''
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
    d1 = ((log(self.S0 / self.K) +
           (self.r + 0.5 * self.sigma ** 2) * self.T) /
           (self.sigma * sqrt(self.T)))
    d2 = ((log(self.S0 / self.K) +
           (self.r - 0.5 * self.sigma ** 2) * self.T) /
           (self.sigma * sqrt(self.T)))
    value = (self.S0 * stats.norm.cdf(d1, 0.0, 1.0) -
             self.K * exp(-self.r * self.T) * stats.norm.cdf(d2, 0.0, 1.0))
    return value
```

```
def vega(self):
    ''' Returns vega of option.
    '''
    d1 = ((log(self.S0 / self.K) +
           (self.r + 0.5 * self.sigma ** 2) * self.T) /
           (self.sigma * sqrt(self.T)))
    vega = self.S0 * stats.norm.pdf(d1, 0.0, 1.0) * sqrt(self.T)
    return vega
```

```
def imp_vol(self, C0, sigma_est=0.2, it=100):
    ''' Returns implied volatility given option price.
    '''
    option = bsm_call_option(self.S0, self.K, self.T, self.r, sigma_est)
    for i in range(it):
        option.sigma -= (option.value() - C0) / option.vega()
    return option.sigma
```

Class Usage

- This class can be as follows:

```
In [1]: from bsm_option_class import *
```

```
In [2]: o = bsm_call_option(100., 105., 1.0, 0.05, 0.2)
         type(o)
```

```
Out[2]: bsm_option_class.bsm_call_option
```

```
In [3]: value = o.value()
         value
```

```
Out[3]: 8.021352235143176
```

```
In [4]: o.vega()
```

```
Out[4]: 39.67052380842653
```

```
In [5]: o.imp_vol(C0=value)
```

```
Out[5]: 0.2|
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Visualisation1

- The option class can also be used to visualize, for example, the value and vega of the option for different strikes and maturities. It is, in the end, one of the major advantages of having an analytical option pricing formula available.
- The following Python code generates the option statistics for different maturity-strike combinations:

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
In [6]: import numpy as np
maturities = np.linspace(0.05, 2.0, 20)
strikes = np.linspace(80, 110, 20)
T, K = np.meshgrid(strikes, maturities)
C = np.zeros_like(K)
V = np.zeros_like(C)
for t in enumerate(maturities):
    for k in enumerate(strikes):
        o.T = t[1]
        o.K = k[1]
        C[t[0], k[0]] = o.value()
        V[t[0], k[0]] = o.vega()
```

Visualisation2

- First, a look at the option values. Figure B-1 (next slide) presents the value surface for the European call option:

Assignment Project Exam Help

```
In [7]: from pylab import cm, mpl, plt
        from mpl_toolkits.mplot3d import Axes3D
        mpl.rcParams['font.family'] = 'serif'
        %matplotlib inline
```

```
In [8]: fig = plt.figure(figsize=(12, 7))
```

```
ax = fig.gca(projection='3d')
surf = ax.plot_surface(T, K, C, rstride=1, cstride=1,
                      cmap=cm.coolwarm, linewidth=0.5, antialiased=True)
ax.set_xlabel('strike')
ax.set_ylabel('maturity')
ax.set_zlabel('European call option value')
fig.colorbar(surf, shrink=0.5, aspect=5);
```

<https://tutorcs.com>

WeChat: cstutorcs

Visualisation3




Figure B-1. Value surface for European call option

Visualisation4

- Second, a look at the vega values. Figure B-2 presents the vega surface for the European call option:

```
In [9]: fig = plt.figure(figsize=(12, 7))
        ax = fig.gca(projection='3d')
        surf = ax.plot_surface(T, K, V, rstride=1, cstride=1,
                               cmap=cm.coolwarm, linewidth=0.5, antialiased=True)
        ax.set_xlabel('strike')
        ax.set_ylabel('maturity')
        ax.set_zlabel('Vega of European call option')
        fig.colorbar(surf, shrink=0.5, aspect=5);
```

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs




Figure B-2. Vega surface for European call option