
CIS 471/571 (Fall 2020):
Introduction to Artificial Intelligence
Assignment Project Exam Help

Lecture 5: Constraint Satisfaction Problems
(Part 2)

<https://tutorcs.com>
WeChat: cstutorcs

Thanh H. Nguyen

Source: <http://ai.berkeley.edu/home.html>



Announcements

- Project 1:
 - Deadline: Oct 13th, 2020
 - Homework 2:
 - Deadline: Oct 24th, 2020
 - Will be posted today
- Assignment Project Exam Help
<https://tutorcs.com>
WeChat: cstutorcs

Reminder: CSPs


- CSPs:

- Variables
- Domains
- Constraints
 - Implicit (provide code to compute)
 - Explicit (provide a list of the legal tuples)
 - Unary / Binary / N-ary

Assignment Project Exam Help


<https://tutorcs.com>

WeChat: cstutorcs



- Goals:

- Here: find any solution
- Also: find all, find best, etc.



Backtracking Search

```
function BACKTRACKING-SEARCH(csp) returns solution/failure
  return RECURSIVE-BACKTRACKING({ }, csp)

function RECURSIVE-BACKTRACKING(assignment, csp) returns soln/failure
  if assignment is complete then return assignment
  var ← SELECT-UNASSIGNED-VARIABLE(VARIABLES[csp], assignment, csp)
  for each value in ORDER-DOMAIN-VALUES(var, assignment, csp) do
    if value is consistent with assignment given CONSTRAINTS[csp] then
      add {var = value} to assignment
      result ← RECURSIVE-BACKTRACKING(assignment, csp)
      if result ≠ failure then return result
      remove {var = value} from assignment
  return failure
```




Improving Backtracking

- General-purpose ideas give huge gains in speed
- Filtering: Can we detect inevitable failure early?
 - Arc consistency
 - Forward checking
 - Constraint propagation
- Ordering:
 - Which variable should be assigned next?
 - In what order should its values be tried?
- Structure: Can we exploit the problem structure?


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Example: Map Coloring



Example: Map Coloring

- An arc $X \rightarrow Y$ is **consistent** iff for *every* x in the tail there is *some* y in the head which could be assigned without violating a constraint
- Enforcing consistency of $X \rightarrow Y$: filter values of the tail X to make $X \rightarrow Y$ **consistent**
- Forward checking: Enforcing consistency of arcs pointing to each new assignment



WA


NT

Q

NSW

V

SA





Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example: Map Coloring

- Constraint propagation: enforce arc consistency of entire CSP
 - Maintain a queue of arcs to enforce consistency
- Important: If X loses a value, neighbors of X need to be rechecked!
 - After enforcing consistency on $X \rightarrow Y$, if X loses a value, all arcs pointing to X need to be added back to the queue



WeChat: cstutorcs

Ordering



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Ordering: Minimum Remaining Values

- Variable Ordering: Minimum remaining values (MRV):
 - Choose the variable with the fewest legal left values in its domain


Assignment Project Exam Help



<https://tutorcs.com>

WeChat: cstutorcs

- Why min rather than max?
- Also called “most constrained variable”
- “Fail-fast” ordering



Ordering: Least Constraining Value

- Value Ordering: Least Constraining Value

- Given a choice of variable, choose the *least constraining value*
- I.e., the one that rules out the fewest values in the remaining variables
- Note that it may take some computation to determine this! (E.g., rerunning filtering)



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- Why least rather than most?

- Combining these ordering ideas makes 1000 queens feasible



Structure



Problem Structure


- Extreme case: independent subproblems
 - Example: Tasmania and mainland do not interact

Assignment Project Exam Help


- Independent subproblems are identifiable as connected components of constraint graph

WeChat: cstutorcs

- Suppose a graph of n variables can be broken into subproblems of only c variables:
 - Worst-case solution cost is $O((n/c)(d^c))$, linear in n
 - E.g., $n = 80$, $d = 2$, $c = 20$
 - $2^{80} = 4$ billion years at 10 million nodes/sec
 - $(4)(2^{20}) = 0.4$ seconds at 10 million nodes/sec



Tree-Structured CSPs




- Theorem: if the constraint graph has no loops, the CSP can be solved in $O(n d^2)$ time
 - Compare to general CSPs, where worst-case time is $O(d^n)$



Tree-Structured CSPs


- Algorithm for tree-structured CSPs:
 - Order: Choose a root variable, order variables so that parents precede children



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



- Remove backward: For $i = n : 2$, apply $\text{RemoveInconsistent}(\text{Parent}(X_i), X_i)$
 - Assign forward: For $i = 1 : n$, assign X_i consistently with $\text{Parent}(X_i)$
- Runtime: $O(n d^2)$ (why?)



Tree-Structured CSPs

- Claim 1: After backward pass, all root-to-leaf arcs are consistent
- Proof: Each $X \rightarrow Y$ was made consistent at one point and Y 's domain could not have been reduced thereafter (because Y 's children were processed before Y)

Assignment Project Exam Help




- Claim 2: If root-to-leaf arcs are consistent, forward assignment will not backtrack
- Proof: Induction on position
- Why doesn't this algorithm work with cycles in the constraint graph?
- Note: we'll see this basic idea again with Bayes' nets



Improving Structure



Nearly Tree-Structured CSPs



- Conditioning: instantiate a variable, prune its neighbors' domains
- Cutset conditioning: instantiate (in all ways) a set of variables such that the remaining constraint graph is a tree
- Cutset size c gives runtime $O((d^c)(n-c)d^2)$, very fast for small c




Cutset Conditioning

Choose a cutset

Instantiate the cutset
(all possible ways)


Compute residual CSP
for each assignment

Solve the residual
CSPs (tree structured)



Cutset Quiz



- Find the smallest cutset for the graph below.




Tree Decomposition*

- Idea: create a tree-structured graph of mega-variables
- Each mega-variable encodes part of the original CSP
- Subproblems overlap to ensure consistent solutions

Assignment Project Exam Help



Iterative Improvement



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs




Iterative Algorithms for CSPs

- Local search methods typically work with “complete” states, i.e., all variables assigned
- To apply to CSPs:
 - Take an assignment with unsatisfied constraints
 - Operators *reassign* variable values
 - No fringe! Live on the edge.
- Algorithm: While not solved,
 - Variable selection: randomly select any conflicted variable
 - Value selection: min-conflicts heuristic:
 - Choose a value that violates the fewest constraints
 - I.e., hill climb with $h(n)$ = total number of violated constraints

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Example: 4-Queens



- States: 4 queens in 4 columns ($4^4 = 256$ states)
- Operators: move queen in column
- Goal test: no attacks
- Evaluation: $c(n)$ = number of attacks



Performance of Min-Conflicts



- Given random initial state, can solve n-queens in almost constant time for arbitrary n with high probability (e.g., n = 10,000,000)!

Assignment Project Exam Help

- The same appears to be true for any randomly-generated CSP *except* in a narrow range of the ratio <https://tutorcs.com>

$$R = \frac{\text{number of constraints}}{\text{number of variables}}$$

WeChat: cstutorcs



Summary: CSPs

- CSPs are a special kind of search problem:
 - States are partial assignments
 - Goal test defined by constraints

Assignment Project Exam Help

- Basic solution: backtracking search


<https://tutorcs.com>

- Speed-ups:

- Ordering
- Filtering
- Structure

WeChat: cstutorcs

- Iterative min-conflicts is often effective in practice



Local Search




Local Search

- Tree search keeps unexplored alternatives on the fringe (ensures completeness)
- Local search: improve a single option until you can't make it better (no fringe!)
- New successor function: local changes

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



- Generally much faster and more memory efficient (but incomplete and suboptimal)



Hill Climbing

- Simple, general idea:
 - Start wherever
 - Repeat: move to the best neighboring state
 - If no neighbors better than current, quit
- What's bad about this approach?
 - Complete?
 - Optimal?
- What's good about it?


Assignment Project Exam Help

<https://tutorcs.com>


WeChat: tutorcs



Hill Climbing Diagram



Hill Climbing Quiz



Starting from X, where do you end up ?

Starting from Y, where do you end up ?

Starting from Z, where do you end up ?



Simulated Annealing

- Idea: Escape local maxima by allowing downhill moves
 - But make them rarer as time goes on

```
function SIMULATED-ANNEALING(problem, schedule) returns a solution state
  inputs: problem, a problem
           schedule, a mapping from time to "temperature"
  local variables: current, a node
                   next, a node
                   T, a "temperature" controlling prob. of downward steps

  current ← MAKE-NODE(INITIAL-STATE[problem])
  for t ← 1 to ∞ do
    T ← schedule[t]
    if T = 0 then return current
    next ← a randomly selected successor of current
     $\Delta E \leftarrow \text{VALUE}[\textit{next}] - \text{VALUE}[\textit{current}]$ 
    if  $\Delta E > 0$  then current ← next
    else current ← next only with probability  $e^{\Delta E/T}$ 
```

