

CS 160 Compilers

Lecture 10: Parsing Algorithms

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Yu Feng
Fall 2021


Extend CFGs for program parsing

- CFGs describe the structure of a program
[Assignment Project Exam Help](https://tutorcs.com)
- But we also need this structure in form of a tree, not just a yes/no answer
<https://tutorcs.com>
WeChat: cstutorcs
- **Insight:** We do not need all program structure, only the relevant part
- We call this an *abstract syntax tree (AST)*

ASTs

- Consider the grammar: $E \rightarrow \text{int} \mid (E) \mid E+E$
[Assignment Project Exam Help](https://tutorcs.com)
- And the string: $5 + (2 + 3)$
<https://tutorcs.com>
[WeChat: cstutorcs](#)
- After lexical analysis as string of tokens:
 - $\text{INT}(5) \text{'+' '(' INT}(2) \text{'+' INT}(3) \text{'})$
 - During parsing, we built a parse tree

Example of parse tree




Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- Capture the nesting structure
- But too much information!
- **Example:** We do not care about the parentheses

Example of abstract syntax tree



- Also captures the nesting structure
- But **abstracts** from the concrete syntax
- More compact and easier to use

From CFG to AST

- Each grammar symbol has one attribute
- For terminals (lexer tokens), the attribute is just the token
- Each production has an action computing its resulting attribute
- Written as: $X \rightarrow Y_1 \dots Y_n \{\text{action}\}$

Attribute
Grammar

<https://tutorcs.com>

WeChat: cstutorcs

https://en.wikipedia.org/wiki/Attribute_grammar

An example


- Consider again the grammar: $E \rightarrow \text{int} \mid (E) \mid E + E$
- For each non-terminal on left-hand side, define its value in terms of symbols on right-hand side
- **Recall:** The value of each terminal is just its token
- Assume value of symbol S is given by $S.\text{val}$
- Grammar annotated with actions to compute the AST:

$E \rightarrow \text{int} \quad \{E.\text{val} = \text{int.val}\}$

$E \rightarrow E_1 + E_2 \quad \{E.\text{val} = \text{makeAstPlus}(E_1.\text{val}, E_2.\text{val})\}$

$E \rightarrow (E') \quad \{E.\text{val} = E'.\text{val}\}$


An example



- You can think of semantic actions as defining a system of equations that describe the values of the let-hand sides in terms of values on the right-hand side
- **Question:** What order do we need to evaluate these equations to compute a solution?

Top-Down parsing: the idea

- The parse tree is constructed
 - From the top
 - From left to right
- Terminals are seen in order of appearance in the token stream:
 - $t_2 t_5 t_6 t_8 t_9$



Recursive Descent Parsing

Recursive descent parsing

- Consider the grammar

$$E \rightarrow T \mid T + E$$

$$T \rightarrow \text{int} \mid \text{int} * T \mid (E)$$

- Token stream is: (int₅) <https://tutorcs.com>
- Start with top-level non-terminal E
- Try the rules for E in order

WeChat: cstutorcs

Recursive descent parsing

$$E \rightarrow T \mid T + E$$
$$T \rightarrow \text{int} \mid \text{int} * T \mid (E)$$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

int

*Mismatch: int is not (!
Backtrack ...*

(int₅)




Recursive descent parsing

$$E \rightarrow T \mid T + E$$
$$T \rightarrow \text{int} \mid \text{int} * T \mid (E)$$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs




*Mismatch: int is not (!
Backtrack ...*

(int₅)



Recursive descent parsing

$$E \rightarrow T \mid T + E$$
$$T \rightarrow \text{int} \mid \text{int} * T \mid (E)$$


TODOs by next lecture

- Hw3 will be out.
- Come to the discussion session if you have questions

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs