

Assignment Project Exam Help

Lecture 5

<https://tutorcs.com>

WeChat: cstutorcs

Last Lecture Recap (Pumping Lemma)

L is regular. long string $w \in L$

xz
 \cap
 L

$xyyz$ $xxyyz$ $xyyyyz$ $\dots \in L$.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

$0^i 1^j$ where $i > j$ (Pump Down)

$$L := \{ w \in 0^i 1^j \mid i > j \}$$

$\exists p. > 0$ such that $|w| > p$.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

$$s = 0^{p+1} 1^p \in L$$

Assume L is regular. Then by P.L.

$$s = \underbrace{0 \dots 0}_{p+1} \underbrace{1 \dots 1}_p$$

$xy \quad z \quad p$

$$xz \in L.$$

$$xyyz$$

$$xyyyz$$

\vdots

contradiction
b/c.

$$xz \notin L.$$

Picture Now

Set of all Languages

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

regular

011

011

w same # of 0's 1's

ww

Regular Language Recap

- DFA , NFA (equivalent)
- Languages accepted by these machines (DFA) is called regular .
Can show that
- L is not regular via Pumping Lemma
 \hookrightarrow there are lots of them .

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Why Regular Language is not so powerful ?

Motivation : Mathematically define Computation

Result : Failure (DFA/NFA)

Cannot even do simple tasks.

WeChat: cstutorcs

Assignment Project Exam Help

<https://tutorcs.com>

Turing Machine

WeChat: cstutorcs

Main Restriction of DFA/NFA

Finite # of states

⇒ only remember few things (finitely many things)
about your input.

<https://tutorcs.com>

could have been avoided if the machine
could "write" in some sense.

But only moves right?



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Historical Context : Define Computation


Alan Turing 1920s. : Turing Machine → Define Computation .

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

A tape (with input)



Head


- access to reading the content of the tape
- ~~AA~~ Write contents to the tape.
- move left / right / stay still.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Transition Function (δ) .



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

$$\delta : \underbrace{\Sigma}_{\text{input alphabet}} \times \underbrace{Q}_{\text{current state}} \longrightarrow \underbrace{Q}_{\text{next state}} \times \underbrace{\{L, R, \text{\$}\}}_{\substack{\text{movement} \\ \text{of the} \\ \text{head}}} \times \underbrace{\Sigma}_{\text{output alphabet}}$$

$Q \cup \{\text{\$}\}$ must be finite .

Accept / Reject

• $q_{\text{accept}} \in Q$.

If the machine transitions into q_{accept} then the machine halts & accepts.

Assignment Project Exam Help

<https://tutorcs.com>

• $q_{\text{reject}} \in Q$.

WeChat: cstutorcs

"

q_{reject} ,

"

rejects.


Final Definition of T.M.

$(\Sigma, Q, \{q_{\text{accept}}, q_{\text{reject}}, q_0\}, \delta)$ → transition function .
↪ initial state

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Example T.M.

$L(M) :=$ the set of inputs
accepted by T.M. M .

$$L = \{ w \# w \mid w \in \{0,1\}^* \}$$

EXAMPLE 3.9

The following is a formal description of $M_1 = (Q, \Sigma, \Gamma, \delta, q_1, q_{\text{accept}}, q_{\text{reject}})$, the Turing machine that we informally described (page 167) for deciding the language $B = \{w\#w \mid w \in \{0,1\}^*\}$.

- $Q = \{q_1, \dots, q_8, q_{\text{accept}}, q_{\text{reject}}\}$,
- $\Sigma = \{0,1,\#\}$, and $\Gamma = \{0,1,\#,x,\sqcup\}$.
- We describe δ with a state diagram (see the following figure).
- The start, accept, and reject states are q_1 , q_{accept} , and q_{reject} , respectively.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs




FIGURE 3.10

State diagram for Turing machine M_1

In class exercise ($0^n 1^n$)

① Either you can count

② Modify the previous T.M.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Language of T.M. M

↳ the set of inputs accepted by the T.M. M .

$L(M)$. Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Turing Decidable

L is Turing Decidable if \exists T.M. M .

which accepts w if $w \in L$, $L(M) = L$.

rejects w if $w \notin L$.

WeChat: cstutorcs

Turing Recognizable

L is Turing Recognizable if

$w \in L$

M accepts w .

$w \notin L$.


reject / infinite loop.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

What's the difference ?



Essentially All computation tasks

- C.T. Thesis : Every computational models are equivalent to Turing Machine

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs