

## ARCH\_share

July 22, 2021

### Importing packages

```
[61]: #importing packages
import statsmodels.api as sm
from statsmodels.tsa.stattools import adfuller
import pandas as pd
import numpy as np
import statsmodels.formula.api as smf
from sklearn import linear_model
import matplotlib.pyplot as plt
```

### Reading Excel file saved in hard drive

```
[62]: #reading the file
df = pd.read_excel("C:\\Users\\rluc\\OneDrive\\share.xlsx")
df
```

```
[62]:
```

	OBS	PRICE
0	1	975.04
1	2	977.07
2	3	966.58
3	4	964.00
4	5	956.05
..	...	...
989	990	1144.80
990	991	1170.35
991	992	1167.10
992	993	1158.31
993	994	1139.93

[994 rows x 2 columns]

### Calculating daily returns and daily squared returns from SP500

Daily returns (R)

$$R = 100 * \ln(P_t / P_{t-1})$$

Daily squared returns ( $R^2$ )

$$R = R^2$$

```
[63]: #computing the inflation rate
df['R'] = 100*np.log(df['PRICE']/df['PRICE'].shift(1))
df['R_squared'] = df['R']**2
df = df.dropna(subset=['R'])
df
```


```
[63]:
```

	OBS	PRICE	R	R_squared
1	2	977.07	0.207980	0.043256
2	3	966.58	-1.079423	1.165154
3	4	964.00	-0.267277	0.071437
4	5	956.05	-0.828108	0.685763
5	6	927.69	-3.011259	9.067679
..	...	...	...	...
989	990	1144.80	1.310082	1.716314
990	991	1170.35	2.207290	4.872129
991	992	1167.10	-0.278081	0.077329
992	993	1158.31	-0.755999	0.571535
993	994	1139.93	-1.599519	2.558461


[993 rows x 4 columns]

\$Plotting the time series:  $R$  and  $R^2$

```
[64]: #plotting the R series
plt.plot(df['R'],label='R')
plt.legend(loc='best', fontsize='large')
plt.show()
```




```
[65]: #plotting the R_squared series
plt.plot(df['R_squared'],label='R_squared',color='Red')
plt.legend(loc='best', fontsize='large')
plt.show()
```



WeChat: cstutorcs

Histogram and descriptive statistics

```
[66]: #Plot histogram of R
plt.hist(df['R'],bins=120,label='R', density=True, alpha=0.6, color='b')
plt.legend(loc='best', fontsize='large')
plt.show()
```



## Assignment Project Exam Help


```
[67]: from scipy import stats
stats.describe(df['R'])
```

```
[67]: DescribeResult(nobs=993, minmax=(-7.043759037302043, 4.964596183505854),
mean=0.01573450555862576, variance=1.694877827267905,
skewness=-0.1468232170367387, kurtosis=3.1016094075647234)
```

```
[68]: stats.jarque_bera(df['R'])
```

```
[68]: Jarque_beraResult(statistic=171.7419793855507, pvalue=0.0)
```

```
[69]: #Plot histogram of R_squared
plt.hist(df['R_squared'],bins=120,label='R_squared', density=True, alpha=0.6,
        color='b')
plt.legend(loc='best', fontsize='large')
plt.show()
```



## Assignment Project Exam Help

```
[70]: stats.describe(df['R_squared'])
```


```
[70]: DescribeResult(nobs=993, minmax=(0.0, 49.614541375574206),
mean=1.693418576326566, variance=11.506356201573688, skewness=6.16939777089506,
kurtosis=59.64692480452559)
```

```
[71]: stats.jarque_bera(df['R_squared'])
```

```
[71]: Jarque_beraResult(statistic=153501.31264418407, pvalue=0.0)
```

ACF , PACF of R


```
[72]: from statsmodels.graphics import tsaplots
fig =tsaplots.plot_acf(df['R'],lags=16)
fig =tsaplots.plot_pacf(df['R'],lags=16)
plt.show()
```



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



```
[73]: # Generating the Q tables
import numpy as np
r,q,p = sm.tsa.acf(df['R'].values.squeeze(), qstat=True)
data = np.c_[range(1,41), r[1:], q, p]
table = pd.DataFrame(data, columns=['lag', "AC", "Q", "Prob(>Q)"])
print (table.set_index('lag'))
```

lag	AC	Q	Prob(>Q)
1.0	0.002187	0.004765	0.944967
2.0	-0.044549	1.983469	0.370933
3.0	-0.042759	3.808159	0.282939
4.0	0.036575	5.144571	0.272783
5.0	-0.068961	9.900359	0.078108
6.0	-0.019748	10.290740	0.112930
7.0	-0.001411	10.292735	0.172582
8.0	-0.019274	10.665353	0.221391
9.0	-0.019877	11.062067	0.271479
10.0	0.014334	11.268578	0.336980
11.0	-0.054077	11.310889	0.231543
12.0	0.077208	20.214671	0.063133
13.0	0.059358	23.766889	0.033343
14.0	-0.008254	23.835639	0.047960
15.0	0.039619	25.421126	0.044542
16.0	-0.040201	27.055817	0.040867
17.0	0.014268	27.261915	0.054337
18.0	-0.057071	30.552506	0.032324
19.0	0.021465	31.029858	0.040039
20.0	-0.010472	31.141257	0.053353
21.0	-0.054597	34.171259	0.034738
22.0	-0.015008	34.400460	0.044705
23.0	0.028022	35.200283	0.049681
24.0	0.036951	36.592496	0.048029
25.0	-0.033563	37.742296	0.049009
26.0	0.017079	38.040350	0.060041
27.0	0.082436	44.991090	0.016296
28.0	0.001189	44.992538	0.022101
29.0	0.017297	45.299169	0.027513
30.0	-0.000220	45.299219	0.036196
31.0	0.004336	45.318524	0.046688
32.0	-0.053556	48.267405	0.032500
33.0	-0.040998	49.997358	0.029234
34.0	-0.089707	58.288305	0.005893
35.0	-0.037434	59.733514	0.005697
36.0	0.025398	60.399493	0.006620
37.0	-0.010012	60.503099	0.008705
38.0	-0.001130	60.504421	0.011575
39.0	0.057283	63.902786	0.007182

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
40.0 -0.073371 69.484020 0.002633
```

```
C:\Users\rluck\anaconda3\lib\site-packages\statsmodels\tsa\stattools.py:657:  
FutureWarning: The default number of lags is changing from 40 to min(int(10 *  
np.log10(nobs)), nobs - 1) after 0.12 is released. Set the number of lags to an  
integer to silence this warning.
```

```
warnings.warn(  

```


```
C:\Users\rluck\anaconda3\lib\site-packages\statsmodels\tsa\stattools.py:667:  
FutureWarning: fft=True will become the default after the release of the 0.12  
release of statsmodels. To suppress this warning, explicitly set fft=False.
```

```
warnings.warn(  


```

\$ACF , PACF of  $R^2$ \$

```
[74]: fig = tsaplots.plot_acf(df['R_squared'],lags=16)  
fig = tsaplots.plot_pacf(df['R_squared'],lags=16)  
plt.show()
```







Assignment Project Exam Help

[75]: `# Generating the Q table.`  
`import numpy as np`  
`r,q,p = sm.tsa.acf(df['R_squared'].values.squeeze(), qstat=True)`  
`data = np.c_[range(1, #1), r[1:], q, p]`  
`table = pd.DataFrame(data, columns=['lag', 'R', 'Q', 'Prob(>Q)'])`  
`print (table.set_index('lag'))`

	AC	Q	Prob(>Q)
lag			
1.0	0.116401	13.495026	2.391966e-04
2.0	0.137366	32.307886	9.647874e-08
3.0	0.045022	34.330823	1.686854e-07
4.0	0.043314	36.205092	2.625763e-07
5.0	0.163064	62.795866	3.208813e-12
6.0	0.055033	65.827678	2.922824e-12
7.0	0.088429	73.663464	2.678057e-13
8.0	0.072519	78.938732	7.992968e-14
9.0	0.026248	79.630526	1.913609e-13
10.0	0.051198	82.265203	1.803486e-13
11.0	0.065028	86.519895	7.988149e-14
12.0	0.041676	88.269223	1.067025e-13
13.0	-0.014482	88.480668	2.726470e-13
14.0	0.010197	88.585610	7.015944e-13
15.0	0.001769	88.588769	1.817136e-12
16.0	0.091960	97.140862	1.186384e-13

17.0	0.036990	98.525997	1.667347e-13
18.0	0.072813	103.898575	4.253523e-14
19.0	0.076362	109.813725	8.627403e-15
20.0	0.020351	110.234269	1.780030e-14
21.0	0.110912	122.738581	2.240937e-16
22.0	0.050038	125.286355	1.894182e-16
23.0	-0.001192	125.287803	4.611835e-16
24.0	0.044396	127.297499	4.775153e-16
25.0	0.003592	127.310670	1.115576e-15
26.0	0.028843	128.160663	1.814862e-15
27.0	0.082465	135.116334	2.425735e-16
28.0	0.026399	135.829855	4.136894e-16
29.0	-0.004892	135.854381	9.184485e-16
30.0	-0.007907	135.918535	1.972095e-15
31.0	0.009156	136.004633	4.128389e-15
32.0	0.079173	142.449347	6.937586e-16
33.0	0.006087	142.487482	1.465969e-15
34.0	-0.039022	144.056309	1.678684e-15
35.0	-0.018729	144.418079	3.052000e-15
36.0	-0.038157	145.929177	3.321024e-15
37.0	-0.025003	146.575300	5.624595e-15
38.0	-0.043604	148.542369	5.383179e-15
39.0	-0.014147	148.749640	9.993128e-15
40.0	-0.042500	150.621304	9.812320e-15

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

```
C:\Users\rluck\anaconda3\lib\site-packages\statsmodels\tsa\stattools.py:657:
FutureWarning: The default number of lags is changing from 40 to min(int(10 *
np.log10(nobs)), nobs-1) after 0.12 is released. Set the number of lags to an
integer to silence this warning.
```

```
warnings.warn(
C:\Users\rluck\anaconda3\lib\site-packages\statsmodels\tsa\stattools.py:667:
FutureWarning: fft=True will become the default after the release of the 0.12
release of statsmodels. To suppress this warning, explicitly set fft=False.
warnings.warn(
```

ARCH(5)

```
[76]: from arch import arch_model
```

```
[77]: dt = df['R']
model = arch_model(dt, mean = 'Constant', vol = 'ARCH', q=5)
x_5 = model.fit(update_freq=0)
x_5
```

```
Optimization terminated successfully      (Exit mode 0)
Current function value: 1664.047869085027
Iterations: 5
Function evaluations: 28
Gradient evaluations: 5
```

[77]:

#### Constant Mean - ARCH Model Results

```
=====
Dep. Variable:          R    R-squared:          0.000
Mean Model:           Constant Mean    Adj. R-squared:          0.000
Vol Model:            ARCH    Log-Likelihood:        -1664.05
Distribution:         Normal    AIC:              3334.10
Method:             Maximum Likelihood    BIC:              3348.80
                                     No. Observations:          993
Date:                Thu, Jul 22 2021    Df Residuals:          992
Time:                20:04:12    Df Model:              1
                                     Mean Model
=====
```

```
=====
              coef      std err          t      P>|t|     95.0% Conf. Int.
-----
mu              0.0293   4.132e-02     0.709     0.478  [-5.170e-02,  0.110]
=====
```

#### Volatility Model

```
=====
              coef      std err          t      P>|t|     95.0% Conf. Int.
-----
omega          1.5238   0.104     14.654  1.266e-28  [ 1.324,  1.733]
alpha[1]        0.0963   4.954e-02     1.944   5.194e-02  [-8.088e-04,  0.193]
=====
```

Covariance estimator: robust  
ARCHModelResult, id: 0x21914bdbbe20

[78]:

```
#Aligning AIC, BIC from Python with Stata's AIC, BIC
n = 993
name = ['AIC_stata', 'BIC_stata']
stata=[x_5.aic/n,x_5.bic/n]
lzip(name, stata)
```

[78]: [('AIC\_stata', 3.357598930684848), ('BIC\_stata', 3.3724047635067365)]

#### ARCH Test

[79]:

```
from statsmodels.stats.diagnostic import het_arch
from statsmodels.compat import lzip
res = het_arch(dt.values, nlags=5)
name = ['lm', 'lm_pval', 'fval', 'f_pval']
lzip(name, res)
```

[79]: [('lm', 52.586810853630816),  
 ('lm\_pval', 4.0887029149590036e-10),  
 ('fval', 11.041163168843253),  
 ('f\_pval', 2.3131694315533897e-10)]


#### ARCH Test of Standardised Residuals

```
[80]: std_resid = x_5.resid/x_5.conditional_volatility
      res = het_arch(std_resid, nlags=5)
      name = ['lm', 'lm_pval', 'fval', 'f_pval']
      lzip(name, res)
```

```
[80]: [('lm', 44.61654794255047),
      ('lm_pval', 1.7360584950680533e-08),
      ('fval', 9.2885771918154),
      ('f_pval', 1.1768118600559285e-08)]
```

### Histogram of Residuals

```
[81]: #Histogram of residuals
      resid = x_5.resid
      plt.hist(resid, bins=120, label='Resid', density=True, alpha=0.6, color='b')
      plt.legend(loc='best', fontsize='large')
      plt.show()
```



```
[82]: stats.describe(resid)
```


```
[82]: DescribeResult(nobs=993, minmax=(-7.073049296466991, 4.9353059243409065),
      mean=-0.013555753606322416, variance=1.694877827267905,
      skewness=-0.1468232170367387, kurtosis=2.016094075647234)
```


```
[83]: stats.jarque_bera(resid)
```

[83]: Jarque\_beraResult(statistic=171.7419793855507, pvalue=0.0)

#### ACF , PACF of Squared Residuals

```
[84]: fig = tsaplots.plot_acf(resid**2,lags=16)  
fig = tsaplots.plot_pacf(resid**2,lags=16)  
plt.show()
```






Assignment Project Exam Help

Histogram of Standardised Residuals

<https://tutorcs.com>

```
[85]: #Histogram of std residuals
plt.hist(std_resid,bins=120,label='Std_Resid', density=True, alpha=0.6,
        color='b')
plt.legend(loc='best', fontsize='large')
plt.show()
```

WeChat: cstutorcs



## Assignment Project Exam Help

```
[86]: stats.describe(std_resid)
```


```
[86]: DescribeResult(nobs=993, minmax=(-5.343797790419605, 3.8965888804733484),
mean=-0.014086543542439298, variance=1.0008098057706427,
skewness=-0.17614610401990488, kurtosis=1.8124982770599578)
```

```
[87]: stats.jarque_bera(std_resid)
```

```
[87]: Jarque_beraResult(statistic=141.05812439839767, pvalue=0.0)
```


### ACF , PACF of Squared Std Residuals

```
[88]: fig = tsaplots.plot_acf(std_resid**2,lags=16)
fig = tsaplots.plot_pacf(std_resid**2,lags=16)
plt.show()
```



Assignment Project Exam Help

<https://tutorcs.com>



WeChat: cstutorcs

Choosing the ARCH lags



```
[89]: #Running ARCH from p=1 to p =9
model_1 = arch_model(dt,mean = 'Constant', vol = 'ARCH', p=1)
model_2 = arch_model(dt,mean = 'Constant', vol = 'ARCH', p=2)
model_3 = arch_model(dt,mean = 'Constant', vol = 'ARCH', p=3)
model_4 = arch_model(dt,mean = 'Constant', vol = 'ARCH', p=4)
model_5 = arch_model(dt,mean = 'Constant', vol = 'ARCH', p=5)
model_6 = arch_model(dt,mean = 'Constant', vol = 'ARCH', p=6)
model_7 = arch_model(dt,mean = 'Constant', vol = 'ARCH', p=7)
model_8 = arch_model(dt,mean = 'Constant', vol = 'ARCH', p=8)
model_9 = arch_model(dt,mean = 'Constant', vol = 'ARCH', p=9)
x_1= model_1.fit(update_freq=0)
x_2= model_2.fit(update_freq=0)
x_3= model_3.fit(update_freq=0)
x_4= model_4.fit(update_freq=0)
x_5= model_5.fit(update_freq=0)
x_6= model_6.fit(update_freq=0)
x_7= model_7.fit(update_freq=0)
x_8= model_8.fit(update_freq=0)
x_9= model_9.fit(update_freq=0)
```

```
Optimization terminated successfully (Exit mode 0)
Current function value: 1664.047869085027
Iterations: 5
Function evaluations: 28
Gradient evaluations: 5
Optimization terminated successfully (Exit mode 0)
Current function value: 1651.3667967409056
Iterations: 8
Function evaluations: 49
Gradient evaluations: 8
Optimization terminated successfully (Exit mode 0)
Current function value: 1650.803109203952
Iterations: 12
Function evaluations: 83
Gradient evaluations: 12
Optimization terminated successfully (Exit mode 0)
Current function value: 1645.3224422301862
Iterations: 13
Function evaluations: 104
Gradient evaluations: 13
Optimization terminated successfully (Exit mode 0)
Current function value: 1639.433689366865
Iterations: 15
Function evaluations: 135
Gradient evaluations: 15
Optimization terminated successfully (Exit mode 0)
Current function value: 1638.5159772755142
Iterations: 15
```

```

Function evaluations: 153
Gradient evaluations: 15
Optimization terminated successfully (Exit mode 0)
Current function value: 1635.51431460451
Iterations: 15
Function evaluations: 170
Gradient evaluations: 15
Optimization terminated successfully (Exit mode 0)
Current function value: 1631.19776764798
Iterations: 17
Function evaluations: 209
Gradient evaluations: 17
Optimization terminated successfully (Exit mode 0)
Current function value: 1631.1128849200488
Iterations: 20
Function evaluations: 264
Gradient evaluations: 20

```

```

[90]: #Computing the AIC (AIC_stata= AIC_Python/ no of obs)
n = 993
aic=[x_1.aic/n,x_2.aic/n,x_3.aic/n,x_4.aic/n,x_5.aic/n,x_6.aic/n,x_7.aic/n,x_8.
    ↪aic/n,x_9.aic/n]
bic= [x_1.bic/n,x_2.bic/n,x_3.bic/n,x_4.bic/n,x_5.bic/n,x_6.bic/n,x_7.bic/n,x_8.
    ↪bic/n,x_9.bic/n]
name_
    ↪=['ARCH_1','ARCH_2','ARCH_3','ARCH_4','ARCH_5','ARCH_6','ARCH_7','ARCH_8','ARCH_9']
lzip(name,aic, bic)

```

```

[90]: [('ARCH_1', 3.357598930684848, 3.3724047635067365),
      ('ARCH_2', 3.334072098168994, 3.3538132085981793),
      ('ARCH_3', 3.3349508745296115, 3.359627262566093),
      ('ARCH_4', 3.325926369043678, 3.3555380346874557),
      ('ARCH_5', 3.316079938301843, 3.350626881552917),
      ('ARCH_6', 3.3162456742709248, 3.3557278951292946),
      ('ARCH_7', 3.31221412810576, 3.3566316265714264),
      ('ARCH_8', 3.305534275222518, 3.35488705129548),
      ('ARCH_9', 3.3073774117221526, 3.361665465402411)]

```

```

[91]: #Defining Conditional_Variance as squared conditional volatility from ARCH(5)
    ↪which was defined as x_5 beforehand
conditional_variance = x_5.conditional_volatility**2


```

```

[92]: #Plotting the R and Conditional Variance from ARCH(5)
dt.plot(figsize=(12,5), color='red',label='R')
conditional_variance.plot(figsize=(12,5),color='blue',label='cond_variance')
plt.title('ARCH (5) Conditional Variance', size=15)
plt.legend(loc='best', fontsize='large')

```

```
plt.show()
```



[ ]: Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs