

ECS656U/ECS796P

Assignment Project Exam Help

Distributed Systems

<https://tutorcs.com>

WeChat: cstutorcs

What this lecture is about

- Joining/Leaving in DHTs
- Key-Value store
- Memcached

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

(thanks to prof. Stoica)

What have we seen so far?

- P2P networks introduction

Assignment Project Exam Help

- Three basic architectures for locating and distributing content

<https://tutorcs.com>

- Centralized directory (Napster, early BitTorrent)

- Query flooding (Gnutella)

WeChat: cstutorcs

- Hierarchical and non-hierarchical overlay designs (Kazaa, BT DHT)

- We finished looking at DHTs and how to locate content

This was the last slide: Chord (finger tables) analysis on lookup


Each node stores a subset of successors:

- $O(\log N)$ memory


The search space is halved at each hop:

- $O(\log N)$ communication

More robust: unless the authority peer of the key ID fails, lookup operations work correctly



The fundamentals of P2P: the Chord example




Chord: joining the network

A peer that wants to join the DHT:

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs




Chord: joining the network

A peer that wants to join the DHT:

- computes its own *id*
- computes its own *finger table*

i	key id	successor
0	$2 + 2^0 \bmod 64 = 3$?
1	$2 + 2^1 \bmod 64 = 4$?
2	$2 + 2^2 \bmod 64 = 6$?
3	$2 + 2^3 \bmod 64 = 14$?
4	$2 + 2^4 \bmod 64 = 30$?
5	$2 + 2^5 \bmod 64 = 46$?




Chord: joining the network

A peer that wants to join the DHT:

- computes its own *id*
- computes its own *finger table*

i	key id	successor
0	$2 + 2^0 \bmod 64 = 3$	peer 4
1	$2 + 2^1 \bmod 64 = 4$?
2	$2 + 2^2 \bmod 64 = 6$?
3	$2 + 2^3 \bmod 64 = 14$?
4	$2 + 2^4 \bmod 64 = 30$?
5	$2 + 2^5 \bmod 64 = 46$?




Chord: joining the network

A peer that wants to join the DHT:

- computes its own *id*
- computes its own *finger table*


i	key id	successor
0	$2 + 2^0 \bmod 64 = 3$	peer 4
1	$2 + 2^1 \bmod 64 = 4$	peer 4
2	$2 + 2^2 \bmod 64 = 6$	peer 4
3	$2 + 2^3 \bmod 64 = 14$	peer 2
4	$2 + 2^4 \bmod 64 = 30$	peer 3
5	$2 + 2^5 \bmod 64 = 46$	peer 6



Chord: joining the network

A peer that wants to join the DHT:


- computes its own *id*
- computes its own finger table
- ask any peer who has authority over *id*



Chord: joining the network

A peer that wants to join the DHT:

- computes its own *id*
- computes its own finger table
- ask any peer who has authority over *id*



Assignment Project Exam Help


<https://tutorcs.com>

WeChat: cstutorcs

Chord: joining the network

A peer that wants to join the DHT:

- computes its own *id*
- computes its own **finger table**
- ask any peer who has authority over *id*
- Trigger updates of the others' tables without creating anomalies!



Chord: joining the network


Steps to trigger update:

- Notify succ/pred pointers

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Chord: joining the network


Steps to trigger update:

- Notify succ/pred pointers

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Chord: joining the network


Steps to trigger update:

- Notify succ/pred pointers

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Chord: joining the network


Steps to trigger update:

- Notify succ/pred pointers

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Chord: joining the network


Steps to trigger update:

- Notify succ/pred pointers

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Chord: joining the network


Steps to trigger update:

- Notify succ/pred pointers

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Chord: joining the network


Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping

Assignment Project Exam Help

<https://tutorcs.com>


WeChat: cstutorcs



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs


Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Notes:

- Peer 7 has authority over [61,2]
- Finger table has 6 entries ($0 < i < 5$)
- $i = 5$ means $\text{Peer}_{\text{ID}} + 2^5 = \text{Peer}_{\text{ID}} + 32$
- Who are the Peers that might fall in Peer 7 authority field for $i = 5$?



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Notes:

- Peer 7 has authority over [61,2]
- Finger table has 6 entries ($0 < i < 5$)
- $i = 5$ means $\text{Peer}_{\text{ID}} + 2^5 = \text{Peer}_{\text{ID}} + 32$
- Who are the Peers that might fall in Peer 7 authority field for $i = 5$?



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Notes:

- Peer 7 has authority over [61,2]
- Finger table has 6 entries ($0 < i < 5$)
- $i = 5$ means $\text{Peer}_{\text{ID}} + 2^5 = \text{Peer}_{\text{ID}} + 32$
- Who are the Peers that might fall in Peer 7 authority field for $i = 5$?




Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Notes:

- Peer 7 has authority over (61,2)
- Finger table has 6 entries ($0 < i < 5$)
- $i = 5$ means $\text{Peer}_{ID} + 2^5 = \text{Peer}_{ID} + 32$
- Who are the Peers that might fall in Peer 7 authority field for $i = 5$?




Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Notes:

- Peer 7 has authority over (61,2)
- Finger table has 6 entries ($0 < i < 5$)
- $i = 5$ means $\text{Peer}_{\text{ID}} + 2^5 = \text{Peer}_{\text{ID}} + 32$
- Who are the Peers that might fall in Peer 7 authority field for $i = 5$?



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Message:

update(target= 32, new-peer=2)



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


i	key id	successor
0	$32 + 2^0 \bmod 64 = 33$	peer 1
1	$32 + 2^1 \bmod 64 = 34$	peer 1
2	$32 + 2^2 \bmod 64 = 36$	peer 1
3	$32 + 2^3 \bmod 64 = 40$	peer 1
4	$32 + 2^4 \bmod 64 = 48$	peer 6
5	$32 + 2^5 \bmod 64 = 0$	peer 4

peer 3

← to update

Message:

update(target= 32, new-peer=2)



Chord: joining the network


Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

i	key id	successor
0	$32 + 2^0 \bmod 64 = 33$	peer 1
1	$32 + 2^1 \bmod 64 = 34$	peer 1
2	$32 + 2^2 \bmod 64 = 36$	peer 1
3	$32 + 2^3 \bmod 64 = 40$	peer 1
4	$32 + 2^4 \bmod 64 = 48$	peer 6
5	$32 + 2^5 \bmod 64 = 0$	peer 7

peer 3

Message:
update(target= 32, new-peer=2)



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs


Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Notes:

- Now Peer 3 is fine!
- But, Peer 2 might not be!




Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
 - Safe to move resource mapping
 - Now? Trigger finger tables update for the other peers!
- <https://>

Notes:

- Now Peer 3 is fine!
- But, Peer 2 might not be!
- Peer 3 sends a message to Peer 2 to warn a potential Finger table update!



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>


WeChat: cstutorcs

i	key id	successor
0	$16 + 2^0 \bmod 64 = 17$	peer 3
1	$16 + 2^1 \bmod 64 = 18$	peer 3
2	$16 + 2^2 \bmod 64 = 20$	peer 3
3	$16 + 2^3 \bmod 64 = 24$	peer 3
4	$16 + 2^4 \bmod 64 = 32$	peer 3
5	$16 + 2^5 \bmod 64 = 48$	peer 6

peer 2



no update needed



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Notes:

- The case $i = 5$ now completed!!!
- What about $i = 4$ now?
- $i = 4$ means $\text{Peer}_{\text{ID}} + 2^4 = \text{Peer}_{\text{ID}} + 16$
- Who are the Peers that might fall in Peer 7 authority field for $i = 4$?



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Notes:

- The case $i = 5$ now completed!!!
- What about $i = 4$ now?
- $i = 4$ means $\text{Peer}_{\text{ID}} + 2^4 = \text{Peer}_{\text{ID}} + 16$
- Who are the Peers that might fall in Peer 7 authority field for $i = 4$?



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Notes:

- The case $i = 5$ now completed!!!
- What about $i = 4$ now?
- $i = 4$ means $\text{Peer}_{\text{ID}} + 2^4 = \text{Peer}_{\text{ID}} + 16$
- Who are the Peers that might fall in Peer 7 authority field for $i = 4$?



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Notes:

- The case $i = 5$ now completed!!!
- What about $i = 4$ now?
- $i = 4$ means $\text{Peer}_{\text{ID}} + 2^4 = \text{Peer}_{\text{ID}} + 16$
- Who are the Peers that might fall in Peer 7 authority field for $i = 4$?




Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Notes:

- The case $i = 5$ now completed!!!
- What about $i = 4$ now?
- $i = 4$ means $\text{Peer}_{\text{ID}} + 2^4 = \text{Peer}_{\text{ID}} + 16$
- Who are the Peers that might fall in Peer 7 authority field for $i = 4$?



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Notes:

- The case $i = 5$ now completed!!!
- What about $i = 4$ now?
- $i = 4$ means $\text{Peer}_{\text{ID}} + 2^4 = \text{Peer}_{\text{ID}} + 16$
- Who are the Peers that might fall in Peer 7 authority field for $i = 4$?



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Notes:

- The case $i = 5$ now completed!!!
- What about $i = 4$ now?
- $i = 4$ means $\text{Peer}_{\text{ID}} + 2^4 = \text{Peer}_{\text{ID}} + 16$
- Who are the Peers that might fall in Peer 7 authority field for $i = 4$?




Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Message:
update(target= 48, new-peer=2)



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs


i	key id	successor
0	$48 + 2^0 \bmod 64 = 49$	peer 5
1	$48 + 2^1 \bmod 64 = 50$	peer 5
2	$48 + 2^2 \bmod 64 = 52$	peer 5
3	$48 + 2^3 \bmod 64 = 56$	peer 5
4	$48 + 2^4 \bmod 64 = 0$	peer 4
5	$48 + 2^5 \bmod 64 = 16$	peer 2

peer 6

to update

Message:

update(target= 48, new-peer=2)



Chord: joining the network


Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

i	key id	successor
0	$48 + 2^0 \bmod 64 = 49$	peer 5
1	$48 + 2^1 \bmod 64 = 50$	peer 5
2	$48 + 2^2 \bmod 64 = 52$	peer 5
3	$48 + 2^3 \bmod 64 = 56$	peer 5
4	$48 + 2^4 \bmod 64 = 0$	peer 7
5	$48 + 2^5 \bmod 64 = 16$	peer 2

peer 6

Message:
update(target= 48, new-peer=2)




Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Notes:

- Now Peer 6 is fine!
- But, Peer 1 might not be!




Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Notes:

- Now Peer 6 is fine!
- But, Peer 1 might not be!
- Peer 6 sends a message to Peer 1 to warn a potential Finger table update!



Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!


Assignment Project Exam Help

<https://tutorcs.com>


WeChat: cstutorcs

peer 1

i	key id	successor
0	$40 + 2^0 \bmod 64 = 41$	peer 6
1	$40 + 2^1 \bmod 64 = 42$	peer 6
2	$40 + 2^2 \bmod 64 = 44$	peer 6
3	$40 + 2^3 \bmod 64 = 48$	peer 6
4	$40 + 2^4 \bmod 64 = 56$	peer 5
5	$40 + 2^5 \bmod 64 = 8$	peer 4



no update needed




Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Notes:

- The cases $i = (5,4)$ now completed!
- What about $i = 3$ now?
- $i = 3$ means $\text{Peer}_{\text{ID}} + 2^3 = \text{Peer}_{\text{ID}} + 8$
- Who are the Peers that might fall in Peer 7 authority field for $i = 3$?




Chord: joining the network

Steps to trigger update:

- Notify succ/pred pointers
- Safe to move resource mapping
- Now? Trigger finger tables update for the other peers!

Notes:

- The cases $i = (5,4)$ not completed!
- What about $i =$
- $i = 3$ means $\text{Peer}_{ID} + 8$
- Who is the peer that might fall in Peer 7's responsibility field for $i = 3$?



Assignment Project Exam Help

<https://tutorcs.com>


WeChat: cstutorcs

This is an iterative process!!

DHT recap

- DHT is a class of a decentralized distributed system that provides a lookup service like a hash table. (key, value) pairs are stored in a DHT

- Keys are unique identifiers which map to values, which in turn can be anything from addresses, to documents, to arbitrary data.



DHT recap

- DHTs can form the infrastructure that can be used to build complex services like P2P


- WARNING: not only that!

- Do not associate DHT to only P2P!

Assignment Project Exam Help

<https://tutorcs.com>


WeChat: cstutorcs



DHT recap

- It is an approach for Key-Value store --> The value is stored in a database in the form of a two-value tuple. One is the identifier(key) and other is the actual data(Value), and hence It is called as Key Value store.

<https://tutorcs.com>



The key-value abstraction

- (twitter.com): user ID --> user profile (e.g., posting history, photos, friends..)
- (amazon.com): item number --> information about it
- (kayak.com): flight number --> information about flight (e.g., availability)
- (yourbank.com): account number --> information about it

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

The key-value abstraction (cont'd)

- It's a dictionary data-structure
- But distributed. (Too much data, you can maintain them in a single server)
Assignment Project Exam Help
<https://tutorcs.com>
- Sound familiar? Here the connection with DHTs!
WeChat: cstutorcs
- It is not surprising that key-value stores reuse many techniques from DHTs


Too much data to maintain in a single server

Key Idea: partition set of key-values across many machines

Assignment Project Exam Help


<https://tutorcs.com>

WeChat: cstutorcs



Challenges

- **Fault Tolerance:** handle machine failures without losing data and without degradation in performance
- **Scalability:**
 - Need to scale to thousands of machines
 - Need to allow easy addition of new machines
- **Consistency:** maintain data consistency in face of node failures and message losses




Directory-based architecture: recursive query

- Have a node maintain the mapping between **keys** and the **machines (nodes)** that store the **values** associated with the **keys**.
- Having the master to relay the requests

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Directory-based architecture: recursive query


- Have a node maintain the mapping between **keys** and the **machines (nodes)** that store the **values** associated with the **keys**.

Assignment Project Exam Help

- Having the master to relay the requests

<https://tutorcs.com>

WeChat: cstutorcs



Directory-based architecture: recursive query


- Have a node maintain the mapping between **keys** and the **machines (nodes)** that store the **values** associated with the **keys**.

Assignment Project Exam Help

- Having the master to relay the requests

<https://tutorcs.com>

WeChat: cstutorcs



Directory-based architecture: iterative query


- Have a node maintain the mapping between **keys** and the **machines (nodes)** that store the **values** associated with the **keys**.

Assignment Project Exam Help

- Return node to requester and let requester contact node

<https://tutorcs.com>

WeChat: cstutorcs



Directory-based architecture: iterative query

- Have a node maintain the mapping between **keys** and the **machines (nodes)** that store the **values** associated with the **keys**.

Assignment Project Exam Help

- Return node to requester and let requester contact node

<https://tutorcs.com>




put(K14, V14)

WeChat: cstutorcs


Master/Directory



K14	N3
K5	N2
K105	N50



...



Directory-based architecture: iterative query


- Have a node maintain the mapping between **keys** and the **machines (nodes)** that store the **values** associated with the **keys**.

Assignment Project Exam Help

- Return node to requester and let requester contact node

<https://tutorcs.com>

WeChat: cstutorcs



Directory-based architecture: iterative query

- The same solution applies also to retrieve a value...

Assignment Project Exam Help

<https://tutorcs.com>




get(K14)

WeChat: cstutorcs


Master/Directory



K14	N3
K5	N2
K105	N50



...



Directory-based architecture: iterative query

- The same solution applies also to retrieve a value...

Assignment Project Exam Help

<https://tutorcs.com>




get(K14)

WeChat: cstutorcs


Master/Directory



K14	N3
K5	N2
K105	N50



...




Directory-based architecture: iterative query

- The same solution applies also to retrieve a value...

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Directory-based architecture: iterative query


- The same solution applies also to retrieve a value...

For the recursive case,
everything is managed
by the Master

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Iterative vs recursive query

- Recursive Query (Master in charge):

- Advantages:

- Faster, as typically master/directory closer to nodes
 - Easier to maintain consistency as master/directory can serialize puts()/gets()

- Disadvantages: scalability bottleneck, as all “Values” go through master

- Iterative Query

- Advantages: more scalable

- Disadvantages: slower, harder to enforce data consistency

Key questions

- put(key, value): where do you store a new (key, value) tuple?
- get(key): where is the value associated with a given “key” stored?

- ...do the above while providing
 - Fault Tolerance
 - Scalability
 - Consistency

<https://tutorcs.com>

WeChat: cstutorcs

Key questions

- put(key, value): where do you store a new (key, value) tuple?
- get(key): where is the value associated with a given “key” stored?

- ...do the above while providing

- Fault Tolerance

- Scalability


- Consistency

<https://tutorcs.com>

WeChat: cstutorcs


Fault tolerance: recursive

- Replicate value on several nodes
- Usually, place replicas on different racks in a datacenter to guard against rack failures



Fault tolerance: iterative

- Replicate value on several nodes
- Usually, place replicas on different racks in a datacenter to guard against rack failures



Replication challenges

- Need to make sure that a value is replicated correctly
- How do you know a value has been replicated on every node?
 - Wait for acknowledgements from every node
- What happens if a node fails during replication?
 - Pick another node and try again
- What happens if a node is slow?
 - Slow down the entire put()? Pick another node?

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Replication challenges

- Need to make sure that a value is replicated correctly
- How do you know a value has been replicated on every node?
 - Wait for acknowledgements from every node
- What happens if a node fails during replication?
 - Pick another node and try again
- What happens if a node is slow?
 - Slow down the entire put()? Pick another node?

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

In general, with multiple replicas:
Slow puts and fast gets

Key questions

- put(key, value): where do you store a new (key, value) tuple?
- get(key): where is the value associated with a given “key” stored?

- ...do the above while providing
 - Fault Tolerance
 - Scalability
 - Consistency

<https://tutorcs.com>

WeChat: cstutorcs

Scalability

- **Storage:** use more nodes

Assignment Project Exam Help

- **Request throughput:**

<https://tutorcs.com>


- Can serve requests from all nodes on which a value is stored in parallel
- Master can replicate a popular value on more nodes

WeChat: estutores


- **Master/directory scalability:**

- Replicate it
- Partition it, so different keys are served by different masters/directories (do you remember Chord? 😊)

Scalability with Chord



Recursively example:
node 44 issue query(31)



Iteratively example:
node 44 issue query(31)

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Scalability: load balancing

- Directory keeps track of the storage availability at each node
 - Preferentially insert new values on nodes with more storage available
- What happens when a new node is added?
 - Move values from the heavy loaded nodes to the new node
- What happens when a node fails?
 - Need to replicate values from fail node to other nodes

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Key questions

- put(key, value): where do you store a new (key, value) tuple?
- get(key): where is the value associated with a given “key” stored?

- ...do the above while providing
 - Fault Tolerance
 - Scalability
 - Consistency

<https://tutorcs.com>

WeChat: cstutorcs

Consistency

- How close does a distributed system emulate a single machine in terms of read and write semantics?

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Consistency

- How close does a distributed system emulate a single machine in terms of read and write semantics?

[Assignment Project Exam Help](https://tutorcs.com)

- Q: Assume `put(K14, V14')` and `put(K14, V14'')` are concurrent, what value ends up being stored?

<https://tutorcs.com>
WeChat: cstutorcs

Consistency

- How close does a distributed system emulate a single machine in terms of read and write semantics? [Assignment Project Exam Help](https://tutorcs.com)

• Q: Assume `put(K14, V14')` and `put(K14, V14'')` are concurrent, what value ends up being stored? <https://tutorcs.com>
WeChat: cstutorcs

• A: assuming `put()` is atomic, then either `V14'` or `V14''`, right?

Consistency

- How close does a distributed system emulate a single machine in terms of read and write semantics?

Assignment Project Exam Help

- Q: Assume a client calls `put(K14, V14)` and then `get(K14)`, what is the result returned by `get()`?

<https://tutorcs.com>

WeChat: cstutorcs

Consistency

- How close does a distributed system emulate a single machine in terms of read and write semantics?

Assignment Project Exam Help

- Q: Assume a client calls `put(K14, V14)` and then `get(K14)`, what is the result returned by `get()`?

<https://tutorcs.com>

WeChat: cstutorcs

- A: It should be V14, right?

Consistency

- How close does a distributed system emulate a single machine in terms of read and write semantics?

Assignment Project Exam Help

<https://tutorcs.com>

Above semantics, not trivial to achieve in distributed systems!!!!
WeChat: cstutorcs

Concurrent writes

- If concurrent updates (i.e., puts to same key) may need to make sure that updates happen in the same order

Assignment Project Exam Help




<https://tutorcs.com>

WeChat: cstutorcs


Master/Directory



K14	N1,N3
K5	N2
K105	N50



...



Concurrent writes

- If concurrent updates (i.e., puts to same key) may need to make sure that updates happen in the same order

Assignment Project Exam Help




<https://tutorcs.com>

WeChat: cstutorcs


Master/Directory



K14	N1,N3
K5	N2
K105	N50




...



Concurrent writes

- If concurrent updates (i.e., puts to same key) may need to make sure that updates happen in the same order



Concurrent writes


- $\text{put}(K14, V14')$ and $\text{put}(K14, V14'')$ reach $N1$ and $N3$ in reverse order
- What does $\text{get}(K14)$ return?
 - Undefined!

- If concurrent updates (i.e., puts to same key) may need to make sure that updates happen in the same order

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Read after write

- Read not guaranteed to return value of latest write
 - Can happen if Master processes requests in different threads

Assignment Project Exam Help




<https://tutorcs.com>

WeChat: cstutorcs


Master/Directory



K14	N1,N3
K5	N2
K105	N50



...



Read after write

- Read not guaranteed to return value of latest write
- Can happen if Master processes requests in different threads

Assignment Project Exam Help




<https://tutorcs.com>

WeChat: cstutorcs


Master/Directory



K14	N1,N3
K5	N2
K105	N50




...




Read after write

- Read not guaranteed to return value of latest write
 - Can happen if Master processes requests in different threads




Read after write

- Read not guaranteed to return value of latest write
 - Can happen if Master processes requests in different threads




Read after write

- Read not guaranteed to return value of latest write
 - Can happen if Master processes requests in different threads



Read after write


- Read not guaranteed to return value of latest write
 - Can happen if Master processes requests in different threads



Read after write

- get(K14) happens right after put(K14, V14')
- get(K14) reaches N3 before put(K14, V14')!

- Read not guaranteed to return value of latest write
 - Can happen if Master processes requests in different threads



The return of an old friend

- Does this remind you something? ☺

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



The return of an old friend

- Does this remind you something? ☺

Assignment Project Exam Help

- Yes, all the consistency models/protocols we have seen apply also here!

<https://tutorcs.com>

WeChat: cstutorcs



Quorum consensus

- Define a replica set of size N
 - **put()** waits for acks from at least W replicas
 - **get()** waits for responses from at least R replicas

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- Why may you use $W+R > N+1$?

Quorum consensus


- $N=3$, $W=2$, $R=2$
- Replica set for K14: $\{N_1, N_3, N_{50}\}$
- Assume `put()` on N_3 fails



Assignment Project Exam Help


<https://tutores.com>

WeChat: cstutorcs



Quorum consensus

- $N=3$, $W=2$, $R=2$
- Replica set for K14: {N1, N3, N50}
- Assume put() on N3 fails




Quorum consensus

Now, for `get()` need to wait for any two nodes out of three to return the answer

Assignment Project Exam Help


<https://tutores.com>

WeChat: cstutorcs



Quorum consensus

Now, for `get()` need to wait for any two nodes out of three to return the answer





Memcached: a Key-Value Store example

- Memcached is an in-memory key-value store for small chunks of arbitrary data (strings, objects) from results of database calls, API calls, or page rendering

Assignment Project Exam Help

- Memcached's APIs provide a very large hash table distributed across multiple machines.

<https://tutorcs.com>

WeChat: cstutorcs

- If table is full: subsequent inserts cause older data to be purged in least recently used (LRU) order.
- Applications using Memcached typically layer requests and additions into RAM before falling back on a slower backing store, such as a database.



Memcached in a figure





Memcached: when to use it?

- Often used for small objects

Assignment Project Exam Help

- Anything what is more expensive to fetch from elsewhere, and has sufficient hitrate, can be placed in memcached

<https://tutorcs.com>

- How often will object or data be used?
- How expensive is it to generate the data?
- What is the expected hitrate?

WeChat: estutorcs



Memcached: trade-offs

- Why YES:

1. to reduce the load on the database by caching data BEFORE
2. improve the entire application response time (much faster hitting the RAM than the disk or the database)

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

- Why NO:

1. Memcache is held in RAM. This is a finite resource.
2. Adding complexity to a system just for complexities sake is a waste. If the system can respond within the requirements without it - leave it alone



Memcached: software architecture

- Client–server architecture

Assignment Project Exam Help

- **The servers** maintain a key–value associative array and do not communicate each other

<https://tutorcs.com>

- **The clients** populate this array and query it by key. They know all servers

WeChat: estutorcs

- If a client wishes to set or read the value corresponding to a certain key, the client's library first computes a hash of the key to determine which server to use.
- The servers keep the values in RAM; if a server runs out of RAM, it discards the oldest values.



Memcached: software architecture

- Clients must treat Memcached as a transitory cache

Assignment Project Exam Help

- They cannot assume that data stored in Memcached is still there when they need it.

<https://tutorcs.com>

WeChat: cstutorcs

- Other databases, such as MemcacheDB, Couchbase Server, provide persistent storage while maintaining Memcached protocol compatibility.

Facebook: a real-world scenario

- Need to support very heavy read load
 - Over 1 billion reads/second


- Geographically distributed

- Support a constantly evolving product

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Scaling Memcache at Facebook, USENIX NSDI 2013


Facebook: a real world scenario

- Memcache as a demand-filled look-aside cache


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Read path for a web server on a cache miss



The write path

Recap on Key-Value Stores

- Very large-scale storage systems

Assignment Project Exam Help

- Two operations

- put(key,value)
- value = get(key)

<https://tutorcs.com>

WeChat: cstutorcs

- Challenges

- Fault tolerance → replication
- Scalability → serve get()'s in parallel, replicate/cache hot tuples
- Consistency → quorum consensus