

eecs2001

Introduction to the Theory of Computation

Lecture 9

Assignment Project Exam Help

<https://tutorcs.com>

Ruth Umer

WeChat: cstutorcs

February 6, 2023

Assignment Project Exam Help

Regular Languages

<https://tutorcs.com>

Reading: IFC Section 1.1

WeChat: cstutorcs

Assignment Project Exam Help

Definition

A language L over some alphabet Σ is called a regular language if there exists a finite automaton M such that $L = L(M)$, that is, if there exists a finite automaton that recognizes it.

<https://tutorcs.com>
WeChat: cstutorcs

Regular language

Definition

A language L is called a **regular language** if there exists a finite automaton M such that $L = L(M)$, that is, if there exists a finite automaton that recognizes it.

Examples of regular languages

① $\{w \in \{0,1\}^* \mid w \text{ contains } 001 \text{ as a substring}\}$

② $\{w \in \{0,1\}^* \mid \text{the number of } 0\text{'s in } w \text{ is odd}\}$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Definition:

Let A and B be languages. Then we define the following operations that each form a new language:

- **Union:** $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$
- **Concatenation:** $A \circ B = \{wv \mid w \in A \text{ and } v \in B\}$.

WeChat: cstutorcs

- **Star:**

$$A^* = \{w_1 w_2 \dots w_k \mid k \geq 0 \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$$

Assignment Project Exam Help

Regular

$$A = \{01, 001, 0001\}$$

$$A \times B \ni (01, 110)$$

Definition.

Let A and B be languages. Then we define the following operations that each form a new language:

- Union: $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.

- Concatenation: $A \circ B = \{wv \mid w \in A \text{ and } v \in B\}$.

$$\text{Ex } A \circ B = \{011, 0011, 00011, 0111, 00111, 000111, 01110, 001110, 0001110, 0110, 00110, 000110\}$$

- Star: $A^* = \{w_1 w_2 \dots w_k \mid k \geq 0, \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$

$$\text{Ex } A^* = \{\epsilon, 01, 001, 0001, 0101, 01001, 00101, 001001, 0001001, 010101, 0100101, \dots\}$$

↑
infinite set of words...

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Regular op

$$\Sigma = \{0, 1\}$$

$$A = \{01, 001, 0001\}$$

$$A \times B \ni (01, 110)$$

Definition.

Let A and B be languages. Then we define the following operations that each form a new language:

- Union: $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.

$$A \cup B = \{01, 001, 0001, 110, 1101\}$$

- Concatenation: $A \circ B = \{wv \mid w \in A \text{ and } v \in B\}$.

$$\text{Ex } A \circ B = \{011, 0011, 00011, 0111, 00111, 000111, 01110, 001110, 0001110, 0110, 00110, 000110\}$$

- Star: $A^* = \{w_1 w_2 \dots w_k \mid k \geq 0, \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$

$$\text{Ex } A^* = \{\epsilon, 01, 001, 0001, 0101, 01001, 010001, 0100001, 01000001, \dots\}$$

\uparrow
infinite set of words...

<https://tutors.com>

WeChat: cstutors

End of presentation. Click to exit.

You are screen sharing Stop share

Mouse Select Text Draw Erase Undo Redo Save

Test

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutores

$$\Sigma = \{0, 1\}$$

$$A = \{1^3\}$$

$$A^* = \{\epsilon, 1, 11, 111, 1111, \dots\}, |A^*| = \infty$$



q0 accepts A^*

$$\Sigma' = \{0, 1, 2\}$$

Automaton

$$(Q, \Sigma, \delta, q_0, F)$$

↑
is part of the definition of an automaton

Regular operations reproduce regular languages

Assignment Project Exam Help

Theorem

The set of all regular languages is closed under the three regular operations

<https://tutorcs.com>

That is: if A and B are regular languages, then A^* , $A \cup B$ and $A \circ B$ are also regular languages.

WeChat: cstutorcs

Problem 1.4 from ITC

Here we design an automaton that recognizes the **intersection** of two languages for which we have simple automata recognizing them.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

We will now use a similar “product” for the general construction of an automaton that recognizes the **union** of two regular languages.

Problem 1.4 from ITC

$\Sigma = \{a, b\}$
Here we design an automaton that recognizes the intersection of two languages for which we have simple automata recognizing them.

Let $A = \{w \in \Sigma^* \mid w \text{ contains at least 3 a's}\}$

$B = \{w \in \Sigma^* \mid w \text{ contains at least 2 b's}\}$

We define automaton M_1 with $L(M_1) = A$



and automaton M_2 with $L(M_2) = B$



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help


Modifications of the Problem 1.4 from ITC

Here we design an automaton that recognizes the intersection of two languages for which we have simple automata recognizing them.

$\Sigma = \{a, b\}$
 $A = \{w \in \Sigma^* \mid w \text{ contains at least 3 a's}\}$
 $B = \{w \in \Sigma^* \mid w \text{ contains at least 2 b's}\}$

We can now construct automaton M that

Accepts as follows:



<https://tutorcs.com>

WeChat: cstutorcs

$U = \{w \in \Sigma^* \mid w \text{ contains at least 3 a's or at least 2 b's}\}$
← 6 accept states!

Regular languages closed under unions

We start by proving that if A and B are regular languages over some alphabet Σ , then so is $A \cup B$.

Assignment Project Exam Help

Proof:

To prove that $A \cup B$ is regular, we need to show that there exists an automaton

<https://tutorcs.com>

$$M = (Q, \Sigma, \delta, q_0, F)$$

with

$$L(M) = A \cup B$$

Since A and B are regular, we know there exist automata $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ with

WeChat: cstutorcs

$$L(M_1) = A \text{ and } L(M_2) = B$$

Regular languages closed under unions

We try to be proving that if A and B are regular languages over some alphabet Σ , then so is $A \cup B$.

Goal for the proof

To show that $A \cup B$ is regular, we need to show that there exists an automaton that recognizes $A \cup B$.

We know that A and B are regular languages, and therefore there exist automata $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ such that $A = L(M_1)$ and $B = L(M_2)$.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Proof continued:

We now define the required automaton M as follows:

1. $Q = Q_1 \times Q_2$

2. We use the same alphabet Σ

3. $\delta((s_1, s_2), a) = (\delta_1(s_1, a), \delta_2(s_2, a))$

4. $q_0 = (q_1, q_2)$

5. $F = \{(s_1, s_2) \in Q \mid s_1 \in F_1 \text{ or } s_2 \in F_2\}$

<https://tutorcs.com>

WeChat: cstutorcs

Regular languages closed

Proof continued:

We now define the required automaton M as follows:

1. $Q = Q_1 \times Q_2$
2. We use the same alphabet Σ
3. $\delta((s_1, s_2), a) = (\delta_1(s_1, a), \delta_2(s_2, a))$
4. $q_0 = (q_1, q_2)$
5. $F = \{(s_1, s_2) \in Q \mid s_1 \in F_1 \text{ or } s_2 \in F_2\}$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Regular languages closed under unions

Proof continued:

We now define the required automaton M as follows:

1. $Q = Q_1 \times Q_2$

2. We use the same alphabet Σ

3. $\delta((s_1, s_2), a) = (\delta_1(s_1, a), \delta_2(s_2, a))$

4. $q_0 = (q_1, q_2)$

5. $F = \{(s_1, s_2) \in Q \mid s_1 \in F_1 \text{ or } s_2 \in F_2\}$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Non-deterministic finite automata

<https://tutorcs.com>

Reading: IFC Section 1.2

WeChat: cstutorcs

To show that regular languages are also closed under the concatenation and star operations, it is convenient to employ the concept of a Non-deterministic Finite Automaton (NFA for short).

Assignment Project Exam Help


In the automata we have seen so far, every state has exactly one outgoing edge for every symbol. That is, for every state, the “reaction” to any input symbol is **uniquely determined**. Such an automaton is also called a **Deterministic Finite Automaton (DFA for short)**.

<https://tutorcs.com>

WeChat: cstutorcs

We will generalize this to also allow non-unique (think randomized or parallelized) computations. NFAs are a model for such computations.

Example: the NFA N_1




<https://tutorcs.com>

WeChat: cstutorcs

For the machine N_1 we get

$$L(N_1) = \{\mathbf{w} \mid \mathbf{w} \text{ contains } 11 \text{ or } 101 \text{ as a substring}\}$$


Example: the NFA N_1



<https://tutorcs.com>

WeChat: cstutorcs

Example: the NFA N_1



<https://tutorcs.com>

WeChat: cstutorcs

references

ε can be "read"

words


10110 ✓
accepted
000 X
not accepted

some states have several instructions for the same letter

some states don't instructions for all letters

Accepted by an NFA
Here is at least one way of reading the word that leads to an accept state.

Example: the NFA N_1



<https://tutorcs.com>

WeChat: cstutorcs

references

ϵ can be "read"

some states have several instructions for the same letter

some states don't instruct for all letters


strings words

10110 ✓
accepted
000 X
not accepted

$|111| = |\epsilon 111|$

Accepted by an NFA
Here is at least one way of reading the word that leads to an accept state.

Example: the NFA M



<https://tutorcs.com>

WeChat: cstutorcs

computation stops


the word
is accepted
since there
exist
branches
leading to
accept
states

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example: the NFA N_1



For the machine N_1 we get

$$L(N_1) = \{w \in \{0,1\}^* \mid w \text{ contains } 101\}$$

Reminder:
For alphabet Σ , the set
of all words
over Σ is
denoted by
 Σ^* .

Formal definition of a non-deterministic finite automaton

For an alphabet Σ , we define: $\Sigma_\epsilon = \Sigma \cup \{\epsilon\}$.

Assignment Project Exam Help

Definition

A non-deterministic finite automaton is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the set of states,
2. Σ is a finite set called the alphabet,
3. $\delta : Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$ is the transition function,
4. $q_0 \in Q$ is the start state, and
5. $F \subseteq Q$ is the set of accept states.

Assignment Project Exam Help

Formal description of the NFA M_1



Formal description of $M_1 = (Q, \Sigma, \delta, q_0, F)$

$Q = \{q_1, q_2, q_3, q_4\}$, $\Sigma = \{0, 1\}$, $q_0 = q_1$, $F = \{q_4\}$.

δ	0	1	ϵ
q_1	$\{q_1\}$	$\{q_1, q_3\}$	\emptyset
q_2	$\{q_3\}$	\emptyset	$\{q_3\}$
q_3	\emptyset	$\{q_3\}$	\emptyset
q_4	$\{q_4\}$	$\{q_4\}$	\emptyset

ϵ

ϵ

ϵ

$\epsilon \epsilon \epsilon \epsilon$

these are the
words

WeChat: cstutorcs

Formal description of the NFA N_1



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

For the machine N_1 we get

$$L(N_1) = \{\mathbf{w} \mid \mathbf{w} \text{ contains } 11 \text{ or } 101 \text{ as a substring}\}$$

Formal definition of acceptance for NFAs

For a string $\mathbf{w} = w_1 w_2 \dots w_n$ where $w_i \in \Sigma$ for some alphabet Σ , we let strings $z_0 w_1 z_1 w_2 z_3 \dots z_{n-1} w_n z_n$ over Σ_ϵ where each z_i is a sequence of 0 or more symbols ϵ represent the same word \mathbf{w} as a string over Σ .

Assignment Project Exam Help

Definition

Let $N = (Q, \Sigma, \delta, q_0, F)$ a non-deterministic finite automaton (NFA) and let \mathbf{w} be a string over Σ . We say that N accepts \mathbf{w} if we can write $\mathbf{w} = y_1 y_2 \dots y_m$ with $y_i \in \Sigma_\epsilon$ and there exists a sequence $s_0 s_1 s_2 \dots s_m$ of states such that

1. $s_0 = q_0$,
2. $s_{i+1} \in \delta(s_i, y_{i+1})$ for $i = 0, 1, \dots, m$, and
3. $s_m \in F$.

https://tutorcs.com
WeChat: cstutorcs

We then define the language $L(N)$ recognized by NFA N in the same way as for DFAs, namely as the set of all words that are accepted by N .

Formal definition of acceptance for NFAs

For a string $w = w_1 w_2 \dots w_n$ where $w_i \in \Sigma$ for some alphabet Σ , we let strings $z_0 z_1 z_2 \dots z_n$ over Σ , where each z_i is a sequence of 0 or more symbols, represent the same word w as a string over Σ .

Definition

Let $N = (Q, \Sigma, \delta, q_0, F)$ a non-deterministic finite automaton (NFA) and let w be a string over Σ . We say that N accepts w if we can write $w = x_0 y_1 \dots y_m$ with $y_i \in \Sigma$, and there exists a sequence $s_0 s_1 s_2 \dots s_m$ of states $s_i \in Q$ that


1. $s_0 = q_0$,
2. $s_{i+1} \in \delta(s_i, y_{i+1})$ for $i = 0, 1, \dots, m$, and
3. $s_m \in F$.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example: the NFA N_2




<https://tutorcs.com>

WeChat: cstutorcs

For the machine N_2 we get

$$L(N_2) = \{\mathbf{w} \mid \mathbf{w} \text{ contains 1 at the third position from the end}\}$$

Example: the NFA N_2



<https://tutorcs.com>

For the machine N_2 we get

$$L(N_2) = \{w \in \{0,1\}^* \mid w \text{ has a } 1 \text{ at the } n\text{-th position from the end}\}$$

$$= \{w = w_1w_2\dots w_n \in \Sigma^* \mid w_{n-2} = 1\}$$