

eecs2001

Introduction to the Theory of Computation

Lecture 11

Assignment Project Exam Help


<https://tutorcs.com>

Ruth Umer

WeChat: cstutorcs

February 13, 2023

Example: the NFA N_2




<https://tutorcs.com>

WeChat: cstutorcs

For the machine N_2 we get

$$L(N_2) = \{\mathbf{w} \mid \mathbf{w} \text{ contains 1 at the third position from the end}\}$$

Example: the NFA N_2



<https://tutorcs.com>


For the machine N_2 we get

$$L(N_2) = \{w \in \{0,1\}^* \mid w \text{ has a } 1 \text{ at the } n\text{-th position from the end}\}$$

$$= \{w = w_1w_2\dots w_n \in \Sigma^* \mid w_{n-2} = 1\}$$

Example: the NFA N_3

Let's consider a **unary alphabet** $\Sigma = \{0\}$.




For the machine N_3 we get

$$L(N_3) = \{\mathbf{w} \mid \text{The number of 0 symbols in } \mathbf{w} \text{ is divisible by 2 or by 3}\}$$

Example: the NFA M

Let's consider a unary alphabet $\Sigma = \{0\}$.



00000 X

<https://tutorcs.com>

WeChat: cstutorcs

$L(N) = \{w \in \{0\}^* \mid w \text{ is divisible by 2 or by 3}\}$


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example:

Let's consider a unary alphabet $\Sigma = \{0\}$.



00000 X

000 ✓
is the same word
as ε00

$L(N) = \{0^n \in 0^* \mid \text{length of } n \text{ is divisible by 2 or by 3}\}$
 $= \{w \in \{0\}^* \mid \text{length of } w \text{ even}\} \cup \{w \in \{0\}^* \mid \text{length of } w \text{ divisible by 3}\}$

Equivalence of NFAs and DFAs

Definition

We call two finite state machines equivalent if they recognize the same language.

Theorem

For every NFA, there exists an equivalent DFA.

Corrolary

A language L is regular if and only if there exists an NFA that recognizes it.

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Equival

Definition

We call two finite state machines equivalent if they recognize the same language. *- automata*

Theorem

For every NFA, there exists an equivalent DFA.

For every DFA N , there exist a DFA

N' s.t. $L(N) = L(N')$

Corollary-

A language L is regular, if and only if there exists an DFA that recognizes L .

Assignment Project Exam Help

To prove the theorem from the previous slide, we need to show that for every NFA N , there exists a DFA M with $L(M) = L(N)$.


<https://tutorcs.com>

Before we see the general proof for this, we go through one concrete example. We transform NFA N_4 into an equivalent DFA.

WeChat: cstutorcs

Transforming an NFA into a DFA—example

Consider the NFA N_4 :




Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Transforming an NFA into a DFA—example

Consider the NFA



Examples of
accepted words

a
a
εa

baba ✓

Examples of
words that are
not accepted;

bbh X

bb X


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Transforming an NFA into a DFA—example

Consider the NFA



$Q = \{1, 2, 3\}$

Examples of accepted words
 a
 ϵa

equivalent DFA $(Q', \Sigma, \delta', q', F')$



$baba$ ✓

examples of words that are not accepted;

bhb X

ab X


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Transforming an NFA into a DFA—example

Consider the NFA



$Q = \{1, 2, 3\}$

Examples of accepted words

a
εa

baba ✓

Examples of words that are not accepted;

bhb X

ab X

<https://tutorcs.com>

WeChat: cstutorcs

General proof of Theorem

Proof

Let $N = (Q, \Sigma, \delta, q_0, F)$ be some NFA.

We need to construct DFA $M = (Q', \Sigma, \delta', q'_0, F')$ with $L(M) = L(N)$.

Assuming that N does not contain any ϵ -transitions, we construct M as follows:

1. $Q' = \mathcal{P}(Q)$
2. For $R \in Q'$ and $a \in \Sigma$, we let

$$\delta'(R, a) = \{q \in Q \mid q \in \delta(r, a) \text{ for some } r \in R\}$$

3. $q'_0 = \{q_0\}$
4. $F' = \{R \in Q' \mid \text{there exists an } r \in F \text{ with } r \in R\}.$

This completes the construction for NFAs that don't contain ϵ -transitions.

General proof of Theorem

Proof

Let $N = (Q, \Sigma, \delta, q_0, F)$ be some NFA.

We need to construct a DFA $M = (Q', \Sigma, \delta', q'_0, F')$ with $L(M) = L(N)$.

Assuming that N does not contain any ϵ -transitions, we construct M as follows:

1. $Q' = \mathcal{P}(Q)$

$$\epsilon Q' = \mathcal{P}(Q)$$

2. For $R \in Q'$ and $a \in \Sigma$ we let

$$\delta'(R, a) = \{q \in Q \mid q \in \delta(r, a) \text{ for some } r \in R\}$$

3. $q'_0 = \{q_0\}$

4. $F' = \{R \in Q' \mid \text{there exists an } r \in R \text{ with } r \in F\}$.

This completes the construction for NFAs that don't contain ϵ -transitions.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Proof continued

If M does contain ϵ -transitions, we extend the above construction as follows:

For a state $R \in Q'$, we let $E(R)$ denote the set of states that can be reached via 0 or more ϵ -transitions from some state $r \in R$ (in N).

Then we modify the transition function of M to be

$$\delta'(R, a) = \{q \in Q \mid q \in E(\delta(r, a)) \text{ for some } r \in R\}$$

and the start state of M' to be

$$q'_0 = E(q_0).$$

<https://tutorcs.com>

WeChat: cstutorcs

Regular languages are closed under regular operations

Theorem

Regular languages are closed under unions.



Assignment Project Exam Help

"Proof" by illustration

Given A and B and DFAs M_A and M_B with
 $L(M_A) = A$ and $L(M_B) = B$. We need to construct an
DFA M that recognizes $A \cup B$.

<https://tutorcs.com>

WeChat: cstutorcs



Regular languages are closed under regular operations

Theorem

Regular languages are closed under unions.

Assignment Project Exam Help

Proof (formal version)

We need to show that if two languages A and B are regular, then so is $A \cup B$. If A and B are regular, then there exist NFAs $N_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $N_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ such that $L(N_1) = A$ and $L(N_2) = B$. We need to show that there exists an NFA M with $L(M) = A \cup B$. The picture on the previous slide illustrates a construction for $M = (Q, \Sigma, \delta, q_0, F)$. Formally, we set:

1. $Q = Q_1 \cup Q_2 \cup \{q_0\}$, where q_0 is a new state, that is $q_0 \notin Q_1 \cup Q_2$ and this state q_0 will then also be the start state of M .

$$2. \delta(q, a) = \begin{cases} \{q_1, q_2\} & \text{if } q = q_0 \text{ and } a = \epsilon \\ \delta_i(q, a) & \text{if } q \in Q_i \\ \emptyset & \text{else} \end{cases}$$

3. $F = F_1 \cup F_2$.


Regular languages are closed under regular operations

Theorem

Regular languages are closed under concatenations.

Assignment Project Exam Help

"Proof" by illustration



Regular languages are closed under regular operations

Theorem

Regular languages are closed under concatenations.

Assignment Project Exam Help

Proof (formal version)

We need to show that if two languages A and B are regular, then so is $A \circ B$. If A and B are regular, then there exist NFAs $N_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $N_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ such that $L(N_1) = A$ and $L(N_2) = B$. We need to show that there exists an NFA M with $L(M) = A \circ B$. The picture on the previous slide illustrates a construction for $M = (Q, \Sigma, \delta, q_0, F)$. Formally, we set:

1. $Q = Q_1 \cup Q_2$

2. $q_0 = q_1$

3.
$$\delta(q, a) = \begin{cases} \delta_1(q, a) \cup \{q_2\} & \text{if } q \in F_1 \text{ and } a = \epsilon \\ \delta_1(q, a) & \text{if } q \in Q_1 \text{ and } (q \notin F_1 \text{ or } a \neq \epsilon) \\ \delta_2(q, a) & \text{if } q \in Q_2 \end{cases}$$

4. $F = F_2$.

<https://tutorcs.com>
WeChat: cstutorcs

Regular languages are closed under regular operations

Theorem

Regular languages are closed under the star-operation.

Assignment Project Exam Help

"Proof" by illustration

<https://tutorcs.com>

$L(A) = A$

WeChat: cstutorcs

$L(A^*) = A^*$

Regular languages are closed under regular operations

Theorem

Regular languages are closed under the star-operation.

Proof (formal version)

We need to show that if language A is regular, then so is A^* . If A is regular, then there exist an NFA $N_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ such that $L(N_1) = A$. We need to show that there exists an NFA M with $L(M) = A^*$. The picture on the previous slide illustrates a construction for $M = (Q, \Sigma, \delta, q_0, F)$. We set:

1. $Q = Q_1 \cup \{q_0\}$, where q_0 is a new state, that is $q_0 \notin Q_1$ and this state q_0 will then also be the start state of M .

$$2. \delta(q, a) = \begin{cases} \{q_1\} & \text{if } q = q_0 \text{ and } a = \epsilon \\ \delta_1(q, a) \cup \{q_1\} & \text{if } q \in F_1 \text{ and } a = \epsilon \\ \delta_1(q, a) & \text{if } q \in Q_1 \text{ and } (q \notin F_1 \text{ or } a \neq \epsilon) \end{cases}$$

3. $F = F_1 \cup \{q_0\}$.

Assignment Project Exam Help

Regular Expressions

<https://tutorcs.com>

Reading: IFC Section 1.3

WeChat: cstutorcs

Assignment Project Exam Help

A regular expression is a compact way of defining a set of words. It is a sequence of symbols that represent a language over some alphabet Σ .

<https://tutorcs.com>

WeChat: cstutorcs

Inductive definition of sets – general pattern

An inductive definition of a set consists of

1. A universe set U
2. A core set $C \subseteq U$
3. A finite set $O = \{o_1, o_2, \dots, o_n\}$ of operations from $o_i: U^i \rightarrow U$ for some arities $i_i \in \mathbb{N}$

WeChat: cstutorcs

We define $\mathcal{I}(U, C, O)$ as the set of elements that we obtain by starting with the core set and putting all those elements of U into $\mathcal{I}(U, C, O)$ that one can reach by successively applying the operations in O .

Let Σ be some alphabet. We define the set \mathcal{R} of regular expressions over Σ inductively by setting $\mathcal{R}_\Sigma = \mathcal{Z}(U, C, \circ)$, where

1. The universe U is the set of all strings over

$\Sigma \cup \{ (,) \} \cup \{ \circ, *, \epsilon, \emptyset \}$

2. The core set C is the set of all symbols in Σ and ϵ, \emptyset and two additional symbols: $C = \Sigma \cup \{ \epsilon, \emptyset \}$.

3. Three operations:
 - ▶ $\circ_\cup(R_1, R_2) = (R_1 \cup R_2)$,
 - ▶ $\circ_\circ(R_1, R_2) = (R_1 \circ R_2)$,
 - ▶ $\circ_*(R) = (R^*)$.

Regular expression-inductive definition

Let Σ be some alphabet. We define the set \mathcal{R} of regular expressions over Σ inductively by setting $\mathcal{R}_\Sigma = \mathcal{I}(U, C, O)$, where

1. The universe U is the set of all strings over $\Sigma \cup \{ (,), \cup, \circ, *, \epsilon, \emptyset \}$.
2. The core set C is the set of all symbols in Σ and ϵ, \emptyset and two additional symbols: $C = \Sigma \cup \{ \epsilon, \emptyset \}$.

3. Three operations:

- ▶ $\cup (R_1, R_2) = (R_1 \cup R_2)$,
- ▶ $\circ (R_1, R_2) = (R_1 \circ R_2)$,
- ▶ $*$ $(R) = (R^*)$.

Exercise:

Prove (by induction) that the number of "(" is always equal to the number of ")" in a regular expression

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Examples:
1. \emptyset
2. $(\cup \emptyset)$
3. $(\epsilon \cup \emptyset)$
4. $(\epsilon \cup \emptyset)^*$

member
of universe
 $(\epsilon \cup \emptyset)$

these two
are not
regular
expressions

The language of a regular expression

Each regular expression $R \in \mathcal{R}_\Sigma$ over some alphabet Σ represents a language over Σ . We define the interpretation $L(R)$ of a regular expression R according to the inductive definition:

Members of the core-set:

- The expression a for $a \in \Sigma$ represents the language $\{a\}$, that is $L(a) = \{a\}$.
- The expression ϵ represents the language $\{\epsilon\}$, that is $L(\epsilon) = \{\epsilon\}$.
- The expression \emptyset represents the language \emptyset , that is $L(\emptyset) = \emptyset$.

Result of operation: For regular expressions R_1 , R_2 , and R , we define:

- $L((R_1 \cup R_2)) = L(R_1) \cup L(R_2)$
- $L((R_1 \circ R_2)) = L(R_1) \circ L(R_2)$
- $L((R^*)) = L(R)^*$

We call $L(R)$ the language of R .

$$\Sigma = \{0, 1\}$$

$$0 \in \mathcal{R}_\Sigma$$

$$L((0)) = \{0\}$$

$$0, \epsilon \in \mathcal{R}_\Sigma$$

$$(0 \cup \epsilon) \in \mathcal{R}_\Sigma$$

$$L((0 \cup \epsilon))$$

$$= \{0, \epsilon\}$$

$$(0 \cup \epsilon) \in \mathcal{R}_\Sigma$$

$$L((0 \cup \epsilon))$$

$$= \{0, \epsilon\}$$

The language of a regular expression

Each regular expression $R \in \mathcal{R}_\Sigma$ over some alphabet Σ represents a language over Σ . We define the interpretation, $L(R)$ of a regular expression R according to the inductive definition:

Members of the core-set:

- The expression a for $a \in \Sigma$ represents the language $\{a\}$, that is $L(a) = \{a\}$.

- The expression ϵ represents the language $\{\epsilon\}$, that is $L(\epsilon) = \{\epsilon\}$.
- The expression \emptyset represents the language \emptyset , that is $L(\emptyset) = \emptyset$.

Result of operation: For regular expressions R_1, R_2 and R , we define:

- $L((R_1 \cup R_2)) = L(R_1) \cup L(R_2)$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

For convenience and readability, we use the following notational conventions:

1. For an alphabet Σ , we use Σ as a regular expression representing all words of length 1 over Σ . And then Σ^* is a regular expression for the set of all words over Σ .
2. We often omit brackets. The order of precedence then is: $*$, \circ , \cup .
3. The \circ -symbol is typically omitted: we use $R_1 R_2$ as shorthand for $R_1 \circ R_2$.
4. We let R^+ be shorthand for RR^* .
5. We let R^k be the k times repeated concatenation of R with itself:
$$R^k = R \circ R \circ R \circ \dots \circ R.$$

<https://tutorcs.com>

WeChat: cstutorcs

We let $\Sigma = \{0, 1\}$.

Now we can interpret the following regular expressions over Σ :

- 0^*10^*
- $\Sigma^*1\Sigma^*$
- $\Sigma^*001\Sigma^*$
- $1^*(01^+)^*$
- $(\Sigma\Sigma)^*$
- $(\Sigma\Sigma\Sigma)^*$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Regular expressions—examples

precedence: \wedge o \cup

We let $\Sigma = \{0, 1\}$.

How we can interpret the following regular expressions over Σ .

- $0^*10^* = ((0^*)o1o(0^*))$

$\{w \in \Sigma^* \mid w \text{ contains exactly one } 1\}$

$$1 \in L(0^*10^*)$$

$$0010 \in L(0^*10^*)$$

$$1000 \in L(0^*10^*)$$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Regular expressions—examples

We let $\Sigma = \{0, 1\}$.

Now we can interpret the following regular expressions over Σ .

- 0^*10^*

- $\Sigma^*1\Sigma^* = (\Sigma^*)1(\Sigma^*) = (\Sigma^*) \circ 1 \circ (\Sigma^*)$

- $\mathcal{L}(\Sigma^*1\Sigma^*) = \{w \in \Sigma^* \mid w \text{ contains at least one } 1\}$

$$1^* \mathcal{L}(\Sigma^*1\Sigma^*)$$

$$\underbrace{01011010}_{\in \Sigma^*} \in \mathcal{L}(\Sigma^*1\Sigma^*)$$
$$\underbrace{\quad}_{\in \Sigma^*} \quad \underbrace{\quad}_{\in \Sigma^*}$$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Regular expressions—examples

We let $\Sigma = \{0, 1\}$.

Now we can interpret the following regular expressions over Σ .

- 0^*10^*

- $\Sigma^*1\Sigma^*$

- $\Sigma^*001\Sigma^*$

$L(\Sigma^*001\Sigma^*) = \{w \in \Sigma^* \mid w \text{ contains } 001 \text{ as a substring}\}$

WeChat: cstutorcs

Regular expressions—examples

~~0~~ 0 1

We let $\Sigma = \{0, 1\}$.

Now we can interpret the following regular expressions over Σ .

- 0^*10^*

- $\Sigma^*1\Sigma^*$

- $\Sigma^*001\Sigma^*$

- $1^*(01^+)^*$

$1^*(1^+(0(1^+)^*)^*) = \{\omega \in \Sigma^* \mid \text{every } 0 \text{ is followed by a } 1\}$ ✓

$1^+ 0 1^+ 1^+ 1^+$
 $\in 1^+ \in 1^+ 1^+ 1^+$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs