

eecs2001

Introduction to the Theory of Computation

Lecture 10

Assignment Project Exam Help

<https://tutorcs.com>

Ruth Umer

WeChat: cstutorcs

February 8, 2023

Assignment Project Exam Help

Non-deterministic finite automata

<https://tutorcs.com>

Reading: IFC Section 1.2

WeChat: cstutorcs

DFA versus NFAs

To show that regular languages are also closed under the concatenation and star operations, it is convenient to employ the concept of a Non-deterministic Finite Automaton (NFA for short).

Assignment Project Exam Help


In the automata we have seen so far, every state has exactly one outgoing edge for every symbol. That is, for every state, the “reaction” to any input symbol is uniquely determined. Such an automaton is also called a Deterministic Finite Automaton (DFA for short).

<https://tutorcs.com>

WeChat: cstutorcs

We will generalize this to also allow non-unique (think randomized or parallelized) computations. NFAs are a model for such computations.

Example: the NFA N_1




<https://tutorcs.com>

WeChat: cstutorcs

For the machine N_1 we get

$$L(N_1) = \{\mathbf{w} \mid \mathbf{w} \text{ contains } 11 \text{ or } 101 \text{ as a substring}\}$$

Example: the NFA N_1




Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example: the NFA N_1



<https://tutorcs.com>

WeChat: cstutorcs

references

ε can be "read"

words

10110 ✓
accepted
000 X
not accepted

some states have several instructions for the same letter

some states don't instructions for all letters


According to an NFA, there is at least one way of reading the word that leads to an accept state.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example: the NFA N_1



References

ϵ can be "read"

some states have several instructions for the same letter

some states don't instruct for all letters

strings words

10110 ✓
accepted
000 X
not accepted

$(111) = (\epsilon 111)$

Accepted by an NFA
Here is at least one way of reading the word that leads to an accept state.

Example: the NFA M



<https://tutorcs.com>

WeChat: cstutorcs

computation stops

the word
is accepted
since there
exist
branches
leading to
accept
states

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example: the NFA N_1



For the machine N_1 we get

$$L(N_1) = \{w \in \{0,1\}^* \mid w \text{ contains } 101\}$$

for $w = \text{substring}$

Reminder:
For alphabet Σ , the set
of all words
over Σ is
denoted by
 Σ^* .

Formal definition of a non-deterministic finite automaton

For an alphabet Σ , we define: $\Sigma_\epsilon = \Sigma \cup \{\epsilon\}$.

Assignment Project Exam Help

Definition

A non-deterministic finite automaton is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the set of states,
2. Σ is a finite set called the alphabet,
3. $\delta : Q \times \Sigma_\epsilon \rightarrow \mathcal{P}(Q)$ is the transition function,
4. $q_0 \in Q$ is the start state, and
5. $F \subseteq Q$ is the set of accept states.

Assignment Project Exam Help

Formal description of the NFA M_1



Formal description of $M_1 = (Q, \Sigma, \delta, q_0, F)$

$Q = \{q_1, q_2, q_3, q_4\}$, $\Sigma = \{0, 1\}$, $q_0 = q_1$, $F = \{q_4\}$.

| δ | 0 | 1 | ϵ |
|----------|-------------|----------------|-------------|
| q_1 | $\{q_1\}$ | $\{q_1, q_3\}$ | \emptyset |
| q_2 | $\{q_3\}$ | \emptyset | $\{q_3\}$ |
| q_3 | \emptyset | $\{q_3\}$ | \emptyset |
| q_4 | $\{q_4\}$ | $\{q_4\}$ | \emptyset |

ϵ

ϵ

ϵ

$\epsilon \epsilon \epsilon \epsilon$

these are the
words

WeChat: cstutorcs

Formal description of the NFA N_1



<https://tutorcs.com>

WeChat: cstutorcs

For the machine N_1 we get

$$L(N_1) = \{\mathbf{w} \mid \mathbf{w} \text{ contains } 11 \text{ or } 101 \text{ as a substring}\}$$

Formal definition of acceptance for NFAs

For a string $\mathbf{w} = w_1 w_2 \dots w_n$ where $w_i \in \Sigma$ for some alphabet Σ , we let strings $z_0 w_1 z_1 w_2 z_3 \dots z_{n-1} w_n z_n$ over Σ_ϵ where each z_i is a sequence of 0 or more symbols ϵ represent the same word \mathbf{w} as a string over Σ .

Assignment Project Exam Help

Definition

Let $N = (Q, \Sigma, \delta, q_0, F)$ a non-deterministic finite automaton (NFA) and let \mathbf{w} be a string over Σ . We say that N accepts \mathbf{w} if we can write $\mathbf{w} = y_1 y_2 \dots y_m$ with $y_i \in \Sigma_\epsilon$ and there exists a sequence $s_0 s_1 s_2 \dots s_m$ of states such that

1. $s_0 = q_0$,
2. $s_{i+1} \in \delta(s_i, y_{i+1})$ for $i = 0, 1, \dots, m$, and
3. $s_m \in F$.

We then define the language $L(N)$ recognized by NFA N in the same way as for DFAs, namely as the set of all words that are accepted by N .

Formal definition of acceptance for NFAs


For a string $w = w_1 w_2 \dots w_n$ where $w_i \in \Sigma$ for some alphabet Σ , we let strings $z_0 z_1 z_2 \dots z_n$ over Σ , where each z_i is a sequence of 0 or more symbols, represent the same word w as a string over Σ .

Definition

Let $N = (Q, \Sigma, \delta, q_0, F)$ a non-deterministic finite automaton (NFA) and let w be a string over Σ . We say that N accepts w if we can write $w = x_0 y_1 \dots y_m$ with $y_i \in \Sigma$ and there exists a sequence $s_0 s_1 s_2 \dots s_m$ of states $s_i \in Q$ that

1. $s_0 = q_0$,
2. $s_{i+1} \in \delta(s_i, y_{i+1})$ for $i = 0, 1, \dots, m$, and
3. $s_m \in F$.

Example: the NFA N_2




<https://tutorcs.com>

WeChat: cstutorcs

For the machine N_2 we get

$$L(N_2) = \{\mathbf{w} \mid \mathbf{w} \text{ contains 1 at the third position from the end}\}$$

Example: the NFA N_2



<https://tutorcs.com>


For the machine N_2 we get

$$L(N_2) = \{w \in \{0,1\}^* \mid w \text{ has a } 1 \text{ at the } n\text{-th position from the end}\}$$

$$= \{w = w_1w_2\dots w_n \in \Sigma^* \mid w_{n-2} = 1\}$$

Example: the NFA N_3

Let's consider a **unary alphabet** $\Sigma = \{0\}$.




For the machine N_3 we get

$$L(N_3) = \{\mathbf{w} \mid \text{The number of 0 symbols in } \mathbf{w} \text{ is divisible by 2 or by 3}\}$$

Example: the NFA M

Let's consider a unary alphabet $\Sigma = \{0\}$.



00000 X

<https://tutorcs.com>

WeChat: cstutorcs

$L(N) = \{w \in \{0\}^* \mid w \text{ is divisible by 2 or by 3}\}$


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Example:

Let's consider a unary alphabet $\Sigma = \{0\}$.



00000 X

000 ✓
is the same word
as ε00

$L(N) = \{0^n \in 0^* \mid \text{length of } n \text{ is divisible by 2 or by 3}\}$
 $= \{w \in \{0\}^* \mid \text{length of } w \text{ even}\} \cup \{w \in \{0\}^* \mid \text{length of } w \text{ divisible by 3}\}$

Equivalence of NFAs and DFAs

Definition

We call two finite state machines equivalent if they recognize the same language.

Theorem

For every NFA, there exists an equivalent DFA.

Corrolary

A language L is regular if and only if there exists an NFA that recognizes it.

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Equival

Definition

We call two finite state machines equivalent if they recognize the same language. *- automata*

Theorem

For every NFA, there exists an equivalent DFA.

For every DFA N , there exist a DFA

N' s.t. $L(N) = L(N')$

Corollary-

A language L is regular, if and only if there exists an DFA that recognizes L .

Assignment Project Exam Help

To prove the theorem from the previous slide, we need to show that for every NFA N , there exists a DFA M with $L(M) = L(N)$.


<https://tutorcs.com>

Before we see the general proof for this, we go through one concrete example. We transform NFA N_4 into an equivalent DFA.

WeChat: cstutorcs

Transforming an NFA into a DFA—example

Consider the NFA N_4 :




Assignment Project Exam Help


<https://tutorcs.com>

WeChat: cstutorcs

Transforming an NFA into a DFA—example



Consider the NFA



Examples of
accepted words

a
aa

baba ✓

examples of
words that are
not accepted;

bbh X

bb X


Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Transforming an NFA into a DFA—example

Consider the NFA



$Q = \{1, 2, 3\}$

Examples of accepted words

a
εa

baba ✓

Examples of words that are not accepted;

bhb X


ab X

<https://tutorcs.com>

WeChat: cstutorcs

Transforming an NFA into a DFA—example

Consider the NFA



$Q = \{1, 2, 3\}$

Examples of accepted words

a
εa

baba ✓

Examples of words that are not accepted;

bhb X

ab X

<https://tutorcs.com>

WeChat: cstutorcs

General proof of Theorem

Proof

Let $N = (Q, \Sigma, \delta, q_0, F)$ be some NFA.

We need to construct DFA $M = (Q', \Sigma, \delta', q'_0, F')$ with $L(M) = L(N)$.

Assuming that N does not contain any ϵ -transitions, we construct M as follows:

1. $Q' = \mathcal{P}(Q)$
2. For $R \in Q'$ and $a \in \Sigma$, we let

$$\delta'(R, a) = \{q \in Q \mid q \in \delta(r, a) \text{ for some } r \in R\}$$

3. $q'_0 = \{q_0\}$
4. $F' = \{R \in Q' \mid \text{there exists an } r \in F \text{ with } r \in R\}.$

This completes the construction for NFAs that don't contain ϵ -transitions.

General proof of Theorem

Proof

Let $N = (Q, \Sigma, \delta, q_0, F)$ be some NFA.

We need to construct a DFA $M = (Q', \Sigma, \delta', q'_0, F')$ with $L(M) = L(N)$.

Assuming that N does not contain any ϵ -transitions, we construct M as follows:

1. $Q' = \mathcal{P}(Q)$

$$\epsilon Q' = \mathcal{P}(Q)$$

2. For $R \in Q'$ and $a \in \Sigma$ we let

$$\delta'(R, a) = \{q \in Q \mid q \in \delta(r, a) \text{ for some } r \in R\}$$

3. $q'_0 = \{q_0\}$

4. $F' = \{R \in Q' \mid \text{there exists an } r \in R \text{ with } r \in F\}$.

This completes the construction for NFAs that don't contain ϵ -transitions.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Proof continued

If M does contain ϵ -transitions, we extend the above construction as follows:

For a state $R \in Q'$, we let $E(R)$ denote the set of states that can be reached via 0 or more ϵ -transitions from some state $r \in R$ (in N).

Then we modify the transition function of M to be

$$\delta'(R, a) = \{q \in Q \mid q \in E(\delta(r, a)) \text{ for some } r \in R\}$$

and the start state of M to be

$$q'_0 = E(q_0).$$

<https://tutorcs.com>

WeChat: cstutorcs

Regular languages are closed under regular operations

Theorem

Regular languages are closed under unions.


Assignment Project Exam Help

"Proof" by illustration

Given A and B and DFAs M_A and M_B with
 $L(M_A) = A$ and $L(M_B) = B$. We need to construct an
DFA M that recognizes $A \cup B$.

<https://tutorcs.com>

WeChat: cstutorcs



Regular languages are closed under regular operations

Theorem

Regular languages are closed under unions.

Assignment Project Exam Help

Proof (formal version)

We need to show that if two languages A and B are regular, then so is $A \cup B$. If A and B are regular, then there exist NFAs $N_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $N_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ such that $L(N_1) = A$ and $L(N_2) = B$. We need to show that there exists an NFA M with $L(M) = A \cup B$. The picture on the previous slide illustrates a construction for $M = (Q, \Sigma, \delta, q_0, F)$. Formally, we set:

1. $Q = Q_1 \cup Q_2 \cup \{q_0\}$, where q_0 is a new state, that is $q_0 \notin Q_1 \cup Q_2$ and this state q_0 will then also be the start state of M .

$$2. \delta(q, a) = \begin{cases} \{q_1, q_2\} & \text{if } q = q_0 \text{ and } a = \epsilon \\ \delta_i(q, a) & \text{if } q \in Q_i \\ \emptyset & \text{else} \end{cases}$$

3. $F = F_1 \cup F_2$.


Regular languages are closed under regular operations

Theorem

Regular languages are closed under concatenations.

Assignment Project Exam Help

"Proof" by illustration



Regular languages are closed under regular operations

Theorem

Regular languages are closed under concatenations.

Assignment Project Exam Help

Proof (formal version)

We need to show that if two languages A and B are regular, then so is $A \circ B$. If A and B are regular, then there exist NFAs $N_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ and $N_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ such that $L(N_1) = A$ and $L(N_2) = B$. We need to show that there exists an NFA M with $L(M) = A \circ B$. The picture on the previous slide illustrates a construction for $M = (Q, \Sigma, \delta, q_0, F)$. Formally, we set:

1. $Q = Q_1 \cup Q_2$

2. $q_0 = q_1$

3.
$$\delta(q, a) = \begin{cases} \delta_1(q, a) \cup \{q_2\} & \text{if } q \in F_1 \text{ and } a = \epsilon \\ \delta_1(q, a) & \text{if } q \in Q_1 \text{ and } (q \notin F_1 \text{ or } a \neq \epsilon) \\ \delta_2(q, a) & \text{if } q \in Q_2 \end{cases}$$

4. $F = F_2$.

<https://tutorcs.com>
WeChat: cstutorcs

Regular languages are closed under regular operations

Theorem

Regular languages are closed under the star-operation.

Assignment Project Exam Help

"Proof" by illustration

<https://tutorcs.com>

$L(A)=A$

WeChat: cstutorcs

$L(A^*) = A^*$

==

Regular languages are closed under regular operations

Theorem

Regular languages are closed under the star-operation.

Assignment Project Exam Help

Proof (formal version)

We need to show that if languages A is regular, then so is A^* . If A is regular, then there exist an NFA $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$ such that $L(M_1) = A$. We need to show that there exists an NFA M with $L(M) = A^*$. The picture on the previous slide illustrates a construction for $M = (Q, \Sigma, \delta, q_0, F)$. We set:

1. $Q \equiv Q_1 \cup \{q_0\}$, where q_0 is a new state, that is $q_0 \notin Q_1 \cup Q_2$ and this state q_0 will then also be the start state of M .

$$2. \delta(q, a) = \begin{cases} \{q_1\} & \text{if } q = q_0 \text{ and } a = \epsilon \\ \delta_1(q, a) & \text{if } q \in Q_1 \text{ and } (q \notin F_1 \text{ or } a \neq \epsilon) \\ \delta_1(q, a) \cup \{q_1\} & \text{if } q \in F_1 \text{ and } a = \epsilon \end{cases}$$

3. $F = F_1 \cup \{q_0\}$.