

eecs2001

Introduction to the Theory of Computation

Lecture 7

Assignment Project Exam Help

<https://tutorcs.com>

Ruth Umer

WeChat: cstutorcs

January 30, 2023

Assignment Project Exam Help

Finite Automata

<https://tutorcs.com>

Reading: IFC Section 1.1

WeChat: cstutorcs

Assignment Project Exam Help

A finite automaton or finite state machine is a simple computational model.

<https://tutorcs.com>

We will work with this model of computation for the next part of this course.

WeChat: cstutorcs

A simple automaton-sliding door example


Consider an automatic sliding door sliding door with two pads that receive signals if someone is standing on them:

Assignment Project Exam Help

<https://tutorcs.com>


We can model the controller of the sliding door as a simple automaton:

WeChat: cstutorcs



Here we use: $C = \text{CLOSED}$, $O = \text{OPEN}$, $F = \text{FRONT}$, $R = \text{REAR}$, $B = \text{BOTH}$, $N = \text{NEITHER}$

A simple automaton—sliding door example




Here we use: $C = \text{CLOSED}$, $O = \text{OPEN}$, $F = \text{FRONT}$, $R = \text{REAR}$, $B = \text{BOTH}$, $N = \text{NEITHER}$

The behavior of the door can be described in terms of the following transition function:

	NEITHER	FRONT	REAR	BOTH
CLOSED	CLOSED	OPEN	CLOSED	CLOSED
OPEN	CLOSED	OPEN	OPEN	OPEN

State diagram of M_1

We can use a **state diagram** to describe a finite automaton M_1 :



Assignment Project Exam Help

<https://tutorcs.com>

Interpretation of the state diagram: This arrow “coming out of nowhere” going into the leftmost state, signals, that this state is the **start state**. This automaton can read letters from the **alphabet** $\Sigma = \{0, 1\}$. Being in some state q , receiving letter σ , the computation finds the outgoing edge from q that has a label σ , and moves along that arrow to a new state.

Examples

WeChat: cstutorcs

- If we feed the string 10010 to M_1 , we move through the states $q_1, q_2, q_3, q_2, q_2, q_3$, and end up in state q_3 , which is not an accept state.
- If we feed the string 1101 to M_1 , we end up in state q_2 , which is an **accept state** (accept states are the nodes with a double circle).
- If we feed the empty string ϵ to M_1 , we end up in state q_1 , which is not an accept state.

State diagram of M_1

We can use a **state diagram** to describe a finite automaton M_1 :



Interpretation of the state diagram. The arrow "coming out of nowhere" going into the leftmost state, signals, that this state is the start state. This automaton can read strings from the alphabet $\Sigma = \{0, 1\}$. Being in some state q , receiving letter σ , the computation finds the outgoing edge from q that has a label σ , and moves along that arrow to a new state.

Examples:

- If we feed the string 10010 to M_1 , *we results in q_3*

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

State diagram of M_1

We can use a **state diagram** to describe a finite automaton M_1 :



Interpretation of the state diagram. The arrow “coming out of nowhere” going into the leftmost state, signals, that this state is the start state. This automaton can read strings from the alphabet $\Sigma = \{0, 1\}$. Being in some state q , receiving letter σ , the computation finds the outgoing edge from q that has a label σ , and moves along that arrow to a new state.

Examples:

- If we feed the string 10010 to M_1 , we move through the states q_1, q_2, q_1, q_2, q_3 , and end up in state q_3 , which is not an accept state.

If we feed the string 110 to M_1 , we end up in the state q_2 which is accept state.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Definition

A finite automaton is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the set of states,
2. Σ is a finite set called the alphabet,
3. $\delta : Q \times \Sigma \rightarrow Q$ is the transition function,
4. $q_0 \in Q$ is the start state, and
5. $F \subseteq Q$ is the set of accept states.

<https://tutorcs.com>

WeChat: cstutorcs

Formal definition of a finite

Definition

A finite automaton is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where


1. Q is a finite set called the set of states,
2. Σ is a finite set called the alphabet,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the transition function,
4. $q_0 \in Q$ is the start state, and
5. $F \subseteq Q$ is the set of accept states.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Formal description of M_1



The above state diagram corresponds to the following formal description:

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

1. $Q = \{q_1, q_2, q_3\}$,
2. $\Sigma = \{0, 1\}$,
3. δ is defined by the following table:

δ	0	1
q_1	q_1	q_2
q_2	q_3	q_2
q_3	q_2	q_2

4. q_1 is the start state, and
5. $F \subseteq \{q_2\}$.

Given the description of an automaton, we can ask: which strings will lead to an accept state when fed into the automaton? As we have seen in the example computations with M_1 before, some strings do and others don't. The set of strings that do lead to an accept state form a language over Σ , the **language of M_1** .

Formal description of M_1



The above state diagram corresponds to the following formal description:
 $M_1 = (Q, \Sigma, \delta, q_1, F)$, where

$Q = \{q_1, q_2, q_3\}$
 $\Sigma = \{0, 1\}$

q_1 is the starting state

$F = \{q_2\}$

	δ	0	1
q_1		q_1	q_2
q_2		q_2	q_3
q_3		q_2	q_3

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Let Σ be the alphabet of some automaton M . Then we let

$$L(M) = \{w \in \Sigma^k \mid k \in \mathbb{N} \text{ and } w \text{ is accepted by } M\}$$

<https://tutorcs.com>

denote the language of machine M . The is $L(M)$ is the set of all words over Σ that are accepted by machine M .

WeChat: cstutorcs
For the language $A = L(M)$ we also say machine M recognizes (or accepts) A .

Assignment Project Exam Help

Definition

Let $M = (Q, \Sigma, \delta, q_0, F)$ a finite automaton and $\mathbf{w} = w_1 w_2 \dots w_n$ a string over Σ . We say that M accepts \mathbf{w} if there exists a sequence $s_0 s_1 s_2 \dots s_n$ of states such that


1. $s_0 = q_0$,
2. $\delta(s_i, w_{i+1}) = s_{i+1}$ for $i = 0, 1, \dots, n-1$, and
3. $s_n \in F$

<https://tutorcs.com>

WeChat: cstutorcs

Language accepted by M_1

Assignment Project Exam Help



<https://tutorcs.com>

For the machine M_1 we get

WeChat: cstutorcs

$L(M_1) = \{w \mid w \text{ contains at least one 1 and the number of 0s after the last 1 is even}\}$

Task for you: convince yourself that this is exactly the set of words accepted by this automaton.

Assignment Project Exam Help

What is the language of M_1 ?

<https://tutorcs.com>

WeChat: cstutorcs



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Language accepted by M_1



For the machine M_1 we get

$$L(M_1) =$$

Task for you: figure out what exactly is the set of words accepted by this automaton.

Language accepted by M_1




For the machine M_1 we get

$$L(M_1) = \{w \in \{0,1\}^* \mid w \text{ contains at least one } 1 \text{ and the number of } 0\text{'s after the last } 1 \text{ is even}\}$$

Task for you: figure out what exactly is the set of words accepted by this automaton.

Assignment Project Exam Help




<https://tutorcs.com>

For the machine M_2 we get

WeChat: cstutorcs
 $L(M_2) = \{w \in \{0, 1\}^* \mid w \text{ ends with letter } 1\}$

Task for you: convince yourself that this is exactly the set of words accepted by this automaton.

Examples automaton M_2



Words accepted

Word	Accepted
001	✓
0101	✓
0111	✓

Words not accepted

Word	Accepted
000	X
010	X

Word	Accepted
0110	X

WeChat: cstutorcs

$L(M_2) = \{w \in \{0,1\}^* \mid w \text{ ends with } 1\}$

Assignment Project Exam Help



<https://tutorcs.com>

For the machine M_3 we get

WeChat: cstutorcs
 $L(M_3) = \{w \mid w \in \{0, 1\}^* \text{ is the empty string or ends with letter 0}\}$


Task for you: convince yourself that this is exactly the set of words accepted by this automaton.

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Examples automaton



Words accepted

010 ✓

0110 ✓

Words not accepted

001 X

0101 X

$$L(M_3) = \{ \varepsilon \cup \sum w \in \{0,1\}^* \mid w \text{ ends with } 0 \}$$


↑ set that contains only the empty word ε

More examples: M_4

Assignment Project Exam Help

<https://tutorcs.com>


WeChat: cstutorcs



Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Design an automaton that verifies if a string contains an odd number of 1s

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Design an automaton that verifies if a string contains an odd number of 1s




Design an automaton that verifies if a string contains 001 as a substring

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs



Assignment Project Exam Help

Regular Languages

<https://tutorcs.com>

Reading: IFC Section 1.1

WeChat: cstutorcs

Assignment Project Exam Help

Definition

A language L over some alphabet Σ is called a regular language if there exists a finite automaton M such that $L = L(M)$, that is, if there exists a finite automaton that recognizes it.

<https://tutorcs.com>
WeChat: cstutorcs

Regular language

Definition

A language L is called a **regular language** if there exists a finite automaton M such that $L = L(M)$, that is, if there exists a finite automaton that recognizes it.

Examples of regular languages

① $\{w \in \{0,1\}^* \mid w \text{ contains } 001 \text{ as a substring}\}$

② $\{w \in \{0,1\}^* \mid \text{the number of } 0\text{'s in } w \text{ is odd}\}$

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutorcs

Assignment Project Exam Help

Definition:

Let A and B be languages. Then we define the following operations that each form a new language:

- **Union:** $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$
- **Concatenation:** $A \circ B = \{wv \mid w \in A \text{ and } v \in B\}$.

WeChat: cstutorcs

- **Star:**

$$A^* = \{w_1 w_2 \dots w_k \mid k \geq 0 \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$$

Assignment Project Exam Help

Regular

$$A = \{01, 001, 0001\}$$

$$A \times B \ni (01, 110)$$

Definition.

Let A and B be languages. Then we define the following operations that each form a new language:

- Union: $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.

- Concatenation: $A \circ B = \{wv \mid w \in A \text{ and } v \in B\}$.

$$\text{Ex } A \circ B = \{011, 0011, 00011, 0111, 00111, 000111, 01110, 001110, 0001110, 0110, 00110, 000110\}$$

- Star: $A^* = \{w_1 w_2 \dots w_k \mid k \geq 0, \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$

$$\text{Ex } A^* = \{\epsilon, 01, 001, 0001, 0101, 01001, 010001, 0100001, \dots\}$$

\uparrow
infinite set of words...

<https://tutors.com>

WeChat: cstutors

Assignment Project Exam Help

Regular op

$$\Sigma = \{0, 1\}$$

$$A = \{01, 001, 0001\}$$

$$A \times B \ni (01, 110)$$

Definition:

Let A and B be languages. Then we define the following operations that each form a new language:

- Union: $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$.

$$A \cup B = \{01, 001, 0001, 110, 1101\}$$

- Concatenation: $A \circ B = \{wv \mid w \in A \text{ and } v \in B\}$.

$$\text{Ex } A \circ B = \{011, 0011, 00011, 0111, 00111, 000111, 01110, 001110, 0001110, 0110, 00110, 000110\}$$

- Star: $A^* = \{w_1 w_2 \dots w_k \mid k \geq 0, \text{ and } w_i \in A \forall i \in \{0, 1, \dots, k\}\}$

$$\text{Ex } A^* = \{\epsilon, 01, 001, 0001, 0101, 01001, 010001, 0100001, 01000001, 010000001, \dots\}$$

\uparrow
infinite set of words...

<https://tutors.com>

WeChat: cstutors

End of presentation. Click to exit.

You are screen sharing Stop share

Mouse Select Text Draw Stamp Highlight Eraser Lasso Undo Redo Save

Test

Assignment Project Exam Help

<https://tutorcs.com>

WeChat: cstutores

$$\Sigma = \{0, 1\}$$

$$A = \{1^3\}$$

$$A^* = \{\epsilon, 1, 11, 111, 1111, \dots\}, |A^*| = \infty$$



q0 accepts A^*

$$\Sigma' = \{0, 1, 2\}$$

Automaton

$$(Q, \Sigma, \delta, q_0, F)$$

↑
part of the definition of an automaton