

Driver Impact Protection and Steering Control System

-
-

203 (1) The steering control system of a vehicle shall be constructed in such a manner that no component or attachment — including any horn actuating mechanism — is capable, during normal driving manoeuvres, of catching the driver's clothing or the driver's jewellery, such as a watch, a ring or a bracelet other than a bracelet with loosely attached or dangling members.

-
-

(2) Subject to subsection (4), the steering control system of every passenger car and three-wheeled vehicle and every multi-purpose passenger vehicle, bus and truck — other than a walk-in van — with a GVWR of 4 536 kg or less shall be tested in accordance with SAE Recommended Practice J944, Steering Control System — Passenger Car — Laboratory Test Procedure (June 1980).

-
-

(3) The following requirements with respect to the steering control system shall be met during the test referred to in subsection (2):

-

-

(a) the system shall be impacted by a body block at a relative velocity of 24 km/h;

-
-

(b) the impact force developed on the chest of the body block and transmitted to the system shall not exceed 11 120 N, except for intervals with a cumulative duration of not more than 3 ms.

-

-

(4) Subsections (2) and (3) do not apply to a vehicle that conforms to the requirements of S5 and S14 of Technical Standards Document No. 208, Occupant Crash Protection (TSD 208), as amended from time to time.

-
-

(5) [Repealed, SOR/2014-307, s. 14]

-