

TimeFlip API Documentation

Table of Contents

TimeFlip API Documentation.....	1
Introduction.....	2
Authentication.....	2
Email Authentication.....	2
Social Authentication.....	3
Password Management.....	4
Account Management.....	5
Task Management.....	5
Task Operations.....	5
Task Property Updates.....	7
Time Allocation.....	10
Reporting and Analytics.....	10
Reports.....	10
Data Export.....	11
Synchronization.....	12
Device Management.....	13
Firmware.....	13
Settings.....	14
User Profile.....	15
Currencies.....	16
Data Models.....	16
Task (TaskDto).....	17
Time Interval (DataInterval).....	17
Settings (SettingsDto).....	18
Currency (CurrencyDto).....	18
Reports Structure.....	18
Daily Report (DailyReportDto).....	18
Weekly Report (WeeklyReportDto).....	19
Personal Token Acquisition.....	19

Introduction

Base URL: <https://newapi.timeflip.io/>

This documentation provides details on endpoints for the TimeFlip API.

Authentication

Email Authentication

Sign Up: `POST /api/auth/email/sign-up` - Register a new user
json

JSON

```
// Request
{
  "fullName": "John Doe", // *
  "email": "john@example.com", // *
  "password": "securepassword" // *
}
```

Sign In: `POST /api/auth/email/sign-in` - Login with email and password
json

JSON

```
// Request
{
  "email": "john@example.com", // *
  "password": "securepassword" // *
}
```

Email Verification:

POST /api/auth/email/sendVerification?email=john@example.com -
Request verification email

GET
/api/auth/email/verify?email=john@example.com&key=verification_key - Verify email with key

Social Authentication

Google/Facebook: POST /api/auth/googleOrFacebook
json

JSON

```
// Request
{
  "token": "your_oauth_token" // *
}
```

Apple ID: POST /api/auth/appleid
json

JSON

```
// Request
{
  "identityToken": "your_apple_identity_token", // *
  "email": "john@example.com",
  "userName": {
    "firstName": "John",
    "lastName": "Doe"
  }
}
```

Password Management

Request Reset: POST /api/auth/password/requestReset
json

JSON

```
// Request
{
  "email": "john@example.com" // *
}
```

Check Reset Key: GET
/api/auth/password/checkResetKey?email=john@example.com&key=reset_key

Reset Password: POST /api/auth/password/reset
json

JSON

```
// Request
{
  "email": "john@example.com", // *
  "password": "new_password", // *
  "key": "reset_key" // *
}
```

Account Management

Delete Account: POST /api/auth/delete

Task Management

Task Operations

Get User Tasks: GET /api/tasks/byUser

Unset

```
// Example Request
GET /api/tasks/byUser
Authorization: Bearer {your_token}

// Example Response
[
  {
    "id": 12345,
    "name": "Project Alpha",
    "description": "Development tasks for Project Alpha",
    "color": "#FF5733",
    "billable": true,
    "highPriority": false,
    "pomodoro": true,
    "pomodoroTime": 25,
    "hourlyRate": 75.00,
    "currencyId": 1
  }
]
```

Get Task by ID: GET /api/tasks/{id}

JSON

```
// Example Request
GET /api/tasks/12345
Authorization: Bearer {your_token}

// Example Response
{
  "id": 12345,
  "name": "Project Alpha",
  "description": "Development tasks for Project Alpha",
}
```

```
"color": "#FF5733",  
"billable": true,  
"highPriority": false  
  
}
```

Update Task: PUT /api/tasks

Unset

```
// Example Request  
PUT /api/tasks  
Authorization: Bearer {your_token}  
Content-Type: application/json  
  
{  
  "id": 12345, // *  
  "name": "Project Alpha Updated",  
  "description": "Updated development tasks",  
  "color": "#33A1FF",  
  "billable": true,  
  "highPriority": true  
}
```

Get Tasks by Period: GET /api/tasks/byPeriod

Unset

```
// Example Request  
GET  
/api/tasks/byPeriod?beginDateStr=2025-04-01&endDateStr=2025-04-27  
Authorization: Bearer {your_token}
```

```
// Parameters:  
// beginDateStr - Start date in format YYYY-MM-DD  
// endDateStr - End date in format YYYY-MM-DD  
// taskIds - (Optional) Array of task IDs to filter  
  
// tags - (Optional) Array of tags to filter
```

Task Property Updates

Update Task Name: PUT /api/tasks/{id}/newName

Unset

```
// Example Request  
PUT /api/tasks/12345/newName  
Authorization: Bearer {your_token}  
Content-Type: application/json  
  
{  
  "name": "New Project Name" // *  
}
```

Update Task Description: PUT

/api/tasks/{id}/newDescription/{newDescription}

Unset

```
// Example Request
```

```
PUT
/api/tasks/12345/newDescription/Updated%20project%20description
Authorization: Bearer {your_token}
```

```
// Note: The description is URL-encoded in the path
```

Update Task Color: PUT /api/tasks/{id}/newColor

Unset

```
// Example Request
PUT /api/tasks/12345/newColor
Authorization: Bearer {your_token}
Content-Type: application/json

{
  "color": "#33A1FF" // *
}
```

Update Task Icon: PUT /api/tasks/{id}/newIcon/{newIcon}

Unset

```
// Example Request
PUT /api/tasks/12345/newIcon/code

Authorization: Bearer {your_token}
```

Update Task Billable Status: PUT

`/api/tasks/{id}/newIsBillable/{newIsBillable}`

Unset

```
// Example Request
PUT /api/tasks/12345/newIsBillable/true

Authorization: Bearer {your_token}
```

Update Task Priority: PUT

`/api/tasks/{id}/newIsHighPriority/{newIsHighPriority}`

Unset

```
// Example Request
PUT /api/tasks/12345/newIsHighPriority/true

Authorization: Bearer {your_token}
```

Time Allocation

Allocate Time to Task: PUT `/api/tasks/allocateTime`

Unset

```
// Example Request
```

```
PUT
/api/tasks/allocateTime?taskId=12345&beginDate=2025-04-27T09:00:00&endDate=2025-04-27T10:30:00&time=5400
Authorization: Bearer {your_token}

// Parameters:
// taskId - ID of the task to allocate time to
// beginDate - Start time (ISO 8601 format) *
// endDate - End time (ISO 8601 format) *

// time - Duration in seconds (optional, calculated from
begin/end if absent)
```

Reporting and Analytics

Reports

Daily Report: POST /report/daily

```
Unset

// Example Request
POST /report/daily
Authorization: Bearer {your_token}
Content-Type: application/json

{
  "beginDateStr": "2025-04-01", // *
  "endDateStr": "2025-04-27", // *
  "taskIds": [12345, 12346]
}
```

Weekly Report: POST /report/weekly

Unset

```
// Example Request
POST /report/weekly
Authorization: Bearer {your_token}
Content-Type: application/json

{
  "beginDateStr": "2025-04-01", // *
  "endDateStr": "2025-04-27", // *
  "taskIds": [12345, 12346]
}
```

Data Export

CSV Export: POST /api/export/csv

Unset

```
// Example Request
POST /api/export/csv
Authorization: Bearer {your_token}
Content-Type: application/json

{
  "beginDateStr": "2025-04-01",
  "endDateStr": "2025-04-27",
  "taskIds": [12345, 12346]
```

```
}
```

XLSX Export: POST /api/export/xlsx

Unset

```
// Example Request
POST /api/export/xlsx
Authorization: Bearer {your_token}
Content-Type: application/json

{
  "beginDateStr": "2025-04-01",
  "endDateStr": "2025-04-27",
  "taskIds": [12345, 12346]
}
```

Synchronization

Sync Data: POST /api/sync

Unset

```
// Example Request
POST /api/sync
Authorization: Bearer {your_token}
Content-Type: application/json
```

```
{
  "tasks": [ /* array of tasks */ ], // *
  "timeIntervals": [ /* array of time intervals */ ] // *
}
```

Get Server Data: GET /api/sync

Unset

```
// Example Request
GET /api/sync

Authorization: Bearer {your_token}
```

Device Management

Firmware

Get Current Version: GET /api/firmware/version

Unset

```
// Example Request
GET /api/firmware/version

Authorization: Bearer {your_token}
```

Download Version: GET /api/firmware/{version}/download

Unset

```
// Example Request
GET /api/firmware/2.5.1/download

Authorization: Bearer {your_token}
```

Settings

Get Settings: GET /api/settings

Unset

```
// Example Request
GET /api/settings

Authorization: Bearer {your_token}
```

Update Settings: POST /api/settings

Unset

```
// Example Request
POST /api/settings
Authorization: Bearer {your_token}
Content-Type: application/json
```

```
{
  "autoPause": true,
  "autoPauseDelay": 300,
  "brightness": true,
  "brightnessLevel": 80
}
```

User Profile

Get Profile: GET /api/profile

Unset

```
// Example Request
GET /api/profile

Authorization: Bearer {your_token}
```

Update Email/Username: POST /api/profile/emailAndUserName

Unset

```
// Example Request
POST /api/profile/emailAndUserName
Authorization: Bearer {your_token}
Content-Type: application/json

{
```

```
"email": "newemail@example.com",  
"userName": "John Doe"  
  
}
```

Currencies

Get Currencies: GET /currencies

Unset

```
// Example Request  
GET /currencies  
Authorization: Bearer {your_token}
```

```
// Example Response  
[  
  {  
    "id": 1,  
    "key": "USD",  
    "symbol": "$"  
  },  
  {  
    "id": 2,  
    "key": "EUR",  
    "symbol": "€"  
  }  
]
```

Data Models

Task (TaskDto)

json

JSON

```
{
  "id": integer,
  "name": string,
  "description": string,
  "color": string,
  "icon": string,
  "tag": string,
  "billable": boolean, // *
  "highPriority": boolean, // *
  "pomodoro": boolean, // *
  "pomodoroTime": integer,
  "hourlyRate": number,
  "currencyId": integer,
  "sideIndex": integer,
  "ownerId": integer,
  "createdAt": timestamp,
  "updatedAt": timestamp,
  "deletedAt": timestamp
}
```

Time Interval (DataInterval)

json

JSON

```
{
  "id": integer,
  "taskId": integer,
  "startedAt": string, // *
  "duration": integer, // *
  "extId": integer,
  "taskLocalId": string,
```

```
"delDate": timestamp
}
```

Settings (SettingsDto)

json

```
JSON
{
  "id": integer,
  "userId": integer,
  "timeflipName": string,
  "brightness": boolean,
  "brightnessLevel": integer,
  "autoPause": boolean,
  "autoPauseDelay": integer,
  "blinkInterval": boolean,
  "blinkIntervalValue": integer,
  "firmwareVersion": string,
  "appVersion": string
}
```

Currency (CurrencyDto)

json

```
JSON
{
  "id": integer,
  "key": string, // *
  "symbol": string // *
}
```

Reports Structure

Daily Report (DailyReportDto)

json

JSON

```
{
  "beginDateStr": string, // *
  "endDateStr": string, // *
  "totalTime": integer,
  "totalPayment": array of PaymentInfo,
  "currencies": array of CurrencyDto,
  "weeks": array of WeekDto
}
```

Weekly Report (WeeklyReportDto)

json

JSON

```
{
  "beginDateStr": string, // *
  "endDateStr": string, // *
  "avgTime": integer,
  "avgPayment": array of PaymentInfo,
  "currencies": array of CurrencyDto,
  "tasksInfoAvg": array of TaskInfoDto,
  "weeks": array of WeekDto
}
```

Personal Token Acquisition

To acquire a personal access token for the TimeFlip API without using Postman, follow these steps:

Register a TimeFlip Account:

Register on the TimeFlip website or app

Verify your email address if required

Obtain an Authentication Token:

Use cURL or any HTTP client to send an authentication request:

bash

Shell

```
curl -X POST https://newapi.timeflip.io/api/auth/email/sign-in \
  -H "Content-Type: application/json" \
  -d
'{"email":"your_email@example.com","password":"your_password"}'
```

Extract the Bearer Token:

The response will contain a JWT token

Look for something like:

json

JSON

```
{
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
  "user": { ... }
}
```

Use the Token in API Requests:

Include the token in the Authorization header for all requests

bash

Shell

```
curl -X GET https://newapi.timeflip.io/api/profile \  
  -H "Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..."
```

Token Expiration:

Tokens typically expire after a period (e.g., 24 hours)

If you get a 401 Unauthorized response, you need to reauthenticate

Store your token securely and renew as needed

Store in Environment Variables:

For scripts, store the token in an environment variable:

bash

Shell

```
export TIMEFLIP_TOKEN="eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..."
```

Then use it in your scripts:

bash

Shell

```
curl -X GET https://newapi.timeflip.io/api/profile \  
  -H "Authorization: Bearer $TIMEFLIP_TOKEN"
```

