(1)Lai	STEEL BEAM GUARDRAIL FOR SIDE OBSTACLE (TWO-WAY PROTECTION) Possible Standards: BA-200, BA-206, BA-210, BA-211, BA-251, LS-625, LS-625, LS-621, SI-172, SI-173, and SI-211. (1) Lane(s) to which the obstacle is adjacent.																LØ8-8B I-19-16									
		Location Side	n		\top		Layout Lengths BA-251 or LS-631								Delineators and Object Markers				Bid Items							
]		'		1						Approach Side (A)		Trailing Side (T)			Long-Span Sy	vstem	Delineator Object Marker			End Te	erminal	_				
oo.	fic	tside dian	Station	(OL)						VT1 _T VF _T	VF _T	VT2 _T	ET			SI-211	CT 172				Steel Beam Guardrail			Post	Remarks	
	rraf	Outs	Station	1	1 ,	(ET)	(VT2 _A)	(VF _A)	(VT1 _A)							31-211	Type 1	Type 2	Тур	pe 3	Guardrail	Standard	Count	Adapter		
			i		1			1					BA-211		White	White	OM2-2	OM3-L	OM3-R	BA-200			BA-210			
	0 0	ΟΣ	·	FT	FT	LF	LF	LF	LF	LF	LF	LF	LF	STATION	TYPE	TYPE	EACH	EACH	EACH	EACH	LF		EACH	EACH		
		'																								