

Simplicity *itself*

# Messages in Grails

# Why?

*Localisation (L10n)*

*Keep display text out of code*

Based on

*Java Resource Bundles*

*Java Locale class*

# Resource bundle

messages.properties:

```
hello.world=Hello World!  
book.title.label=Book title
```



Message key



Default text for this key

# Resource bundle

messages\_fr.properties:

```
hello.world=Bonjour le Monde!  
book.title.label=Titre de livre
```



Message key



French text for this key

# Resource bundle

Can be parameterised:

`greeting=Hello {0}!`

# File names

messages.properties

*Fallback text if no bundle matches requested locale*

messages\_fr.properties

*Generic French text*

messages\_fr\_CA.properties

*French Canadian text*

<bundle name>\_<lang>\_<country>.properties

# Locales consist of

## Two-letter language code

*en, fr, zh, es, de, etc.*

## Two-letter country code (optional)

*GB, CA, US, PT, BR, etc.*



# Rules

Requested locale: es\_CL

Matches (highest priority first):

messages\_es\_CL.properties

messages\_es.properties

messages.properties

# Rules

Requested locale: es

Matches (highest priority first):

messages\_es.properties

messages.properties

**How is the current locale  
determined?**

# In Grails

- lang URL/form parameter
  - stored in session
- *Accept-Language* HTTP header
- Default JVM locale (may come from platform locale)

# For example

<http://example.org/my-app/home?lang=fr>

# Fetch request locale

```
import org.springframework.web.servlet.support.  
RequestContextUtils as RCU  
  
RCU.getLocale(request)
```

# How do I fetch messages?

# GSP tag

## In GSP

```
<g:message code="hello.world"/>
```

```
<g:message error="${book.errors.getFieldError('title')}" />
```

## In controller

```
g.message code: "hello.world"
```



# Bean

```
import org.springframework.context.MessageSource

class MyService {
    MessageSource messageSource

    List greeting(String name, Locale locale) {
        return messageSource.getMessage(
            "greeting",
            [name] as Object[],
            locale)
    }
}
```


Grails resource bundles have a base name of *messages* and are stored in the *grails-app/i18n* directory.

Internationalisation

# Spring Security plugin provides

- Authentication
  - Form-based, HTTP Basic authentication and more
- Access control
  - Roles (*authorities* in Spring Security core)
  - Access Control Lists (ACLs)

# Spring Security filter chain



The SS filter chain is wrapped by a standard Servlet filter

# Example SS filters

- Logout
- Anonymous user
- Username/password authentication
- Remember me
- Attach security context to request thread
- Authority checks

*Filters can trigger on different URLs:*

Logout



/j\_spring\_security\_logout

Authentication




/j\_spring\_security\_check

Anonymous




/\*\*

Authority check




/\*\*

# Other core objects



# Getting Started

```
grails s2-quickstart org.example User Role
```



- Creates User and Role domain classes
  - provide authentication & access control
- Creates login & logout controllers



# Getting Started

- Add any extra properties to User you want
  - e.g. full name, email address, etc.
- Decorate or replace the login page
- Lots of config options
  - access control rules
  - login form URL

# The bare minimum

# Add access rules for URLs

- via annotations on controllers/actions
- via static URL rules
- via URL rules stored in the database (Requestmap)

# Annotations

```
import grails.plugin.springsecurity.annotation.Secured

@Secured(['IS_AUTHENTICATED_ANONYMOUSLY'])
class MyController {

    @Secured(['ROLE_USER'])
    def secret() {
        ...
    }

    @Secured(['IS_AUTHENTICATED_FULLY'])
    def home() {
        ...
    }
}
```

# URL rules (Config.groovy)

```
g.p.ss.securityConfigType = "InterceptUrlMap"
g.p.ss.interceptUrlMap = [
    '/' : ["permitAll"],
    '/assets/**' : ["permitAll"],
    '/login/**' : ["permitAll"],
    '/logout/**' : ["permitAll"],
    '/secret/**' : ["hasRole('ROLE_USER')"],
    '/**' : ["isAuthenticated()"]
]
```

*(see plugin guide for dynamic rules)*

# Rules

Constant	Expression	Description
IS_AUTHENTICATED_ANONMOUSLY	permitAll	Anyone has access
IS_AUTHENTICATED_REMEMBERED	isAuthenticated()	Client must be authenticated or have a 'remember me' cookie
IS_AUTHENTICATED_FULLY	isFullyAuthenticated()	Client must be authenticated in this session
ROLE_USER	hasRole('ROLE_USER')	Custom role (must be added to database)

# Other common config options

```
g.p.ss.userLookup.userDomainClassName = "org.example.User"  
g.p.ss.userLookup.authorityJoinClassName =  
    "org.example.UserRole"  
g.p.ss.authority.className = "org.example.Role"  
  
g.p.ss.userLookup.usernamePropertyName = "loginId"  
g.p.ss.userLookup.passwordPropertyName = "passwordHash"  
  
g.p.ss.auth.loginFormUrl = "/login/form"  
g.p.ss.successHandler.defaultTargetUrl = "/"
```



# Is the user authenticated?

via a service method:

```
springSecurityService.isLoggedIn()
```

via a GSP tag:

```
<sec:ifLoggedIn>  
  ...  
</sec:ifLoggedIn>
```

# Who's logged in?

via a service method:

```
springSecurityService.currentUser  
springSecurityService.authentication  
springSecurityService.principal
```

Domain instance



Token



UserDetails object



via a GSP tag:

```
<sec:username/>
```

```
<sec:loggedInUserInfo field="fullName"/>
```

# Has access?

via a utility method:

```
SpringSecurityUtils.ifAllGranted("ROLE_USER")  
SpringSecurityUtils.ifAnyGranted("ROLE_USER")  
SpringSecurityUtils.ifNotGranted("ROLE_USER")
```

via a GSP tag:

```
<sec:ifAnyGranted roles="ROLE_USER">  
    ...  
</sec:ifAnyGranted>  
<sec:access expression="hasRole('ROLE_USER')">  
    ...  
</sec:access>
```

# Banner...

...does things differently

# Banner overview

- Security in *banner\_core* plugin
- Custom authentication provider
- Custom authentication token
- Custom access voter
- No domain classes

Seems to be based on Oracle  
Forms security

# Core configuration

```
formControllerMap = [  
    'commonmenu':          ['GUAGMNU'],  
    'medicalinformation':  ['GOAMEDI'],  
    'informationtexteditor': ['GUAINFO'],  
    ...  
]  
  
g.p.ss.securityConfigType = "InterceptUrLMap"  
g.p.ss.interceptUrLMap = [  
    '/' :                  ["permitAll"],  
    ...  
    '/**' :                ["ROLE_DETERMINED_DYNAMICALY"]  
]
```



**Good luck!**